



**ATLAS SOUND AP-15 OMNI-PURPOSE PAGING HORN**

The 8-ohm Model AP-15 and transformer-equipped Model AP-15T are double re-entrant loudspeakers which deliver 15W of continuous power handling, superior intelligibility and unparalleled efficiency. The speakers operate within a nominal frequency response range of 400Hz-14kHz and offer a sensitivity of 120dB at rated power to provide clear voice and signal communication. The transformer-equipped version includes a versatile, 3-way, 25V/70.7V/100V line transformer to meet a variety of distributed system needs. The transformer is easily adjustable using the exclusive Vari-Tap® Connect Center which features a 7-position, Watts/impedance selection switch.



ITEM	DESCRIPTION	PRICE
AP-15	Paging horn, 8ohms, 15W, 70° dispersion, grey	76.50
AP-15T	As AP15 but with 25V/70.7V/100V transformer, with 5 tap settings, grey	92.50
AP-15TC	As AP15T but in beige.	94.50

**ATLAS SOUND APX CD HORNS** The APX constant-directivity speaker brings “pro-audio” control technology to the indoor/outdoor commercial sound market. Now you can point and direct sound where you want it with excellent clarity in the target zone. APX models achieve consistent beamwidth control in both horizontal and vertical directions over a wide frequency range. Available in a 40W version, this model is equipped with 25V/70.7V/100V internal transformers. Mounts to 1-gang, 2-gang, or 4-inch sq. E.O. box.



ITEM	DESCRIPTION	PRICE
APX40TN	40W CD horn	97.50

**ATLAS SOUND APT-34AT BI-DIRECTIONAL LOUDSPEAKERS** Atlas Sound Model APT-34AT is a high-intelligibility loudspeaker with a single compression driver which delivers 30W of power and 175° sound dispersion in opposite directions. It incorporates the exclusive Vari-Tap®-control connect center, which features a built-in 25V/70.7V/100V transformer and a 7-position Watts/impedance switch (screwdriver adjustable) with a 45-ohm tap. It is environment-resistant and includes a protective terminal cover with built-in cable strain relief for versatile indoor/outdoor intercom and signaling use. The single adjustment Omni-Purpose mounting bracket provides positioning flexibility on conventional surface installations (vertical and horizontal planes) and includes provisions for strap-mounting to I-beams or pillars. Finished in durable grey epoxy. Weight is 9lbs.



ITEM	DESCRIPTION	PRICE
APT-34AT	30W bi-directional, 175° PA horn	132.50
BX-1A	Vandal-resistant cable/conduit cover plate	8.50

**ATLAS SOUND AP-30 SERIES HORN LOUDSPEAKERS** The 8-ohm Model AP-30 and transformer-equipped Models AP-30T and AP-30T-25 are double re-entrant loudspeakers which deliver 30W of continuous power handling, superior intelligibility and unparalleled audio conversion-efficiency. The AP-30 Series operates within a nominal frequency range of 300Hz-12kHz and offers a sensitivity of 126dB at rated power to provide clear voice and signal communication. Models AP-30T and AP-30T-25 each feature an integral transformer to meet a variety of distributed system needs. The AP-30T is equipped with a versatile, 3-way, 25V/70.7V/100V line transformer, while Model AP-30T-25 includes a 25V only line transformer. Transformers are adjustable using Atlas Sound’s exclusive Vari-Tap® Connect Center which features a 7-position, Watts/impedance selection switch. The labor saving Vari-Tap terminal is screwdriver adjustable and includes a protective cover with built-in strain relief.



ITEM	DESCRIPTION	PRICE
AP-30	8-ohm 30W horn loudspeaker	105.50
AP-30T	With 3-way, 25V/70.7V/100V line transformer	120.50
AP-30T-25	With 25V only line transformer	102.70



**EV CDP DUPLEX HORNS**

The CDP848AT (30W transformer version) is a hi-fidelity, 2-way paging horn with 150° dispersion. The CDP850T (60W transformer version) is a high-powered, hi-fidelity, 2-way paging horn with 150° dispersion.



ITEM	DESCRIPTION	PRICE
CDP848AT	30W with transformer	438.00
CDP850T	60W with transformer	541.00

**EV COBRA-IIB** The Cobraflex IIB has a slightly smaller size and coverage pattern than the Cobraflex III. Driver must be ordered separately. Recommended drivers: ID30C-8, ID30C-16, ID30CT, ID60C-8, and ID60CT. 80° x 60° beamwidth. 9.3" x 18.5" x 10.3" (HWD).



ITEM	PRICE
COBRA-IIB	134.00

**EV PA430 CONSTANT DIRECTIVITY PAGING HORN**

The world’s only constant directivity paging projector the PA430 provides predictable performance and offers a unique patented omnidirectional swivel-mount system. The PA430 solves many of the problems encountered by designers of distributed paging systems. The PA430T version has an input transformer to match 25V, 70.7V, or 100V lines.



ITEM	DESCRIPTION	PRICE
PA430	Paging horn	98.00
PA430T	70V paging horn	134.00

**EV COMPRESSION DRIVERS**

Ideal for Cobraflex and other EV/University horns, available in 8-ohm or with built-in 70V transformer.



ITEM	DESCRIPTION	PRICE
ID30C8	30W 8ohms	124.00
ID30CT	30W 25V/70V	144.00
ID30C16	30W 16ohms	124.00
ID60DT	60W 25V/70V	252.00



**TOA CS SERIES WIDE-RANGE PAGING HORNS**

Ideal for indoor and outdoor commercial sound system applications, voice paging, background music and tone signaling distribution. Compared to traditional metal paging horns, CS Series speakers offer a wider frequency range and superior sound quality.



Each includes a built-in 70.7V/100 V transformer with screwdriver-adjustable power taps. All CS models are fully weather-resistant to withstand demanding environments with a sealed enclosure, full-range moisture-resistant cone speaker, stainless steel mounting hardware and a protective mesh grille. The enclosure is also coated with polyurethane resin paint to resist the fading effects of prolonged exposure to ultraviolet light. Speakers have a 5-year warranty.

ITEM	DESCRIPTION	PRICE
CS64	6W horn, 130Hz-13kHz, 96dB max SPL	64.50
CS64/U	UL listed version of CS64	73.50
CS154	15W horn, 150Hz-15kHz, 97dB max SPL	102.00
CS154/U	UL listed version of CS154	124.50
CS304	30W horn, 120Hz-15kHz, 98dB max SPL	121.50
CS304U	UL listed version of CS304	139.50



**TOA SC SERIES PAGING HORN SPEAKERS**

These provide intelligible voice paging and tone signaling for indoor and outdoor sound system applications. SC Series models are available with a choice of power ratings from 10W to 50W and are easy to install in wall, pole or ceiling-mount applications and include corrosion-resistant stainless-steel mounting hardware. They are designed for intercom talkback applications requiring dual operation as both a microphone and speaker. Each model is a double re-entrant horn with compression driver for high sensitivity and a lightweight aluminum enclosure. They are fully weather-resistant for reliable operation in demanding environments and the loudspeaker diaphragm is heat and moisture-resistant. The SC Series are also IP-65 standards compliant for dust and moisture-resistance with a wide operating temperature range from -4°F to 130°F. Includes a 5-year warranty.

ITEM	DESCRIPTION	PRICE
SC610	10W horn, 315Hz-12.5kHz, 110dB max SPL	48.00
SC610T	SC610 with 25V/70.7V transformer	55.50
SC615	15W horn, 280Hz-12.5kHz, 112dB max SPL	64.50
SC615T	SC615 with 25V/70.7V transformer	72.00
SC630	30W horn, 250Hz-10kHz, 113 dB max SPL	84.00
SC630T	SC630 with 25V/70.7V transformer	97.50
SC651	50W horn, 250Hz-6kHz, 108dB max SPL	148.50