



CABLES TO GO TRULINK® WIRELESS DIGITAL SIGNAGE DISTRIBUTION SYSTEM This system enables video with stereo audio to be distributed and synchronized wirelessly across multiple displays. The 802.11a/g wireless capabilities allow easy installation of digital signs in locations where running cables is difficult. Can also be used in wired mode using standard Cat5/6 cables. Supports up to 32 screens wirelessly or supports up to 1000 screens in wired mode. Wireless mode supports distances up to 100' by using the included antennas in an indoor environment while wired mode supports distances up to 3000'. Supports resolutions up to 1280x1024 @ 20fps, 1024x768 @ 30fps. Supports 10Base-T/100Base-TX & 802.11a/g. Connections include DVI-I, VGA and dual RCA audio. One year warranty.



ITEM	DESCRIPTION	PRICE
29505	TruLink wireless digital signage transmitter	676.00
29506	TruLink wireless digital signage receiver	676.00



GEFEN DIGITAL SIGNAGE PLAYBACK WITH WI-FI

An easy-to-operate media player that features software, live video input and RS-232. Live video can be directly inserted into any digital signage application with the composite video input. Includes 4 GB of built-in flash memory, a flash card slot, and two USB 2.0 ports. Also features HDMI and VGA out connections. An Auto-play function starts playing scheduled contents automatically.



NEW!

ITEM	DESCRIPTION	PRICE
EXT-HD-DSWFP	Digital signage playback w/ Wi-Fi & live video input	818.18

GEFEN DVI VIDEO WALL CONTROLLER

Creates a 2x2 video wall for digital signage applications with a max resolution of 1920x1200p60 supported on each output. Many configurations are available including full-screen enlargement, horizontal array, 4 identical displays and more. Multiple input and output resolutions are supported and automated control is supported with RS232. Rack ears, IR remote control, 6' DVI cable and 6' DB9 serial cable included.



ITEM	DESCRIPTION	PRICE
EXT-DVI-VWC-242	Video wall controller for digital signage	1007.18

Panasonic

PANASONIC DIGITAL SIGNAGE SOLUTIONS

The LF20 series of 1920x1080 LCD digital signage screens are slim (4" or less), lightweight (42" is ~39 lbs), feature narrow bezels (0.7"), built-in rear speakers, 700 cd/m2 brightness, a fan-less design, tamper-resistant control locks, and vertical and horizontal mounting settings. Both models can be oriented in multi-display video wall formations. Standard connections include 1x video in, 1x S-video in, 2x HDMI in, 1x DVI-D in, 1x component/RGB in, 1x PC in, 3x RCA in and RS232C.



ITEM	DESCRIPTION	PRICE
TH42LF20U	42" HD digital signage LCD flatscreen	923.40
TH47LF20U	47" HD digital signage LCD flatscreen	1177.20
TYSTLF20	Pedestal for LCD displays	164.37

PANASONIC WEATHERPROOF LCD DISPLAYS

These monitors offer IP66-compliant dust-proof, water-resistant performance and have a trans-reflective LCD panel for high visibility in bright places while keeping power consumption low. They are designed for installation in pool areas, factories and more. The aluminum cabinet resists corrosion and the tempered glass provides strong resistance to impacts. A "winter mode" ensures the display can be used in temperatures as low as -4 °F. Inputs include (1) BNC Video, (1) L/R RCA, (2) HDMI, (3) component, (1) DVI-D 24 pin, (1) MINI D-SUB 15 pin PC in, and (1) M3 jack in.



NEW!

ITEM	DESCRIPTION	PRICE
TH42LFP30	42" weatherproof LCD display	COMING SOON!
TH47LFP30	47" weatherproof LCD display	COMING SOON!

SONY

SONY INTERACTIVE LCD TOUCH SCREEN MONITORS

These 42" and 47" LCD monitors use 3M's optically clear Dispersive Touch Technology (DST) within the Sony factory LCD housings. The technology is designed for high traffic, high use environments, and serves as an extra layer of protection for the LCD panel itself. Supports gesture functions and offers the users standard USB 2.0 touch interface with touch connections located in the connector bay area of the LCD. All models feature 1920x1080 native resolution and 1000:1 contrast ratio. They support audio in/out (pinjack), DVI-D, composite video out, Ethernet, HD component I/O, S-Video, and video-in interfaces. Also equipped with a network port for remote control/monitoring. An option slot accepts a range of adapters for versatility.



ITEM	DESCRIPTION	PRICE
FWDS42E1TOUCH	42" LCD touch screen, 500 cd/m2 brightness	3260.65
FWDS42H1TOUCH	42" LCD touch screen, 700 cd/m2 brightness	3481.59
FWDS47H1TOUCH	47" LCD touch screen, 700 cd/m2 brightness	CALL

SONY GXDL-52H1 52" FULL HD DIGITAL SIGNAGE LCD DISPLAY

This 920x1080 HD screen works well in semi-outdoor environments such as stadiums, airports, and train stations. Features burn-in resistant LCD technology, an IP30-rated dust & tamper-resistant aluminum chassis, replaceable tamper-proof glass, a LAN connection for status and control, internal heat sink, 1 HDMI in, and 1 DVI in. SNMP compatible for remote status and diagnostics purposes.



ITEM	DESCRIPTION	PRICE
GXDL52H1	52" full HD LCD display for digital signage	CALL
BKMFW15	HDMI input adapter	113.19
BKMFW16	HD-SDI adapter	879.89
ICSFW400	High-definition streaming card for digital signage w/ 60GB HDD	888.31
VSPNT	HD storage player for digital signage	1564.08
BKMFW21	Monitor RS232 control adapter	113.19

SPINETIX

SPINETIX HMP100/200 DIGITAL SIGNAGE MEDIA PLAYERS

These media players are a unique alternative to proprietary, PC based solutions for digital signage. With the HMP100 and HMP200 SpinetiX offers a new and simplified way to schedule, combine, update, stream and display content, whether it be audio, video, vector graphics, pictures or text. Their fanless design and the absence of moving parts make these boxes extremely durable and well-suited for harsh environments. Plus their small design means they can be hidden nearly anywhere. Both players feature internal flash memory, flash drive and HDD support via USB, HDMI and VGA outs, 1/8" TRS audio out, real time event communication, horizontal and vertical display capability, animation capabilities, and support for touchscreen, keyboard, joystick, gamepad or mouse interaction. The HMP200 adds full HD 1080p video, and has 8GB of internal memory. SpinetiX Fusion software is included.



ITEM	DESCRIPTION	PRICE
HMP-100	Hyper Media Player with Fusion, 4GB, 720p	1549.00
HMP-200	Hyper Media Player with Fusion, 8GB, 1080p	1999.00
HMD-STANDARD	Hyper Media Director software, standard license	399.00
HMD-PRO	Hyper Media Director software, pro license	1699.00
HMD-SITE	Hyper Media Director software license, 20 seats	CALL

TECH GLOBAL

TECH GLOBAL MICRO-TOUCH DST TOUCH SCREENS

3M MicroTouch DST touch systems feature chemically-strengthened glass and fast, accurate and repeatable operation. The Dispersive Signal Technology (DST) determines the touch position by pinpointing the source of "bending waves" created by the finger (or fingernail, pencil, baby carrot, etc) within the glass substrate. DST will also "ignore" a static object left on the screen and continue to respond to the user's touch. With a durable anti-glare glass surface that withstands surface contaminants such as dirt and dust, operation is unaffected by minor surface damage. For full list of screen specifications, please visit www.fullcompass.com



NEW!

ITEM	DESCRIPTION	PRICE
TGDTST-3204CCBA-3	LG MC3204CCBA w 3M DST	1727.04
TGTDST-400EX-3	Samsung LCD 400EX w/ 3M DST	CALL
TGTDST-460EX-3	Samsung LCD 460EX w/ 3M DST	CALL



- AUDIO
- COMPUTER AV
- VIDEO
- LIGHTS
- MUSIC
- ACCESSORIES



TIGHTROPE MEDIA SYSTEMS SOLO SERIES

An advanced digital signage solution that needs no extra hardware. Connect a Solo series device to a network, either Ethernet or WiFi (optional). Setup is done through a web browser on a remote PC. Output video up to 1080p with stereo audio. Plays back Windows Media, QuickTime, MPEG-2/4, Flash and PowerPoint slides. Both can display streaming web video and RSS feeds. The Solo 240 is a small, 6lb box that can mount behind a monitor. It offers HDMI & VGA outputs, optional WiFi. The Solo 310 is a 2RU device that offers DVI, VGA, component & composite outputs. Includes 1 year warranty.

ITEM	DESCRIPTION	PRICE
CAR-SOLO240	Solo 230, HDMI and VGA outputs.....	3425.00
CAR-SOLO310	Solo 300R, DVI, VGA, component and composite outputs.....	CALL
CAR-WIFI	Optional WiFi networking hardware for Solo 230, factory-installed, must order at time of purchase	390.00
CAR-SOLO240-SILVER	Silver Assurance Contract for Solo 240	375.00
CAR-SOLO240-GOLD	Gold Assurance Contract for Solo 240	518.75
CAR-SOLO310-SILVER	Silver Assurance Contract for Solo	375.00
CAR-SOLO310-GOLD	Gold Assurance Contract for Solo 310	543.75

TIGHTROPE MEDIA SYSTEMS PLAYER SERIES

Deliver your messages to the right place, at the right time, to the right people. As part of a complete digital signage solution, both devices integrate with Carousel Server, Pro and Enterprise.



Connected through a wired or wireless network, setup and control is done through a web interface from a Carousel sever. Supported media includes Windows Media, QuickTime, MPEG-2/4, Flash and PowerPoint slides, up to 1080p video with stereo audio. Display streaming web video and RSS feeds. Output video up to 1080p with stereo audio. The Player 240 is a small, 6lb box that can mount behind a monitor. It offers HDMI & VGA outputs and optional WiFi (requires CAR-WIFI). The Player 310 is a 2RU device that offers DVI, VGA, component & composite outputs. Includes 1-year warranty.

ITEM	DESCRIPTION	PRICE
CAR-PLR240	Player 230, HDMI and VGA outputs	2706.00
CAR-PLR310	Player 300R, DVI, VGA, component and composite outputs ..	3018.75
CAR-WIFI	Optional WiFi networking hardware for Player 230, factory-installed, must order at time of purchase	390.00
CAR-PLR240-SILVER	Silver Assurance Contract for Player 230	187.50
CAR-PLR240-GOLD	Gold Assurance Contract for Player 230	306.25
CAR-PLR310-SILVER	Silver Assurance Contract for Player 300R.....	187.50
CAR-PLR310-GOLD	Gold Assurance Contract for Player 300R.....	331.25



TIGHTROPE MEDIA SYSTEMS CAROUSEL SERVER Manage all of your digital signage from one location. It can be set up by a web-based user interface from any browser and acts as both a server and player in a multi-channel system. It supports 2 Solo/ Player devices (not included) in addition to an internal player, creating 3 unique channels. Plays back Windows Media, QuickTime, MPEG-2, Flash and PowerPoint slides. Also stream web video and RSS feeds. It has NVIDIA® Quadro® FX 380 LP for professional graphics. The Carousel Server is a 2RU device that offers DVI, VGA & composite outputs and S-video and HDMI inputs.

ITEM	DESCRIPTION	PRICE
CAR-SVR310	Carousel Server, DVI, VGA and composite outputs.....	CALL
CAR-SVR310-SILVER	Silver Assurance Contract for Carousel Server.....	425.00
CAR-SVR310-GOLD	Gold Assurance Contract for Carousel Server	637.50



TIGHTROPE MEDIA SYSTEMS CAROUSEL PRO SERVER Reduce communications costs by eliminating traditional production, distribution and installation of signs and schedules. Controlling the Carousel Pro is done through a web browser and simple interface. This server can control up to 300 Solo/Player devices (not included) for up to 300 different channels. Plays back Windows Media, QuickTime, MPEG-2, Flash and PowerPoint slides. Also displays live Internet web video and RSS feeds. The Carousel Pro is a 2RU device, it does not have video outputs and needs a Carousel Solo or Player for content viewing. There is also a hot swappable Enterprise hard drive for a total of 1TB RAID 1 storage.

ITEM	DESCRIPTION	PRICE
CAR-SVR410	Carousel Pro Server.....	CALL
CAR-SVR410-SILVER	Silver Assurance Contract for Carousel Pro	682.50
CAR-SVR410-GOLD	Gold Assurance Contract for Carousel Pro	987.50

TOTE VISION TOTE VISION LED DIGITAL SIGNAGE

MONITORS Ideal for digital signage, production or hospitality situations, these LED monitors feature a true high definition image with no down-scaling and a durable metal case with an even front bezel. All controls are located on the back of the units. Both models feature ATSC/QAM tuners and 1920x1080 resolution. The LED-2361HDMT is 23", with a contrast ratio of 1,000:1, and inputs for composite, component, HDMI, S-Video, VGA and RS-232 control. The LED-4200HDMT is a higher-end 42" model with a 4000:1 contrast ratio with inputs for composite (x2), component (x3), S-video (x2), HDMI (x2), VGA (x1), RS-232 control (x1), and multiple RCA audio inputs.



ITEM	DESCRIPTION	PRICE
LED2361HDMT	LED monitor, 23", 1920x1080	746.00
LED4200HDMT	LED monitor, 42", 1920x1080	1850.00

TOTE VISION LCD-1701TS TOUCHSCREEN MONITOR

This 17" touchscreen LCD monitor is ideal for use in educational displays or informational kiosks. Features a 5 wire resistive touch screen with a wide 170° viewing angle and low power consumption. It has 1280x1024 (SXGA) resolution, 1,000:1 contrast ratio, CCFT back light, 2 x 2W built-in speakers, VGA 15-pin mini D-SUB input, and USB connection for the touch screen.



ITEM	DESCRIPTION	PRICE
LCD1701TS	Touchscreen monitor, 17", 1280x1024.....	837.00

VIDEO DISTRIBUTION AMPS



PAGES 302-305



Follow us!

PRICES SUBJECT TO CHANGE WITHOUT NOTICE. Call today or visit us online!