

















COMPUTER AV



































VIDEO MONITORS & DISPLAYS (LCD, PLASMA, & CRT)

Blackmagicdesign



BLACKMAGIC DESIGN SMARTVIEW LCD MONITORS Smartview Monitors include 3-color integrated tally borders,

international power supply, Ethernet connection, USB 2.0 update port, SDI inputs with loop out, switchable between SD-, HD-, & 3G-SDI. Duo features (2) 8" LCD screens in a compact 3RU design while HD features (1) 17" 1080p LCD screen in a sleek 6RU design. Both are only 1" thick and perfect for any rackmount setup.

		1
ITEM	DESCRIPTION	PRICE
SMARTVIEW-DUO	Dual 8" LCD 3RU rackmount monitor	. 660.25
SMARTVIEW-HD	17" HD LCD 6RU rackmount monitor.	. 850.25

datavideo



DATAVIDEO TLM-702 7" X 2 TFT LCD MONITORS The TLM-702 includes two 7" TFT LCD monitors (1440 x 234) in a standard 19" rackmount, 3RU high. It can tilt up to +/- 30° and lock in any position. Controls include flip, 4:3 aspect, 16:9 aspect, mirror image, source select, contrast, brightness, color, and tint.

•		•	-		-		
ITEM	DESCRIPTION						PRICE
TLM702	7" x 2 TFT LCD r	nonitor, 3RL	١				816.00
TLM702MH	TLM-702 monito	r w/holder t	o atta	ach to	SE-500 sv	witcher	1008.00



DATAVIDEO TLM433 THREE 4.5" LCD MONITOR UNIT This rackmountable unit has adjustments for contrast, brightness, color & tint and an LED tally light indicator above each screen. Includes 3 composite video BNC outs for loop-through.

		U
ITEM	DESCRIPTION	PRICE
TI M433	Rackmount 3x 4 5" LCD broadcast monitors 2RII	960 00

DATAVIDEO TLM-170H LCD MONITOR The

TLM-170H is a 17.3", HD-SDI desktop monitor. It features a 1600 x 900 resolution and a backlit LED screen (desktop only). It also has built in stereo speakers and an audio level indicator. Connections include two CV inputs, one S-video, HD-YUV, HD-SDI and HDMI.



ITEM	DESCRIPTION	PRICE
TLM-170H	Desktop monitor w/ backlit LED	1632.00
TLM-170HM	1U rack-mounted LCD monitor	2112.00
TLM-170HR	7U rack-mounted LCD monitor	1728.00

DATAVIDEO TLM-700HDPD 7' **HD/SD-SDI FIELD MONITOR Suited**

for use in the field or studio, this unit can be powered with 12V DC or AC and automatically switches between PAL and NTSC. It features a standard V-mount that allows you to use universal batteries. A sunshade is included for in-the-field applications. It can be calibrated with an internal color bar,



color temperature, color select and the "blue-only" mode. Inputs include HD/ SD-SDI, HDMI, YUV component and composite and a 15-pin D-sub connector for tally control. Includes 12V DC power supply, battery not included.

ITEM	DESCRIPTION	PRICE
TLM-700HDPD	7" TFT LCD field monitor with HD/SD-SDI input	768.00
MO-TLM700	Porta-Brace case for TLM700HD	181.41
E7\$	IDX Li-lon V-Mount battery 71Wh/4.8Ah, 14.8V	259.00













See Page 432 For iKan Lighting Products!

PIO AUDIO I VIDEO I AV I LIGHTINO MUSICAL INSTRUMENTS

800-356-5844

FULLCOMPASS.COM















































IKAN D-SERIES LCD MONITORS These small and lightweight camera field monitors have a HD resolution of 1280x800 pixels and are equipped with 3G-SDI (input/output) and a HDMI input. Features false color, peaking, DSLR scaling and customizable function buttons on the back. Units come in 5" or 7" IPS and are available as wave-



form monitors with waveform, vectorscope, and RGB parade options.

ITEM	DESCRIPTION	PRICE
D5	. 5.6" 3G-SDI LCD monitor w/ hi-def panel	99.00
D5W-C	. same as above, but w/ waveform	1080.00
D7	. 7" 3G-SDI LCD monitor w/ hi-def IPS panel	179.00
D7W-C	. same as above, but w/ waveform	1214.00

IKAN VL5 5" HDMI FIELD MONITOR With a resolution of 800 x 480 and the additional functionality of DSLR Scaling, the lightweight VL5 5" HDMI monitor is complemented by pro features such as peaking, under scan, switchable aspect ratio & aspect ratio guides, blue gun and adjustable RGB. It accepts 480i/p, 576i/p, 720p, and 1080i/p inputs via HDMI.



Included with the VL5 are an AC adapter, your choice of Sony, Panasonic or Canon DV battery adapter plates and an anti-glare visor for bright conditions. Deluxe Kit is also available which includes choice of battery and charger, battery plate, AC adapter, shoe mount, mini & standard HDMI cables, sun visor and a soft case.

ITEM	DESCRIPTION	PRICE
VL5-C	5" HDMI field monitor w/ Canon battery adapter plate	270.00
VL5-P	As above but w/ Panasonic battery adapter plate	270.00
VL5-S	As above but w/ Sony battery adapter plate	270.00
VL5-C-DK	5" HDMI field monitor deluxe kit w/ Canon accessories	360.00
VL5-P-DK	As above but w/ Panasonic accessories	360.00
VL5-S-DK	As above but w/ Sony accessories	360.00

IKAN VK5 & VK7 HDMI MONITORS The ikan 5" VK5 and 7" VK7 are perfect solutions for DLSR monitoring with their light weight, low profile designs. Both monitors feature HDMI inputs, and many pro features such as red peaking, DSLR scaling, false color and clip guides. The VK7 has additional features including looping HDMI, composite, and component inputs, as well as an RJ45 tally connection and a pro XLR power



connector. Powering these monitors in the field is easy with snap-on/screw-on battery plates that are compatible with a variety of Pro, DV style, and LP-E6 style batteries. Deluxe kits are also available which include the battery, battery charger and soft case in addition to the standard accessories.

ITEM	DESCRIPTION	PRICE
VK5-C	.5" HDMI field monitor w/ Canon battery adapter plate	360.00
VK5-P	.As above but w/ Panasonic battery adapter plate	360.00
VK5-S	.As above but w/ Sony "L" Series battery adapter plate	360.00
VK7-C	.7" HDMI field monitor w/ Canon battery adapter plate	405.00
VK7-P	.As above but w/ Panasonic battery adapter plate	405.00
VK7-S	.As above but w/ Sony "L" Series battery adapter plate	405.00
VK7-SU	.As above but w/ Sony BPU Series battery adapter plate	405.00
VXPBK-A	."Gold" mount pro battery adapter plate	135.00
VXPBK-S	."V" mount pro battery adapter plate	135.00

JVC BROADCAST LCD MONITORS Full 1080p image displays that offer a wide color range and wider viewing. A 3G/dual-link HD-SDI input enables monitoring of 1080/60p signals. Includes digital closed captioning, superior scaling and de-interlacing, 10-bit 4:4:4 1080p processing. Models also have 12-channel



audio level meter with peak hold. Inputs include DVI-D, component and composite video as well as RCA audio-in. The DT3D24G1U uses passive 3D technology to display flicker-free images and is compatible with side-by-side and line-by-line 3D formats.

ITEM	DESCRIPTION	PRICE
DTV17G1Z	17" HD LCD, 1080p, with HD/SD-SDI in	2695.00
DTV21G11Z	21" HD LCD, 1080p, with HD/SD-SDI in	3250.00
DTV24G11Z	24" HD LCD, 1080p, with HD/SD-SDI in	CALL
DT3D24G1U	24" HD 3D LCD monitor with 3G & dual HD-SDI in	CALL
RAK17LCDGS	Rackmount kit for DTV17G1Z	140.00
RAK2024LCD	Rackmount kit for DTV 20" to 24" LCDs	173.05

Marshall Electronics



MARSHALL ELECTRONICS MD SERIES LCD RACK DISPLAYS WITH MODULAR INPUTS The MD series of rack monitors feature interchangeable input modules. The V-MD434 & V-MD503 units feature advanced front panel menu and feature control. The V-MD702, V-MD171X, and V-MD201 feature composite & component inputs. All models feature false color filter, markers, freeze function, status display, color temp presets, RGB gain/bias adjust, blue gun, pixel-to-pixel, hard tally. V-MD171X & V-MD201 monitors can be used on desktops with purchase of optional stand. Monitors can be purchased with 3GSDI input modules already installed.

stand: Monitoro can be parenased with 600D1 input includes an eady	mo tamo ai
TEM DESCRIPTION	PRICE
V-MD434	
w/front-panel menu/feature control, w/o input modules	2597.85
/-MD503	
menu/feature control, w/o input modules	2011.35
V-MD563	
w/composite/component inputs	2988 85
/-MD72 3RU (2) 7" LED-backlit 800x480 rack monitor unit,	
w/o input modules	1723 85
/-MD702 Same as V-MD72, but w/composite/component inputs	
/-MD171X	
/-MD201	
	iiputs 1433.63
Input Modules for V-MD434, V-MD503	
MD-3GSDI-B3G/HD/SDI input module w/loop-through	
MD-HDSDIX2-B 2-channel HDSDI input module w/switched output	
MD-HDMIX2-B 2-channel HDMI input module	166.75
MD-DVII-BDVI-I input module	166.75
Input Modules for All Other Models	
MD-3GSDI-A3G/HD/SDI input module w/loop-through	320 85
MD-HDSDIX2-A 2-channel HDSDI input module w/switched output	
MD-HDMIX2-A2-channel HDMI input module	
MD-DVII-ADVI-I input module	
Production of the control of the con	100.73
Desktop Stands	24.44
V-ST15 Desktop stand for V-MD171X rack monitor	
/-ST20 Desktop stand for V-MD201 rack monitor	45.94

V-R231-IMD-HDSDI



ELECTRONICS IN-MONITOR DISPLAY-CAPABLE LCD MONITORS Allows UMD (Under-Monitor Display) information and tallies to be displayed directly within the monitor. Available features include on-screen video time code, 3-color "Soft" Tallies, audio presence indicator and easy menu navigation. Integrates easily with existing Tally systems and controllers, while supporting Image Video, NVISION, TSL, and MEI protocols. All except the Quad Viewer monitors include HDSDI/SDI inputs and can be used as standalone displays with HDSDI loop-through. Quad Viewer models offer full-screen mode for video and DVI and quad-split mode (via built-in HD quad splitter) which is scaled to fit onscreen in the highest resolution. The Quad Viewer models have (4) independent HDSDI inputs, (1) DVI input, field-upgradeable firmware, and an RS422/485 port with pass-through. Dual Link/Waveform models feature 10-bit video path with 3G capable monitors and can display live video, audio bars, waveform and vectorscope in quad-view mode. They also have (2) 3G/HD/SDI inputs, Dual Link, a DVI input, RS485 firmware updating, and closed captioning (CEA-608-B, CEA-708-B). The NCB-1005 allows connected IMD monitors to be controlled by PC via Ethernet.

ITEM DESCRIPTION PR	ICE
V-R653P-IMD-TE (3) 6.5" HD/SD monitors in 2RU rack unit, 1024xRGBx768	ALL
V-R653SB-IMD As above but outdoor version	ALL
V-R1041-IMD-TE4U 10.4" HD/SD rackmount monitor, 4RU, 1024xRGBx768 2068	3.85
V-R1042-IMD-TE4U (2) 10.4" HD/SD monitors in 4RU rack unit, 1024xRGBx768 3444	.25
V-R171X-IMD-HDSDI 17" HD/SD rackmount monitor, 6RU	.85
V-R201-IMD-TE 20" HD/SD rackmount monitor, 6RU, 1680xRGBx1050).85
VP-LCD171H-ST-01 VESA mount stand w/pivot and tilt for 20", 23" monitors 182	2.85
NCB-2010 Network control box for -IMD monitors	3.85
V-R171X-IMD-HDSDI 17" rackmount monitor, 6RU, 1920xRGBx1200	3.85
QV171X-HDSDI 17" HD rackmount Quad Viewer monitor, 6RU, 1920x1200 3448	3.85
V-ST15 Desktop stand for Quad Viewer monitors	.44
V-R171X-DLW 17" Dual link/waveform monitor, 1920x1200	3.85
V-R261-DLW	ALL





Everything you need ...



Versatile and Affordable Pro Cameras

Whether your application is Broadcast Studio, ENG, Production, Educational, Corporate, or Event, ProHD cameras deliver superb image quality along with unmatched versatility in the form factor you need. And want. Nothing makes the transformation from SD to HD smooth and affordable like ProHD. You'll have the flexibility to record broadcast-quality HD footage in multiple file formats directly to off-the-shelf, affordable memory cards. In addition, JVC's native file recording serves up the fastest, shoot-to-edit workflow and promises the outstanding performance you can always count on from JVC.



True to Life Monitors



JVC's Vérité Series of professional studio and field monitors deliver exceptional true-to-life picture quality, flawless color reproduction in each model, and screen sizes ranging from 9-inch to 24-inch. You'll find a wide range of capabilities in the Vérité family including 3G and Dual-link inputs, waveform and vectorscope displays, digital closed captioning and 10-bit 4:4:4 video processing. And, of course, we know no matter what your needs you'll want JVC's proven reliability that's guaranteed built-in to every monitor.

















































1	Hamito II	S		9800920	3
					H
					Н
				2	Т
	Custom I	1	Swaw 5	100	
	******			(5) (6)	Ш

MARSHALL ELECTRONICS PROFESSIONAL LCD RACK MOUNT MONITORS These come in a wide variety of size and mounting arrangements. Displays are ightweight, have a shallow depth, run cool and tilt for optimum viewing. Many models feature TFT MegaPixel™ displays for better images and pixel density compared to other monitors. Configurations are available with HDSDI, SDI, DVI, Component HD/SD, and composite video inputs.

- · · · · ·		
ITEM	DESCRIPTION	PRICE
V-R43P	Triple 4" in 2RU, composite ins on each	.006.25
V-R44P	Four 4" in 2RU, composite ins on each	263.85
V-R573P	Triple 5.7" in 3RU, 2 composite ins on each	378.85
V-R653P-HDSDI	Triple 6.5" HD in 3RU, SDI/HDSDI inputs, composite & component ins 3	103.85
V-R70P-HDSDI	Standalone 7" HD widescreen 1.2 TFT-Megapixel, video	
	assist monitor, HDSDI/SDI ins	608.85
V-R70-1M	Rackmount adapter for V-R70P units	59.80
V-R72DP-2C	Dual 7" widescreen in 3RU, 2 composite ins on each	608.85
V-R72P-2HD	Dual 7" multiformat widescreen 1.2 Megapixel in 3RU, has composite,	
	S-video, component HD/SD(YPbPr) & HD/SDI ins on each	161.35
V-R82SB-AFHD	Dual 8.4" backlit/for outdoor use in 4RU, 800x600, with	
	HDSDI/SDI, component, composite, S-video, DVI, SXGA ins on each	CALL

V-LCD15SB-AFHD-DT V-LCD651STX-HDA

MARSHALL ELECTRONICS PORTABLE FIELD MONITORS These models are designed for outdoor and high ambient light situations. The LCD70XP and LCD651STX models have expanded hi-definition input options (HDMI, 3GSDI, e.g.), false color exposure assist, and peaking filter focus assist. The LCD651STX and LCD70XP models are also available with Canon. JVC. Panasonic and Sony battery mounts.

are also available iiii	in carron, or c, randoome and bon, batter, meanter	
ITEM	DESCRIPTION	PRICE
Sunbright Models		
V-LCD65SB-HDA	.6.5" Hi-res Sunbright monitor, RGB, 640x480	1493.85
V-LCD84SB-AFHD	.8.4" Hi-def Sunbright monitor, RGB, 800x600,	
	also has SDI/HDSDI, VGA, DVI & S-Video inputs	1608.85
V-LCD15SB-AFHD-DT	.15" Hi-def Sunbright monitor, 1024x768, also has SDI/HDS	DI,
	VGA, DVI & S-Video inputs, includes desktop stand	
5" Model		
V-LCD50-HDMI	.5" HDMI camera-top monitor, 800x480, powered w/AA batti	eries 516.35
6.5" Models		
V-LCD651STX-HDA	.6.5" Hi-res camera-top monitor, 1024x768	1528.35
V-LCD651STX-HDA-AB	.As above w/Anton Bauer battery adapter	1631.85
V-LCD651STX-HDA-VM .	.As above w/V-Mount battery adapters	1631.85
V-LCD651STX-HDMI	.6.5" Hi-res camera-top monitor w/HDMI in, 1024x768	1608.85
V-LCD651STX-HDMI-AB	.As above w/Anton Bauer battery adapter	1723.85
	.As above w/V-Mount battery adapters	
V-LCD651STX-3GSDI	.6.5" Hi-res camera-top monitor w/3G/HD/SD in, 1024x70	58 1769.85
V-LCD651STX-3GSDI-AB.	.As above w/Anton Bauer battery adapter	1884.85
V-LCD651STX-3GSDI-VM.	.As above w/V-Mount battery adapter	1884.85
7" Models		
V-LCD70XP-HDMIPT	.7" Hi-res camera-top monitor w/HDMI in, 800x480	895.85
V-LCD70XP-HDMIPT-AB	.As above w/Anton Bauer battery adapter	1010.85
V-LCD70XP-HDMIPT-VM.	.As above w/V-Mount battery adapter	1010.85
V-LCD70XP-3GSDI	.7" Hi-res camera-top monitor w/3G/HD/SD in, 800x480	987.85
V-LCD70XP-3GSDI-AB.	.As above w/Anton Bauer battery adapter	1102.85
V-LCD70XP-3GSDI-VM	.As above w/V-Mount battery adapter	1102.85

Follow us!

Marshall Electronics

MARSHALL ELECTRONICS LYNXTM SERIES LCD MONITORS Displays are lightweight, shallow in depth, run cool and tilt for viewing. Many models feature TFT MegaPixel™ displays offering the highest pixel density for improved images compared to similar CRT and standard LCD products. Available in 10" to 19" displays. Significant improvements



have been made to brightness, contrast ratio, and viewing angles. Various input configurations available. MegaPixel models feature screens calibrated to SMPTE/ IBU standards for color gamut and color temperature.

ITEM	DESCRIPTION	PRICE
M-LYNX-10	10" 4:3 LCD monitor, 800x600 w/composite,	
	S-video, VGA & stereo inputs	306.03
M-LYNX-10W	10" TFT 16:9 LCD monitor w/rear speakers, remote control,	
	1024x600, composite, S-video, DVI, VGA & stereo audio inputs	368.81
M-LYNX-15	. 15" 4:3 LCD monitor w/speakers, 1024x768, (2) composite,	
	component, S-video, VGA, DVI and (2) audio inputs	413.65
M-LYNX-17	17" 5:4 LCD monitor w/speakers,1280x1024, (2) composite,	
	component, S-video, VGA, DVI and (2) audio inputs	447.28
M-LYNX-17SDI	17" 4:3 LCD monitor w/ SD-SDI BNC loop-thru	265.61
M-LYNX-19	. 19" 5:4 LCD monitor w/speakers, 1280x1024, (2) composite,	
	component, S-video, VGA, DVI inputs and (2) audio inputs	548.17
M-LYNX-19SDI	. 19" 5:4 LCD monitor w/ SD-SDI BNC loop-thru	344.08



MARSHALL ELECTRONICS ORCHID® SERIES RACKMOUNT BROADCAST LCD MONITORS This series of rackmount monitors not only integrates interchangeable components or DVI input modules, but is also packed with additional features such as re-clocked outputs, auto-sensing HDSDI inputs, real-time waveform monitors and color vectorscopes, tri-color tally indicators, adjustable color temperature, timecode, precision gamma settings, adjustable clipping indicators, and more. All models are capable of de-embedding & displaying up to 16 channels of audio, any 2 channels of which can be monitored at one time. Each unit comes with at least one HDSDI input, one HDSDI output, and one input slot per screen, and stereo audio 3.5mm outputs

OR-434Four 4.3" monitors, 2RU, 5 assignable function keys & 1 joystick menu system, 800x480OR-503Three 5" monitors, 3RU, 6 assignable buttons/screen,	
OR-503 Three 5" monitors, 3RU, 6 assignable buttons/screen,	
	. CALL
	. CALL
4 assignable rotary encoders, 5-button menu system, 800x480	
OR-701ASingle 7" monitor, 3RU, dual HD/SD-SDI inputs, stereo speakers,	
11 assignable function keys, 4 assignable rotary encoders,	
5-button menu system, 800x48024	13.85
OR-702Two 7" monitors, 3RU, 11 assignable function keys, 4 rotary	
encoders, 5-button menu system, 800x48033	10.85
OR-841-HDSDI Single 8.4" portable field monitor, 4RU, 1024x768,	
	58.85
OR-901-XDI9" monitor, rack/camera mountable, 4RU, HD-SDI/HDMI, 3D ready 32	76.35
OR-YPR Optional component input module	28.85
OR-DVI Optional DVI-I input module	82.85

BTLH1760

<u>Panasonic</u>

PANASONIC BROADCAST LCD MONITORS

Designed for critical broadcast and production applications as reference grade HD and SD monitors

applications as re-	reference grade fib and 5b monitors.	
ITEM	DESCRIPTION	PRICE
BTLH910GJ	9" HD/SD LCD 15:9 EVF monitor, 1280x768, HD/SD-SDI, HDMI,	
	BNC, & D-Sub inputs, 3.7lbs	. 2383.56
BTLH1760PJ	17" LCD monitor (16:9), 1280x768, Vectorscope/WFM, DVI-D &	
	(2) HD-SDI/SDI inputs, embedded audio, time code/CC capable,	
	and desk stand, 13.7lbs	CALL
BTLH2550PJ		
	(2) HD-SDI inputs, composite, component, vectorscope, 18.1lbs	. 3382.56
Accessories		
BT-MOUNT	Camera monitor mount for BTLH910GJ	153.60
MO-LH910B	Porta-Brace flat screen monitor case for the BTLH910G, black	181.41
BTMA1710G	Rackmount adapter for BTLH1760, 2RU	247.20
	Thermodyne case for BTLH1760	
	Travel case for BTLH2550	
0.11.6		

Call for more accessories.

COMPUTER AV

||||0

LIGHTS

ACCESSORIES

Panasonic

PANASONIC PROFESSIONAL PLASMA DISPLAYS & HOSPITALITY PLASMA DISPLAYS

	TH65PF30U	TH60PF30U	TH50PF30U	TH42PF30U	TH50PH30U	TH42PH30U
DISPLAY	1080p			HD Model		
SCREEN SIZE (DIAG.)	64.7 inch	60.1 inch	49.9 inch	41.6 inch	49.9 inch	41.6 inch
3D READY		Ye	s		No	
EFFECTIVE DISPLAY AREA (W x H)	56.5" x 32.8"	52.3 x 29.4"	43.5" x 24.5"	36.3" x 20.4"	43.6" x 24.5"	36.3"x 20.4"
RESOLUTION (H x V)		1920 x 108	30 pixels		1024 x 768 pixels	1024 x 768 pixels
CONTRAST RATIO (BRIGHT AREA)	Max 5,000,000:1 Max 2,000,000:1			00,000:1		
PC SIGNAL COMPATIBILITY					VGA, WVGA, SVGA, XGA, VXGA, SXGA, UXGA, WUXGA	
VIDEO SIGNAL COMPATIBILITY		525 (480)/60i, 60p; 625 (575)/50i, 50p; 625 (576)/50p; 525 (480)/60i, 60p; 625 (575)/50i, 50p; 625 (576)/50p; 750 (720)/60p, 50p; 625 (676)/50p; 750 (720)/60p; 750 (720)/6			p; 625(576)/50p; 750(720)/60p, 50p, 5p, 30p, 60p, 50p, 1250(1080)/50i	
INPUT/OUTPUT						
PC/IN AUDIO	Mini D-sub 15pin x 1, Plug & Play (VESA DDC 2B), M3 jack x 1					
SERIAL		D-sub 9pin x1, external control, RS232C compatible				
INTERCHANGEABLE TERMINALS						
SLOT 1			Va	cant		
SLOT 2	Vacant					
BUILT-IN TERMINAL		Composite In w/ st	ereo audio, Component/RGB I	n (BNCx3) w/ stereo audio, HD	MI, DVI-D w/audio	
SOUND/AUDIO OUT	20W (10W + 10W)			16W (8W + 8W)		













TYFB10WPU





TYST20K





Visit fullcompass.com today!

UP TO 100,000-HOUR PANEL LIFE (SEE CHA	ART ABOVE)
ITEM DESCRIPTION	PRICE
Professional Plasma Models – up to 100,000 hou	ur panel life
TH65PF30U 65" HD plasma display, 1080p, bla	ack 2879.36
TH60PF30U 60" HD plasma display, 1080p, bla	ack2007.96
TH50PF30U50" HD plasma display, 1080p, bla	ack 1379.27
TH42PF30U	ack1096.20
TH50PH30U50" HD plasma display, black	845.74
TH42PH30U42" HD plasma display, black	618.00
Partial List of Accessories/Terminal Boards for Pr	o Series
TYFB10HMD Dual HDMI terminal board (slot 1 o	or 2) 170.30
TY42TM6G RGB active through terminal board	d (slot 1 or 2)157.01
TYFB11DD DVI-D terminal board (slot 1 or 2).	157.01
TYFB9RT IR through terminal board (any slo	ıt)138.90
TY42TM6P PC input terminal board (any slot)	
TYFB9BD BNC dual video terminal board (slo	ot 1 or 2)163.05
Continued in next column	

Continued from previous column...

TYFB9BD

ITEM	DESCRIPTION	PRICE
TY42TM6B	BNC composite video terminal board (slot 1 or 2)	144.94
TY42TM6Y	Composite/component video terminal board	
	(slots 1&2, or slots 2&3)	251.22
TY42TM6Z	RCA component video terminal board (any slot)	107.49
TY42TM6V	RCA composite video terminal board (slot 1 or 2)	144.94
TYFB11DHD	Dual Link HD-SDI board (slot 1 or 2)	2631.80
TYFB10HD	HD-SDI terminal board w/audio (slot 1 or 2)	1632.95
TYFB9HD	HD-SDI terminal board (slot 1 or 2)	1316.50
TYFB10WPU	Wireless presentation board (slots 1&2, or slots 2&3),	
	c(IEEE802.11b/11g)	339.39
Miscellaneous Ac	cessories	
TYAR65P9W	Anti-glare filter for TH65PF30U	845.46
TYTP65P10S	Touch Panel for TH65PF30U	CALL
TYTP42P10S	Touch Panel for TH42PH30U	2397.88
TYST20K	Pedestal stand for TH50PF30U/TH42PF30U/TH50PH30U/TH42PH	30U 163.05
TYWK65PR20	Wall hanging bracket, angled	376.83

TYWK65PR20

















































BRAVIA® LED INTERNET TELEVISIONS These slim LED TV's feature Full HD 1080p for picture detail and Edge LED backlighting for better contrast. Enjoy wireless access to Sony Entertainment Network, YouTube and more with the included Wi-Fi adaptor.



Digital Noise Reduction enhances detail while MotionFlow™ XR 240 technology will smooth out fast camera motion. Audio power output is 8W+8W (10W+10W on KDL55EX640). This series includes analog audio (2 in/1 out), (1) component and (2) composite inputs, digital audio out, (4) HDMI, PC in, USB and Ethernet.

(=)				
ITEM	DESCRIPTION	PRICE		
KDL40EX640	40" 1080p LED HDTV w/ MotionFlow	899.99		
KDL46EX640	46" 1080p LED HDTV w/ MotionFlow	1199.99		
KDL55EX640	55" 1080p LED HDTV w/ MotionFlow	1799.99		

SONY PROFESSIONAL LCD COLOR MONITORS

An extensive line-up of SD and SD/HD professional LCD monitors from 15" to 42" featuring fast video response, extremely high brightness, contrast, color



depth and wide viewing angle. A one-piece construction that includes integrated stand. The LMD4251TD add 3D capability, 3D glasses required. All models are ideal for HDV production applications with some models supporting HDMI or DVI.

ITEM	DESCRIPTION	PRICE
LMD1510W	15.6", 1366x768, HDMI, Composite, Component, Y/C, SDI	752.75
LMD1530W	15", 1280x768, HDMI, SDI, Composite, Y/C and RGB	1078.77
LMD1541W	15", 1280x768, HDMI, SDI, Composite	2123.43
LMD1751W	17", 1280x768, DVI-D, SDI	2259.96
LMD2110W	21.5",1920x1080, HDMI, SDI, Composite, Y/C and RGB	951.06
LMD2451W	24", 1920x1200, DVI inputs, Composite, Y/C and RGB	CALL
LMD2451WHD	LMD2451W packaged with BKM243HS HD/SD SDI adapter	CALL
LMD4251TD	42", 1920x1200, 3D, DVI inputs, Composite BNC	CALL
Accessories		
MB533	Rackmount kit for LMD1530W	225.50
MB534	Rackmount kit for LMD1541W	188.51
BKM243HS	HDSDI/4:2:2 SDI input adapter, for LMD2051W, LMD2451W	1030.38
TDGBR250/B	3D glasses	48.00

SONY PVM SERIES OLED PROFESSIONAL VIDEO MONITOR The PVM series uses a 960x540 OLED (Organic Light Emitting Diode) panel, which creates true blacks and higher contrast than LCDs. Picture quality is excellent both indoors and outdoors. Supports broadcast standards SMPTE-C, EBU, and ITU-R BT.709, with resolutions from NTSC/PAL to 1080p60. The PVM740 comes standard with one



composite, one auto detecting SDI/HDSDI/3G input, one HDMI input, internal waveform monitor, 1/4" and 3/8" holes for camera mounting, and AC power adapter.

ITEM	DESCRIPTION	PRICE
PVM740	7 1/4" OLED professional monitor	2243.21
PVM1741	17" OLED monitor, (2) 3G/HD/HD-SDI, HDMI & cor	nposite inputsCALL
PVM2541	25" OLED monitor, (2) 3G/HD/HD-SDI, HDMI, & co	mposite inputsCALL
VF510	ENG field kit for PVM740L	385.14
MB531	Rackmount kit	288.86

SONY FWD SERIES HD LCDS These public display HD LCD's have slim bezels for a more refined and stylish look for signage. Incorporating high-quality, professional 47" and 42" (diagonal) LCD panels, they offer full HD (1920x1080) resolution and high brightness for use in bright light conditions. They support audio in/out (pinjack), DVI-D, composite video out, Ethernet, HD component I/O, S-Video, and video-in interfaces. Also equipped with a network port for remote control/monitoring. An



option slot accepts a range of adapters for versatility. Well suited for retail shops, shopping malls, hospitals or schools. The FWDS42B1 is a low power consumption (120W) model and has DVI-D & HDMI input and remote control.

ITEM	DESCRIPTION .42", slim HD LCD	PRICE
FWDS42H1	. 42", slim HD LCD	1520.55
	. 47", slim HD LCD	
FWD42B2	. 42" slim HD LCD, low power consumption model	1303.95
BKMFW15	. HDMI input adapter	150.92
BKMFW16	. SDI/SDI input adapter	879.89



ITEM



TOTE VISION LCD MONITORS

DESCRIPTION

4" to 5.6" Monitors

All include LED backlight for better color saturation and longer life.
LCD400X4 Four 4" LCD units in 19" rackmount kit, tilts 90°, NTSC/PAL, 2RU 1211.00 LCD410 4" field monitor with audio, battery pack, NTSC ... LCD411 As LCD410, adds BNC in/out... LCD501 5" field monitor with stereo audio headphone jack, NTSC/PAL. 310.00 RM501. EIA standard 19" rackmount kit for 3 units LCD-501, 3RU.... . 116.00 LCD560X3 ... Three 5.6" LCD units in rackmount kit, tilts 90°, NTSC/PAL, 3RU... 1306.00 5.6" field monitor with audio, battery pack, NTSC/PAL LCD562. 380.00 LCD565 As LCD562, adds BNC 380.00 - 8" Monitors LCD703HD. . HD 7", 16:9, DVI, component in/out, S-Video in/out, BNCin/out, 1080p... 754.00 LCD703HD-KIT..... LCD-703HD with rechargeable battery pack, tote bag, and AC..... LCD703HD1. 1 LCD-703HD in rackmount kit, 3RU LCD703HD2 2 LCD-703HD in rackmount kit, 3RU. LCD703HDA LCD-703HD with Anton Bauer QRC-Gold mount 741.00 LCD703HDV LCD-703HD with "V" lock mount for IDX batteries ... 714.00 LCD842HD. . HD 8.4", 4:3 with 16:10 capability, composirt, component, S-Video, VGA, HDMI.... 942.00 LCD842HD2 .Two 8" LCD in rackmount kit, no audio, 4RU...... 10.4" MONITORS .. 9.7", 2x composite in/out, 2x speakers, 1024x768... LED1002HD. .811.00 15.4" MONITORS LCD1560HD. . 15.4", 16:9, audio, composite, component, S-Video analog RGB, HDMI, 795 00 RS232, supports 1080p/i, 720p & 480p/i..... LCD1560HDR LCD-1560HD in rackmount kit, 6RU... 795.00 19" MONITORS LCD1901HD.. . 19" in metal case, 16:9, audio, S-Video, component, NTSC/PAL, RGB, RS232, 1080p... 975.00 LCD1901HDRLCD-1901HD in rackmount kit, 7RU...



TV ONE PROFESSIONAL RACK MOUNT LCD

MONITORS The LCD monitors are available in a wide variety of screen sizes and input configurations to satisfy most applications. All LCD panels used are



PRICE

top grade, professional products. High brightness and contrast ratios are standard features, along with wide viewing angles. All models are 4:3 aspect ratio.

. 0		
ITEM	DESCRIPTION	PRICE
LM401M	Single 4.0", dual-composite inputs, metal case	293.25
LM404R	Quad 4", composite and S-video inputs, tilt rackmount	1440.75
LM563R	Triple 5.6", composite and S-video inputs, tilt rackmount	1695.75
LM701M	Single 7" w/ dual composite inputs, metal case, Vesa	505.75
LM1042R	Dual 10.4", composite and PC SVGA, optional expansion	
	to SXGA & all HDTV rackmount	2290.75
LM1511R	Single 15" composite, S-video, PC, stereo, XGA tilt	
	rackmount, VESA mount	1270.75
LM1911R	Single 19" composite, S-video, PC, stereo, SXGA tilt	
	rackmount, VESA mount	1610.75
LM1920R	Single 19", composite, S-video, PC, stereo, VESA mount	930.75

vaddi0

VADDIO PREVIEW RACK MOUNT MONITORS

Excellent rack mount monitors for a variety of applications that require high resolution monitoring of HD/

SD cameras. Color, contrast, brightness, and On/Off controls per LCD (except PREVIEW-QUAD-4). The HD monitors offer 16:9 LCD screens, VGA input, and tally indicators. Other features include Component, S-Video and composite inputs, with loop-thru outputs. The SD monitors offer active matrix LCD screens and inputs with active looping outputs on BNC connectors.

ITEM	DESCRIPTION	PRICE
PREVIEW-DUAL-6.4	Dual 6.4" LCD rack mount monitor, 3RU	1148.40
PREVIEW-TRIPLE-5.6	Triple 5.6" LCD rack mount monitor, 3RU	1071.60
PREVIEW-QUAD-4	Quad 4" LCD rack mount monitor, 2RU	994.80
PREVIEWHD-DUAL-7	Dual 7" LCD rack mount monitor, 3RU	2034.00
PREVIEWHD-TRIPLE-5	Triple 5" LCD rack mount monitor, 3RU	2274.00

VariZoom

VARIZOOM VZ-TFT7 16:9 7" ON-CAMERA MONITOR

An external video display allowing more free movement away from camera with a generous 30°/60° viewing angle. Can use for most aspect ratios and has RCA video and 2.1mm 12V DC input. 10W max power consumption. Includes AC adapter and 4' RCA cable.







