



QSC PROCESSING AMPLIFIERS These powerful four-channel amplifiers, each with onboard DSP, have the capability to configure and combine channels in various ways to drive a wide range of loudspeaker systems. The CXD series is designed for installed sound applications, including 70V/100V systems while the PLD series is designed for portable live sound use. All models feature Flexible Amplifier Summing Technology™ (FAST) which actively distributes the total amplifier power in various configurations across one, two, three or all four outputs. They also use QSC's next-generation Class-D power amp design in combination with a custom power stage utilizing a new MOSFET output device which offers high voltage operation with better audio quality and thermal performance. The onboard DSP offers four channels of crossover filters, parametric EQ, alignment delay and dynamics processing. Additionally, when using QSC speakers, these amplifiers offer Intrinsic Correction™, a combination of filtering, limiting and speaker processing that compensates for the non-linearities in array and horn design, resulting in exceptional performance. CXD series I/O is provided via Phoenix Connectors, while the PLD series has XLR inputs and Speakon outputs.

ITEM	DESCRIPTION	PRICE
Installed Sound Models		
CXD4.2-NA	4-channel power amp, 400W @ 4Ω	1900.00
CXD4.3-NA	4-channel power amp, 625W @ 4Ω	2500.00
CXD4.5-NA	4-channel power amp, 1150W @ 4Ω	3100.00



ITEM	DESCRIPTION	PRICE
Portable Live Sound Models		
PLD4.2-NA	4-channel power amp, 400W @ 4Ω	1399.99
PLD4.3-NA	4-channel power amp, 625W @ 4Ω	1899.99
PLD4.5-NA	4-channel power amp, 1150W @ 4Ω	2399.99

QSC RMX SERIES

Compact and powerful, taking only 2 rack spaces, quiet with variable speed rear to front fan cooling. Front panel level controls, XLR/TRS/Barrier Strip inputs, Speakon and binding post outputs. Independent-user definable clip limiters and selectable low cut filters.



ITEM	(ST/CH) 8Ω	4Ω	2Ω	WEIGHT	PRICE
RMX850A	200W	300W	430W	35 lbs.	399.99
RMX1450A	280W	450W	700W	40 lbs.	529.99
RMX2450A	500W	750W	1200W	44.5 lbs.	749.99
RMX4050A	800W	1400W	2000W	68 lbs.	1499.99
RMX5050A	1050W	1600W	2000W	75 lbs.	1699.99

QSC POWERLIGHT 3 SERIES

This series has 3 models ranging in power from 1250W to 4000W per channel at 2Ω. All are 2RU, only 15.6" deep and 22 lbs. They feature high-efficiency switchmode power supplies, DataPort for remote computer control, removable knobs with lock-out security plate, user-defeatable clip limiters and selectable low-frequency filter per channel, 3 selectable input gains, front and rear panel LEDs to indicate switch settings, Parallel Dataport, XLRM and XLRF connectors, and Speakon and "Touch Proof" binding post outputs.



ITEM	(ST/CH) 8Ω	4Ω	2Ω	WEIGHT	PRICE
PL325	500W	850W	1250W	22 lbs.	1377.00
PL340	800W	1250W	2000W	22 lbs.	1597.00
PL380	1500W	2500W	4000W	24 lbs.	2358.00

QSC PLX2 SERIES POWER AMPLIFIERS

Premium quality high-power amplifiers combining light-weight, superlative audio quality and proven QSC reliability. The "02" models support 2Ω loading for users who need to drive up to 4 loudspeakers from each amplifier channel, or when extremely high power bridge mono operation is required. Models feature built-in subwoofer processing, filter switches, and front panel indications of bridge mono status. The compact "04" models are designed to power 1 or 2 speakers from each amplifier channel (4Ω minimum loading). Weighing just 13 pounds these "plug-and-play" amplifiers are perfect for ultra-portable rigs, as well as reference-quality playback. All models feature balanced XLR and 1/4" TRS input connectors, and Speakon NL-4 output connectors.



ITEM	(ST/CH) 8Ω	4Ω	2Ω	PRICE
PLX1104	325W	550W	N/A	629.99
PLX1804	600W	900W	N/A	739.99
PLX1802	330W	575W	900W	899.99
PLX2502	450W	750W	1250W	949.99
PLX3102	600W	1000W	1550W	1059.99
PLX3602	775W	1250W	1800W	1259.99

QSC GX SERIES PROFESSIONAL POWER AMPLIFIERS

For those who need superior performance and portability for less. All models supply maximum possible power to 4Ω and 8Ω loads. The GuardRail™ feature protects the amp and speakers from overdrive or temperature-related damage without shutting down the system. Has XLR, 1/4" TRS and phono input connectors, Speakon combo output connectors (accepts 1/4" TS plugs or Speakon 2-pole and 4-pole plugs), and binding post outputs. The GX7 features PowerLight supply in its Class 'H' output section for more overall output power.

ITEM	8Ω/2 CHNLS	4Ω/2 CHNLS	8Ω/1 CHNL	4Ω/1 CHNL	PRICE
GX3	300W	425W	350W	550W	299.99
GX5	500W	700W	600W	850W	399.99
GX7	725W	1000W	800W	1200W	599.00



ART SLA SERIES POWER AMPLIFIERS

Units are self-contained in a steel enclosure, with XLR, 1/4" TRS, and Euroblock balanced (except SLA1) inputs and binding post outputs. SLA1 and SLA2 are 2-channel units, while the SLA4 has 4 channels and can be switched easily from multi-channel, stereo and bridged mono modes.

ITEM	(ST/CH) 8Ω	4Ω	PRICE
SLA1	100W	130W	269.00
SLA2	200W	280W	369.00
SLA4	4x 100W	140W	439.00

Shop fullcompass.com today!

For expert advice - call: 800-356-5844

M-F: 9:00-5:30 Central



- AUDIO
- VIDEO
- COMPUTER AV
- LIGHTS
- ACCESSORIES



behringer

BEHRINGER iNUKE SERIES POWER AMPLIFIERS

These amps pack massive amounts of output power into exceptionally lightweight, rack-mountable packages. High-density Class 'D' technology combined with switch-mode power supplies means these amplifiers drive your rig effortlessly. Efficient power supplies eliminate the need for heat sinks and toroid transformers, drastically reducing the weight of these amps. All channels feature positive-detent gain controls with signal and clip LED indicators. I/O includes combo XLR and 1/4" TRS inputs and professional twist-lock speaker outputs. Other features include dual mono/stereo/mono bridge modes, a built-in crossover switch which allows biamp operation, subwoofer out and built-in overload protection. The DSP models add a DSP section featuring delay, crossover with 3 filter types – up to 48dB/octave, EQ, dynamics processing, USB interface for control/monitoring and lockable security settings.

ITEM	(ST/CH)	8Ω	4Ω	2Ω	WT	PRICE
Standard iNUKE Models						
NU1000	150W	300W	500W	7 lbs	149.99	
NU3000	440W	880W	1500W	7 lbs	229.99	
NU6000	1500W	3000W	n/a	12 lbs	349.99	
DSP Models						
NU1000DSP	150W	300W	500W	8 lbs	199.99	
NU3000DSP	440W	880W	1500W	8 lbs	279.99	
NU6000DSP	1500W	3000W	n/a	12 lbs	399.99	



BEHRINGER EUROPOWER EPQ SERIES POWER AMPLIFIERS

Reliable and rugged, the new EPQ power amps utilize ATR (Accelerated Transient Response) technology and independent limiters for each channel to achieve punch and clarity. Combines maximum output level with reliable overload protection and a variety of I/O options. Mono, stereo, or mono bridged 4Ω or 8Ω operation offers ample power and high-tech efficiency in an all-steel rack-mountable chassis.

ITEM	DESCRIPTION	PRICE
EPQ304	4-channel power amplifier, 300W @ 4Ω, 1RU	229.99
EPQ450	2-channel power amplifier, 460W @ 4Ω, 1RU	149.99
EPQ900	2-channel power amplifier, 900W @ 4Ω, 1RU	179.99
EPQ1200	2-channel power amplifier, 1,200W @ 4Ω, 2RU	249.99
EPQ2000	2-channel power amplifier, 2,000W @ 4Ω, 2RU	299.99



LAB.GRUPPEN

LAB GRUPPEN IPD SERIES POWER AMPLIFIERS

With high sustained power output, exemplary performance and robust build quality, the IPD series offer everything you'd expect from Lab Gruppen products. Both models have analog and AES digital inputs, on-board DSP, 4-channel input mixers, horizontal VU meters, software configurable limiters, as well as binding post and Neutrik outputs. An Ethernet connection allows for monitoring and control via a computer at FOH or with a freely roaming iPad by using a WiFi router. All setup parameters for input mixing, DSP features and limiter setting are accessible on the front panel using two navigation buttons, a rotary encoder and the backlit display.

ITEM	(ST/CH)	8Ω	4Ω	2Ω	PRICE
IPD-1200	300W	600W	500W	CALL	
IPD-2400	600W	1200W	800W	CALL	



ASHLY

ASHLY NX SERIES POWER AMPLIFIERS Reliable, powerful amplifiers that pack up to 12,000-Watts total power into a compact 2RU package and are available in 2- and 4-channel configurations. Class 'D' amplifier technology and switch-mode power supply. The nX series features Neutrik® combo jack and Euroblock input connectors, SpeakOn® output connectors, high pass filter, limiter and per-channel remote DC level control. The networkable nXe series adds Ethernet/serial data control, aux preamp outputs, preset recall and fault condition logic outputs, all controlled with Ashly's Protea™ software. Optional Cobranet®, Dante® or AES3 digital audio inputs are available. The flagship nXp series adds 32-bit SHARC DSP processing (@ 48/96kHz), onboard signal generator and precision swept load impedance monitoring. Models ending in 2 are 2-channel versions.

POWER (PER CH)	70V	100V	2Ω	4Ω	4Ω(BRIDGED)	8Ω	PRICE
nX Series							
NX1.52	1500W	1250W	1500W	1500W	3000W	1250W	1950.00
NX1.54	As above, 4-channel version						3150.00
NX3.02	2450W	1250W	3000W	2000W	6000W	1250W	2540.00
NX3.04	As above, 4-channel version						4250.00
NX4002	400W	400W	400W	400W	800W	400W	1115.00
NX4004	As above, 4-channel version						1800.00
NX8002	800W	800W	800W	800W	1600W	800W	1475.00
NX8004	As above, 4-channel version						2385.00
nXe Series (Networkable)							
NXE1.5	1500W	1250W	1500W	1500W	3000W	1250W	2575.00
NXE1.54	As above, 4-channel version						3910.00
NXE3.02	2450W	1250W	3000W	2000W	6000W	1250W	3170.00
NXE3.04	As above, 4-channel version						CALL
NXE4002	400W	400W	400W	400W	800W	400W	1620.00
NXE4004	As above, 4-channel version						2410.00
NXE8002	800W	800W	800W	800W	1600W	800W	1980.00
NXE8004	As above, 4-channel version						2995.00
nXp Series (Networkable with DSP)							
NXP1.52	1500W	1250W	1500W	1500W	3000W	1250W	2930.00
NXP1.54	As above, 4-channel version						4265.00
NXP3.02	2450W	1250W	3000W	2000W	6000W	1250W	3520.00
NXP3.04	As above, 4-channel version						CALL
NXP4002	400W	400W	400W	400W	800W	400W	1910.00
NXP4004	As above, 4-channel version						2700.00
NXP8002	800W	800W	800W	800W	1600W	800W	2270.00
NXP8004	As above, 4-channel version						3285.00



EV Q-SERIES The Q-Series is based on EV's reference-standard P-Series. Designed for cost-limited, mobile applications or smaller installations. Neutrik Speakon® outs for channels A/B and active balanced XLR ins with paralleled XLR outs for easy signal routing. Includes rear-mounted, dB-scaled level controls, and is packed into 3RU zinc-plated steel housing.

ITEM	(ST/CH)	8Ω	4Ω	8Ω BRIDGED	PRICE
Q44-II	270W	450W	900W	729.00	
Q66-II	380W	600W	1200W	856.00	
Q99	550W	900W	1800W	1071.00	
Q1212	750W	1200W	2400W	1339.00	

YAMAHA

YAMAHA P SERIES AMPS

The upgraded P series feature high output in a 2 rack-space unit. All units have XLR balanced and 1/4" TRS balanced inputs, Speakon/binding post/1/4" outputs, low cut filtering and integrated subwoofer crossover and YSP speaker protection circuitry.

ITEM	(ST/CH)	8Ω	4Ω	2Ω	PRICE
P2500S	250W	310W	650W	419.99	
P3500S	350W	450W	1000W	529.99	
P5000S	500W	700W	1300W	629.99	
P7000S	700W	950W	1600W	749.99	



Follow Us!

PRICES SUBJECT TO CHANGE WITHOUT NOTICE. Call today or shop online!

Discover True Balance.



As you climb, uncertainty can set you on the wrong path. Count on Ashly nX to get to the top.

When you're ready to choose a power amplifier for your next install, you have choices. You can take the route of many before, or you can chart your own course—based on careful research, budgetary planning and sound judgment. We're here to offer you a new direction to help you reach your goals.

Ashly nX offers three series of amplifiers: nX (base model), nXe (w/ Ethernet) & nXp (w/ Protea™ DSP) with a range of power to complete virtually any system. With features like Ashly EMS™ (Energy Management System), programmable High-Z & Low-Z speaker output, and network audio options like Dante™ or CobraNet™, you can count on nX to anchor your most demanding install.

We've expanded the nX family to include 400W and 800W models in 2 and 4-channel configurations. These medium output amplifiers are the perfect complement to the high-output 3,000W and 1,500W nX models.

At Ashly, we take pride in designing and building our amplifiers to exceed expectations and withstand the elements. Our goal is to give you years of audio clarity and uninterrupted service. So make a sound choice. When you choose Ashly nX, you choose a hand-built, US-made product backed by our team of engineers and an industry-leading 5-year warranty.



Design a custom remote interface with Ashly Remote for iPad®

Learn More About Ashly NX! Call Today!



800-356-5844
fullcompass.com



Ashly amplifiers and processors

- AUDIO
- VIDEO
- COMPUTER AV
- LIGHTS
- ACCESSORIES



CROWN XLI SERIES POWER AMPS

Affordable power amps designed for musicians, DJs, and entertainers as well as houses of worship, discos, and pubs. The 4 models in the series are identical except for output power. Features user-selectable input sensitivity of 0.755V or 1.4V, stereo/parallel/bridge-mono modes, fan speed-regulated forced-air cooling, power LED, and 6 LEDs that indicate signal presence, clip and fault for each channel. The amps incorporate protection against shorts, no-load, on/off thumps and radio-frequency interference. I/O consists of RCA and XLR inputs and Speakon® and binding post outputs.

ITEM	(ST/CH) 8Ω	4Ω	8Ω BRIDGED	PRICE
XLI800	200W	300W	600W	249.00
XLI1500	330W	450W	900W	349.00
XLI2500	500W	750W	1500W	449.00
XLI3500	1000W	1350W	2700W	849.00



CROWN XLS SERIES AMPS

The XLS Series of power amplifiers consists of four economical models, identical except for output power, depth and weight. All models feature Class 'D' amps, XLR, 1/4" and RCA inputs, integrated PureBand™ Crossover System, Peakx™ Limiters, forced-air fans, a switched-mode power supply, touchproof binding post and Speakon® outputs. They also have precision detented level controls, power switch, power LED, and 6 LEDs which indicate signal, clip and fault for each channel. Designed for 4Ω to 8Ω loads in stereo, and 8Ω in bridged mono mode. 3-year, no-fault, fully transferable warranty.

ITEM	DESC.	(ST/CH) 8Ω	4Ω	8Ω BRIDGED (MONO)	WT (LBS)	PRICE
XLS1000	2RU	215W	350W	700W	8.6	299.00
XLS1500	2RU	300W	525W	1050W	8.6	399.00
XLS2000	2RU	375W	650W	1300W	10.75	499.00
XLS2500	2RU	440W	775W	1550W	10.75	599.00



CROWN MACRO TECH I SERIES

Features Crown Audio's patented Class-I circuitry and studio-quality analog signal processing with built-in load, line voltage, input and output monitoring. Standard Ethernet networking (via HiQnet's System Architect®) allows the system to become operable from any location as well as providing integrated monitoring, and its global power supply delivers maximum power anywhere. A 3-year, no-fault, fully-transferable warranty is offered as well.

ITEM	(ST/CH) 8Ω	4Ω	8Ω BRIDGED	4Ω BRIDGED	PRICE
MA5000I	1250W	2000W	4000W	3600W	CALL
MA9000I	1500W	3000W	6000W	5000W	CALL
MA12000I	2100W	4000W	8000W	7000W	CALL



CROWN XTI2 SERIES These power amps feature Peak Plus™ limiters that allow full control over threshold, attack and release. Enhanced Subharmonic Synth allows you to manage frequency, gain and filter type for application-specific tuning. Amps have 29 user-defined presets, software visibility of AC line voltage and power supply temperature, and come with updated HiQnet Band Manager™ and System Architect™ control software. All units feature XLR inputs and speakon NLAMP binding post outputs.

ITEM	(ST/CH) 8Ω	4Ω	2Ω	8Ω BRIDGED	4Ω BRIDGED	PRICE
XTI1002	275W	500W	700W	1000W	1400W	499.00
XTI2002	475W	800W	1000W	1600W	2000W	699.00
XTI4002	650W	1200W	1600W	2400W	3200W	999.00
XTI6002	1200W	2100W	3000W	4200W	6000W	1999.00

SAMSON

SAMSON SXD SERIES POWER AMPLIFIERS WITH DSP

The SXD series features 3 models; the SXD3000 (450W per side @ 4 ohms), SXD5000 (750W per side @ 4 ohms) and the SXD7000 (1,000W per side @ 4 ohms). In addition to their power capabilities, each model guarantees crystal clear audio over a wide frequency spectrum of 20Hz-20kHz. They also feature editable advanced DSP settings including Crossover, Filter, EQ, Limiter, Delay and more, as well as presets ideal for DJ, live sound and commercial installations. Input connections are made via combo XLR-1/4" connectors and outputs are provided via Binding Post and Speakon™ connectors. All models feature multi-stage protection for power-up, over-heating, over-current, short-circuit, low output impedance and DC voltage.

ITEM	DESCRIPTION	PRICE
SXD3000	Power amp, 450W per side @ 4 ohms	349.99
SXD5000	Power amp, 750W per side @ 4 ohms	399.99
SXD7000	Power amp, 1,000 per side @ 4 ohms	499.99



SAMSON SERVO SERIES POWERED AMPS

The Servo 200, 201A, 300 and 600 amplifiers feature large 3-color level LED meters and independent channel volume controls. The rear panels include 1/4" balanced and RCA input connectors, as well as 5-way binding post and 1/4" speaker outputs. They also feature stage power protection circuitry that ensures optimal performance and protection of connected components. The 120A is the same as the above models with 5-segment, 3-color LED meters, headphone jack and is convection-cooled.

ITEM	DESCRIPTION	8Ω BRIDGED (MONO)	4Ω PER SIDE	PRICE
SERVO120A	1RU, convection-cooled	120W	60W	199.99
SERVO200	2RU	200W	100W	199.99
SERVO300	2RU	300W	150W	279.99
SERVO600	2RU	600W	300W	329.99



Follow Us!

Our Sales Pros will provide you with the solutions you need.

RUN THE SHOW



XLS Take command of center stage with Crown's new XLS amplifiers. The high-performance class-D amplifier combined with its integrated PureBand™ Crossover System deliver unmatched performance and sound; while its multiple inputs let you plug in anything you want. Peak[™] Limiters effortlessly protect your speaker investment, and at 12 pounds moving from show to show is a breeze. Powerful, flexible, portable, and reliable — **RUN THE SHOW** with a power amplifier designed to play hard all night long.



XLS



FULL COMPASS

PRO AUDIO VIDEO LIGHTING
MUSICAL INSTRUMENTS

800-356-5844
fullcompass.com

©2014 Crown International