

















































## AKG WMS420 WIRELESS MICROPHONE SYSTEMS

WMS420 is a highly flexible wireless solution, equally suitable for stage and locations where a single-channel or multi-channel solution is needed. The complete system consists of the SR420 stationary by HARMAN receiver, HT420 handheld transmitter and the PT420 pocket transmit-

ter. The HT420 is available with an optional D5 capsule which provides improved feedback rejection and decreased handling noise. Both transmitters feature charging contacts for easy recharging. It is available in three body pack configurations, a head worn set with a C555L condenser microphone, a presenter set with the C417L lavalier microphone and a guitar set that ships with an instrument cable. The WMS420-VOCAL configuration ships with a handheld microphone transmitter.

ORDERING INFO: BAND A	OPERATES IN 530.000-559.0 614.100-633.7	DOOMHz
U2	014.100-033.1	UUMINZ
ITEM	DESCRIPTION	PRICE
WMS420-HFADSFT	Wireless microphone system,	
TIMO IZO IIZIDOZI		349.00
WMC420 DDECENTED	Wireless microphone system,	
WW342U-FRESENIER		
		299.00
WMS420-INSTRUMENT	Wireless microphone system,	
	with instrument cable	299.00
WMS420-VOCAL	Wireless microphone system,	
	with handheld transmitter	

#### (A) audio-technica. always listening.

**AUDIO-TECHNICA 2000 SERIES UHF FREQUENCY-AGILE SYSTEMS** 

This series delivers professional performance, easy setup, automatic scanning, true diver-

sity reception, Tone Lock<sup>TM</sup> tone squelch & other advanced features at an affordable price. Any of its 10 channels may be used together, eliminating frequency coordination problems. The metal half-rack receiver features XLR & unbalanced 1/4" outputs, ground lift switch, an included rack-mount kit and detachable UHF antennas. The ATW-T220a handheld transmitter features the PRO 41 capsule for maximum feedback rejection & lasting dependability. Body pack transmitter has switchable 10mW/30mW RF output. Both body pack & handheld transmitters operate on 2 AA cells, for up to 9hrs of use. Under ideal conditions may yield up to a 300' operating range. Models shown below are in the "AD" band. For opposite band substitute "AI" for "AD" at end of part number.

ORDERING INFO		OPERATES IN THIS RANGE:	
AD Band, TVCH 45-48 656.125-678.500 MHz			
Al Band, TVCH 16-1	19	487.125-506.500 MHz	
ITEM	ITEM DESCRIPTION PRICE		PRICE
ATW-2110AD			. 299.00
ATW-2129AD	D Lavalier system, with AT829CW unidirectional lapel mic 349.00		
ATW-2192AD	TW-2192AD Head worn system, with AT892CW omni condenser head mic, black 549.00		. 549.00
ATW-2192AD-TH As ATW-2192, in beige		. 549.00	
ATW-2120AD	120AD Handheld system with ATW-T220 cardioid dynamic mic 349.00		
ATW-CHG2Two-bay recharging station for (2) ATW-T220 handheld			
	transmitters, and/or ATW	/-T210 body pack transmitters	
in any combination, with auto shut-off feature			
ATW-DA49 UHF (wideband 400-900MHz) active unity-gain antenna			
distribution system, provides (2) 1-in/4-out RF channels,			
	for ATW-2000/3000 serie	S	. 399.00
AT8630	Joining plate kit for (2) 2	000 series receivers	25.29

#### (A) audio-technica.

always listening...

**AUDIO-TECHNICA 3000 SERIES UHF** WIRELESS SYSTEMS The "C" and "D' bands in this series feature 996 selectable UHF frequencies ("I" band has 1001) in 25kHz steps with true diversity protection from RF hits and dropouts. Nine precoordinated frequency scan groups simplify

ORDERING INFO:

BC band, TVCH 25-3



selection of usable frequencies. Maximum operating range is up to 300'. Frequency response is 70Hz-15kHz. Receiver features XLR and 1/4" TS outs and a ground lift switch. Transmitters are powered by 2 AA batteries, for 6-8hrs of operation. Body pack features a backlit screen for low-light situations, a locking battery door, and 3-position sliding cover to prevent accidental shutoff or channel switching. It has a switchable RF power output of 10mW or 30mW. The handheld transmitter in the ATW-3141 system features the same dynamic capsule as the AE4100 microphone. The handheld transmitter in the ATW-3171 system features the same condenser capsule as the ATM710. The handhelds also feature dual color power/mute LEDs to indicate on/mute status. Systems are backed with a 2-year manufacturer warranty. (Models shown below are in the "D" band. For the "C" or "I" bands, replace the "BD" with "BC" or "BI".) Please call for assistance configuring systems.

OPERATES IN THIS RANGE:

541.500-566.375MHz

Do Balla, 17011 20 00	041.000 000.070MHZ
BD band, TVCH 44-49	655.500-680.375MHz
BI band, TVCH 16-20	482.000-507.000MHz
ITEM DESCRIPTION	PRICE
ATW-3110BDBody pack system, no mic	
ATW-3131BDBody pack system with AT83	1CW cardioid lapel mic499.00
ATW-3192BDHead worn system with AT89	2CW omni condenser headmic, black 639.00
ATW-3192BD-TH As above, in beige	639.00
ATW-3192BD-THAs above, in beige ATW-3193BDEarset system with BP893CW I	MicroEarset omni condenser mic, black 579.00
ATW-3193BD-TH As above, in beige	
ATW-3141BDHandheld system with ATW-T341 dynamic cardioid mic transmitter 499.0	
ATW-3171BDHandheld system with ATW-T	
cardioid mic transmitter	
ATW-T341BDHandheld transmitter with cardioid dynamic element	
and stand clamp	
ATW-T371BDHandheld transmitter with cardioid condenser element	
and stand clamp342.70	
ATW-DA49UHF (wideband 400-900MHz) active unity-gain antenna	
distribution system, provides	
	399.00
AT8630Joining plate for mounting (2) 3000 Series receivers	
mounting (2	, 0000 001100 1000101011111111111111111

#### **AUDIO-TECHNICA MICS/ACCESSORIES FOR A-T WIRELESS SYSTEMS**

ITEM DESCRIPTION	PRICE
Microphones (with 4-pin locking connector for A-T Unipak body packs)	
MT830CWLapel mic, omni condenser	90.86
AT829CWLapel mic, cardioid condenser	
AT831CWLapel mic, cardioid condenser	
AT899CWLapel mic, subminiature omni without power module	149.81
PRO8HE-CWHead worn mic, hypercardioid dynamic	92.67
ATM75CWHead worn mic, cardioid condenser	97.77
AT889CWHead worn mic, noise canceling condenser	162.75
BP892CWHead worn mic, omni condenser	299.00
PRO92CWHead worn mic, omni condenser, black	129.00
PRO92CW-THAs PRO92CW, in beige	129.00
Accessories	
AT-GCWGuitar input cable for A-T UniPak body packs	18.62
AEW-DA550CUHF (540-565MHz) active unity-gain antenna distribution system	
for "C" band, provides (2) 1 in-4 out RF channels for	
up to 4 receivers (for 3000/4000/5000 series)	691.43
<b>AEW-DA660D</b> As AEW-DA550C, with (655-680MHz) for "D" band	
ATW-A49Wideband directional 6dB gain antenna, mounts on wall/mic stand	
ATW-A54PPair of UHF (541-567MHz) powered dipole antennas	552.92
ATW-A64PAs ATW-A54P but 655-681MHz	
ATW-A3CPair of UHF (540-565MHz) 1/2 wave antennas with BNC conn	
for ATW-3000 series wireless	48.24
ATW-A3DAs ATW-A3C, with 655-680MHz operation	
ATW-DA49UHF (wide-band 440-900MHz) active unity-gain antenna distribution	on
system, provides (2) 1 in-4 out RF channels for up to 4 receivers	
(for 2000/3000 series)	399.00

**Looking for** wireless in-ear systems?

> See pages 87-88











# WMS420 Free yourself!

AKG's newest wireless system leverages our proven technologies and heritage, along with the famous AKG sound, in order to bring you a highly flexible solution. The WMS420 was conceived to be equally suitable on stage for performers as well as being an ideal single channel solution for installers and houses of worship due to its external antennas and outstanding gain before feedback.

The complete WM5420 wireless system consists of the SR420 stationary receiver with detachable external antennas, HT420 handheld transmitter and the PT420 pocket transmitter. The SR420 provides a wide frequency range and high S/N ratio. Easy set-up and use are a hallmark of the robust WM5420 wireless system.

- + D5 patented State-of-the-Art dynamic capsule
- + Transmitter with charging contacts
- + 8 hours of operating time on a single AA battery
- + Dry or rechargeable battery
- + Detachable receiver antennas
- + Up to 8 channels coexistence in one band
- + Low Battery Warning indicator



800-356-5844 fullcompass.com

10















ORDERING INFO:

T2 TRAVEL

































AUDIO-TECHNICA SYSTEM 8 VHF WIRELESS These single-channel, fixedfrequency systems are designed for reliability, are easy to use and have a clear, natural sound quality. These systems operate in "traveling" frequencies, which are much less likely to face interference from other wireless systems in the area. An advanced dipole antenna system offers extended operating range. Volume control, 1/4" output jack and user-adjustable squelch are standard. Transmitters run on AA batteries, have locking connectors, variable trim control and multi-color battery/ power indicator. Receivers have power, RF and AF peak indicators. Systems are available in handheld, head worn, guitar, lavalier and body pack configurations.

T3 TRAVEL		170.245	
T8 TRAVEL		171.905	
ITEM	DESCRIPTION		PRICE
ATW-801	Basic wireless system with r	eceiver and	
	body pack transmitter, no m	ic	84.95
ATW-801/G	Guitar wireless system with	AT-GCW guitar/instrument cable	99.95
ATW-801/H	Head worn wireless system v	vith PRO-8HECW	
	hypercardioid over-ear mic		144.95
ATW-801/H92	Head worn wireless system v	vith PRO-92CW omni over-ear mic	199.95
		h omnidirectional lavalier mic	
ATW-802	Handheld wireless system w	ith	

OPERATES AT THIS FREQUENCY:

99.95



#### **AUDIO-TECHNICA SYSTEM 9 FREQUENCY-AGILE WIRELESS VHF SYSTEM**

A 4-channel frequency-agile system designed for solid performance along with easy setup and clear, natural sound quality. Operates in "traveling" frequencies which are less likely to face interference from other wireless systems in the area. Features 4 compatible user-switchable VHF channels, balanced XLR and unbalanced 1/4" output jacks. Has advanced dipole antenna design for extended operating range. Transmitters run on AA cells (not included), have locking connectors, variable trim control and multi-color battery/ power indicator. Receivers offer volume control and have power, RF and AF peak indicators. Available in handheld, head worn, guitar, lavalier and body pack configurations.

	J 1 0		_
ORDERING INFO		OPERATES AT THIS FREQUENCY:	1
T2 TRAVEL		169.505	1
T3 TRAVEL		170.245	1
T8 TRAVEL		171.905	]
ITEM	DESCRIPTION PRICE		
ATW-901	Basic wireless system with receiver and		
	body pack transmitter (no mic)		
ATW-901/G	Guitar wireless system with AT-GCW guitar/instrument cable 169.95		
ATW-901/H	Head worn wireless system with PRO-8HECW		
	hypercardioid over-ear mic		
ATW-901/H92	Head worn wireless system with PRO-92CW omni over-ear mic 259.95		
	Lavalier wireless system with omnidirectional lavalier mic		
ATW-902	ATW-902Handheld wireless system with ATW-T902		
	handheld transmitter/mic		5



#### AUDIO-TECHNICA SYSTEM 10 FREQUENCY-AGILE WIRELESS SYSTEM

A digital high-fidelity system designed to provide advanced 24-bit operation, easy setup and clear, natural sound quality, System 10 operates in the 2.4Ghz range. Up to 8 channels may be used simultaneously in a single location. Three levels of diversity assurance are provided: frequency, time and space. Frequency Diversity sends the signal on 2 dynamically allocated frequencies, Time Diversity sends the signal in multiple time slots to maximize immunity to multi-path interference and Space Diversity uses 2 antennas on each transmitter and receiver to maximize signal integrity. The ATW-R1700 camera mount receiver allows System 10 to be used in ENG or filmmaking applications. Available with handheld, headworn, guitar, stompbox and lavalier microphone/transmitter configurations, System 10 is a solution for virtually any application.

URDERING INFU:   UPERATES IN THIS RANGE:	
Default Band	2.4GHz
ITEM DESCRIPTION	PRICE
Standard Systems	
ATW-1101Basic wireless sys	stem with ATW-R1100 receiver
and ATW-T1001 b	oodypack transmitter (no mic)279.95
ATW-1101/GGuitar wireless sy	stem with AT-GCW instrument cable
ATW-1101/HHead-worn wirele	ss system with PRO-8HECW hypercardioid mic 349.95
ATW-1101/H92Head-worn wireless system with PRO-92CW omnidirectional mic 379.95	
ATW-1101/LLavalier wireless	system with MT830CW omnidirectional mic 349.95
ATW-1102Handheld wireless	s system with ATW-T1002
	itter/mic299.95
ATW-1501Stompbox wireles	s system with ATW-R1500 stompbox receiver 349.95
Camera-Mount Systems	
ATW-1701Camera-mount w	ireless system with no mic
ATW-1701/LCamera-mount w	ireless system with MT830CW lavalier mic 449.95
ATW-1702Camera-mount w	ireless system with
ATW-T1001 handl	held mic/transmitter399.95



#### **BEYERDYNAMIC TG-1000 DIGITAL WIRELESS SYSTEM**

Covering an impressive 319MHz of the UHF bandwidth (470-789MHz), this 24-bit digital wireless system can be used in a variety of venues worldwide. Its wireless transmission signal features advanced digital encryption and is functional at a range of up to 984 feet. The dual receiver has BNC I/O, (2) XLR outs, (2) balanced 1/4" TRS outs, 1/4" headphone out and features intuitive pre-installed Chameleon Software.

The handheld transmitter is available with a choice of 5 interchangeable capsules, offering a solution for any application. Beltpack transmitters utilize a 4-pin mini-male XLR connector, wired for use with Beyerdynamic lavalier and head worn microphones as well as the WA-CGI instrument cable.

ITEM	DESCRIPTION	PRICE
TG1000	. Receiver, dual-channel UHF, 24-bit, digital	2999.99
TG1000-BELTPACK	. Beltpack transmitter, UHF, 24-bit, digital	799.99
WA-CGI	. Instrument cable for TG1000 Beltpack	79.99
TG1000-HANDHELD	. Handheld transmitter, UHF, 24-bit, digital,	
	capsule sold separately	799.99
	. Capsule, dynamic cardioid	
TG-V56W-CAPS	. Capsule, electret condenser cardioid	249.99
TG-V70W-CAPS	. Capsule, dynamic hypercardioid	249.99
TG-V90W-CAPS	. Capsule, ribbon cardioid	499.99
TG-V96W-CAPS	. Capsule, true condenser cardioid	699.99
TG-H54C	. Microphone, head worn cardioid	149.99
TG-L55C	. Microphone, lavalier, omidirectional	149.99
WA-CGI	. 1/4" to 4-pin mini male XLR instrument cable	
	for use with the TG1000-BELTPACK	79.99
WA-ATD-PASS	. Passive wideband directional antenna	399.99
WA-AS6	. 6-way antenna splitter with power supply	1349.99
	. Antenna amplifier	











WE'VE TAKEN

DIGITAL WIRELESS

TO THE NEXT LEVEL...

# THE FLOOR



#### SYSTEM TO STOMPBOX

#### DIGITAL 2.4 GHZ HIGH-FIDELITY WIRELESS

Combining advanced 24-bit, field-proven performance, easy setup and clear, natural sound quality, our System 10 Stompbox delivers the ultimate wireless experience. With the tap of a foot on the rugged, metal Stompbox receiver, guitarists can toggle between dual ¼" balanced outputs or mute one output without affecting the other. And, since the System operates in the 2.4 GHz range, it's free from TV and DTV interference. You can also pair multiple UniPak® body-pack transmitters with a single receiver to easily change guitars. So go ahead, give it a try – we think you'll be floored.





















































EV R300 SERIES UHF WIRELESS SYSTEMS This series features ClearScan<sup>TM</sup> for finding the next open channel available, and EZsync<sup>TM</sup> which allows for infrared transfer from receiver to transmitter for error-free setup. The R300 receiver has 32 preset channels, with compatible groups allowing up to 8 systems to operate simultaneously under ideal conditions. It has 1/4" TS, and XLR outputs, and a frequency response of 80Hz-18kHz (±2dB). The BP-300 body pack terminates to a TA4 connector for use with all EV lapel/head worn mics. The HT-300 handheld transmitter features a PL22 cardioid, dynamic head. All transmitters feature metal construction, have 8mW RF outputs, and operate up to 14 hours using 2 AA alkaline cells. Please specify band A or B when ordering, or call for assistance.

UKDEKING INFU:		UPERATES IN THIS KANGE:	
A Band - TVCH 38-4	A Band - TVCH 38-41 618.000-634.000 MHz		
B Band - TVCH 48-5	1	678.000-694.000 MHz	
ITEM	DESCRIPTION		PRICE
R300-L	. Body pack system with U	LM18 unidirectional lapel mic	. 299.00
R300-E	. Head worn system with H	IM-3 omnidirectional head worn mic	. 309.00
R300-HD	Handheld system with PL22 cardioid, dynamic mic		
R300-RX	. R300 series receiver only		. 265.50
HT-300	. Handheld transmitter onl	ly, with PL22 head	. 163.50
BP-300	. Body pack transmitter on	ily	. 143.00
APD4+	. Antenna/Power distributi	on for up to (4) R300 receivers	. 561.00
RM-300	. Rackmount kit for (1) R3	00 receiver	24.00
RMD-300	. Rackmount kit for (2) R3	00 receivers	31.50

#### EV RE2 WIRELESS MICROPHONE

Features include Advanced ClearScan $^{\mathrm{TM}}$  Auto Channel Select, over 1,112 selectable channels, automatic or manual group and channel selection, LCD display, balanced XLR and 1/4" outputs (mic/line switchable), battery level status, and more. The RE2 Pro versions feature dual "high/ low" power switching on the transmitters and interchangeable capsules on the handheld transmitters. Body pack specific features include magnesium case and detachable antenna. The Pro receiver features



rack-mount kit with front antenna extensions. Please call to determine best frequency band when ordering. Please note that the RE2 Pro series components are only available in the "A" band.

ITEM	DESCRIPTION	PRICE
RE2 UH	F Series Single Channel Systems	

ORDERING INFO:	OPERATES IN THIS RANGE:
	614.000-642.000MHz
A Band, TVCH 43-48	648.00-676.000MHz
RE2-N2 Handheld system with ND	0267A dynamic cardioid head 459.00
RE2-N7 Handheld system with NE	0767A dynamic supercardioid head 499.00
RE2-410 Handheld system with RE	410 cardioid condenser head 529.00
RE2-510 Handheld system with RE	
RE2-COMBO Combo system with ND267	
RE2-BP Body pack system, no mic	2449.00
RE2-L10 Lavalier system, with OLM	M10 omni lapel mic
RE2-L21 Lavalier system, with ULN	M21 unidirectional lapel mic529.00
RE2-E-BEIGE Body pack system, with R	E97 head worn mic, omni, beige 699.00
RE2-GGuitar/instrument system	
APD4+ Antenna/power distro syst	em for up to (4) RE2 series receivers 561.00
RE2-PRO UHF Series - sold as component	ts

ORDERING INFO:	OPERATES IN THIS RANGE:
A Band, TVCH 43-48	648.00-676.000MHz
RE2-PRO-71910X1 Single-channel UHF receive	er only, includes rackmount kit, antennas 379.00
PHTU-2D7 HH transmitter only with N	D767A dynamic supercardioid head 429.00
HTU-2C5 HH transmitter only with RE510 supercardioid condenser head 549.00	
WTU-2 Magnesium body pack	672.50



SAMSON CONCERT 88 WIRELESS SYSTEMS The frequency-agile Concert 88 system allows up to 16 systems to operate simultaneously across two frequency bands with up to 300 feet of range. The CR88 True-Diversity receiver minimizes signal dropouts and features an auto-mute function to eliminate background noise in the unlikely event of a dropout. Its front panel provides a Select button for autosyncing to a transmitter, a 7-segment channel LED, volume knob, power button, dual antennas and indicators for Audio and Ready status. The CB88 beltpack transmitter operates up to 8 hours on two AA batteries. The CH88 handheld transmitter is mated to a Q6 dynamic capsule and will operate for up to 8 hours on two AA batteries. Part numbers listed below are C band – change the final letter to D for D-band systems.

C		542.000-566.000MHz	
D		638.000-662.000MHz	
ITEM	DESCRIPTION		PRICE
SWC88BGT-C	. Guitar/instrument systen	n, with CB88 transmitter	
	and instrument cable		169.99
SWC88HCL6-C	. Handheld system with CI	H88 transmitter and Q6 capsule	169.99
SWC88BLM5-C	. Lavalier system with CB8	88 transmitter and LM5 microphone	169.99
SWC88BHS5-C	. Headset system with CB8	88 transmitter and HS5 microphone	169.99
SWC88BCS-C	As above with SF10 mic	ronhone	169 99

INPERATES IN THIS BAND.

#### SAMSON AIRLINE MICRO -**UHF WIRELESS SYSTEMS**

These UHF systems are fully rechargeable with included lithium ion batteries charged by USB DC power inputs on the transmitters and the AR2 receiver. A dock station for the AR2 also has a USB DC



input and 1/8" audio output (camera system has a dual dock with same features to secure both the AR2 receiver & AL2 transmitter). The Earset system has an AH2/SE10 transmitter that houses an omni microphone. It is water resistant; a good choice for fitness instructors. The lithium ion battery system offers up to 5-6 hours of operation for the AH2/SE10 and 7-8hrs for the AR2 receiver. The AR2 receiver also has a 1/8" balanced mic/line output, tone squelch auto mute, and includes an AC adapter, charging cables, and a system carrying case. The camera system shares the same AR2 receiver. The AL2 micro transmitter for the camera system includes a LM10 omni lapel mic, and a lithium battery system for 7-8hrs of operation. The camera system is ideal for most small camcorders or DSLR cameras.

ORDERING INFO:	OPERATES AT THIS FIXED FREQUENCY:
N1, TV CH 42	642.375MHz
N2, TV CH 42	642.875MHz
N3, TV CH 43	644.125MHz
N4, TV CH 43	644.750MHz
N5, TV CH 43	645.500MHz
N6, TV CH 43	645.750MHz

ITEM	DESCRIPTION	PRICE
SWAM2SES	EarSet system, with AH2 micro x-mitter with built-in SE10 mic,	
	AR2 micro receiver, AR2D dock, accessory cables, and case	. 249.99
SWAM2SLM10	Camera/lav system, with AL2 micro x-mitter, AR2 micro receiver,	
	LM10 lav mic with 3.5mm plug, AR2DT dock, accessory cables,	
	shoe mount adapter, power supply, case	. 299.99









#### ... HAS PROFESSIONAL WIRELESS TECHNOLOGY BEEN OFFERED AT THIS PRICE.

Concert 88 series offers high performance, 16-channel selectable UHF wireless solutions for a variety of applications... and for only \$169<sup>99</sup> each. Up to 16 systems can be used simultaneously and operate flawlessly within 300' from transmitter to receiver. Available in earset, lavalier, headset, handheld and guitar configurations, the frequency-agile Concert 88 is perfect for all your wireless needs.

Call your Full Compass Sales Associate at (800) 356-5844 to learn more about Samson's Concert 88 wireless systems.



800-356-5844 fullcompass.com















































**LECTROSONICS DIGITAL HYBRID WIRELESS™** Combines 24-bit digital audio with an analog FM radio link to provide outstanding audio quality and the extended operat-

ing range of the best analog wireless systems. Overcomes channel noise in a dramatically new way, digitally encoding the audio bit-stream in the transmitter and decoding it in the receiver, yet sending the encoded information via an analog FM wireless link. This proprietary DSP algorithm eliminates a compander circuit and its artifacts, and preserves the RF spectral footprint of analog FM designs to simplify multi-channel coordination with existing analog wireless systems. Here are the frequency blocks/detailed choices for most of the Lectrosonics products shown in this section:

ORDERING INFO:	OPERATES IN THIS RANGE:
Block 470, TVCH 14-18	470.100-495.600MHz
Block 19, TVCH 16-20	486.400-511.900MHz
Block 20, TVCH 21-25	512.000-537.500MHz
Block 21, TVCH 25-29	537.600-563.100MHz
Block 22, TVCH 29-33	563.200-588.700MHz
Block 23, TVCH 34-37 (note 608-614MHz	
may not be used in US for wireless)	588.800-614.300MHz
Block 24, TVCH 38-42	614.400-639.900MHz
Block 25, TVCH 42-46	640.00-665.500MHz
Block 26 TVCH 46-50	665 600_691 100MHz



LECTROSONICS DIGITAL HYBRID WIRELESS™ TRANSMITTERS A wide array of compatible transmitters are available to work with Lectrosonic's portable and studio receivers. The SMQV and SMV are part of the "Super-Mini" series of transmitters which are ideal when concealment is a primary concern. They feature membrane switches, LCD interfaces, current servo input for maximum dynamic range, accept a wide variety of mic types, and have an aluminum splash-proof housing. The RM remote unit allows you to change settings while these units are hidden on the talent. The UM400a model features spring-loaded belctips, servo-input amps for a wide range of gain, and a tough extruded powder-coated housing. The MM400c is a water-resistant mini transmitter with 100mW RF output for long range use with minimal interference. Body packs have locking Switchcraft TA5 connections unless otherwise noted. Please specify frequency block when ordering as it must match the receiver's frequency in order to work. Call your Sales Pro for assistance when setting up your system.

ORDERING INFO:	OPERATES IN THIS RANGE:
Blocks 470, 19, 20, 21, 22, 23, 24, 25, 26	See chart above in this column
ITEM DESCRIPTION	PRICE
Transmitters	
SMQV Super-miniature transmitter, variab	le output (50/100/250mW),
water-resistant, includes pouch, use	es (2) AA cells,
lithium battery provides up to 7.5hrs	s of operationCALL
SMVSuper-miniature transmitter, variab	le output (50/100mW),
water-resistant, uses (1) AA cell	CALL
UM400A Beltpack transmitter, 100mW RF out	tput, requires (1) 9V cellCALL
MM400C Water-tight beltpack transmitter, 10	OmW RF output,
	CALL
LMA Beltpack transmitter, 50mW RF outp	out, requires (1) 9V cellCALL
WMWaterproof body pack transmitter, swi	tchable output, LCD interface with lockout .CALL
Accessories	
RMRemote control option for all "SM" n	
SMBCUP Beltclip for SM models, connectors p	
SMBCDNBeltclip for SM models, connectors p	
SMDBC Hinged beltclip for SMQV, connector	s can point up or downCALL
Handheld and Plug-On Transmitters	
HHHandheld transmitter only, selectab	
	s battery life, requires capsuleCALL
HHCCardioid capsule for the HH	CALL
HMPlug-on transmitter for 100/200/IFB	
multi-voltage phantom power, quick	
(up to 12hrs using lithium cells), 40	OHz-20kHz ±1dBCALL

#### LECTROSONICS SYSTEMS MICS/ACCESSORIES (PARTIAL LISTING)

ITEM DESCRIPTION PRICE	
Lectrosonics Models	
M1195POmni lapel mic, with locking TA5-F connector	
M152/5PHigh-performance omni lapel mic, with locking TA5-F connectorCALL	
M119MCOmni lapel mic, with locking micro plug (for MM400C beltpack)CALL	
M152/MCHigh-performance omni lapel,	
with locking micro plug (for MM400C beltpack)	
M152/WPWaterproof version of M1252/MC (for MM400C beltpack)	
RK119Windscreen for M119 style mics	
RK150Windscreen for M150/M152 style micsCALL	
Third Party Models	
AT899CT5Audio-Technica sub-mini omni lapel mic,	
with TA5-F connector, blackCALL	
AT899CT5-THAs above, in beige	
BP893CT5Earset mic, single boom, sub-mini, omni condenser,	
with TA5-F connector, blackCALL	
BP893CT5-THAs above, in beige	
B6W4FF05B-LSCountryman B6 mini lavalier mic, omni, TA5-F connector, blackCALL	
MEMWF05B-LSCountryman EMW (square) lavalier mic, omni,	
TA5-F connector, blackCALL	
E610W5L-LSCountryman E6 headset mic, with replaceable cable,	
omni, TA5-F connector, light beige	



#### LECTROSONICS VENUE SERIES/VF FIELD MODULAR RECEIVER SYSTEMS

The Venue receiver system is a modular UHF design that operates with Digital Hybrid Wireless™ transmitters and DSP modes to support a variety of analog transmitters. It consists of a master assembly that accepts 1 to 6 plug-in receiver modules (VRS or VRT modules - not included with base unit). The VRMWB master assembly includes an antenna mulit-coupler, computer communications interface and the rackmount for the receiver modules. It has 6 balanced XLR audio outputs, 500hm BNC antenna inputs and outputs, USB, RS232 port for the computer interface, as well as an LCD interface for setup and monitoring. It operates on 10 to 18 VDC from external power supply (included). The system Includes LecNet2™ software for simplifying setup and monitoring of your system. All functions and settings can be made via software, including firmware updates through the USB and serial ports. System requires a pair of antennas with coax feed cables. Choose from the ALP models of Log Periodic Dipole Array wideband directional antennas or the SN600A omnidirectional dipole listed below.

ORDERING INFO:	OPERATES IN THIS RANGE:
Blocks 470, 19, 20, 21, 22, 23, 24, 25, 26	See chart in previous column
ITEM DESCRIPTION	PRICE
VRM-WB-MSTR-ASSEMBLY	
230MHz wideband master asse	embly only with power supply,
(no receivers or antennas inclu	
	CALL
	- fixed bandwidth front-end design
	ents, select frequency blockCALL
	same as VRS but with addition of
advanced frequency tracking f	
	juency blockCALL
	model for fixed applicationsCALL
	sign for decreased wind loadingCALL
SNA600A Collapsible dipole antenna kit,	adjustable from SouMHz to ttern. Includes mounting kit
	ax, BNC/BNC 2ftCALL
	BNC/BNC, 15ftCALL
	BNC/BNC, 25ftCALL
	BNC/BNC, 50ftCALL
	BNC/BNC, 100ftCALL
maroo	71107 D110, 1001t











# POST-APOCALYPSE COOKING SHOW







16













































#### LECTROSONICS DIGITAL SECURE WIRELESS SYSTEM

Featuring AES-256-CTR encryption technology, this wireless system is ideal for use in environments where privacy is of paramount concern, such as corporate boardrooms, shareholder meetings and government facilities. It is also well-suited to theaters, film making, touring and other demanding applications. The system consists of the DR receiver frame, individual DRM digital receiver modules and the DB digital wireless Beltpack transmitter. Similar in form to Lectrosonics' Venue receiver systems, the DR frame supports up to six channels/modules in 1RU. Analog and digital (AES/EBU) XLR outputs are selectable on the device menu. The DB Beltpack features wideband tuning and its highly linear RF output stage allows for high channel counts even with minimal available RF spectrum. The TA5M mic/line input accepts all Lavalier microphones wired for Lectrosonics transmitters. Please specify frequency band when ordering.


ORDERING INFO:	OPERATES IN THIS BAND:
A1	470.100-537.757MHz
B1	537.600-614.375MHz
C1	614.400-691.175MHz
D1	691.200-767.975MHz

ITEM	DESCRIPTION	PRICE
DR	Receiver frame, 1RU	CALL
DRM-XX	Receiver module	CALL
DB	Beltpack transmitter	CALL

NEW!

#### **LECTROSONICS L SERIES WIRELESS SYSTEMS**

These Large Bandwidth systems employ Lectrosonics' patented Digital Hybrid Wireless® technology for compander-free audio. The system consists of the LMb and LT Beltpack transmitters and the LR miniature receiver. The LMb has all-metal housing, 50mW of RF power, 25 or 100kHz tuning steps (for up to 3,072 selectable frequencies) and an IR Sync port. The LT transmitter adds to the LMb's feature set with selectable RF output power, detachable antenna and the



UKDEKING INFU:		OPERATES IN THIS BAND:	
A1		470.100-537.757MHz	
B1		537.600-614.375MHz	
C1		614.400-691.175MHz	
D1		691.200-767.975MHz	
ITEM	DESCRIPTION		PRICE
LT	Miniature wireless transr	nitter bodypack	CALL
LMB	Miniature wireless transr	nitter Beltpack, switchable power	CALL

Miniature wireless receiver....



Ask us about our 2- and 3-year protection plans!



#### **DPA D:FACTO II VOCAL CAPSULE** WITH SL1 ADAPTER

This high-quality stage vocal microphone provides extraordinary natural sound, high separation from nearby sound sources and extreme sound level handling. It is suitable for both sound

reinforcement and recording applications. Its supercardioid pattern and superb definition gives high separation and true sound color on stage, equally suitable for PA amplification and recording. A robust three-stage pop protection grid built into the microphone removes unwanted noise. Features SPL handling of 160dB and seamless integration with Shure, Sony and Lectrosonics v1 wire-



TEM	DESCRIPTION	PRICE
FA4018VSL1B	d:facto II supercardioid vocal capsule with SL1 adapter	949.95



LINE 6 XD-V75 DIGITAL WIRELESS SYSTEMS Exclusive digital technology prevents audio interference. Setup is simple, just turn it on and pick a channel. Fullrange compander-free operation delivers clear sounding vocals. The XD-V75 system operates in the 2.4GHz band, which is free from TV broadcast and white space device interference. All systems feature rackmountable receivers and an operating range of 300'. The handheld system includes a cardioid handheld transmitter and features digital models of 10 popular live-sound microphones. The optional V75-SC handheld transmitter has a supercardioid polar pattern and four mic models onboard. The lavalier, headworn and bodypack systems each feature 9 different EQ filter models, digital channel lock and standard TA4 mini-XLR input on the transmitter. Shop fullcompass.com for a full list of individual Line 6 wireless components. The handheld transmitter is available in the V75-SC supercardioid model and the V75-40V hypercardioid model with Earthworks WL40V premium capsule.

ORDERING INFO:		OPERATES AT:	
<b>Default Band</b>		2.4GHz	
ITEM	DESCRIPTION		PRICE
XD-V75	Handheld digital wireless syst	em	599.99
XD-V75L	Lavalier digital wireless syster	n	599.99
XD-V75HS	Headworn digital wireless syst	em (available in black or tan)	649.99
XD-V75TR	Bodypack digital wireless syst	em, NO MIC	549.99
V75-SC	Handheld transmitter, superca	rdioid	399.99
V75-40V	Handheld transmitter with Ear	thworks capsule, hypercardioid	1199.99











#### SENNHEISER EVOLUTION G3 UHF WIRELESS SYSTEMS

The receivers commonly feature 1/2 rack width metal housings, true diversity operation, 42MHz bandwidth with 1,680 switchable frequencies, LCD displays, AutoScan for frequency selection, sound check mode to check audio and RF signal during setup, HDX compander, wireless sync of transmitters via infrared interface, integrated EQ, XLR and 1/4" TS output jacks. The compact transmitters have integrated charging contacts (for use with optional charging accessories), use AA cells and will operate up to 8 hours. Frequency response is 25Hz-18kHz. Backwards compatible with G1/ G2 series.

**EVOLUTION 100 SERIES-G3** The EM100-G3 receiver has a SN ratio of >110dB, and has up to 12 compatible frequencies per bank. It also has a built-in guitar tuner and cable emulation.

**EVOLUTION 300 SERIES-G3** The EM300-G3 receiver has a SN ratio of >112dB, an ethernet port that allows you to control settings via a computer, and has up to 24 compatible frequencies per bank. No guitar tuner or cable emulation. Body pack transmitters have configurable mute modes and switchable RF output power (10/30mW).

**EVOLUTION 500 SERIES-G3** The EM500-G3 receiver shares the features of the 300 series but improves to a SN ratio of 115dB and has 32 compatible frequencies per bank. The 500 series handheld transmitters feature 900 series Sennheiser capsules. Like the 100 series, the receivers have a built-in guitar tuner and cable emulation.

ORDERING INFO: A Range, TVCH 21-28

EW145-G3.....

EW165-G3.....

OPERATES IN THIS RANGE:

G Range, TVCH 30-37		566.000-608.000	MHz
B Range, TVCH 40-47		626.000-668.000	MHz
ITEM DESCRI	PTION		PRICE
100 Series Sets with I	rackmountable	e EM100 receiver	
(GA3 rack ears not inc	luded)		
EW112-G3Presentation set with SK100-G3 body pack & ME2 omni lapel mic 649.95			
EW122-G3Presenta	ition set with SK!	100-G3 body pack & ME	4 cardioid lapel mic . 649.95
EW152-G3Head wo	orn set with SK10	00-G3 body pack & ME	3 cardioid,
condens	er headset		649.95
EW172-G3Instrum	ent set with SK1	00-G3 body pack & Ci	l instrument cable 499.95
EW135-G3Vocal se	t with E835 han	idheld cardioid dynami	c mic 599.95

#### 100 Series Sets with portable EK100 receiver (for camera use) - includes Ci1 1/8" output cable, CL100 XLR unbalanced output cable, CA2 camera mount

......Rackmount kit for wireless receiver ......

..Vocal set with E845 handheld supercardioid dynamic mic..

EW100ENG-G3ENG set with SK100-G3 body pack, ME2 omni lapel mic,			
& SKP100 plug-on transmitter (no phantom power)	9.95		
EW112P-G3ENG set with SK100-G3 body pack, & ME2 omni lapel mic	29.95		
EW122P-G3ENG set with SK100-G3 body pack, & ME4 cardioid lapel mic62	29.95		
EW135P-G3ENG set with SKM835 handheld transmitter, cardioid dynamic mic 59	9.95		

#### 300 Series Sets with rackmountable EM300 receiver (GA3 rack ears included)

EW312-G3	Presentation set with SK300-G3 body pack & ME2 omni lap	oel mic 849.95
EW322-G3	Presentation set with SK300-G3 body pack & ME4 cardioid la	pel mic . 849.95
EW352-G3	Head worn set with SK300-G3 body pack and	
	ME3 cardioid condenser headset	899.95
EW335-G3	Vocal set with E835 handheld cardioid dynamic mic	849.95
EW345-G3	Vocal set with E845 handheld supercardioid dynamic mic	899.95
EW365-G3	Vocal set with E865 handheld supercardioid condenser mic	999.95

#### 500 Series Sets with rackmountable FM500 receiver (GA3 rack ears included)

EW512-G3Presentation set with SK500-G3 body pack & ME2 omni lapel mic 1049.95
EW572-G3Instrument set with SK500-G3 body pack & Ci1 instrument cable 849.95
EW500/935-G3Vocal set with E935 handheld cardioid dynamic mic
EW500/945-G3Vocal set with E945 handheld supercardioid dynamic mic
EW500/965-G3Vocal set with E965 handheld switchable cardioid or
supercardioid condenser mic1499.95



SENNHEISER XS SERIES WIRELESS SYTEMS XS Wireless delivers renowned Sennheiser sound to small venues, conference rooms or houses of worship. Truediversity reception offers worry-free operation. It features 24MHz switching bandwidth, 8 frequency banks containing 12 coordinated channels each and 960 available frequencies which are tunable in 25kHz steps. The powerful scan function identifies available channels while the new Remote Channel sync allows components to be synchronized at a distance. Transmitters will operate up to 10hrs on 2 AA batteries. Operates at ranges up to 250'.

ORDERING INFO		OPERATES IN THIS RANGE:	
A Range		548.000-572.000MHz	
B Range		614.000-636.000MHz	
ITEM	DESCRIPTION		PRICE
XSW-12		(20 body pack, EM10 receiver,	
	ME2-2 clip-on lapel mi	c	399.95
XSW-52	Head worn system with	SK20 body pack, EM10 receiver,	
	ME3 headset mic		449.95
XSW-35	Handheld system with	SKM35 HH dynamic	
	cardioid transmitter, El	W10 receiver	399.95
XSW-65	Handheld system with	SKM65 HH condenser	
	supercardioid transmit	ter, EM10 receiver	449.95
XSW-72	Instrument system with	SK20 body pack, EM10 receiver,	
	CL1 instrument cable		399.95

SENNHEISER 2000 SERIES UHF WIRELESS SYSTEMS Series features include backwards compatibility with Evolution G1/G2/G3 transmitters, true diversity operation (rackmount receivers only), built-in Ethernet port for linking to PCs, switching bandwidth between 42-75MHz in 25kHz

steps, and up to 64 compatible presets per band. The rack mount receivers (EM2000/EM2050) feature integrated power supply, and active splitter (up to 8 receivers may be linked w/out using additional splitters);

transformer balanced XLR and 1/4" outputs, scan feature for compatible frequency selection, 4 selectable EQ presets, HDX compand-



er, built-in guitar tuner, Soundcheck mode for monitoring transmission conditions, and IR sync with compatible transmitters.

ORDERING INFO:	OPERATES IN THIS RANGE:	
A Range, TVCH 21-28	516.000-558.000MHz	
G Range, TVCH 28-40	558.000-626.000MHz	
B Range, TVCH 40-51	626.000-698.000MHz	
ITEM DESCRIPTION PRIC		
EM2000Single-channel UHF wire	Single-channel UHF wireless receiver, 1RU	
M2050Dual-channel UHF wireless receiver, 1RU279		
EK2000Camera-mount UHF wireless receiver		
<b>SK2000XP</b> UHF body pack transmitter only (no mic)		
SKM2000-BLACK Handheld transmitter, black (note: no capsule included) 799.95		
<b>SKP2000</b>		
supplies phantom power, 3-pin Lemo socket		

Please call for info on accessories and capsules for handheld transmitters!























































#### AUDIO

















































ORDERING INFO:



#### SENNHEISER 5000 SERIES PROFESSIONAL WIRELESS SYSTEMS

This system centers around the EM3732-II dual-channel receiver (except the BP-PACKAGE-4) and transmits across the UHF spectrum. They have up to 184MHz of switching bandwidth and are capable of integrating with 2000 Series systems. An integrated antenna splitter allows daisy chaining of up to 8 units for 16 channels of audio. The integrated Ethernet port allows for remote control via Wireless System Manager Software. Transmitters have switchable output power and a Low Intermodulation mode which allows larger numbers of transmitters to operate in congested RF environments. Transmitters are available in Nickel, Black or Steel Blue and you must also indicate frequency range when ordering.

also indicate frequency range when ordering.			
ITEM		RICE	
Handheld Package	es (transmitters available in black, blue or nickel)		
HH-PACKAGE-1	(2) SMK5200-II handheld transmitters, (2) B5000-2 battery sleds,		
	(2) Neumann KK104-S capsules, (1) EM3732-II receiver	CALL	
HH-PACKAGE-2	(2) SMK5200-II handheld transmitters, (2) B5000-2 battery sleds,		
III I MOIBIGE E	(2) Neumann KK105-S capsules, (1) EM3732-II receiver		
NN DVCKVGE 3	(2) SMK5200-II handheld transmitters, (2) B5000-2 battery sleds,	JALL	
IIII-F AUNAUL-3	(2) Sennheiser MD5235 capsules, (1) EM3732-II receiver	ALL	
IIII DACKACE 4		JALL	
TIT-PAUNAUE-4	(1) SKM5200-II handheld transmitter, (1) B5000-2 battery sled,	2411	
	(1) Neumann KK104-S capsule, (1) EM3731-II receiver	ALL	
HH-PACKAGE-5	(1) SKM5200-II handheld transmitter, (1) B5000-2 battery sled,		
	(1) Neumann KK105-S capsule, (1) EM3731-II receiver	JALL	
HH-PACKAGE-6	(1) SKM5200-II handheld transmitter, (1) B5000-2 battery sled,		
	(1) Sennheiser MD5235 capsule, (1) EM3731-II receiver	CALL	
Body Pack Packag	ges (available with black or beige lav mics)		
BP-PACKAGE-2	(2) SK5212-II body pack transmitters,		
	(2) MKE2 Gold lavalier kits, (1) EM3732-II receiver	CALL	
BP-PACKAGE-4	(1) SK5212-II body pack transmitter,		
	(1) MKE2 Gold lavalier kit, (1) EM3731-II receiver	CALL	
Accessories	(1) 111122 dota tavanor int, (1) 21107 01 11 1000101 1111111111111111111	,,,,,,,	
	Passive circularly-polarized UHF antenna	9 95	
	Passive wideband directional remote UHF antenna		
	Passive wideband omnidirectional UHF antenna		
	Low-loss RF antenna cable, 50', BNC connectors, MIL-SPEC 19		
KGZ13-100	Low-loss RF antenna cable, 100', BNC connectors, MIL-SPEC 34	9.95	

SMK5200-II NICKEL	SMK5200-II STEEL BLUE
	EM3732-II
O. L. Hillian &	B THERESON
	0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0
ORDERING INFO:	OPERATES IN THIS RANGE: 470-638MHz

614-698MHz



**OPERATES IN THIS RANGE** 

470.000-558.000MHz 550.000-638.000MHz 630.000-718.000MHz 710.000-798.000MHz

#### SENNHEISER DIGITAL 9000 SERIES WIRELESS SYSTEM

This system has been developed for professional users in broadcast studios, theaters and live performance situations who are unwilling to compromise on sound. Its unique uncompressed digital audio transmission offers artifact-free sound with superb dynamics. The use of extremely narrow filters allows a very narrow set-up of the respective radio frequencies within the available range without risking intermodulation. The EM9046 receiver offers 328MHz of switching bandwidth from 470 to 798MHz. Its modular design can support up to 8 receiver modules with modules for analog and digital output. Its intuitive icon-based user interface is displayed via a large TFT display, which can also be used to view the built-in graphical spectrum analyzer and RF level recorder. The SK9000 body pack transmitter is lightweight and durable with magnesium housing and a 3-pin Lemo connector for lavalier microphones, guitars and instruments. The SKM9000 handheld transmitter is available with 4 new capsule choices and is also compatible with Neumann, Sennheiser Evolution and 2000 series capsules. For more information about this system please call your Sales Pro.

ITEM DESCRIPTION	PRICE
EM9046-SU Modular receiver system, multi-channel (up to	o 8)CALL
EM9046-DRX Digital receiver module	2000.00
EM9046-DAO Digital audio output module	2000.00
EM9046-AAO Analog audio output module	4500.00
SK9000Body pack transmitter	2600.00
SKM9000-BK Handheld transmitter, black	2600.00
SKM9000-NI As above, in nickel	2600.00
SKM9000-BK-COM Handheld transmitter with command button,	
SKM9000-NI-COM As above, in nickel	2995.00
ME9002 Omnidirectional capsule, condenser	600.00
ME9004Cardioid capsule, condenser	600.00
ME9005Supercardioid capsule, condenser	600.00
MD9235Supercadioid capsule, dynamic – available in	ı black,
nickel or combination finishes	

MX153







PRICE





































the system scans the wireless landscape and identifies a clear channel instantly. With over 960 operating frequencies across 24MHz of UHF bandwidth, users can easily set up to 20 systems (across multiple bands) in a

given location. Each rugged metal SLX Wireless receiver uses diversity technology to improve reception and minimize dropouts. The receiver is outfitted with rackmount hardware, detachable 1/4-wave antennas, a backlit LCD display, 1/4" and XLR output connectors, frequency and power lockouts, an inline power supply and a rear-panel volume control. SLX's handheld and body pack transmitters have a 300ft operating range, and run on 2 AA batteries for 8 hours of continuous use.

OPERATES IN THIS RANGE

G5	494.000-518.000MHz, TVCH 17-22
H5	518.000-542.000MHz, TVCH 22-25
J3 L4	572.000-596.000MHz, TVCH 31-34
L4	638.000-662.000MHz, TVCH 42.45
ITEM DESCRIPTION	PRICE
SLX14Body pack system — SLX1/SLX4	4 with WA302 instrument cable, no mic 559.00
SLX14/93Lavalier system — SLX1/SLX4	with WL93 omni lavalier mic 599.00
SLX14/84Lavalier system — SLX1/SLX4	with WL184 hypercardioid lavalier mic 659.00
SLX14/85Lavalier system — SLX1/SLX4	with WL185 cardioid lavalier mic 659.00
SLX24/58Handheld system - SLX4 wit	h SLX2/58 HH transmitter 599.00
SLX24/BETA58Handheld system - SLX4 wit	h SLX2/BETA58 HH transmitter 639.00

SLX14/93Lavalier system — SLX1/SLX4 with WL93 omni lavalier mic
SLX14/84Lavalier system — SLX1/SLX4 with WL184 hypercardioid lavalier mic 659.00
SLX14/85Lavalier system — SLX1/SLX4 with WL185 cardioid lavalier mic 659.00
SLX24/58Handheld system – SLX4 with SLX2/58 HH transmitter
SLX24/BETA58Handheld system — SLX4 with SLX2/BETA58 HH transmitter 639.00
SLX24/BETA87AHandheld system — SLX4 with SLX2/BETA87A HH transmitter 729.00
SLX24/BETA87CHandheld system — SLX4 with SLX2/BETA87C HH transmitter 729.00
SLX24/86Handheld system – SLX4 with SLX2/86 HH transmitter
SLX124/85/58Combo system — SLX4 with SLX1, WL185 lavalier mic
and SLX2/SM58 HH transmitter



SHURE ULX SERIES WIRELESS SYSTEMS These are frequency agile UHF wireless systems with 1400 user-selectable channels and auto frequency selection. Up to 60 systems are simultaneously compatible within the 3 frequency groups (up to 20 per band). ULX Transmitters feature a 3-segment battery gauge, on/off switch lock-out and frequency lockout. Other features include 8hr battery life, and a -20dB pad on the ULX1 body pack. ULX standard receivers feature RF presence LED, 5-segment audio meter, 3-segment battery gauge, detachable 1/4 wave antennas, plastic chassis, XLR and 1/4" outputs, mic/line switchable. Rack hardware not included. Components shown are in the G3 band — for alternate bands replace the "G3" with bands shown below on chart, or call a Full Compass Sales Pro for assistance.

ORDERING INFO:	OPERATES IN THIS RANGE:
G3 – Note: some metro areas have	
Public Safety Channels in this band –	
call your Sales Pro for assistance with G3	470.000-506.000MHz, TVCH 14-20
J1	554.000-590.000MHz, TVCH 28-33
M1	662.000-698.000MHz, TVCH 46-51
ITEM DESCRIPTION	PRICE
ULXS4-G3 Standard receiver, plastic chassis, no rack hardware included 446.00	
ULX1-G3 Body pack transmitter	
ULX2/58-G3 Handheld transmitter wit	th SM58 head253.00
ULX2/87-G3 Handheld transmitter with SM87 head	
ULX2/BETA58-G3 Handheld transmitter wit	th Beta58 head303.00
ULX2/BETA87A-G3 Handheld transmitter with Beta87A head	
ULX2/BETA87C-G3 Handheld transmitter with Beta87C head	
UA506	
UA507 Rack hardware for dual L	JLXS4 receiver

### SHURE LAVALIER AND HEADMICS FOR SHURE BODY PACKS ITEM DESCRIPTION

MX150B/0

MX150B/C

	Lavalier Micropho	nes	
	MX150B/0-TQG	. Omni subminiature lav mic, condenser, matte black, TQG	199.00
- 1	MX150B/C-TQG	. As MX150B/O-TQG, cardioid version	199.00
1	WL93	. Omnidirectional micro-lavalier mic, condenser, black	68.54
1	WL93T	. As WL93, in tan	68.54
1	WL93-6	. As WL93, with 6' cable	73.11
1	WL93-6T	. As WL93T, with 6' cable	73.11
1	WL183	. Omnidirectional lavalier mic, condenser, black	91.74
1	WL184	. Supercardioid lavalier mic, condenser, black	113.70
1	WL185	. Cardioid lavalier mic, condenser, black	107.24
	Headset Micropho	nes	
- 1	MX153B/0-TQG	. Omni single earset mic, condenser, black, TQG	199.00
- 1	MX153T/O-TQG	. As MX153B/0-TQG, in tan	199.00
		. As MX153B/O-TQG, in cocoa	
	PGA31-TQG	. Cardioid condenser mic, black	39.00
;	SM31FH-TQG	. Cardioid condenser mic, water-repellant	99.00
1	WH20TQG	. Cardioid dynamic mic, black	79.95
1	WBH53B	. Beta 53 omnidirectional condenser mic, black	299.00
1	WBH53T	. As WBH53B, in tan	299.00
١		/ /	2



ers incredibly efficient, agile RF performance at a price point that accommodates the budgets of mid-sized venues. These systems offer the most efficient use of available on-air channels than any other system in its class, with 17 compatible systems per 6MHz TV channel. Automatic channel scan and IR sync allow for easy location and assignment of open frequencies and AES-256 encryption is standard for all system configurations. Networked control capabilities are available via ShurePlus Channels for iOS devices and Wireless Workbench 6.10 and third-party systems including AMX and Crestron. Shure's intelligent rechargeable battery technology allows for up to 10 hours of continuous use. Individual components are also available, shop fullcompass. com or call a Sales Pro for more information.

1130	3/2.000-030.000MHz, 176H 24-33
J50	632.000-696.000MHz, TVCH 31-41
L50	632.000-696.000MHz, TVCH 41-51
ITEM DESCRIPTION	PRICE
Single-Channel Systems	
QLXD14Instrument system with QLXD1	bodypack and instrument cable 973.00
QLXD14/SM35 Headworn system with QLXD1 b	oodypack and SM35 microphone 1073.00
QLXD14/83Lavalier system with QLXD1 boo	dypack and WL183 microphone 1053.00
QLXD14/84Lavalier system with QLXD1 boo	dypack and WL184 microphone 1083.00
QLXD14/85Lavalier system with QLXD1 boo	dypack and WL185 microphone 1076.00
QLXD14/93Lavalier system with QLXD1 boo	dypack and WL93 microphone 1048.00
QLXD24/B58Handheld system with QLXD2 to	ransmitter and Beta58 microphone 1055.00
QLXD24/B87AHandheld system with QLXD2 to	ransmitter and Beta87A microphone . 1136.00
QLXD24/SM58 Handheld system with QLXD2 to	ransmitter and SM58 microphone 999.00
QLXD124/85 Combo system with QLXD1 body	
microphone and QLXD2 transm	itter with SM58 microphone1439.00


Looking for		
Shure FP		
portable		
wireless system?		
See page 394		

ORDERING INFO:



OPERATES IN THIS BAND: 534.000-598.000MHz, TVCH 14-24 572.000-636.000MHz, TVCH 24-35





WIRELESS MICROPHONES

GLXD24/B87A SHURE GLX-D DIGITAL WIRELESS SYSTEMS Featuring LINKFREQ automatic frequency management for easy frequency location, these 2.4GHz digital wireless systems are rugged and available in a variety of configurations to match your performance needs. All systems include a power supply, rechargeable battery, USB charge cable or wall charger and carrying case. ORDERING INFO: OPERATES IN THIS BAND: DEFAULT BAND ITEM DESCRIPTION PRICE Complete Systems GLXD14 .... Guitar system - GLXD1, GLXD4, WA302 instrument cable ... 449.00 GLXD16 Guitar pedal system - GLXD1, GLXD6, WA305 locking instrument cable GLXD14/B98 Instrument system - GLXD1, GLXD4, WB98H/C instrument clip-on condenser. 589.00 GLXD14/PGA31 . Head worn system — GLXD1, GLXD4, PGA31 head worn condenser.. 519.00 . Lavalier system — GLXD1, GLXD4, WL185 Microflex® GLXD14/85 549.00 lavalier with windscreen/tie clip GLXD14/93 Lavalier system, GLXD1, GLXD4, WL93 omnidirectional micro-lavalier with windscreen/tie clip. 519 00 GLXD24/B58 Vocal system - GLXD2/B58, GLXD4, mic clip. 549.00 GLXD24/B87A Vocal system - GLXD2/B87A, GLXD4, mic clip ...... 589.00 GLXD24/SM58 Vocal system — GLXD2/SM58, GLXD4, mic clip...... 499.00 GLXD24/SM86 Vocal system - GLXD2/SM86, GLXD4, mic clip....... 549.00 Components GLXD1 Body pack transmitter... 229.00 GLXD2/B58 Handheld transmitter with Beta 58 microphone ....... 329.00 GLXD2/B87A As above, with Beta 87A microphone ..... 389.00 GLXD2/SM58 As above, with SM58® microphone ... 279.00 GLXD2/SM86 As above, with SM86 microphone... 329.00 GLXD4 Wireless receiver, with PS42US power supply. 219.00 GLXD6 Guitar pedal receiver, with PS23US power supply... 219.00 Accessories 29 99 SB902 Rechargeable Lithium-ion battery SBC-USB-MICROB.. USB wall charger for GLXD1/GLXD2... 14 99 Car charger for GLXD1/GLXD2 ... SBC-CAR SBC-902 Battery dock charger for SB902..... SHURE PGX-D SERIES DIGITAL WIRELESS SYSTEMS This series uses 24-bit/48kHz digital technology at the 900MHz frequency range to avoid interference from TV signals. It offers true digital diversity, frequency response of 20Hz-20kHz, (±2dB), an operating range of up to 200', and the ability to use up to 5 systems simultaneously. The PGXD4 receiver features an automatic scan and sync system for easy setup, durable ABS housing, padded carrying case, and 1/4" and XLR audio outputs. Body pack and handheld transmitters operate on 2 AA cells, yielding up to 9 hours (handheld models), or 10 hours (PGXD1 body pack) of operation. ORDERING INFO: OPERATES IN THIS RANGE: Default Band - X8 902.000-928.000Mhz ITEM DESCRIPTION PRICE Single-Channel Systems PGXD14.. Instrument system - PGXD4/PGXD1, with WA302 (1/4" to TA4-F) guitar cable 429 00 PGXD14/85 Lavalier system - PGXD4/PGXD1, with WL185 cardioid lav mic 499.00 PGXD14/93. Lavalier system - PGXD4/PGXD1, with WL93 omni lav mic... 469 00 PGXD14/BETA98H . Instrument system - PGXD4/PGXD1, with Beta98H/C clip-on mic .. 549.00 PGXD14/PGA31.... Head worn system - PGXD4/PGXD1, with PGA31 cardioid condenser mic PGXD24/PG58 Handheld system - PGXD4 with PGXD2/PG58 transmitter..... 429.00 PGXD24/SM58 . Handheld system - PGXD4 with PGXD2/SM58 transmitter... 449 00 PGXD24/BETA58.... Handheld system - PGXD4 with PGXD2/BETA58 transmitter..... 499 00 PGXD24/SM86...... Handheld system - PGXD4 with PGXD2/SM86 transmitter... 499.00 Individual Components PGXD4. Single-channel digital receiver only. 251 00 PGXD1 248 00 Body pack transmitter only Handheld transmitter only, with PG58 cardioid head... PGXD2/PG58 228 00 PGXD2/SM58 Handheld transmitter only, with SM58 cardioid head. 248 00 PGXD2/BETA58..... Handheld transmitter only, with BETA 58 supercardioid head. 318 00 PGXD2/SM86...... Handheld transmitter only, with SM86 condenser cardioid head...



LIGHTS

ACCESSORIES





PGXD14/PGA31

**BLX® Wireless Systems** 

WIRELESS FREEDOM, MADE SIMPLE.

#### LEGENDARY SOUND, RIGHT OUT OF THE BOX.

Shure BLX Wireless Systems combine professional quality sound with simple setup and an intuitive interface, for performance you can trust right out of the box. Available in single, dual and half-rack mountable receiver options in a variety of handheld, lavalier, instrument and headset configurations, it's the most accessible way to own the stage.



#### BLX4R RACK MOUNT WIRELESS RECEIVER SYSTEMS

- Simple setup and operation
- · One-touch QuickScan frequency selection quickly locates the best frequency
- Removable antennas for quick antenna distribution
- LCD display with detailed RF and audio metering
- Rugged metal construction, with rack mount hardware included





LEGENDARY PERFORMANCE"

C 2014 Shure Incorporated





















































These systems offer uncompromising audio clarity and extremely efficient RF performance with rugged, intelligent, encryption-enabled hardware. The 24-bit/48kHz digital audio delivers a clear and accurate reproduction of the source material. It features up to 64MHz overall tuning. Over 60 compatible channels are available on one frequency band.

Proprietary Gain Ranging optimizes the system's dynamic range, eliminating the need for transmitter gain adjustments. Optimized scanning automatically finds and deploys the cleanest frequencies available. Ethernet networking ability allows for streamlined setup across multiple receivers, Wireless Workbench® 6 integration and AMX/Crestron control. Advanced Li-Ion rechargeable batteries and intelligent Shure battery circuitry give 12+ hours of life and zero memory effect. Other features include interference detection with alerts, upgraded LCD screens and rugged metal housing on transmitters and receivers. A quad receiver is also available, please shop fullcompass.com for details. Models listed are in the G50 band - for alternate bands replace the "G50" with a band listed

in the chart below, or call your Sales Pro for assistance.

in the chart below, or can jour bales i to for applicance.			
ITEM	DESCRIPTION	PRICE	
System Compon	nents		
ULXD10	.Bodypack transmitter	445.00	
ULXD40	.Receiver, single, with power supply, antenna and rackmount kit	875.00	
ULXD4D0	.Receiver, dual, with power supply, antenna and rackmount kit	2505.00	
ULXD4Q0	.Receiver, quad, with power supply, antenna and rackmount kit	CALL	
ULXD2/B58	.Handheld transmitter with Beta 58A capsule	554.00	
ULXD2/B87A	.Handheld transmitter with Beta 87A capsule	630.00	
ULXD2/B87C	.Handheld transmitter with Beta 87C capsule	630.00	
ULXD2/SM58	.Handheld transmitter with SM58 capsule	474.00	
ULXD2/SM86	.Handheld transmitter with SM86 capsule	554.00	
	.Handheld transmitter with SM87 capsule		
ULXD2/KSM9	.Handheld transmitter with KSM9 capsule	1050.00	
ULXD2/KSM9HS	.Handheld transmitter with KSM9HS capsule	1050.00	

ORDERING INFO:	OPERATES IN THIS RANGE:
G50	470.000-534.000MHz, TVCH 14-24
H50	534.000-598.000MHz, TVCH 24-35
J50	572.000-636.000MHz, TVCH 31-41
L50	632.000-696.000MHz. TVCH 41-51

ITEM Accessories	DESCRIPTION	PRICE
UA864US	Wideband antenna, wall-mounted	440.28
WA305	Instrument cable, with locking TQG connector	
SB900	Rechargeable battery, lithium-ion	100.80
SB900-8	As above, 8-pack	655.20
SBC800-US	Battery charger, 8-bay	453.60
SBC200	Battery charger, dual-docking, no power supply	172.03
	As above, with power supply	





ORDERING INFO:	OPERATES IN THIS RANGE:
Band G1, TVCH 14-24	
(Note: some metro areas have Public	
Safety Channels in this band – call for	
assistance if using this band)	470.000-530.000MHz
Band H4, TVCH 22-31	518.000-578.000MHz
Band J5, TVCH 32-41	578.000-638.000MHz
Band L3, TVCH 42-51	638.000-698.000MHz

SHURE UHF-R SERIES WIRELESS MICS A UHF series with 2400 selectable frequencies spanning across 60MHz bandwidth. Up to 40 preset compatible systems per band and up to 160 systems with multiple bands. Stores six 60-channel custom frequency groups. Has a multi-function bit-mapped backlit LCD and includes Wireless Workbench<sup>TM</sup> software for PC management of networked wireless systems with USB and Ethernet network options. Models shown are components in the G1 band – for alternate bands replace the "G1" with bands shown below on chart, or call for assistance.

ITEM	DESCRIPTION	PRICE
UR4S+-G1	Single-channel receiver, with 2 half-wave antennas,	
	accessory cables, power supply	1954.00
UR4D+-G1	Dual-channel receiver, with 2 half-wave antennas,	
	accessory cables, power supply	2889.00
UR5-G1	Portable ENG body pack receiver with TA3M jack, camera	
	shoe mount, stand strap mount, 1/8" headphone out	
UR2/SM58-G1	Handheld transmitter with SM58 head	929.00
UR2/SM86-G1	Handheld transmitter with SM86 head	1039.00
	Handheld transmitter with SM87 head	
	Handheld transmitter with Beta 58 head	
UR2/BETA87A-G1	Handheld transmitter with Beta 87A head	1159.00
UR2/BETA87C-G1	Handheld transmitter with Beta 87C head	1159.00
UR2/KSM9/BK-G1	HH transmitter with KSM9 condenser head, black	1799.00
UR2/KSM9/SL-G1	HH transmitter with KSM9 condenser head, champagne	1799.00
UR1-G1	Body pack transmitter with threaded TA4-F connector	799.00
UR1M-G1	Micro body pack transmitter, 10mW or 50mW RF power,	
	TA4-F conn	
	As UR1M, with Lemo connector	
UR3-G1	Plug-on transmitter for XLR mics	999.00

#### **SHURE WIRELESS ANTENNAS & ANTENNA DISTRIBUTION ACCESSORIES**

Antennas and receivers must be from the same band. Please call a Sales Pro for assistance choosing the correct part for your system.

IIEW	DESCRIPTION	PRICE
SLX/ULX Sei	ries	
UA844SWB	.Wideband UHF 4-way active antenna splitter & power distr for SLX/U	JLX
	series, 470-952MHz, external PS, includes power antenna cables	437.65
UA830USTV	.Inline RF amplifier for UA844SWB (470-698MHz)	175.23
UA860SWB	.1/2-wave omni wideband antenna SLX/ULX (470-1100MHz)	278.30
UA400B	.Replacement 1/4-wave antenna (470-752MHz)	23.56
UA221	.Passive antenna/splitter combiner kit for 2 receivers	148.72
UA505	.1/2-wave antenna remote mount kit hardware	
	(requires antenna, not included)	22.09

ITEM UA440	DESCRIPTION .Front mount antenna kit with (4) BNC-BNC 2' coax cables,	PRICE
	(4) Bulkhead adapters	111.91
UA806	Coaxial antenna cable, 6'	22.09
UHF-R Serie	es e e e e e e e e e e e e e e e e e e	
UA845SWB	.Wideband UHF 5-way active antenna & power distr, 470-952MHz,	
	internal switching power supply (NOTE: not for use with ULX)	787.51
UA830USTV	Inline RF amplifier for UA845SWB (470-698MHz)	175.23
UA600	Front mount antenna kit for U4S/U4D receivers	47.12
UA874US	Active directional antenna (470-698MHz)	353.78
PA805SWB	Passive directional wide-band antenna (470-870MHz)	254.02
UA860SWB	1/2-wave omni wideband antenna UC/UHF-R (470-1100MHz)	278.30
UA505	1/2-wave antenna remote mount kit hardware	
	(requires antenna, not included)	22.09

SHURE SLX/ULX SYSTEMS DESCRIPTION

3I-1711-XLX.

GM4WR









































REVOLABS MICROPHONES FOR REVOLABS SINGLE/DUAL HD, AND **EXECUTIVE HD SYSTEMS** These mics feature RF Armor (impervious to RF interference), CD-quality 50Hz-20kHz frequency response, built-in rechargeable battery for up to 8hrs of talk time after a full charge, and 128-bit encryption for security.

ITEM	DESCRIPTION	PRICE
01-HDEXEMIC-11	Wearable lapel style mic, rotatable clip, with earbud, lanyard	349.00
01-HDTBLMIC-OM-11	Tabletop mic, omnidirectional	349.00
01-HDTBLMIC-DR-11	Tabletop mic, unidirectional	349.00
01-HDXLRMIC-11	XLR plug-on transmitter for dynamic mics only (no phantom)	349.00
01-HDCOMAN-11	HD microphone adapter for Countryman E6 or	
	B6 style microphones	349.00
B6W4FF05BRV	Countryman B6 omni mini-lav mic, black, for Revolabs	293.16
E610W5B2RV	Countryman E6i omni headset mic, black, for Revolabs	337.82
E610W5L2RV	Countryman E6i omni headset mic, light beige, for Revolabs	337.82

#### REVOLABS SINGLE/DUAL CHANNEL HD WIRELESS MIC

**SYSTEMS** These systems use the same high definition audio, and DFS20TM technology found in the HD Executive series. They have some audio processing EQ and mixing capability, eliminating the need for external equipment in most cases. Each system ships with a charger base

(1- or 2-mic charging docks) and a base station. Mics are purchased separately. The HD Single Channel System has an analog input and output (1/8" TRS), and the HD Dual Channel System has 2 of each, plus the ability to mix both outputs into one. All outputs can be line or mic level. This provides maximum flexibility to use the HD Single/Dual Channel System wherever a wired microphone can be used, making the system perfect for videoconferencing, voice lift and PA applications. Other features include 128-bit encryption, 2hr charge time, and 65' operating range.

	OPERATES IN THIS RANGE:
Default Band	1.92GHz-1.93GHz (UPCS North America)
ITEM DESCRIPTION 02-HDSGL-NM HD wireless mic system, 02-HDDUAL-NM HD wireless mic system,	



The M80 features a low-mass capsule build with a super-thin Mylar membrane coupled to a pro-

prietary step-up transformer, offering superior clarity and extended high frequency response. Designed to withstand the daily abuse of touring bands, these capsules offer another capsule choice for those using Shure wireless systems.

ITEM	DESCRIPTION	PRICE
M80-WH	. Capsule for Shure handheld transmitters, chrome grille	249.00
M80-WH-BLACK	. As above, with black grille	249.00

#### Looking for these brands?

Shop fullcompass.com or call 800-356-5844





accessory pocket, foam lid, carpet lined interior	249.99
GM-6W-TSAHolds 6 wireless mics, battery storage with form fitting foam s	lots,
polyethylene construction, each mic drop is 10.25" L x 2.25" D,	
with TSA locking latches	129.99
GM-7W-TSAHolds 7 wireless mics with battery storage, polyethylene constr	ruction,
2 lift-out trays with 4 adjustable dividers, with TSA locking lat	ches 169.99
Nylon or EVA Rubber Foam Exterior Cases	
GM-1WEVAA EVA rubber foam, for single 1/2 rack system, front and rear un.	zips
for access, storage for receiver, beltpack, hh x-mitter,	
flexible foam receiver cavity dims: 8" L x 8" W x1.75" H	64.99
GM2WFor 2 wireless systems, 600-denier nylon construction,	
2 extra-deep 8.5" mic drops, and compartments,	
interior receiver dimensions: 8.5" L x 8.5" W x 3.25" H	64.99
GM5WFor 5 wireless systems, nylon construction, 8.5" mic drop,	
storage compartment for receivers and accessories,	
interior receiver dimensions: 8.5" x 7" W x 4" H	64 90

Holds 4 wireless systems (1/2 rack with double sided tape), 4 slot mic/body pack holder under trap door in lid,

Wireless Mic Rack Drawer - 3RU drawer, black powder-coat finish, 16ga steel GE-WIRELESSDRWR Stores 4 wireless mics/body packs, foam storage holds 16 AA cells, accessory compartment, plywood dividers, included lock and key........ 159.99

# SENNHEISER



#### SENNHEISER AC 3200 II ACTIVE HIGH-POWER ANTENNA COMBINER

Combines up to eight channels for transmission via one antenna, with a broadband design covering 500 - 870 MHz. It significantly reduces intermodulation of wireless monitoring transmitters while keeping backstage clutter to a minimum. Long distances can be covered reliably as the AC 3200 accepts up to 250mW of input power. Includes a NT12-125D in-line power supply, power cable and 4 self-adhesive feet for tabletop use.

•		
ITEM	DESCRIPTION	PRICE
AC3200-II	Active antenna transmitter combiner	3999.00

















































SHURE AXT600 AXIENT® SPECTRUM MANAGER RF management tools inside this easy-to-use 1RU device include wide-band UHF spectrum scanning and analysis, compatible frequency coordination and continuous back-up frequency monitoring. Scan the global UHF spectrum (470-952MHz) in under a minute and back-up frequencies are instantly and automatically deployed when a compatible receiver detects interference. Other features include "Listen" signal monitoring, RF cascade allowing up to 5 receivers to be connected to one source, and 2 Ethernet ports for computer or ShowLink® Access Point connection. Frequency lists can be imported from Shure's free Wireless Workbench® 6 software, available separately. Works with ULXD and UHF-R systems.

ITEM	DESCRIPTION	PRICE
AXT600US	. RF spectrum manager/analyzer	. 4999.00



RF VENUE DFIN DIVERSITY FIN™ **ANTENNA** A portable, simple-to-operate wireless microphone antenna, capable of pushing diversity microphone systems to the limits of their performance while excelling in tough RF environments. It reduces micro-



phone drop-outs by using two elements - one that captures vertically polarized waves, and another that captures horizontally polarized waves. Covers a frequency range of 470MHz to 698MHz. Coaxial cables not included. The DFINDISTRO is a 4-channel distribution & Diversity Fin<sup>TM</sup> Antenna bundle with a 2A internal switching power supply, coaxial cables, and power distribution for 4 receiver units.

ITEM	DESCRIPTION			PRICE
DFIN	Diversity Fin™ ant	enna		399.00
DFINDISTRO4	Diversity Fin™ ant	enna and distro	bundle kit	949.00

RF VENUE RF SPOTLIGHT™ FLOOR PAD ANTENNA A low profile floor pad antenna that enables wireless mics and IEMs to work in the most crowded RF environments. Perfect for stages, hotel breakout rooms, conventions, or church sanctuaries. Effective where multiple wireless systems are inter-operating across facilities and open channels are limited. Features a

hemispherical pattern, is elliptically polarized and made of durable PVC material with a 50-pound tensile strength rated cabled connector that meets the rigors of production and rental applications. Its operating frequency range is 470MHz to 698MHz. The RF Spotlight is strong enough to pick up signals through most types of composite or wood deck stages and can be placed out of the way in the corner of the stage, installed under a carpet, or where convenient to limit foot traffic and maximize the signal-to-noise ratio for your wireless system.

ITEM	DESCRIPTION	PRICE
RFS	. RF Spotlight™ floor pad antenna	499.00

#### RF VENUE 2.4 GHZ CP BEAM HELICAL

ANTENNA A miniaturized version of the CP Beam UHF helical antenna, this lightweight version is specially designed for maximum gain in the 2.4GHz band. Well-suited for use with digital wireless systems and wireless intercoms, the 2.4GHz CP Beam is equally at home extending Wi-Fi networks or for long range wireless network access. With 14dB of



gain, the 2.4GHz CP Beam antenna significantly increases the useable range of digital microphone systems and 2.4GHz devices. Its circularly polarized design reduces signal dropouts and improves link quality.


ITEM	DESCRIPTION	PRICE
24BEAM	. Miniature helical beam antenna	299.00

Follow Us!

# Kaltman (reations

#### **KALTMAN CREATIONS, LLC INVISIBLE WAVES™ X RF COMMAND CENTER™**


This easy-to-use RF spectrum analyzer is perfect for theaters, houses of worship or corporate events. The unique Click to Listen<sup>TM</sup> function aids in identifying, naming, monitoring and cataloging interesting transmissions, and



ITEM	DESCRIPTION	PRICE
IWXLIVE	.RF spectrum analyzer, 9KHz-1.8GHz	1657.35
IWXAV	.RF spectrum analyzer, 9KHz-3.5GHz	1966.08
IWXAV-PR0	As above, with battery pack, directional	
	amplified antenna, adapters	2141.25
IWXBATT	Rechargable LiPO battery	226.56

#### KALTMAN CREATIONS, LLC INVISIBLE WAVES™ X RF-INTERMOD PRO™ SOFTWARE

Designed to assist wireless mic users, AV installers, and broadcasters RF-intermodProTM simplifies calculation and prediction of intermodulation interference of wireless devices.




SHOWN WITH FIONAL MIC STAND

It graphically displays the predicted locations of intermod components and assists in the frequency coordination process. Zoom in and out of the RF spectrum or create custom wireless inventories and groups with easy-to-use "click & drag" functionality. Interfaces with IWx RF Command Center.

ITEM	DESCRIPTION	PRICE
IWXIMP1	Intermodulation calculator, standalone	444.16
IWXIMP2	Intermodulation calculator for Command Center	271.36

#### **KALTMAN CREATIONS, LLC** INVISIBLE WAVES™ X RF-ID **FREQUENCY COUNTER**

Designed for production companies, RF technicians, and rental houses these RF-ID devices key in on wireless transmissions as near-field frequency counters The handheld RF-id SOLO confirms exact



	5 1	
ITEM	DESCRIPTION	PRICE
IWXID1.	 RF-id SOLO handheld frequency counter	221.44
IWXID8.	 RF-id STATION 8-slot frequency counter station	885.76



KALTMAN CREATIONS. LLC RF-VUE™

Touch tablet RF analyzers geared for use at concerts, theaters, places of worship and corporate events. This handheld unit integrates into a 10" touch tablet with Windows 8 The T10 covers the standard wireless microphone and IEM fre quency range of 470MHz to 700MHz.

ITEM	DESCRIPTION	PRICE
IWXT10	. RF Analysis tablet, 470MHz-700MHz	1711.96









#### **COUNTRYMAN E6/E6I/E6S SERIES EARSET MICS**

Light and springy, Isomax Earsets clip around the ear, not around the head and never interfere with hairstyles, headphones or hats. Available in hardwired XLR or pre-wired for most wireless body pack transmitters. The standard E6 series is recommended for daily use by one person, due to its stiff, shape-holding construction. For users sharing the mic, the E6i



series is ideal. It features a soft, flexible boom and a larger silicone rubber earpiece. The E6s series models are made of durable stainless steel and resists makeup and sweat. Ideal for theatre applications, these ultra-compact mics are an alternative to taping a lavalier to the face or hiding it in the hair. The new E6 Flex series combines the slim, springy ear section of a classic E6, while retaining the flexible boom design of the E6i series. All models come standard with 1mm diameter cable. For a thicker, 2mm dia. cable, add "DURAMAX" to the part number suffix. Please call for part number verification (E6s models have their own part numbering scheme.) See "GUIDE" in this listing to help create most common Countryman E6 part numbers.

most common countryman to part numbers.
ITEM DESCRIPTION PRICE E6 Omnidirectional Earset – ships with storage case, windscreen, (3) protective
caps (flat, bright & very bright), cable, (2) clips (black & white)         E60P[A][B]
E6 Directional Earset – ships with storage case, windscreen, (2) protective caps (hypercardiod & cardioid), cable, (2) clips (black & white)
E60P[A][B]
E6i Omnidirectional Earset – ships with storage case, windscreen, (3) protective caps (flat, bright & very bright), cable, 2 clips (black & white)
E6iOP[A][B]
E6i Directional Earset – ships with storage case, windscreen, (2) protective
caps (hypercardiod & cardioid), cable, (2) clips (black & white)  EGIDP[A][B]
E6s Omnidirectional Earset — ships with storage case, (3) protective caps (flat, bright & very bright), cable, (2) clips (black & white)
E6S OP[A][B]
E6s Earset, omni, pre-wired for wireless body packCALL
E6 Flex Omnidirectional Earset – ships with storage case, windscreen, (3) protective caps (flat, bright & very bright), cable, (2) clips (black & white) E6XOP[A][B]

ITEM	DESCRIPTION	PRICE
E6 Flex Directiona	I Model Template – ships with storage case, windscreen	,
2 protective caps	(hypercardioid & cardioid), cable, 2 clips (black & white	e)
E6XDP[A][B]	. E6 Flex Earset, directional, with flex boom, hardwired	CALL
E6XDW[A][B][C]	. As above, pre-wired for wireless body pack	CALL
E6-EARCLIP	. Comfortable, adjustable, extremely low-profile 2-ear support fo	r all
	Countryman Earsets. Available in left or right mic placement	
	and tan or black color	CALL
	AUIDE	

#### – GUIDE –


#### For Hardwired Versions:

Sensitivity [A] = 5 for normal speech, 6 for theater, 7 for very loud vocals Color [B] = L for Light Beige, T for Tan, C for Cocoa, B for Black

#### For Pre-Wired Versions for Wireless Body Pack Transmitters:

Sensitivity [A] = 5 for normal speech, 6 for theater, 7 for very loud vocals (on E6s models use HG for general speech, MG for vocals, LG for strong vocals) Color [B] = L for Light Beige, T for Tan, C for Cocoa, B for Black Connector [C] = Choose based on brand/type of connector and common brand suffixes are listed below. Call to verify which is right for your body pack. AK = AKG (TA3F), AT = Audio-Technica (Hirose 4 pin), ET = Electro-Voice (TA4F), LS = Lectrosonics (TA5F - M Series over 185), LW = Lectrosonics (MM400),

SM = Lectrosonics (TA5F for SM Series), L4 = Lectrosonics (TA5F for IMVLM series), ST = Sabine (TA4F for SW70), SV = Samson (TA3F for CT3,VT2L, UT1L,T32), AS = Samson (TA3F for CT3,VT2L,UT1L,T32), AS = Samson (2.5mm for Airline Al.1), SL = Shure (all with TA4F), S3 = Shure (all with Lemo 3-pin), SR = Sennheiser Evolution (3.5mm), SN = Sony (3.5mm locking – for WRT805, 806, UTXB1, UWP806), NC = pigtail/bare leads



**COUNTRYMAN E2 EARSET** The E2 is similar to the popular E6 series in that it rests over the ear, but it has a much shorter boom, with a unidirectional element. It provides a similar level of isolation as the E6 omni model at the mouth, but offers a near invisible appearance. It has an equalizing circuit built into the audio connector. Ships with a cable, carrying case, black and white cable clips, windscreen, and protective cap. (NOTE: E2 and E6 cables are not interchangeable.) This series is available for Sennheiser Evo, Lectrosonics, and Shure TA4F packs.



ITEM	DESCRIPTION	PRICE
E2P[A][B][C]	. E2 earset mic, unidirectional, hardwired	CALL
E2W[A][B][C][D]	. As above, terminated for wireless body packs	CALL

#### How to specify which earset you need for hardwired versions:

[A]=Sensitivity: 5 for normal speaking, 6 for theater

[B]=Color option: L=Light Beige, T=Tan, C=Cocoa, B=Black

[C]=Cable diameter: 1 = 1 mm cable, 2 = 2 mm cable

#### How to specify pre-wired versions for wireless body pack transmitters:


[A]=Sensitivity: 5 for normal speaking, 6 for theater

[B]=Color option: L=Light Beige, T=Tan, C=Cocoa, B=Black

[G]=Cable diameter: I=Imm cable, Z=2mm cable [D]=Connector suffix: SL=Shure (all with TA4F), SR=Sennheiser Evolution (3.5mm), SM=Lectrosonics SM, UMa and LMa

#### **COUNTRYMAN H6 OMNI HEADSET MICROPHONE** The

H6 Omni Headset is the lowest profile headset microphone in the world. Combining the transparent sound quality and waterresistant capsule design of the



ITEM	DESCRIPTION			PRICE
H6[A][B]	Omnidirectional he	adset microphone, hardwir	ed	CALL
H6[A][B][C]	As above, terminat	ed for wireless body packs		CALL

#### How to specify which headset you need for hardwired versions [A]=Sensitivity: W5 for general speaking, W6 for speaking and vocals,

W7 for very powerful vocals
[B]=Color: L = Light Beige, T = Tan, C = Cocoa, B = Black

How to specify pre-wired versions for wireless body pack transmitters
[A]=Sensitivity: W5 for general speaking, W6 for speaking and vocals,

W7 for very powerful vocals [B]=Color: L = Light Beige, T = Tan, C = Cocoa, B = Black

[C]=Cable Connector: SL = Shure (all with TA4F),

SR = Sennheiser Evolution (1/8" locking plug), SM = Lectrosonics (SM, UMa, LMa series)

Shop fullcompass.com for more connector options








ACCESSORIES

COMPUTER AV







# H6 HEADSET

Nearly Invisible.

Natural Sound.





800-356-5844 fullcompass.com

DESCRIPTION



















































ITEM

VU HEAD WORN MICROPHONES The Vu® head worn mic is ideally suited for vocal and spoken word applications. Its flexible, lightweight design allows total freedom of movement and it is virtually invisible. It has an omnidirectional polar pattern and is available with a choice of 4 different connectors, allowing it to be used with most popular wireless systems. All models feature kevlar reinforced cables. Rugged and extremely comfortable, this low-profile microphone is perfect for corporate presentations, houses of worship, lectures, theater and stage performances.

HM2000-HR4-BGOmnidirectional head worn mic, Hirose connector, beige	125.95
HM2000-LM3-BGOmnidirectional head worn mic, 1/8" (3.5mm) connector, beige	91.95
HM2000-TA3F-BGOmnidirectional head worn mic, 3-pin mini XLR connector, beige	101.95
HM2000-TA4F-BGOmnidirectional head worn mic, TA4F connector, beige	101.95
HMD1000-BGOmnidirectional head worn mic, beige (cable not included)	90.95
Cables for HMD1000	
DC-HR4-4-BGDetachable cable, Hirose connector, beige	42.95
DC-LM3-4-BGDetachable cable, 1/8" (3.5mm) connector, beige	27.95
DC-TA3F-4-BGDetachable cable, 3-pin mini XLR connector, beige	30.95
DC-TA4F-4-BG Detachable cable, TA4F connector, beige	33.95







DPA D:FINE™ SERIES HEAD WORN MICS A fine spring automatically adjusts the headset to each wearer, ensuring that the earpiece stays in place. By rotating the boom, the mic can be moved from left to right ear, or into an optimum position. Because the microphone isn't hard-wired, the cable can be easily replaced. They have max SPL of 144dB and include 2 windscreens. For use with wireless beltpacks, choose from the adapters listed below. Three boom lengths for the omnidirectional versions are available to accommodate different applications and head sizes: long (4.3"), medium (3.5") and short (1.6"). Two boom lengths for the directional versions are available: long (4.7"), and medium (3.9"). Shop fullcompass.com for a full listing of d:fine microphones.

Ш	M DESCRIPTION					PRICE	
Si	ngle Ear Models						
FI	BOOd:fine cardioid headse	et mic with	long boom, b	lack		629.95	
FI	IFOOd:fine cardioid headse	et mic with	long boom, b	eige		629.95	
FI	IBOOd:fine omnidirectional	headset n	nic with long l	boom, black		579.95	
FI	IF00d:fine omnidirectional	headset n	nic with long l	boom, beige		579.95	
Di	al-Ear Models						
FI	IBOO-2d:fine dual-ear omnid	irectional I	neadset mic w	ith long boom	ı, black	639.95	
FI	IF00-2d:fine dual-ear omnid	irectional I	neadset mic w	ith long boom	1, beige	639.95	
FI	ICON_2 d.fina dual_aar omnid	irectional I	neadset mic w	ith long hoom	hrown	639 95	

#### DPA D:FINE 4066/4088 CLASSIC MODELS

PRICE

Available in 3 sizes with a robust dual-ear headband, these head worn microphones can be worn on either side of the face. The 4066 models are omnidirectional while the 4088 models offer a cardioid pick up pattern and extended boom. All models have a double-vent protection system with water-resistant materials, an input sensitivity of 6mV/Pa and an SPL of 144dB. They terminate with DPA's standard MicroDot connector. For use with wireless beltpacks, choose an adapter from the list below.



ITEM	DESCRIPTION	PRICE
4066-B	. Omnidirectional headband mic, 20Hz-20kHz, black	649.95
4066-C	. Omnidirectional headband mic, 20Hz-20kHz, brown	649.95
4066-F	. Omnidirectional headband mic, 20Hz-20kHz, beige	649.95
4088-C	. Cardioid headband mic, 100Hz-20kHz, brown	699.95
4088-B	. Cardioid headband mic, 100Hz-20kHz, black	699.95
4088-F	. Cardioid headband mic, 100Hz-20kHz, beige	699.95

DPA MICRODOT ADAPTERS Use these adapters to integrate your DPA mic into other brands of wireless systems.

	DESCRIPTION	PRICE
DAD6001BC	XLR, accepts 48V phantom, with belt clip	110.00
DAD6003	For Sennheiser SK50/250/3063	93.00
DAD6008	For Sony WRT8020/860	93.00
DAD6010	For Shure TA4F	93.00
DAD6017	For AKG PT40/60/80/81, Samson UT1L/VT2L	93.00
DAD6019	For Sony WRT805, Sennheiser Evolution/SK300	93.00
DAD6020	For Telex TA4F	93.00
DAD6021	For Lectrosonics TA5F	93.00
DAD6034	For Sennheiser Evolution	93.00









800-356-5844 fullcompass.com



# d:fine™ headset mic

#### Boom Length

Choose from 40mm, 90mm 100mm, 110mm or 120mm boom lengths to accommodate the smallest to the largest head sizes.

#### Single or Dual

Although the single ear headset provides excellent support, the dual ear option is for those with a more energetic and vigorous performance.



















































A professional subminiature earset mic ideal for applications that need high gain before feedback. Ideal for corporate presentations, houses of worship, AV conferencing, and live sound reinforcement. Delivers exceptional speech clarity with no proximity effect. Has an extremely comfortable over-the-ear design, is fully compatible with all Shure wireless systems and comes in 3 colors.

ITEM	DESCRIPTION	PRICE
MX153B/O-TQG	Microflex® omnidirectional earset mic	
	with TQG connection, black	.199.00
MX153C/O-TQG	As above, in cocoa	.199.00
	As above, in tan	

SHURE PGA31 HEADSET CONDENSER **MICROPHONE** The PGA31 wireless microphone NEW! is designed for speech and vocal performance applications. The lightweight wireframe headset ensures a comfortable and secure fit while performing. Cardioid polar pattern prevents unwanted noise from outside sources. Flexible gooseneck allows for precise microphone adjustments for vocal clarity. Includes windscreen and features a TA4F (TQG) connector for use with Shure wireless bodypacks.

ITEM	DESCRIPTION			PRICE
PGA31-TQG	Headset condenser mi	c with TA4F con	nector	39.00

SHURE SM10A-CN **HEAD** WORN MICROPHONE A low-impedance, unidirectional dynamic microphone designed for close-talk, headworn applications. It is very lightweight with superior noise rejection and a smooth, natural-sounding frequency response. An adjustable pivot on the headband allows the boom to be moved 20° in any direction. The boom also slides out so the mic can be positioned up to 3.5" from the pivot housing. Close-talk design provides excellent isolation and minimizes gain-before-feedback. It has a frequency response of 50Hz-15kHz, and sensitivity rating of -65dBV/Pa at 1kHz

response or some r	omining and denotifying rading of doublying at times	
ITEM	DESCRIPTION	PRICE
SM10A-CN	Head worn dynamic cardioid mic	. 131.38
RK184WS	Windscreen	15.68



SHURE SM31FH FITNESS HEADSET CONDENSER MICROPHONE The SM31FH wireless microphone is designed for use in fitness instruction. It is NEW! made with water-resistant materials to protect against moisture damage. The lightweight, comfortable headset offers a secure fit for active use, and its cardioid microphone allows for intelligible sound while rejecting ambient noise. Flexible gooseneck ensures vocal clarity by allowing for precise adjustment of the microphone position. Includes

ITEM	DESCRIPTION	PRICE
SM31FH-TQG	Fitness headset condenser mic with TA4F connector.	99.00

NEW

PRICE

#### SHURE SM35 PERFORMANCE HEADSET **CONDENSER MICROPHONE** The SM35 cardioid

windscreen and TA4F (TQG) connector for use with

Shure wireless bodypacks.

headset microphone is designed for active handsfree applications such as vocal or multi-instrumental performances. The lightweight headset allows for long-lasting comfort while ensuring a tight fit for active users. The flexible gooseneck enables on-the-fly microphone adjustments to maintain vocal clarity. Cardioid polar pattern ensures clear on-axis pickup while preventing off-axis noise and feedback.

TA4F (TQG) model is compatible with Shure wireless bodypacks and the XLR model includes inline preamplifier. Both models include windscreen.

ITEM	DESCRIPTION	PRICE
SM35-TQG	Cardioid condenser headset mic with TA4F connector	99.00
SM35-XLR	Cardioid condenser headset mic with XLR connector	149.00



ITEM	DESCRIPTION	PRICE
Wired Versions		
BP892	. Headmic, omni condenser, with 55" cable w/locking 4-pin HRS conn. includes AT8539 power module, 2 element covers, 2 windscreens, moisture guard, cable clip, case, black	399.00
BP892C	. As BP892, less power module, with 55" cable unterminated	289.00
Models for use wit	th Wireless Bodypack Transmitters	
(all are w/out pow	er modules, and have 55" cables)	
BP892CW	. Black, terminated with locking 4-pin connector for AT UniPak	299.00
BP892CL4	. Black, terminated for Sennheiser systems	
	utilizing Lemo connectors	359.00
BP892CLM3	. Black, terminated for Sennheiser Evolution,	
	locking 3.5mm connector	329.00
BP892CT4	. Black, terminated for Shure TA4F-type connetor	329.00
BP892CT5	. Black, terminated for Lectrosonics TA5F type connector	329.00



#### AUDIO-TECHNICA BP894 MICROSET® SUBMINIATURE CONDENSER

MICROPHONES These microphones feature a rotating capsule housing with talk-side indicator for use on either ear and perfect polar pattern placement. Their uniform pickup pattern provides excellent rejection of outside noise, with exceptional gain-before-feedback when used with live sound systems and stage monitors. They hook securely behind the ear and can be worn for hours without fatigue. The standard model is equipped with a locking 4-pin connector and is compatible with all Audio-Technica UniPack transmitters. All models below are black; add -TH to the part number for beige models.

Wired Versions		
BP894 Omni h	head worn condenser mic with powe	er module, black 449.00
	worn condenser mic, no power modu	
55" un	nterminated cable	339.00
Wireless Body Pack Tran	nsmitter Versions	
	odules, and have 55" cables)	
	-pin connector, for A-T UniPack sys	
	emo connector for Sennheiser wirele	
	ocking 1/8" connector for Sennheise	
BP894CT4 With TA	A4F connector for Shure wireless	379.00







DESCRIPTION

ITEM



#### ROTATING ELEMENT AND CARDIOID PATTERN PUT YOUR VOICE IN FOCUS

With its innovative rotating capsule housing, the new BP894 MicroSet® Subminiature Cardioid Condenser Headworn Microphone doesn't let anything come between your message and your audience. Unlike its counterparts that face forward, the BP894's microphone element can be aimed directly toward the user's mouth, producing an unparalleled level of intelligibility perfect for public speaking, theater performances and houses of worship. The targeted cardioid polar pattern effectively controls feedback and eliminates unwanted background noise, even when using stage monitors. The result? Your message, on target.













by HARMAN





































always listening...

#### AUDIO-TECHNICA PROSHEX HYPERCARDIOID DYNAMIC

MIC Professional-quality vocal pickup with hands-free operation with a Hi-ENERGY® neodymium element for crisp sound reproduction. It features a low-visibility headband for stable, comfortable fit, and a pivot-mounted flexible mic boom.

ITEM	DESCRIPTION		PRICE
PRO8HEX	Dynamic mic,	with XLR	89.58
PR08HE-CW	Dynamic mic,	for AT bodypacks	92.67





differential of the front and back elements,

increasing rejection of distant sound sources such as monitor loudspeakers and instruments. The CM311A terminates in a belt clip housing that can be phantom powered or battery powered. It has XLR out, as well as a line out, to feed a wireless transmitter.


ITEM	DESCRIPTION	PRICE
CM311A	Differoid (cardioid element with noise	
	canceling) XLR connector	419 00





GALAXY AUDIO HSE SERIES HEADSET MICS Available as omnidirectional or unidirectional mics in single- or dual-ear hook versions. Comes with choice of one cable for use with either Galaxy, Sennheiser, Audio-Technica, Shure or AKG products. Additional cables may be purchased separately. All models have an operating voltage of 1V-10V. Models listed below are beige; please call to order mics and adapters in black or cocoa.

ITEM	DESCRIPTION	PRICE
HSE-OBG	Omnidirectional headset mic, single-ear hook, -65dB, 20Hz-20kHz	199.99
HSE-UBG	Unidirectional headset mic, single-ear hook, -67dB, 70Hz-16kHz	199.99
HSD-OBG	Omnidirectional headset mic, dual-ear hook, -65dB, 20Hz-20kHz	199.99
HSD-UBG	Unidirectional headset mic, dual-ear hook, -67dB, 70Hz-16kHz	199.99
CBLSHU	Replacement cable with TA4F connector for Shure	49.99
CBLAT	Replacement cable with HIROSE 4-pin connector for Audio-Technica	49.99
CBLSEN	Replacement cable with 3.5mm locking connector for Sennheiser	49.99
CBLAKG	Replacement cable with TA3F connector for AKG	49.99
AS-HSCLIP	Cable clip for headset mics	9.99



RØDE HS1 HEADSET CONDENSER MICROPHONE Versatile in application, this headset mic has an ergonomic design that includes 3 axes of adjustment and features a lightweight and flexible tube arm and headband. The MiCon™ connector system allows you to connect your HS1 mic to a variety of wireless systems. Includes storage case, pop filter, furry windshield, cable, lapel-style clip, adjustment tools, and cleaning wipes.

ITEM	DESCRIPTION	PRICE
HS1-B	Black headset condenser mic, omni-directional, 60Hz-18kHz	. 299.00
HS1-P	. As above, in light beige	. 299.00
MICON-1	Adapter for Sennheiser SK500, SK300G3, SK100G3,	
	SK500G2, SK300G2, SK2-Freeport	18.00
MICON-2	3.5 stereo mini jack adapter (1V minimum power supply)	18.00
MICON-3	Adapter for Shure UR1, UR1M, ULX1, SLX1, PGX1, PG1	23.00
MICON-4	. Adapter for Audio Technica UniPak	
	Body-Pack Series 1800, 2000, 3000	27.00
MICON-5	. 48V phantom power adapter, 3-pin XLR	27.00
MICON-CABLE-1.2M	. 1.2m MiCon cable	32.00
MICON-CABLE-3M	. 3m MiCon cable	39.00



LINE 6 HS70 HEADSET MIC HS70 is an adjustable headset microphone for use with XD-series TBP06 and TBP12 belt pack transmitters and other compatible belt packs with a TA4F. Its integrated compact omnidirectional condenser microphone helps resist feedback and minimize background noise. Windscreen included.

ITEM	DESCRIPTION	PRICE
HS70	Headset Mic with TA4F connector, comes in beige	
	(shown in nicture) or black	139 99





#### QUE AUDIO PERFORMANCE SERIES HEADMICS

Both mics feature a 2.5mm full frequency capsule with water resistant enclosure and interchangeable adapter options. The DA12 is an omni, high SPL head worn mic with adjustable earpiece/boom. It comes with zipper pouch, cable, cable clip and 2 windscreens. The DA15 is an omni head worn mic with an in-ear monitor piece suitable for news, sports, theater, music on stage or a communication headset. It includes 2 detachable cables, 2 windscreens, tie clip and leatherette zip pouch. Both available in black or beige. Cable adapter required unless stated otherwise - see listing below for possible terminations.

ITEM	DESCRIPTION	PRICE
DA12BE	Head worn mic, -35dB sensitivity, 140dB max SPL, beige, no adapter	309.00
DA12BE/SHL	Head worn mic, -35dB sensitivity, 140dB max SPL, beige,	
	includes Shure adapter	309.00
DA12BE/SEL	.Head worn mic, -35dB sensitivity, 140dB max SPL, beige,	
	includes Sennheiser adapter	
DA15BE	.As above, with in-ear monitor, beige	. 339.00
Adapters (so	old separately)	
QAD3	.Q compact thread (female) to 90° male XLR, requires 48V phantom po	wer,
	balanced low impedance connection to digital recorders, standard or	
	camera-mount mixers and pro video camcorders.	
	Also available in beige	34.99
DAADAKL	.AKG adapter, black	29.99
DAADATL	Audio-Technica adapter, black	29.99
DAADCHL		
	Electro-voice adapter, black	
	JTS adapter, black	
	Lectrosonics adapter, black	
DAADMIL		
	Sennheiser adapter, black	
	Shure adapter, black	
	Sony adapter, black	
	Samson adapter, black	
	Sennheiser SK50 adapter, black	
DAADTOL	TOA adapter, black	29.99

SAMSON SE10/SE50 OMNI **HEAD WORN MICS** These are low profile, miniature condenser models. The SE10T offers a 3mm capsule, while SE50 has a 2.5mm capsule. They may be shaped to fit the left or right ear and the retaining band is suitable for fitness applications. The mic has been treated with a water resistant coating for extra protection against sweat and other moisture. They also have a moistureguard drip ring to further protect the capsule. Includes 3 windscreens, clothing cable clip, carry case & detachable

**SE50** cable for Samson wireless beltpack transmitters. Mics also include 4 adapters for use with other manufacturer's beltpack systems (Shure, AT, AKG and Sennheiser).

ITEM	DESCRIPTION	PRICE
SE10T	Omni headmic, 3mm capsule, beige	99.99
	Omni headmic, 2.5mm capsule, beige	









#### **DA12 Headworn Microphone**

- Superior Sound
- Permanent Positioning
- Continuous Comfort

#### Trusted Performance

The widely used Que Audio DA12 Headworn Microphone is well known for it's superb sound, comfortable fit, and "stay-in-place" performance. The exceptional sound quality of the DA12 is the result of its 2.5mm European micro condenser capsule delivering the same trusted, high-end, water resistant, full frequency, superlative audio quality since 2008.

The extremely small size of the capsule makes it inconspicuous and easy to position, while it's big clear sound, and high SPL characteristics deliver the presentation and performance expected from a top of the line microphone. Perfect for church pastors, theater actors and singers, sportscasters, on-air or video talent, aerobics instructors, presenters, in the boardroom, and more.

- 2.5mm full-bandwidth water resistant micro capsule
- . Spring-loaded ear cushion for better comfort and hold
- Moveable fully adjustable boom arm for added flexibility
- Includes new thermoplastic "stretch" cable, tie clip, (2) windscreens

Available in Black or Beige, Standard and Petite (child) models

Specifications: DA12

Element: Back Electret Condenser Polar Pattern: Omnidirectional Frequency Response: 20Hz-20Khz Sensitivity: -45dB ±3dB

Output impedance: 2K ohms ± 30%

SPL max: 140dB

Operating voltage: 0.9V (optimal) - 5V (maximum)

Cable: 1.4mm \* 1.8m

Weight: 1g (W/O cable and connector)

Mic Dimension: 3.5mm

Q Connectors sold separately for most 3rd party wireless transmitters and 48V phantom powered XLR

\*Specification and design subject to change without notice



Also available as the DA04 Lavalier Microphone





















































AKG C417 OMNIDIRECTIONAL MICROPHONE Part of the MicroMic series, the C417 has an extended frequency range of 20Hz-20kHz and features a design that can easily be hidden on a lapel on in clothing. It comes with a lapel clip and windscreen. Requires 48V phantom power.


•		
ITEM	DESCRIPTION	PRICE
C417/L	.Mic with mini-XLR connector and integrated phantom power	99.00
B29L	.Battery pack for C417	79.00

#### (A) audio-technica. always listening...

#### **AUDIO-TECHNICA ATR3350IS OMNI-**DIRECTIONAL LAVALIER MIC The

ATR3350iS is a newscaster-style omnidirectional condenser lavalier microphone that is designed for intelligible and accurate voice

recording. Includes tie clip, battery and foam windscreen.



 <b>DESCRIPTION</b> Omnidirectional lavalier mic with smartphone adapter	<b>PRICE</b> 29.95
CA PRO70 CARDIOID  VALIER MIC This miniature	THE .

condenser microphone provides natural vocal reproduction and is also excellent for full sounding acoustic guitar pickup. It is equipped with a low-frequency roll-off switch to reduce low frequency room noise and a cardioid polar pattern that further isolates the desired sound source. Operates on battery or phantom power and has a 6' cable attached between the mic and power module. Includes mic clip, instrument adapter, windscreen, battery, and soft pouch.

ITEM	DESCRIPTION	PRICE
PR070	. Lav/instrument mic, 100Hz-14kHz	. 119.06

AUDIO-TECHNICA AT803/AT831 LAPEL MICS These clip-on lavalier mics were specifically designed for professional video, broadcast and performance applications. Specially tailored response assures crisp, natural voice and instrument pickup in an unobtrusive package. The omnidirectional AT803 provides traditional performance while the cardioid pickup

pattern of the AT831 reduces ambient noise for improved sound isolation. The AT803 and AT831B are powered by 11-52V phantom power or a 1.5V AA-type battery. The AT831C and R use phantom power only. Includes clip, windscreen, and protective carrying case. The AT831B and R also include an instrument adapter mount and all but the AT831C include a power module with on/off/rolloff switch.

ITEM	DESCRIPTION	PRICE
AT803	Miniature omni lapel, phantom power or battery	. 155.83
AT831B	Miniature cardioid lapel, phantom power or battery	. 192.77
AT831C	Miniature cardioid lapel, phantom only, unterminated	90.86
AT831R	Miniature cardioid lapel, phantom only, no power module	. 192.77

**AUDIO-TECHNICA MT830R OMNIDIRECTIONAL CONDENSER LAVALIER MICROPHONE** Designed to be worn as a lavalier or hidden in loose clothing or in the hair, the MT830R provides high intelligibility for lecturers, stage/TV performers and singers. The mic's wide-range capability ensures clean, accurate reproduction. It operates on phantom power only. Clothing clip and windscreen included.

1	3 1	
ITEM	DESCRIPTION	PRICE
MT830R	. Includes AT8533 power module, black finish	180.07
MT830C	. Includes 55" cable, unterminated, black finish	86.07
MT830CT5	. Includes 55" cable with TA5F connector for ATW-U101	
	and Lectrosonics body pack systems, black finish	93.40
MT830CT5-TH	. As MT830CT5, in beige	93.40
MT830CW	. Includes 55" cable with locking 4-pin connector	
	for Audio-Technica UniPak wireless, black finish	90.86
MT830CW-TH	. As MT830CW, in beige	90.86

#### **AUDIO-TECHNICA AT899 SUBMINI OMNI LAPEL MICROPHONE**


Only 5mm in diameter with clean, accurate reproduction. Includes 12 accessories. Available in black or beige.

ITEM	DESCRIPTION	PRICE
AT899	With battery/phantom power module and low-cut switch	228.55
AT899CW	With 4-pin AT wireless connector	149.81
AT899CT5	5-pin connector for AT wireless	146.66
AT899C	With bare end cable for custom termination	138.52



#### **DPA D:SCREET MINIATURE MICROPHONES**

These omnidirectional miniature microphones are resistant to humidity, sweat, wind and plosive sounds. All



ITEM	DESCRIPTION	PRICE
SC4060-BM	. Lapel, high sensitivity, MicroDot connector	429.95
4061	. Lapel, low sensitivity, MicroDot connector	429.95
4062	. Lapel, extra-low sensitivity, MicroDot connector	429.95
4066	. Adjustable headband microphone, MicroDot connector	649.95



#### POINT SOURCE AUDIO CO8 OMNIDIRECTIONAL LAVALIER

MICROPHONE This lavalier microphone features a low-profile element that's only 4mm in diameter yet provides clear sound from 20Hz-20kHz. The omnidirectional polar pattern provides natural vocal sound and is ideal for low- to moderate-noise environments. 148dB max SPL handling provides plenty of gain before feedback, while the IP57 waterproof rating means water, sweat and makeup won't stop this mic. Each mic includes one threaded X-Connector of your choice, available for all popular wireless systems. Also includes windscreen, clothing clip and storage box.

ITEM	DESCRIPTION	PRICE
CO-8WL-BL	. Lavalier microphone, in black	285.00
CO-8WL-BE	. Lavalier microphone, in beige	285.00





QUE AUDIO PERFORMANCE SERIES LAVALIER MICS Features a 2.5mm full frequency capsule with a water-resistant enclosure and interchangeable adapter options. The capsule has an omnidirectional pattern and high SPL. It comes with a tie clip, zipper pouch and 2 windscreens. Cable adapter required.

1, 11 1	1 1	
ITEM	DESCRIPTION	PRICE
DA04BL	Lavalier mic, -45dB sensitivity, black	. 229.00
DAN4RF	As above in heige	229 00

See page 36 for list of adapters (sold separately) for Que Audio mics.

#### sanken

The world's most <u>original</u> microphone make

**SANKEN COS 11D MINI LAVALIER** MICS Specifically to diminish the instances where interference is an issue, this omnidirectional, selfpolarized condenser mic has a frequency range of 50Hz-20kHz, and a sensitivity rating of -35dB. It is ideal



for live broadcasting, location recording and studio applications and operates on 48V phantom power (COS-11D) or battery power (COS-11D-BP). Includes clip, windscreen, rubber mount, AA battery and vinyl case. Available in black, gray, beige and white.

ITEM	DESCRIPTION	PRICE
COS-11D	. Mini lavalier mic, 48V, XLR	469.00
COS-11D-BP	. Mini lavalier mic, battery powered, XLR	469.00









# **DIRECTIONAL LAVALIER**

One of the smallest directional lavaliers in the world. Features a tight hypercardioid pattern with



an extra 6-10 dB of headroom, has moisture resistance and a rugged build, is tuned for speech, and has detachable cables for a wide variety of wireless and wired applications. Its hypercardioid pattern means less problems with feedback, ambient noise, room rumble, and phase cancellations with multiple mics. Supplied with wireless adapter, carrying case, shock mount clip, windscreen and protective cap. There are 3 sensitivity options - standard for general, mid for head miking/theater and low for head miking powerful vocals/opera. Five colors are available: Black, White, Light Skin, Cocoa and Gray (models listed below are Black). The B2D may be ordered with XLR/phantom termination (shown below) or pre-wired for a variety of wireless transmitters. Please call for options.

ITEM	DESCRIPTION	PRICE
B2DP4FF05B-HW	. Hypercardioid lavalier, XLR male, standard sensitivity, black	448.87
B2DP5FF05B-HW	. Hypercardioid lavalier, XLR male, mid sensitivity, black	448.87
B2DP6FF05B-HW	. Hypercardioid lavalier, XLR male, low sensitivity, black	448.87

#### COUNTRYMAN ISOMAX-B6 MICRO LAPEL MIC

The B6 is the world's smallest lapel mic. At only .1" in diameter, the B6 offers a 40Hz- 25kHz response, is available in four colors and has a Kevlar reinforced cable for high strength and ultra-low noise. Get the visual effect of a hidden mic without the hassle and loss of sound quality you get from hiding one in clothing. The B6 is resistant to sweat and makeup and can be custom configured with connectors for most wireless transmitters or for XLR inputs with phantom power.

ITEM	DESCRIPTION	PRICE
B6P4FF05B	Omni sub-micro lapel mic, black	297.68
B6P4FF05G	Omni sub-micro lapel mic, gray	297.68
B6P4FF05L	Omni sub-micro lapel mic, light beige	297.68
B6P4FF05W	Omni sub-micro lapel mic, white	297.68

COUNTRYMAN EMW LAPEL MIC This electret condenser mic offers an omnidirectional polar pattern, uniform pickup and a wide frequency range of 20Hz-20kHz. A mere 1/8" thick, the flat EMW offers discreet placement for broadcast and performance. Other features include: Kevlar-reinforced cable with low handling noise, sealed design for excellent moisture resistance and a variety of clip options. Three fre-

quency response patterns are available: "F" Flat-response, "S" Shelved-up response (6dB curve, 2kHz-15kHz) and "P" Peaked-response (sharp upward curve at 12kHz). All versions are available pre-wired for wireless use.

ITEM	DESCRIPTION EMW, XLR, flat response	PRICE
MEMWP4F05B	.EMW, XLR, flat response	185.19
MEMWP4P05B	.EMW, XLR, peaked response	185.19
MEMWP4S05B	.EMW, XLR, shelved-up response	185.19
AEMWCLIP-B	.Replacement tie clip, black	14.54
AEMWVIPER-B	.Viper clothing clip	13.02
	.Replacement windscreen	

**COUNTRYMAN ISOMAX-II** The Isomax-II series of precision electret condenser microphones are equally suited for recording and sound reinforcement. Available in 3 polar patterns (omni, cardioid, hypercardioid), they have extremely low noise and are capable of handling high SPLs to 150dB. The

subtle black finish and miniature size allow for unobtrusive use in television and theater applications. Comes with a 10' cord with XLR output, mounting clip and windscreen. Phantom power required.

1 ,	1	1
ITEM		PRICE
M2CP6FF10/ISOMAX2-C	Cardioid lavalier mic, 50Hz-20kHz	196.17
M20P6FF10	Omni lavalier mic, 20Hz-20kHz	196.17
M2HP6FF10	Hypercardioid lavalier mic, 50Hz-20kHz	196.17
A2WS-BLK	Replacement windscreen, black	9.99
AXBPM	Battery module	87.27



Røde's lavalier mic features low handling noise and designed to be worn discreetly. Includes a mic clip, detachable cable, a water-resistant pop filter, mini furry windscreen, adjustment tools, cleaning wipes, and an anti-trauma water-resistant



case. Mic is compatible with Røde's MiConTM adapters (see below).

ITEM	DESCRIPTION	PRICE
LAVALIER	Omnidirectional lav mic, black, 60Hz-18kHz	249.00

#### MICON

MICON ACCESSORIES FOR RØDE LAVALIER MIC SYSTEM Adapters and cables to connect Røde Pinmic and Lavalier to various wireless systems.

ITEM	DESCRIPTION	PRICE
MICON-1	Adapter for Sennheiser SK500, SK300G3, SK100G3,	
	SK500G2, SK300G2, SK2-Freeport	18.00
MICON-2	3.5 stereo mini jack adapter (1V minimum power supply)	18.00
MICON-3	Adapter for Shure UR1, UR1M, ULX1, SLX1, PGX1, PG1	23.00
MICON-4	Adapter for Audio Technica UniPak	
	Body-Pack Series 1800, 2000, 3000	27.00
MICON-5	48V phantom power adapter, 3-pin XLR	27.00
MICON-CABLE-1.	2M. 4ft MiCon cable	32.00
MICON-CABLE-31	M 9ft MiCon cable	39.00



ITEM	DESCRIPTION B3 lavalier mic, XLR	PRICE
	B3 for Audio-Technica, 4-pin	
	B3 for Samson, 6-pin	
	B3 for Samson, 3-pin	
	B3 for Sennheiser, 3-pin	
B3W4FF05B-SL	B3 for Shure TA4F	
B3W4FF05B-S0	B3 for Sony, 4-pin	211.34
B3W4FF05B-TS	B3 for Telex TA4F	180.52
B3W4FF05B-TL	B3 for Telex LEMO, 4-pin	189.43
B3W4FF05B-VS	B3 for Vega TA4F	180.52
B3W4FF05B-NC	B3 with 2-wire pigtails	153.82
	Replacement windscreen	
	Replacement beltclip	
AXBPM	Battery module	87.27

































































































#### SHURE

SHURE CVL LAVALIER CONDENSER MICROPHONE The CVL is a cardioid condenser lavalier microphone designed for professional presentations and speeches. It has a frequency response of 50Hz-20kHz and the cardioid polar pattern ensures off-axis noise rejection while maintaining vocal clarity. Includes windscreen and tie clip and features a TA4F (TQG) connector for use with Shure wireless

Douypacks.		
ITEM	DESCRIPTION	PRICE
CVL-B/C-TQG	Cardioid condenser lavalier microphone	
	with TA4F connector	39 00



SHURE MX150 SUBMINIATURE LAVALIER MICROPHONE A professional electret condenser mic ideal for low-profile placement applications. Fully compatible with all Shure wireless systems, it offers uncompromising sound quality and high reliability for television broadcasting, corporate lectures, AV teleconferencing, houses of worship, and sound reinforcement. Features include CommShield® Technology to prevent cellular RF signal interference, matte black finish, multiposition tie clip, reduced handling noise, user-changeable equalization caps (omni only), snap-fit windscreen. Requires phantom power.

ITEM	DESCRIPTION	PRICE
MX150B/O-TQG	Microflex® omnidirectional subminiature lavalier	
	microphone with TQG connection	199.00
MX150B/0-XLR	As above, with XLR connection	299.00
MX150B/C-TQG	Microflex® cardioid subminiature lavalier microphone	
	with TQG connection	199.00
MX150B/C-XLR	As above, with XLR connection	299.00
MX150B/O-XLR MX150B/C-TQG	microphone with TQG connection	299.00



SHURE MICROFLEX LAPEL MICS The Microflex lapel condenser mics feature high sensitivity, a frequency response of 50Hz-17kHz, interchangeable condenser cartridges (MX models), & a variety of low-visibility mounting options. MX models are terminated to XLR & include a belt-clip preamp. WL versions are terminated with TA4F connectors for Shure wireless systems.

ITEM	DESCRIPTION	PRICE
MX183	. Omnidirectional condenser lapel mic, phantom only	160.52
MX184	. Supercardioid condenser lapel mic, phantom only	178.61
MX185	. Cardioid condenser lapel mic, phantom only	172.97
WL183	. Omnidirectional, terminated for Shure wireless (TA4F)	91.74
WL184	. Supercardioid, terminated for Shure wireless (TA4F)	113.70
WL185	. Cardioid, terminated for Shure wireless (TA4F)	107.24
R183B	. Omnidirectional cartridge option for MX184/MX185	38.28
R184B	. Supercardioid cartridge option for MX183/MX185	61.85
R185B	. Cardioid cartridge option for MX183/MX184	53.01

SHURE SM11 OMNI DYNAMIC LAVALIER For those who need a dynamic lavalier microphone, the SM11 is the smallest model available. Shure ruggedness and dependability in a mic no longer than a paper clip. ITEM DESCRIPTION PRICE

#### SHURE

NEW!

#### **SHURE SM93 OMNI MICRO CONDENSER**

LAPEL The SM93 lapel microphone is ideal for broadcast, stage and film because of its tiny size and clear, tailored frequency response. Features: Omni directional pattern,



a variety of low-visibility mounting options, 80Hz-20kHz frequency response, windscreen and in-line preamp with XLR output.

ITEM	DESCRIPTION	PRICE
SM93	Omnidirectional lapel mic, preamp, XLR out	141.65
WL93	Omnidirectional lapel mic for Shure wireless (TA4F)	68.54
WI 93T	As WI 93 with tan finish	68 54

#### "SENNHEISER"

#### SENNHEISER MKE2 OMNI MICRO LAPEL CONDENSER

Available unwired for a variety of wireless applications, wired to an XLR connector or as part of the K6 modular system. 6mm in diameter and flat from 20Hz-20kHz. Gold versions have reduced sensitivity and improved moisture resistance.

ITEM	DESCRIPTION	PRICE
MKE2-5-K	. Pigtail, black finish	379.95
MKE2-5-3C-GOLD	. Pigtail, buff finish	349.95
MKE2-5C-GOLD	. Pigtail, black finish	349.95
MKE2-60-GOLD	. For use with the K6 power unit	369.95
MKE2-EW-GOLD	. For EW wireless, black finish	389.95
MKE2-P-C	. With XLR for phantom power	399.95
	. Power module for MKE2-60	
MZQ222	. Replacement clip for MKE2	15.95



#### SONY

#### SONY ELECTRET SERIES CONDENSER MICS

These mics operate on a single AA battery and come with a urethane windscreen and clip.

#### **SONY ECM44B OMNIDIRECTIONAL**

Mic head 8.5x14.5mm. Freq. resp. 40Hz-15kHz. Max input: 122dB SPL. Dynamic range: 90+dB.

ITEM	DESCRIPTION	PRICE
ECM44B	Omnidirectional lapel mic, XLR	CALL
ECM44BC	Omnidirectional for Sony 4-pin wireless	CALL
ECM44BMP	Omnidirectional for Sony 1/8" mini-lock wireless	CALL
ADR44B-12PK	Replacement windscreen, pack of 12	CALL
SADH44B-10PK	Replacement tie clip for ECM44, pack of 10	CALL

SONY ECM55B OMNIDIRECTIONAL Mic head 10.6x21mm. Freq. resp. 30Hz-18kHz. max input: 126dB SPL. Dynamic range: 98+dB. Connector: XLR.

ITEM	DESCRIPTION	PRICE
ECM55B	Omnidirectional lapel mic	CALL
	Replacement tie clip for ECM55B, pack of 10	

SONY ECM77B ULTRA MINI OMNIDIRECTIONAL Mic head 5.6x12.55mm. Freq. resp. 40Hz-20kHz. Max input: 120dB SPL. Dynamic range: 90+dB. Connector: XLR.

ITEM	DESCRIPTION	PRICE
ECM77B	. Mini Omnidirectional lapel mic	CALL
ECM77BC/9X	. Mini Omnidirectional for Sony 4-pin wireless	CALL
ADR77B-6PK	. Replacement windscreen, pack of 6	CALL
SADH77B-10PK	. Replacement tie clip for ECM77B, pack of 10	CALL

Looking for more from these brands?

Shop fullcompass.com



#### AUDIO-TECHNICA AE4100/LE 50TH ANNIVERSARY HANDHELD MICROPHONE

This special limited edition 50th anniversary cardioid dynamic microphone features a silver colored metallic finish with blue accents and an individual serial number etched into the surface. It has a frequency response of 90Hz-18kHz and features anti-shock engineering for low handling noise. Its hardened steel outer grille has a fine steel mesh and a layer of open-cell foam and a foam disk placed on top of the element to prevent plosives. Includes Quiet-Flex<sup>TM</sup> stand clamp, 5/8"-27 to 3/8"-16 threaded adapter and soft protective pouch.

ITEM AE4100/LE	<b>DESCRIPTION</b> 50th anniversary ha	ndheld cardioid dyna	amic mic	<b>PRICE</b> 99.99



P3S

#### (A) audio-technica. always listening...

#### **AUDIO-TECHNICA ARTIST** SERIES VOCAL MICS ATM410

The ATM410 cardioid dynamic is designed for smooth, natural vocal reproduction, features a neodymium magnet for high output, and a multi-stage grille. The ATM610 is hypercardioid and



features dual-wall floating construction where the back-cavity assembly "floats" inside the handle shell, providing outstanding isolation from handling noise. The ATM710 is a high-fidelity cardioid condenser mic with an integral 80Hz hi-pass filter and a switchable 10dB pad.

ITEM	DESCRIPTION	PRICE
ATM410	Cardioid dynamic mic with	
	neodymium magnet	79.00
ATM610	Hypercardioid dynamic mic	149.00
ATM710	Cardioid condenser mic with HP	
	filter and 10dB nad	199 00


#### **AUDIO-TECHNICA AT2010** HANDHELD CONDENSER VOCAL


MICROPHONE Designed to bring the studio-quality articulation and intelligibility of AT's renowned 20 Series to the stage. Featuring the same 16mm low-mass diaphragm found in the AT2020 studio condenser, the AT2010 excels wherever articulate vocals are needed such as in houses of worship, for solo performances,

AT2010.

AE6100.

AE3300.





AUDIO-TECHNICA ARTIST ELITE	AE330
State-of-the-art live performance	
vocal microphones with excellent	
noise isolation. The AE5400 has a	
cardioid true condenser large-dia-	
phragm element and a switchable HP	
filter and pad switch. The AE3300 is a	
andiaid and denoughth IID filter and	

.....Cardioid, 40Hz-20kHz ......

cardioid condenser with HP filter and pad switch. AE6100 is a hypercardioid dynamic. The AE4100 is a cardioid AE4100 dynamic. ITEM DESCRIPTION AE4100. .Cardioid dynamic.. 189 00

.Hypercardioid dynamic......

.Cardioid condenser mic ...... .Cardioid condenser mic .....



AKG PERCEPTION LIVE VOCAL MICS The P3 and P5 vocal micro-

phones, with cardioid and supercardioid characteristics respectively, provide the perfect sound for vocalists on stage. They feature metal casing, a spring steel

grille, scratch-resistant finish, high max SPL and a carrying case.

ITEM	DESCRIPTION	PRICE
P3S	.Cardioid, dynamic, on/off switch, 40Hz-20kHz	59.00
P5	.Supercardioid, dynamic, 40Hz-20kHz	65.00

#### AKG C5/D5 HANDHELD VOCAL **MICROPHONES** The C5 features

a 24-carat gold-sputtered housing that protects the condenser capsule against moisture and humidity, plus a removable Presence Boost adapter for increased intelligibility. The D5 dynamic mic includes new Laminate Varimotion diaphragm technology to deliver a smooth frequency response and the highest gain-before-feedback.



ITEM DESCRIPTION		PRICE	
C5Condenser, ca	rdioid, 65Hz-20kHz	179.00	
D5Dynamic, supe	ercardioid, 70Hz-20kHz	99.00	
<b>D5S</b> D5 with on/off	switch	109.00	

#### beyerdynamic)))


BEYERDYNAMIC M88TG HYPERCAR-DIOID DYNAMIC MIC With a frequencyindependent pickup pattern which reduces feedback and off-axis coloration to a minimum and delivers high output over a wide range of working distances. Its wide frequency response and fast transient response enhance the presence and articulation of voices, while accurately reproducing bass frequencies. The M88 has a natural, well-balanced sound and its rugged design virtually eliminates non-linear distortion at extreme SPLs. The integral humbucking coil reduces interference from stray magnetic fields by as much as 20dB. Comes with black leatherette foam-lined carry case and MKV8

·····o op.		
ITEM	DESCRIPTION	PRICE
M88TG	.Hypercardioid dynamic mic	.399.00
PS88	.Pop filter, dark grey polyurethane foam	19.90
WS59	Windscreen, charcoal grey	24.90

#### AUDIX OM SERIES VOCAL MICS

Dynamic hypercardioid handheld vocal microphones for maximum gain before

ITEM	DESCRIPTION	PRICE
OM1	Reissue of the flagship OM1,	
	lead vocal, solid brass housing,	
	50Hz-18kHz, hypercardioid	239.00
OM2	.50Hz-16kHz, warmth and mid boost	99.00
OM2S	.OM2 with switch	119.00
	.50Hz-18kHz, natural accurate	
	.0M3 with switch	
	.48Hz-19kHz, gentle presence rise	
OM6	.40Hz-19kHz, flat response	219.00
OM7	.45Hz-19kHz, low gain, pro-touring	229.00





#### N/DYM PERFORMANCE MICS

EV was the first to use neodymiumbased magnets in microphones and is the only manufacturer that offers Vocal-Optimized-Bass technology, providing a clear vocal sound that cuts through the mix. Mics feature very low handling noise, high output, and extended frequency response.

ICE
.00
.00
.00
.00
.00
.00



#### **HEIL SOUND** PR SERIES **DYNAMIC MIC**

The PR20 and PR22 feature neodymium, iron, boron magnet construction and steel case structures. Both models have a large 1-1/8" low mass voice coil assembly, 50Hz-18kHz frequency response and a 3-pin XLR output connection. The PR20 is recommended for live vocal and snare drum applications.

The PR22 includes the ISO Band, a Sorbothane rubber suspension system to eliminate low frequency handling noise. Both mics come with a carrying bag, mic clip and set of 3 metal windscreens (black, silver and gold). The PR20-UT is a "utility" package and has only the mic clin and a cilver mech windscreen

the fine cup and a suver mesh windscreen.			
	ITEM	DESCRIPTION	PRICE
	PR20	Cardioid mic with black, silver and	
		gold mesh head windscreen	.155.00
	PR20-UT	PR20 microphone with silver (only)	
		windscreen head, clip and pouch	.101.00
	PR22	.Cardioid mic with Sorbothane	
		suspension	.184.00

HEIL SOUND PR35 SUPERCARDIOID DYNAMIC VOCAL MIC Features neodymium, iron & boron magnet structures. The PR35 utilizes the PR30 capsule in a rubber internal suspension specifically designed for handheld vocal applications. It has a 3-position I E vollaff quitab

Lr folioii :	140	
ITEM	DESCRIPTION	PRIC
PR35	Vocal mic 40Hz-18kHz	276.0















N/D267AS

PR20























































































#### **DPA D:FACTO II VOCAL MIC**

This high-quality supercardioid handheld vocal stage microphone provides exceptional off-axis rejection. Features a robust 3-stage pop protection grid, 160dB SPL and a well tailored 20Hz - 20kHz frequency range. Requires 48V phantom power.

ITEM	DESCRIPTION	PRICI
FA4018VD	PABHandheld vocal mic	949.9

#### *SAMSON*

#### SAMSON Q8 HANDHELD DYNAMIC

MIC A supercardioid dynamic handheld mic for live performance and studio. Features a neodymium dynamic element, high gain output, low impedance design, reduced feedback and unwanted signals, 150dB SPL, and a rugged zinc-alloy die-cast body. Includes carry case and mic clip.

TEM	DESCRIPTION	PRICE
אצח-אנ	IAMIC-MIC	

Handheld supercardioid dynamic mic .99.99



#### **NEUMANN KMS104/105 HANDHELD**

VOCAL MICS Handheld condenser mics designed with superb vocal reproduction in mind. Available in cardioid as the KMS104 or supercardioid as the KMS105, these mics combine low noise and colorless off-axis pickup for outstanding live stage vocal work. A unique 4-layer acoustic filter plus electrical

filtering removes most popping and handling noise. Response is 20Hz-20kHz, 150dB maximum SPL. 48V phantom power required. The KMS104D/105D mics are 48kHz digital versions based on AES2 standards with extended dynamic range, 60Hz-20kHz fre-

quency response, internal peak limiter/compressor (avoids clipping), and Remote Control Software (RCS - downloadable via Neumann's website) permits pre-programmed settings to be stored into the mic (Digital Microphone Interface, "DMI-" is required for RCS).

KMS105D

ITEM		PRICE
KMS104-NI	Cardioid vocal condenser, nickel	699.95
KMS104-MT	Cardioid vocal condenser, black	699.95
KMS104-D	Digital cardioid vocal condenser (choose black or nickel when ordering)	999.95
KMS105-NI	Supercardioid vocal condenser, nickel finish	699.95
KMS105-MT	Supercardioid vocal condenser, black finish	699.95
KMS105-D	Digital supercardioid vocal condenser (choose black or nickel when ordering)	999.95
DM18	Digital mic interface, 8-channel, for the KMS104D and KMS105D digital mics	3249.95





stand mount adapter and a protective zipper case.

	-	-			
ITEM		DESCRIPTION	l		PRICE
M82-BROADCAST	-PACK	. End-address	dynamic n	nicrophone,	
		with broadca	st boom ar	nd accessories	499.00

TELEFUNKEN **ELEKTROAKUSTIK M80 DYNAMIC VOCAL MIC Features** a wider frequency response and higher SPL capabilities than most dynamic microphones, the M80 is equally suitable for voice, instruments or drums. Its low-mass capsule and super-thin capsule membrane provide "condenser-like" performance in both live performance and recording environments. Its head and capsule assembly are designed to reduce proximity effect

for added low-end clarity on vocals. It also features include a custom-wound, American-made impedance matching transformer. The M80 has a cardioid polar pattern and ships with a mic clip and storage bag.

KMS104

DESCRIPTION M80-BLACK....Cardioid dynamic mic, 30Hz-18kHz...249.00



**SENNHEISER** MD431-II DYNAMIC SUPERCARDIOID MIC The ability to provide high gain-before-feedback, handle high sound pressure levels and produce a clean, open sound have made the MD431-U famous among discerning musicians and engineers alike. Features include supercardioid pattern, triple-layer steel mesh grille, shock-suspended capsule, specially contoured low frequency response, humbucking coil, and a removable magnetic-reed on/ off switch.

ITEM	DESCRIPTION	PRICE
MD431-II	Supercardioid dynamic mic,	
	with low handling noise	449.95
A25DM	Replacement stand adapter	45.60
MZW4032	Foam windscreen	39.95


SENNHEISER EVOLUTION SERIES Evolution mics offer Sennheiser's highest standards of performance and construction at affordable prices. Each mic features a rugged steel-blue metal housing and removable capsule. The E835 cardioid mic features a subtle presence boost for lead/stage vocals and an extended frequency response. The E865 is a condenser supercardioid with great transient response. The E835 and E845 are also available with a silent on/off switch. The E965 is a large diaphragm condenser mic, with switchable cardioid/ supercardioid polar patterns and a -10dB cut switch. All models are dynamic except for the E865 and E965 which are condenser mics.

		DESCRIPTION				PRICE
E815S-C		Cardioid vocal mid	c with switch and	clip, 80Hz-12kHz.		59.95
E835		Cardioid vocal mid	c, 40Hz-18kHz			99.99
E835S		As E835, with swith	tch			
E845		Supercardioid voc	al mic. 40Hz-16kH	Hz		139.95
						149.95
						269.95
						169.95
						219.95
E965		Large diaphragm	condenser vocal n	nic.		
					z	699.95
THREEPACK83	5					249.95
						5.99











# One of a Kind.

EVOLUTION E600/800 SERIES STAGE MICROPHONES

Rugged, reliable, and surprisingly affordable, Sennheiser's evolution e600/800 series microphones fit every style of performance. The evolution e600 (instrument) and e800 (vocals, speech) series includes a wide range dynamic and condenser microphones, each tailored to yield great sound with low handling noise and high feedback rejection. Experience German engineering on your stage, with evolution e600/800 series microphones.



800-356-5844 fullcompass.com





















ITEM

SV100-W...

SV200-W .....

storage bag.

ITEM

ITEM

SM58CN

SM58LC.

SM58X2II

A25D

SM48LC































SHURE 55SH SERIES II AND SUPER 55 DELUXE VOCAL MICROPHONES Both models feature vintage design with modern performance. The iconic 55SH-II unidyne mic features a satin chrome-plated die-cast casing and a cardioid directional pattern that minimizes sound pickup from the rear of the mic. It has a 50Hz-15kHz frequency response, swivel base with on/off switch, and XLR connector. The Super 55 Deluxe features the same casing but a supercardioid polar pattern and includes a blue foam pop filter. It offers additional clarity and high gain-before-feedback, has a 60Hz-17kHz frequency response and includes a swivel stand mount.

ITEM	DESCRIPTION	PRICE
55SH-II	. Cardioid vocal mic	. 179.00
SUPER-55	.Supercardioid vocal mic, blue foam pop filter	. 249.00

**SHURE SV MICROPHONES** 

These entry-level microphones

are cost-effective yet retain good

sound quality. The SV100 is a

dynamic microphone ideal for the

spoken word, karaoke, multimedia

and instrument use. The SV200 is

a dynamic mic that delivers crisp, vibrant sound optimized for lead

DESCRIPTION

SV100-WA ... As above, plus clip,

SV200-WA ... As above, plus clip,

and backup vocals. Both models feature a cardioid

pickup pattern, on/off switch, frequency range of

Dynamic cardioid multi-purpose mic

50Hz-15kHz, and -52dBV/Pa at 1kHz sensitivity.

with XLR-1/4" cable ....

thread adapter, pouch.

with XLRM-XLRF cable ..

thread adapter, pouch..

SHURE SM48LC DYNAMIC CARDIOID

MIC Designed for pro sound reinforcement,

studio recording, and broadcasting applications. Both include a shock mounted cartridge, a steel mesh grille, and an integral "pop" filter. The SM48S also includes a lockable on/off

switch. Includes stand adapter and carrying/

DESCRIPTION

.Cardioid dynamic...

SM48S-LC ...... Cardioid dynamic with switch.....

SHURE SM58 DYNAMIC VOCAL

MICROPHONE This cardioid mic has a

dynamic range of 50Hz-15kHz, features

built-in spherical wind and pop filter, and a pneumatic shock-mount system to reduce

handling noise. Its frequency response is

tailored for vocals, with brightened mid-

range and bass roll-off. Ships with stand

As SM58LC, with switch..

(other colors available) 300-BLACK.. Optional Windtech windscreen, black (other colors available) ...

XLR to USB adapter...

SM58LC packaged with X2U

Replacement stand clamp ......

Cardioid dynamic vocal mic, with cable .. 109.00

. Cardioid dynamic vocal mic, no cable ...... 99.00

Follow Us!

DESCRIPTION

A58WS-BK... Foam windscreen, black

adapter and storage bag.

Dynamic cardioid vocal mic

SV100

SV200

PRICE

.34.99

PRICE

.51.86

PRICE

.104.00

...199.00

..7.44

SHURE 588SDX The versatility and economy champ for general sound reinforcement. Switch selectable dual-impedance design with locking on/off switch

55SH-II

SUPER-55

OIF OII OWITCH.			
ITEM	DESCRIPTION	PRICE	
588SDX	Cardioid dynamic vocal mic	59.16	
A58WS	Foam windscreen	7.44	
A25D	Replacement stand adapter	5.76	

SHURE 565SD-LC Perfect for sound reinforcement applications such as voice reproduction on lecterns, stages, church and school sound systems. Dual impedance and locking on/off switch.

ITEM	DESCRIPTION	PRICE
	Cardioid dynamic vocal mio	
A25DM	Replacement stand adapte	r 45.60

#### SHURE SM86 CONDENSER VOCAL MIC

The SM86's condenser capsule provides studioquality sound and tailored frequency response for clear reproduction of vocals. Cardioid polar pattern, built-in 3-point shock mount, 2-stage filter reduces wind and "pop" noise.

ITEM	DESCRIPTION	PRICE
SM86LC	Condenser vocal mic	179.00

BETA87A

BETA87C

SHURE BETA-87 VOCAL MICS Studio-quality sound in live vocals with smooth, tailored response and an extremely accurate supercardioid pattern at all frequencies, providing greater gain before feedback. A break-resistant stand adapter is included for the new larger handle. Also includes high sound level capability, a 3-stage pop filter, low-noise electronics and full

magnetic shielding. Ideal for concert sound and music production

productio	111.	
ITEM	DESCRIPTION	PRICE
BETA87A	Supercardioid condenser mic	rophone 249.00
BETA87C	Cardioid microphone	249.00
A85WS	Windscreen	10.75

SUPERCARDIOID SHURE SM87A CONDENSER MIC Tailored for warm, rich, vocal reproduction. Includes the A25D breakresistant swivel adapter. Requires phantom power. Frequency response is 50Hz-18kHz.

ITEM	DESCRIPTION	PRICE
SM87A	Supercardioid condense	er mic 212.49



MICS Legendary reliability and quality in easy-to-use microphones. Designed for specific applications, they come complete with a 25-ft cable, clip and storage bag. The onstage vocal microphones feature a convenient on/off switch.

ITEM	DESCRIPTION	PRICE
PG48-QTR	Dynamic cardioid, speech/karaoke	
	mic with XLR-1/4" cable	39.00
PG48-XLR	Dynamic, speech/karaoke mic,	
	with XLR-XLR cable	39.00
PG52-XLR	Kick drum mic	119.00
PG56-XLR	Drum mic	69.00
PG57-XLR	Instrument mic	59.00
PG58-QTR	Dynamic, vocal performance mic,	
	with XLR-1/4" cable	59.00
PG58-XLR	Dynamic, vocal performance mic,	
	with XLR-XLR cable	59.00

SHURE BETA58A A true supercardioid polar pattern at all frequencies gives you unprecedented gain-before-feedback. Extended high frequency response provides clarity normally only found in condenser mics.

ITEM	DESCRIPTION	PRICE
BETA58A	Supercardioid dynamic	
	vocal mic	159.00
A58WS	Foam windscreen	7.44

#### SHURE KSM9 HANDHELD CONDENSER MICROPHONE

Provides extraordinary vocal reproduction for critical applications. The KSM9 features a dualdiaphragm design with choice of cardioid and supercardioid patterns, smooth response, minimal proximity effect, and maximum gain-before-feedback. A 2-stage shock mount greatly reduces handling noise. 50Hz-20kHz response, 1E2dD CDI 22 dDA aolf naise A v

1550D 5FL, 22 0DA Sell-Holse A-weighted.		-
ITEM	DESCRIPTION	PRICE
KSM9/CG	Dual-pattern, handheld condenser	
	mic in gray	699.00
KSM9/SI	Champagne colored version	699 00





MICROPHOME DISINFECTANT FOAM & MIC **CLEANING KIT** Designed to disinfect exterior mic surfaces while not touching sensitive inner electronics. Microphome is antimicrobial, alcohol-free, fastdrying and leaves no residue. One 50 mL bottle is good for 100 disinfections. Cleaning kit comes with a bottle of Microphome, microfiber cleaning cloth, soft nylon scouring pad, two-sided cleaning brush and zippered black vinyl mic bag.

ITEM	DESCRIPTION	PRICE
MICROPHOME-BOTTLE	50ml bottle of microphone	
	disinfectant	8.95
MICROPHOME-KIT	Disinfectant, cloth, brush, scour pad and mic bag	19.95









**AKG D112 BASS MIC** Ideal for kick drum and bass guitar applications. It features zero distor-

by HARMAN tion even at high sound pressure levels, very low diaphragm resonance, a relatively narrow-band rising high frequency response at 4kHz, frequency response range of 20Hz-17kHz and extremely robust construction. Perfect for both studio and live applications.

ITEM	DESCRIPTION	PRICE
D112	.Bass microphone	199.00

#### beyerdynamic)



#### BEYERDYNAMIC M201TG HYPERCARDIOID

Low-mass moving coil transducer design, high SPL handling, and rugged construction make the M201 an excellent choice for drum and percussion miking. High sensitivity provides excellent intelligibility and transient response. 40Hz-18kHz.

ITEM	DESCRIPTION	PRICE
M201TG	Tour group version (int shock mounting)	299.00

#### BEYERDYNAMIC M69TG DYNAMIC

The M69's tight hypercardioid pattern and reduced proximity effect make it an excellent choice for vocals or instruments.

ITEM	DESCRIPTION	PRICE
M69TG	Hypercardioid moving coil	
	dynamic microphone	299.00
WS59	Replacement foam windscreen.	24.90
MKV8	Replacement stand adapter	19.90
	Replacement pop-screen	



#### ENCORE 1001 DYNAMIC

INSTRUMENT MIC Features a new dynamic capsule with a custom-tuned diaphragm to provide a tighter polar pattern, custom circuit with transformer, hi-pass filter, and a specially-designed grill to fit in tight spaces and protect from instrument strikes.

ITEM	DESCRIPTION	PRICE
ENCORE-1001	Dynamic cardioid mic,	
	50Hz-16kHz, clip & pouch	89.99



noise from floor vibrations and

enables rumble-free close-miking

of the singer. With its robust construction and heavy feel, it's sure to

withstand t	he rigors of the road.	
ITEM	DESCRIPTION	PRICE
CR-77	Dynamic vocal stage mic	179.95

#### **AUDIX D-SERIES INSTRUMENT MICS**

The D-Series dynamic microphones feature very lowmass diaphragms for accurate and sensitive pickup of instrument harmonics and subtle nuances. Housed in tooled aluminum cases, these microphones are extremely rugged, yet lightweight and compact. A tight hypercardioid pickup pat-

tern allows for clear definition and excellent feedback rejection. All microphones have a max SPL rating of 144dB.

ITEM	DESCRIPTION	PRICE
D2	.Instrument microphone (toms, kick drum, conga, sax)	129.00
D4	.Instrument microphone (low-frequency instruments)	150.00
D6	.Kick drum microphone	200.00
D6-KD	.As above, with boom stand	229.00

AUDIX I-5 DYNAMIC CARDIOID A dynamic microphone that can be used for any instrument miking application for stage and studio. With its sleek styling and unique probe cap design, the I-5 features a durable cast zinc alloy body and black E-coat finish. The I-5 is designed with a cardioid polar pattern, allowing it to focus on the particular instrument without picking up other instruments or ambient noise on stage. With a smooth and uniform frequency response of 50Hz-16kHz and an ability to handle sound pressure levels in excess of 140dB, the I-5 can be used for a wide variety of applications and for all genres of music.

ITEM	•	••	DESCRIPTION	PRICE
I-5			Cardioid	99.00
CAB-GRAB	1		Mic clamp for guitar amps and cabinets	49.95

EV RE20/RE27N/D DYNAMIC CARDIOID The legendary RE20 is designed for critical recording and broadcast. Peak free response even up close, it is ideal for the studio as well as voice overs, announce booths. Features include a bass roll-off switch and Variable-D cardioid pattern which

has no proximity effect for the same response at any distance. RE27N/D is a modernized version of the RE20, with a neodymium alloy magnet, and extended high frequency response for a condenser like sound.

	DESCRIPTION	PRICE
RE20	Dynamic cardioid, 45Hz-18kHz	449.00
RE27N/D	Dynamic cardioid, 45Hz-20kHz	499.00
309A	Spider shock mount	172.50
320	Replacement stand clamp	59.50
20/421	Windtech windscreen	31.95
VAC-RE20	Integrated dual 3.5" screen pop filter & mount for RE20/RE27 .	65.86

EV RE320 VARIABLE-D DYNAMIC MICROPHONE Designed for recording and reinforcement applications requiring extremely low noise as well as predictable tonal and transient response. The "Variable-D" proximity control minimizes positional and off-axis tonal shifts. Its unique "Dual-Personality" switch effectively creates 2 microphones in 1 body. One switch position delivers voice, electric and acoustic instruments with a lively, yet natural tonal response. The other position delivers an "insta-kick" curve designed specifically for kick drums. Other features include integrated hum-bucking coil, built-in pop filter, neodymium magnet structure, cardioid pickup pattern, dynamic element and frequency responses of 30Hz-18kHz (insta-kick mode) and 45Hz-18kHz (voice/instrument mode).

ITEM	DESCRIPTION	PRICE
RE320	Dynamic cardioid microphone	299.00



HEIL SOUND PR SERIES DYNAMIC MICS The PR28 has a unique dual suspension system between the element, grill and body to reduce vibration making it great for toms and snares. The PR30 features the largest dynamic element available making it great for guitars and broadcasters alike. The PR40 has a large low-mass aluminum voice coil and is recommended for studio voice applications as well as bass drums and bass guitar.

ITEM	DESCRIPTION	PRICE
PR28	55Hz-18kHz, cardioid, black finish, internal dual suspension	149.00
PR30	40Hz-18kHz, supercardioid, anodized matte champagne finish, includes stand clip	. 252.00
PR40	28Hz-18kHz, supercardioid, anodized matte champagne finish, includes metal carrying	
	case and stand clip	327.00









PR30



PR40



ii ii ii ii


COMPUTER AV





























































#### **CAD AUDIO CADLIVE MICROPHONES**

Perfect for stage or studio, these low-profile mics are ideal for miking guitar cabinets or percussion. Whether used individually or in tandem to create unique tones, these mics deliver performance, value and sonic quality. D80 is a large diaphragm dynamic microphone offering a tight supercardioid polar pattern and high output level while D84 is a large diaphragm condenser microphone with internal shock mounting to reduce handling noise. D82 is a ribbon microphone with a figure-8 pattern, 30Hz-20kHz frequency response and 140dB max SPL handling, making it perfect for use high volume environments.

ITEM	DESCRIPTION	PRICE
D80	Large diaphragm dynamic mic	99.00
D82	Ribbon mic	. 159.00
D84	Large diaphragm condenser mic	. 159.00



#### T SENNHEISER

#### SENNHEISER E900 SERIES CARDIOID DYNAMIC INSTRUMENT

MICS Cardioid dynamic microphones designed for instrument pickup in live performance and recording applications. Each has been specifically optimized for a particular family of instruments. E906 features a flat physical design and three switchable presence filter levels.

1 5	Transfer of the state of the st	1000
ITEM	DESCRIPTION	PRICE
E902.	For deep bass frequencies-kick drums, bass guitar amps, and tuba, 20Hz-18kHz	199.95
E904.	For drums — includes MZH 604 drum clip, 40Hz-18kHz	199.95
E906.	For guitar amps, percussion and horns, 40Hz-18kHz	189.95

#### SENNHEISER E602II BASS DRUM

MIC A big fat bottom end with very smooth top-end. Can be used with no EQ. 20Hz-16kHz response, cardioid pattern, with built-in stand mount.

ITEM	DESCRIPTION	PRICE
E60211	Bass drum microphone	e 159.95



#### SENNHEISER E609-SILVER **INSTRUMENT MIC** This supercardioid mic with a response of 40Hz-18kHz has the unique shape which allows it to be hung on

the amp. No S	PL limits on this mic.	-
ITEM	DESCRIPTION	PRICE
E609-SILVER	Silver finish super cardioid	109.95

#### **SENNHEISER MD421-II DYNAMIC CARDIOID**

One of the most versatile and popular of Sennheiser's dynamic microphones. The MD421-II is renowned for its sonic quality, ability to handle high sound pressure levels and durability. A favorite of musicians, broadcasters, recording studios and sound contractors. Five position bass roll-off switch provides equalization control up to 1000Hz. Humbucking coil to reduce interference from equipment and power.

ITEM	DESCRIPTION	PRICE
MD421-II	Dynamic cardioid	379.95
MZA421	Replacement stand bracket	33.95
MZW421	Windscreen	34.95
20/421	Windtech windscreen	31.95

#### SHURE

SHURE PERFORMANCE GEAR MICROPHONES Performance Gear microphones, the Shure name and Shure quality at a great price. The PG57 is for both amplified and acoustic instruments. The PG52 is for kick drum for low-end punch. The PG56 is for snare or tom and includes the A50D drum mount. All are dynamic cardioid and include stand mounts and 25' cable

iyilamic cardioid and incidde stand mounts and 25 cable.				
ITEM	DESCRIPTION	PRICE		
PG52-XLR	. Kick drum mic	119.00		
PG56-XLR	Drum mic	69.00		
PG57-XLR	Instrument mic	59.00		

SHURE SM7B The smooth and silky unidirectional SM7 is famous for making voices and other sources sound their best. A humbucking coil has been added to this classic to help reject interference in environments where computers are present. Extremely popular for radio and television, especially voice-overs. Unique graphic EQ tailoring switches permit the choice of four different response curves. Yoke assembly allows exact positioning.

ITEM	DESCRIPTION	PRICE
SM7B	Cardioid microphone	349.00
RK345	Replacement foam windscreen	13.78
A7WS	Closetalk windscreen	22.80

#### SHURE

SHURE BETA52A Its specially tailored, low frequency response is designed to deliver a new level of lowend punch on kick drums and other bass instruments. Adjustable, locking mount makes for fast, easy set up-even in the confines of a kick drum. It is designed

to withstand the wear and tear of life on the road, with features like a hardened grille and shock mount.

ITEM	DESCRIPTION	PRICE
BETA52A	Supercardioid microphone	189.00

SHURE BETA56A It mounts quickly and easily, thanks to its adjustable locking base and compact swivel head design. Features a wear-resistant, hardened grille and a unique shock mount that minimizes mechanical noise and pickup even in abusive environments both on and off stage.

ITEM	DESCRIPTION	PRICE
BETA56A	Supercardioid microphone	159.00
A1WS	Foam windscreen (gray)	4.92

SHURE BETA57A All the impact of the original SM57 with extended low bass response plus smoother, more gradual presence and extended high frequency response. With a steel grille and a true supercardioid polar pattern providing maximum isolation and minimum feedback this mic is excellent for instruments, studio and live performance.

ITEM	DESCRIPTION	PRICE
BETA57A	Supercardioid microphone	139.00
A57AWS	Locking magnetic windscreen	9.98
A25D	Replacement stand adapter	5.76

SM57 DYNAMIC CARDIOID MIC Exceptional for musical instrument pickup and vocals. With its bright, clean sound and contoured frequency response, the SM57 is ideal for musical instruments or vocals, live sound reinforcement and recording. It has an extremely effective cardioid pickup pattern which isolates the main sound source while minimizing background noise. In the studio, it is excellent for recording drums, guitar, and woodwinds.

		_
ITEM	DESCRIPTION	PRICE
SM57LC	Dynamic mic, cardioid,	
	40Hz-15kHz, no cable	99.00
SM57X2U	SM57LC packaged with X2U	
	XLR to USB adapter	199.00
A2WS-BLK	Optional locking windscreen, bla	ack 17.28

SHURE 545SD-LC This microphone's remarkably faithful response makes it a favorite choice for instrument pickup, lecterns, speakers and entertainers. Dual impedance for use with most sound equipment. With locking on/off switch.

ITEM	DESCRIPTION	PRICE
545SD-LC	Microphone	95.85
A2WS-GRA	Foam windscreen with	
	locking feature (gray)	17.28
A2WS-BLK	Foam windscreen with	
	locking feature (black)	17.28
A25D	Replacement stand	
	adanter	5.76











#### TELEFUNKEN ELEKTROAKUSTIK

M81 DYNAMIC MIC A cardioid mic that features minimal proximity effect, superior feedback rejection, and an articulate mid-range. Great for applications needing more body and clarity. The top end is pulled back to yield a flatter frequency response, making it a great tool for taming brighter vocals, guitar tones and for fattening up percussion, horns and thinner sound sources. Comes with wooden box, additional black head grille, and mic clip.

ITEM	DESCRIP	TION		PRICE
M81	.Cardioid	dynamic	microphone	249.00

TELEFUNKEN ELEKTROAKUSTIK **CARDIOID** DYNAMIC MICROPHONE This flexible endaddress microphone offers 4 voice settings via two discrete switches, allowing the response to be customtailored to the source. The KICK EQ switch reduces frequencies centered around 350Hz, while the HIGH BOOST emphasizes upper mids, boosting

them 6dB from 2kHz-6kHz. SPL-handling capabilities of up to 160dB SPL, a 35mm diaphragm, and 25-18kHz frequency response make this mic ideal for almost any application. Includes a stand mount adapter and protective zipper case.

ITEM	DESCRIPTION	PRICE
M82	. Cardioid dynamic microphone	399.00



#### TELEFUNKEN ELEKTROAKUSTIK M80-SH/ **M81-SH CARDIOID DYNAMIC MICROPHONES**

Ideal for live use due to their small form and feedback rejection, these dynamic microphones were designed to complement each other during use. Both models offer 30Hz-18kHz frequency response,  $200\Omega$  impedance and cardioid polar patterns. M80-SH is voiced for midrange-heavy sources such as snare drums and vocals. The M81-SH has a slightly decreased treble response, making it ideal for use on vocals, guitars, percussion and horns. The M80-SH has a chrome grille and the M80-SHB has a black grille. Includes a spare grille, leather carrying bag and 5-meter (16.4ft) right angle XLR cable.

ITEM	DESCRIPTION	PRICE
M80-SH	Cardioid dynamic microphone,	
	chrome grille	249.00
M80-SHB.	Cardioid dynamic microphone,	
	black grille	249.00
M81-SH	Cardioid dynamic microphone,	
	chrome grille	249.00



#### **AUDIX BP7PRO BAND PACK PERCUSSION MICROPHONE KIT**

This seven-piece professional microphone pack includes everything you need to capture a great-sounding drum performance. The kit consists of (1) D6 kick drum microphone, (1) OM5 snare drum microphone, (3) i5 tom microphones, (2) OM2 overhead microphones, (6) MC1 microphone clips and (1) DCLIP microphone clip. It ships in a sturdy aluminum road case.

ITEM	DESCRIPTION	PRIC
BP7PR0	.7-piece drum microphone kit	699.0

AUDIX DP-QUAD 4-PIECE DRUM MIC PACK The Audix DP Series QUAD pack is the simplest and most effective combination of microphones that will allow you to capture the depth and imaging of a full drum kit. Kit includes (1) D6 kick drum mic, (1) I5 for snare, (2) ADX51 overhead mics, (1) DVICE rim mount with MC1 mic clip, (3) DCLIP mic clips, and (2) WS81C windscreens.

ITEM	DESCRIPTION	PRICE
DPQUAD	4-piece drum microphone kit	599.00



and easy set up and perfect mic placement. DESCRIPTION ITEM .5-mic kit with (1) i5 snare, (2) D2-toms, (1) D4 kick/floor tom, (1) D6 kick, (4) D-vice gooseneck clips. 659.00 7-mic kit with (1) i5 snare, (2) D2 toms, (1) D4 kick/floor tom, (1) D6 kick, (2) ADX51 condensers, (4) D-vice gooseneck clips. 899.00 .8-mic kit with (1) i5 snare, (2) D2 toms, (1) D4 kick/tom, (1) D6 kick, (2) SCX1 condensers, (1) SCX1-HC hi-hat, (4) D-vice gooseneck clips. 2199.00

#### **AUDIX FUSION SERIES DRUM MIC**

**AUDIX DP SERIES DRUM MIC KITS** 

drums. The D6 is the quintessential kick

drum mic and the i5 snare drum mic is

gooseneck rim mount allows for quick

designed for sonic accuracy, con-

sistency and durability. The ADX51

and SCX condensers are ideal for

hi-hat & overheads. The DVICE

Each kit contains a minimum of 5 mics. The

D2 is designed to be used for toms and the

D4 is designed for floor toms or small kick

KITS Designed, assembled and tested in the USA, these mics fulfill all the performance criteria required for pro-

All mics come with	h high impact stand avy-duty foam lined	4	4		•
aluminum carrying		8 .	7	77	
ITEM FP5-FIISION	DESCRIPTION  Kit includes: (1) F5 sna	re mic	(3) F2 tom mics	(1) F6 kick mic	

ITEM	DESCRIPTION	N				_						8		PRICE
FP5-FUSION	Kit includes:	(1) F5	snare mi	c, (3)	F2 tom	mics,	(1) F	6 kick	mic					349.00
FP7-FUSION	Kit includes:	(1) F5	snare mi	c, (3)	F2 tom	mics,	(1) F	6 kick	mic, (2)	F9 over	head	conde	enser	mics 499.00



KIT AKG's Rhythm Pack contains (1) D112, (2) C430's for overheads, (3)

D40's for toms and snare, and stand adapters, all in a protective aluminum carrying case.

ITEM	DESCRIPTION	PRICE
RHYTHM-PA	ACKDrum mic kit	699.00

#### **GROOVE PACK**

A complete 6-piece drumkit mic pack with an aluminum carrying case, all mounting clamps and stand adapters. All PERCEPTION live microphones feature a metal casing, steel microphone grill, scratch-resistant finish, gold plated XLR pins, and high maximum SPL.

ITEM	DESCRIPTION	PRICE
GROOVE-PACK	6-mic drum pack with (1) P2 bass	mic,
	(3) P4 tom/snare mics, (2) P17 ov	erheads
	(P17 has identical specifications	
	+o D170)	200 00















































M-F: 9:00-5:30 Central



















































This premium reference drum microphone set offers 8 high-quality mics, handselected for touring, live and studio applications. The kit includes (1) D12 VR dynamic bass drum mic, (1) matched pair of C214 condenser mics for overhead use, (1) C451 B condenser microphone for hi-hats, and (4) D40 dynamic instrument microphones for snare and toms. Comes in a heavy-duty metal case and includes mic clamps and stand adapters.

•		
ITEM	DESCRIPTION	PRICE
DRUMSET-PREMIUM	.8-piece drumset mic package	1999.00



feature combinations of the D29 dynamic tom mic, D19 supercardioid dynamic snare mic, D10 cardioid dynamic kick drum mic and the C9 cardioid condenser overhead mic. Touring7 offers the TSM411 dynamic tom/snare mic, D12 dynamic kick drum mic and GXL1200 over overhead condenser mic.

ITEM	DESCRIPTION	PRICE
STAGE4	Includes (2) D29 tom mics, (1) D19 snare mic,	
	(1) D12 kick drum mic with drum clips and vinyl carry case	. 119.00
STAGE7	Includes (3) D29 tom mics, (1) D19 snare mic, (1) D12 kick drum mic,	
	(2) C9 overhead with drum/mic clips and hardshell carry case	. 199.00
TOURING7	Includes (4) TSM411snare mics, (1) D12 kick drum mic,	
	(2) GXL1200 overhead mic, (4) DMX-1 drum-mounting clips,	
	and metal carry case	299 00



sturdy shock mounts and detachable heavy-duty cables. They can easily be unclipped and repositioned or moved to another instrument with only one hand. The dvote mounting system is designed to be extremely gentle, never marring the surface of an instrument. The 10-piece kit comes with 10 microphones, 7 drum clips, and a wide selection of instrument clips. The 4-piece kit includes 4 microphones, 2 universal clips and a wide selection of instrument clips. Both packages include all necessary cable and adapters.

ITEM	DESCRIPTION	PRICE
V04-R0CK	4-piece microphone kit	2499.00
V010-ROCK	10-piece microphone kit	5999.95



studio recording applications, these dynamic microphone Elektroakustik packages each feature one

M82 large diaphragm kick drum microphone, one M80-SHB snare drum microphone and two (DD4) or 3 (DD5) M81-SH tom microphones. These versatile kits include all the necessary drum mounts, a 15ft XLR cable for each microphone and ship in a hard shell flight case.

ITEM	DESCRIPTION	PRICE
DD4	Drum microphone kit, (1) M82, (1) M80-SHB, (2) M81-SH	1149.00
DD5	Drum microphone kit, (1) M82, (1) M80-SHB, (3) M81-SH	1349.00

### **TSENNHEISER**

### SENNHEISER DRUMKIT-600 DRUM

MIC KIT Includes (1) e602-II for the kick drum, (4) e604s for snare and toms, and (2) e614s for overheads. The e602-II is a cardioid mic designed for low frequency instruments. The e604 handles SPL ratings of over 150dB and has a cardioid pattern optimized for use on drum sets. It is housed in a tough, reinforced glass fiber body and has an inte-



grated, pivoting mount that can attach to mic stands or the rim of a drum. The e614's supercardioid pattern, neutral response and moderate sensitivity ensures optimum isolation. The phantom-powered e614 tolerates extremely high SPLs and precisely captures cymbals and hi-hats.

ITEM	DESCRIPTION	PRICE
DRUMKIT-600	Drumset microphone kit	999.95

SHURE DMK57-52 DRUM MIC KIT This kit is ideal for a kick drum, snare drum, and rack/floor toms. Includes (3) SM57 mics, (1) Beta 52A mic, (3) A56D drum-mounting systems, and a lightweight carrying case. The SM57 cardioid dynamic mic is perfect for a snare drum & toms. The supercardioid Beta 52A is perfect for a kick drum and

is designed with an integral locking stand mount for easy set up. The A56D universal mounting system can be used to position mics virtually anywhere.

ITEM	DESCRIPTION	PRICE
DMK57-52	. Drum mic kit with (3) SM57 mics, (1) Beta 52A mic,	
	(3) A56D mounts, case	. 399.00

### SHURE PG SERIES DRUM MIC KITS

All-in-one mic kits including XLR-to-XLR cables, drum mounting hardware, and carrying case. Each mic has a tailored frequency response tuned specifically for drums. The PG56 is a compact drum mic for up-close recording. The PG52 is designed for the kick drum while the



ruot is ideal for ove	ernead & cymbais.	PGDMK4-XLR	PGDMK6-XLR
ITEM	DESCRIPTION		PRICE
PGDMK4-XLR	4-mic drum kit with (3) PG56 mic	s, (1) PG52 mic,	
	(3) A50D drum mounts, (4) XLR ca	ables, case	249.00
PGDMK6-XLR	6-mic drum kit with (3) PG56 mic	s, (1) PG52 mic,	
	(2) PG81 mics, (3) A50D drum mo	unts, (6) XLR cables,	case 399.00

### Select Accessories for Percussion Mics





PRIMACOUSTIC **DRUM MIC SHIELD** 

PRIMACOUSTIC









AUDIX ADX10-FL FLUTE MICROPHONE A miniature, high-performance professional condenser mic with a custom-designed

DESCRIPTION

ADX10-FL-P









PRICE

229 00





















PRICE

















Each MicroMic offers a flexible gooseneck for optimal positioning, elastic suspension to suppress spurious noise, metal capsule housings and detachable cable. These cardioid mics also have an adapter plate that allows them to be attached directly to AKG WMS40PRO and WMS400 body pack transmitters, eliminating cable runs between the mic and wireless transmitter.

ITEM DESCRIPTION F	PRICE
C516MLFor accordion, guitar speakers, piano and keyboard/organ cabinets 1	89.00
C518MFor drums and percussion (external phantom power)	49.00
C519MFor woodwinds and brass (external phantom power)	49.00
C519MLFor woodwinds and brass, for use with AKG B29L/WMS	
body pack transmitters	89.00
B29LPortable phantom power supply (battery powered)	79.00

AKG C411/L ACOUSTIC PICKUP FOR STRING **INSTRUMENTS** This condenser acoustic pickup with its tailored frequency response is ideal for acoustic guitar, mandolin, violin and most other stringed instruments. Placing the small ultra-light C 411 on or near the bridge will reproduce a clear and uncolored sound without changing the balance of the instrument. Attaching it is easy with the included non-marring reusable adhesive compound.



C519

	3	
ITEM	DESCRIPTION	PRICE
C411/L	.Acoustic instrument pickup, Figure-8 polar pattern, 10Hz-18kHz	129.00

APPLIED MICROPHONE TECHNOLOGY M40 PIANO

MICROPHONE This omnidirectional condenser mic is especially suited for piano, but also works well for boundary layer recording. With its mono design, the system can

be used even when the piano lid is closed. The M40's signal can also be split with frequencies rolled off to create a stereo image. It can handle sound pressure levels up to 141dB, and its rugged construction of anodized aviation aluminum is lightweight and durable. Comes with an AP40 aluminum preamp and protective case.

ITEM	DESCRIPTION	PRICE
M40	Omni condenser piano mic	. 471.00

### (A) audio-technica. always listening...

AUDIO-TECHNICA ATM350 CARDIOID CONDENSER CLIP-ON INSTRUMENT MICROPHONE Supplied with Audio-Technica's versatile UniMount® clip and new violin mount, the low-profile ATM350 is an exceptional cardioid condenser microphone designed to clip to brass, reeds, piano, snare, toms, and violin. The microphone offers a crisp, clear, well-balanced response, even at high SPLs. It features an integral 80Hz hi-pass filter and is also equipped with a new in-line power module. Its cardioid polar pattern reduces pickup of sounds from the side and rear for effective protection against feedback.




ITEM	DESCRIPTION	PRICE
ATM350	Clip-on condenser mic, 40Hz-20kHz	. 279.00
AT8418	Replacement instrument mount and windscreen	34.02

AUDIO-TECHNICA PRO35 CARDIOID CONDENSER CLIP-ON **INSTRUMENT MICROPHONE** Designed for saxophones, toms, brass and percussion, the PRO35 excels in high-SPL applications and is ideal for active stage performances. A UniMount clip permits accurate positioning, provides shock resistance and protects the element. Switchable low frequency roll-off at 80Hz. 6' cable permanently attached between microphone and power module, XLRM connector on module.

Shop fullcompass.com today!

ITEM

PRO35





### Wired flute microphone ...... As above, for use with RAD360 wireless ... ADX10-FL..... 199.00

flute head joint mount that keeps the microphone in place, making it ideally suited for

live performance. The ADX10FLP offers a warm, rich sound atypical for microphones

this size. The ADX10FLP comes wired with an 8' cable terminating to a mini XLRF con-

nector and a phantom power/battery power adapter (APS 911). Also available as the

ADX10FL; for use with the Audix RAD360 wireless system which includes a flute clip, 3'

attached cable terminating to a mini-XLRF connector (no power supply).

AUDIX ADX20-IP Pre-polarized condenser microphone designed to handle a wide variety of clip-on applications. It is ideally suited for saxophone, trombone, trumpet and other brass instruments. With a smooth uniform response over a frequency range of 40Hz-20kHz, it provides a rich, warm sound not typical of microphones this size. Low noise electronic circuitry, and balanced low impedance output allow for interference-free performance even with long cable runs. Phantom power required.

•		•	-	
ITEM	DESCRIPTION			PRICE
ADX20-IP	Cardioid, $250\Omega$	 		179.00

AUDIX MICRO-D Pre-polarized condenser microphone designed for many applications including drums, percussion, amplified cabinets, speech, vocals and acoustic instruments. Can be used in conjunction with 3 different specialized clips and 2 different interchangeable capsules to fulfill a wide variety of creative needs. Operates on phantom power of 9-52V and is supplied with a phantom power adapter, integral DVICE clamp, cable, windscreen, and carrying pouch.



ITEM	DESCRIPTION	PRICE
MICRO-D	. 40Hz-20kHz, hypercardioid, 250 $\Omega$	189.00


4000-27587

**BARCUS-BERRY 4000 PIANO & HARP PLANAR WAVE** 

**DARCUS-** SYSTEM Recording a piano can be a nightmare but this piano pickup reproduces the key-

board's full frequency range with perfect amplitude balance. It provides excellent isolation from ambient sounds with superior feedback rejection. It is quick to set-up - no holes to drill. Includes preamp with 1/4" hi-Z and XLR lo-Z outputs, piezo crystal, adhesive patches, 4 rubber

Piano pickup





BARCUS-BERRY ACOUSTIC INSTRUMENT PICK-UPS A specialized line of pickups designed for specific instruments to provide high quality pick-up, free of hum and feedback in amplified live performance applications. They are ideal for use with wireless transmitters to permit free movement on the stage.

DESCRIPTION	PRICE
Violin bridge with built in piezo pickup, 1/4" output jack	104.99
Outsider piezo transducer, 1' cable	59.00
Outsider piezo transducer, 2' cable	59.99
Acoustic guitar bridge pickup for 6-string instruments	49.00
Violin clamp-on piezo pickup, 1/4" output jack	118.00
Cello clamp-on piezo transducer with pre-amp	271.95
Flute electret mic with preamp/power supply, headjoint cork	271.95
Bass piezo transducer & preamp, clamp style with preamp	277.00
External mount soundboard transducer	41.00
	Violin bridge with built in piezo pickup, 1/4" output jack Outsider piezo transducer, 1' cable













































SENNHEISER E604 DYNAMIC INSTRUMENT MICROPHONE The e604 is a compact dynamic instrument microphone designed for drums and percussion. The integrated swivel mount allows for easy use in small spaces like drum kits. Its rugged glass fiber composite housing is makes it ideal for touring. The cardioid polar pattern, neodymium magnet and featherweight membrane provide enhanced low end response, excellent transient response and the ability to handle very high SPL's in excess of 160dB. Includes drum mounting clip and protective carrying pouch.

	3 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	
ITEM	DESCRIPTION PRIC	Ε
E604	Dynamic cardioid instrument microphone, 40Hz-18kHz	5
THREE	PACK604PThree-pack of E604's with 3 pouches	5

TG-D57C

### beyerdynamic)))

BEYERDYNAMIC TOURING GEAR D SERIES CLIP ON DRUM MICS The TGD52d is a hypercardioid dynamic mic designed for toms and features channel separation reducing crosstalk, high SPL handling, treble resonator for optimal high

frequency reproduction and a quick mounting gooseneck. The TGD57c is a cardioid condenser mic designed for toms, snare or percussion and features expanded frequency range, patented quick mounting, 72mm flexible gooseneck, treble resonator, 2nd treble resonator, and a frequency-independent polar pattern. The TGD58C is a cardioid condenser mic for rack toms, snare or percussion has the same features as the TGD57C plus an integrated pre-amplifier,

ITEM	DESCRIPTION	PRICE
TG-D52D	Clip-on cardioid dynamic mic	. 129.99
TG-D57C	Clip-on cardioid condenser mic	. 149.99
TG-D58C	Clip-on cardioid condenser mic with integrated pre-amp	. 149.99



low resonance housing.



Each 4099 is designed and optimized for one

particular instrument family to ensure the finest audio reinforcement when performing live. These condenser

microphones feature supercardioid polar patterns for highly uniform off-axis frequency response, superior gain-before-feedback, and are capable of handling high sound pressure levels. The versatile gooseneck provides stable positioning, and can easily be unclipped and repositioned with only one hand. The gentle mounting system will not mar the finish of the instrument. The included MicroDot connector and more than 35 available DPA adapters (purchased separately) ensure compatibility with just about any wireless system. It can also be used as a standard 48V phantom powered microphone with the supplied XLR connector.

ITEM	DESCRIPTION	PRICE
VO-4099-BASS	Double bass microphone with MicroDot connector	599.95
VO-4099-C	. Cello microphone with MicroDot connector	599.95
VO-4099-D	Drums microphone with MicroDot connector	599.95
VO-4099-G	Guitar and strings microphone with MicroDot connector .	599.95
VO-4099-P	Piano microphone with MicroDot connector	1198.98
VO-4099-SAX	SATB sax microphone with MicroDot connector	599.95
VO-4099-TRUMPET	. Trumpet/trombone microphone with MicroDot connector .	599.95
VO-4099-VIOLIN	Violin/banio/viola microphone with MicroDot connector	599.95

MicroDot Adapters - see page 28 in Head Worn Mics section for current models.



EARTHWORKS PIANOMIC™ SYSTEM This system meets piano recording needs for churches, performing arts centers and recording studios with high definition audio - whether the piano lid is up or down. It cannot be seen from outside the piano, needs no stands or mic booms, and allows virtually no leakage from sounds outside the piano. The touring version is collapsible and fits in an airline carrying case.

	0	
ITEM	DESCRIPTION	PRICE
PM40		łz 2999.00
PM40T	Touring version, collapsible, fits in small	er case3199.00
PMVM1	Leather pouch for PM40/PM40T electronic	cs box

### **SENNHEISER**°

SENNHEISER E908B CLIP-ON CONDENSER MIC The e908b condenser mic has an exceptionally lively and clear sound, designed for brass instruments. Comes with a mounting clamp for quick, flexible set-up and optimal positioning with the long-necked, flexible boom. The e908d is designed for drums and percussion, and comes with a drumset clamp and integrated shock absorber. Includes MZA 900 P preamp (cable, phantom power and level check).

ITEM	DESCRIPTION	PRICE
E908B	. For brass	279.95
E908B-EW	Wireless version of E908B	199.95
E908D	. For drums	279.95



SHURE BETA98 CONDENSER MINIATURE MICS High-performance mini-condenser mics for sound reinforcement and recording. Great for instruments or drums. The ultra-uniform pickup pattern provides high gainbefore-feedback and excellent rejection of unwanted noise. Other features include a frequency response of 20Hz-20kHz, an included preamplifier,

integrated shock mount and windscreen.

U		
	DESCRIPTION	PRICE
BETA98H/C	Clip-on instrument mic with preamp, 155dB max SPL	209.00
WB98H/C	Wireless version of BETA98H/C, 10ft cable terminated	
	with 4-pin mini (TA4F), 156dB max SPL	134.65
BETA98A/C	Instrument mic with preamp, RK282 for standard mic stands,	
	144dB max SPL	199.00
BETA98AD/C	Drum mic with preamp, A98D drum mount, 144dB max SPL	229.00
BETA98AMP/C	Drum mic with preamp, A75M universal mount, 153dB max SPL	269.00
A75M	Universal mic mount with clip adapters (large and small)	86.45
A98D	Clip-style mic mount	65.55

### **Looking for Instrument Pickups?** See page 277









R122V

SF12





**AEA BIG RIBBON™ MICROPHONES** These mics have a wideband response from 20Hz-20kHz, low self-noise and high SPL capabilities. R84 features a pure natural sound, figure-8 directional sensitivity and quick smooth transients. The A840 is the active version of the R84 and requires less gain than passive ribbons. R88 is

a stereo mic with 2 ribbon motors oriented at 90°, has excellent off-axis frequency response and is specifically designed for recording orchestras and choirs. The R92 has reduced proximity effect and excellent wind-blast protection making it suitable for close recording (6"-12"). KU4 features a supercardioid pattern, reduced proximity effect, field- replaceable ribbon assembly, and smooth, high bandwidth frequency response. The phantom-powered N22 is a bidirectional mic, specifically designed for singer-songwriters, musicians and home studio owners.

ITEM DESCRIPTION PRIC	Ε
R84General-purpose large ribbon mic with case, 165dB max SPL	0
R84SLEAs above, Silver Limited Edition version	0
A840Active, phantom-powered version of R84,	
with hard case,141dB max1553.0	0
R88Stereo large ribbon mic with case and 4-meter 5-pin female XLR	
to 3-pin male XLR break-out cable, 165dB max SPL	0
R92Large ribbon mic for close recording,	
includes case and attached 2-meter cable, 135dB max SPL	0
KU4Supercardioid ribbon mic, includes case,	
stand adapter and attached 1.5-meter cable, 140dB max SPL 4356.0	0
N22NUVO series phantom-powered ribbon mic	
with storage/shipping case, stand clip, mic sleeve	0
R84VCStorage and shipping case for (1) R84 series mic	0
TRP2-channel ribbon mic preamp	0



CLOUD MICROPHONES 44A ACTIVE RIBBON MIC This mic was made to emulate the early RCA 44 microphone designs and is suited for vocals, voice-overs and

also as overheads for classical recordings or drums. While the ribbon retains its original 1930's specs, the rest of the 44A has been engineered using 21st century technology, making this mic the best of both worlds: historical voicings and the strength, clarity and purity of today's current technology. The 44A also features

a high-pass filter for reduced proximity effect, but when turned off, it captures challenging fine details with incredibly high sensitivity.

ITEM	DESCRIPTION	PRICE
44A	. Active ribbon mic	1899.00



# **PREAMPLIFIERS** The Cloudlifter microphone preamplifers are designed for use with low-gain passive ribbon microphones and come in either a single- or dual-channel configurations, providing up to 25dB of gain. The single-channel CLZ adds a variable input impedance selector, switchable high-nass filter and a variable output

variable input impedance selector, switchable high-pass filter and a variable output gain selector.

ITEM DE	SCRIPTION	PRICE
CLOUDLIFTER-CL1 Sir	ngle-channel microphone preamplifier	
for	dynamic/ribbon microphones	149.00
CLOUDLIFTER-CL2 As	above, but dual-channel	249.00
CLOUDLIFTER-CLZ Sir	ngle-channel microphone preamplifier with variable input	
im	pedance, high-pass filter and output gain selection for	
dvi	namic/ribbon microphones	299.00

### beyerdynamic))))

### BEYERDYNAMIC M160 HYPERCARDIOID DOUBLE RIBBON MIC

Dynamic double ribbon microphone featuring a hypercardioid polar pattern, the M160 is an outstanding microphone for all types of remote and in-studio voice reproduction. Recommended for studio miking of string instruments such as violins, violas, cellos and for pianos, saxophones as well as for hi-hat, and toms. In conjunction with the M130 ribbon microphone the M160 is ideal for stereo recordings in MS technique.

ITEM	DESCRIPTION	PRICE
M160	. 40Hz-18kHz, hypercardioid	. 699.00



ROYER RIBBON MICS Smooth and clear with many of the attributes of condenser mics but with a wider dynamic range without pads and clipping. The frequency response is very flat

and the panoramic soundfield is well balanced. The figure-8 pattern offers excellent rejection at the sides – the ribbon is lengthwise providing a side-address type

microphone. The R-121 is compact and lightweight, but with high output. The R101 bears an offset-ribbon transducer, a 2.5 micron ribbon, and is great for studio and live settings.

The R-122 has a 48V phantom powered internal amplifier to provide 15dB more gain. The SF-12 offers 2 matched ribbon mics placed one above the other, each aimed 45° from the center in the classic Blumlein configuration. The SF-24 is an active version of the SF-12 and its output of 38dB is a full 14dB more sensitive than the SF-12. "LIVE" models feature a thicker, more durable

more sensitive than the SF-12. "LIVE" models feature a thicker, more durable ribbon suitable for the rigors of live stage applications. All models except for the SF12 come solely in a nickel finish.

TEM	DESCRIPTION	PRICE
R101	. Mono passive ribbon microphone	895.00
R121	Mono ribbon microphone	. 1295.00
R121-LIVE	R121 with thicker ribbon	. 1295.00
R122	Mono active ribbon microphone	. 1750.00
R122-LIVE	. R122 with thicker ribbon	. 1750.00
R122V	Vacuum tube version of R122	. 3095.00
F12	Stereo ribbon microphone, matte black (nickel finish optional)	. 2695.00
F24	Stereo active ribbon microphone, matte black	. 4295.00
	Vacuum tube version of SF24	
	Metal popscreen	



### SE ELECTRONICS SE X1R RIBBON MICROPHONE

The XIR is an entry-level passive ribbon microphone that is great for project studios or for someone looking to add a new flavor to their microphone collection. With its wide frequency response (20Hz-16kHz), figure-8 polar pattern

and a max SPL of 135dB, this microphone is well-suited for many different applications such as recording guitar cabs, overhead drums, voiceovers, strings, etc. The ribbon element is enclosed with neodymium magnets and features High Frequency extension technology from sE's Voodoo microphone series, giving the XIR classic smooth ribbon sound with a slight boost to high frequency content. The microphone uses a standard 3-pin XLR connection and includes a clip for attachment to microphone stands.

ITEM	DESCRIPTION
SE-X1R	Passive ribbon microphone, 20Hz-16kHz, figure-8 pattern

SHURE RIBBON MICROPHONES Featuring Roswellite<sup>TM</sup> ribbon technology for superior resilience at extreme SPLs, these premium mics are crafted for studio and concert hall applications. The KSM313 offers a dual-voice design and bidirectional polar pattern. The KSM353 has a bidirectional polar pattern,

features a custom ribbon motor assembly and double-shielded

matched full-sized transformer for minimizing signal loss. Both offer 146dB SPL across 30Hz-15kHz frequency response, and 3-pin XLR.

ITEM	DESCRIPTION	PRICE
KSM313NE	Dual-voice ribbon mic, black and red	1295.00
KSM353ED	Premier bidirectional ribbon mic, silver	2695.00





































NEW!



















MHSIC

COMPUTER AV

LIGHTS

ACCESSORIES





series microphones, using the same 1" diaphragm in a single-capsule, cardioid-only design. Its dynamic range is up to 156dB SPL and features an integrated suspension to reduce mechanical noise, a 20dB attenuation

pad, 13dB noise floor, and low cut switch. The double mesh, all-metal grille protects the capsule while ensuring high RF immunity. The allmetal diecast body and scratch-resistant finish also ensures protection.

metal diceast body and scrutch resistant limbs diss choures protection.		
ITEM	DESCRIPTION	PRICE
C214	Large single capsule cardioid condenser microphone	
	with shock mount, windscreen and metal carrying case 3	99.00
C214-ST	.Matched stereo pair of C214 mics with shock mounts,	
	stand adapters, windscreens and metal carrying case 8	399.00

AKG C414 STUDIO MICROPHONES These mics feature dual 1" diaphragms with flat 20Hz-20kHz response, transformerless output, all-metal shielded construction, phantom powering, electronic switching of pickup patterns, -6dB, -12dB and -18dB pre-attenuation levels, and bass cut filters at 40Hz, 80Hz and 160Hz. These versions of the C414 classic now have intermediate settings for 9 polar patterns, as well as control Lock Mode and Peak Hold LED. All come complete in an all-metal road case with an H-85 shock mount, a PF80 external 2-stage pop-filter, and W414 external windscreen. Also available in factory-matched stereo pairs packaged with an H50 stereo bar instead of the external pop-filter.



C414/XLS	C414/XLI
	100
	_

DESCRIPTION	PRICE
. Classic sonic character for beautifully detailed	
pickup of any acoustic instrument, 9 patterns,	
control Lock Mode and Peak Hold LED	1049.00
. Stereo XLS pair with H50 bar mount	2199.00
. Distinctive timbre especially for recording solo vocals	
and solo instruments, 9 patterns, control Lock Mode	
and Peak Hold LED	1099.00
. Stereo XLII pair with H50 bar mount	2299.00
	Classic sonic character for beautifully detailed pickup of any acoustic instrument, 9 patterns, control Lock Mode and Peak Hold LED.  Stereo XLS pair with H50 bar mount

AKG C451B MICROPHONE It has an acoustically identical version of the legendary CK1 capsule that is permanently mounted. This combination can handle high output transients as well as subtle harmonics. Also included are switchable 75Hz and 150Hz 12dB per octave rolloff, and switchable -10 and -20dB input pad. It is a single pattern (cardioid), and has frequency response of 20Hz-20kHz with 135dB SPL. Requires 12 to 48V phantom power. Kit comes with bag, windscreen and clip.

ITEM	DESCRIPTION	PRICE
C451B	. Cardioid condenser microphone	499.00
C451B-STEREO-PAIR	.Stereo pair of C415B	1099.00

AKG C1000S MKIV This updated version of the C1000 small-diaphragm condenser mic is ideal for video production, ENG/EFP, recording and live sound. It features a polar pattern converter, allowing it to quickly switch between cardioid and hypercardioid patterns, as well as a presence boost with 3 selectable frequency settings to enhance speech and/or instrument sounds. Other useful features include a bass-cut switch, -10dB pad and humidity-resistant gold-sputtered capsule. It can be powered by phantom power or 2 AA batteries. Includes windscreen and transport bag.

•	-			
ITEM	DESCRIPTION			PRICE
C1000S-NEW	Small-diaphragm multi-pattern condenser	mic	)	. 199.00

### Looking for these brands?

Shop fullcompass.com or call 800-356-5844





### AKG PROJECT STUDIO MICROPHONE SERIES

These five microphones feature a 20Hz-20kHz frequency response, switchable -20dB pad, switchable high-pass filter (except on P170) and very low self-noise. The



P120, P170 and P220 feature cardioid polar patterns, the dual-diaphragm P420 features switchable Cardioid, Figure-8 and Omnidirectional polar patterns and the P820 dual-diaphragm tube microphone features 9 different selectable polar patterns. The P120 and P170 include a microphone stand adapter, while the P220, P420 and P820 include a metal carrying case and a spider shock mount.

ITEM	DESCRIPTION	PRICE
P120	Large 2/3" diaphragm cardioid condenser microphone	99.00
P170	Small 1/2" diaphragm cardioid condenser microphone	79.00
P220	Large 1" diaphragm cardioid condenser microphone	. 149.00
P420	Large 1" dual-diaphragm multi-pattern condenser microphone	. 199.00
P820-TUBE	Large 1" dual-diaphragm multi-pattern tube condenser microphone	. 699.00

### AKG C SERIES LARGE **DIAPHRAGM MICS** The ver-

satile C series has long been a standard of quality and affordability in the AKG line. The C2000 is a high-sensitivity, high-SPL, large-diaphragm cardioid condenser mic with a 1/2" capsule element making it great for studio and live performance. The C3000 is a standard cardioid mic for both stage and studio applications. It features a 10dB



pad and a first-order 500Hz low frequency switch. The C4000 is a large diaphragm condenser mic with selectable patterns (cardioid, omni and hypercardioid), a 10dB pad and a low frequency roll-off switch. It is well-suited for a range of applications from vocals, brass, acoustic and electric guitar, kick drum and most recording situations as well as on stage. The C4500-BC cardioid large-diaphragm mic is geared for live broadcasting, studio vocals, post production, instruments and film sound. With its smooth frequency response, high SPL capability, low frequency roll-off switch and a switchable pre-attenuation pad for another 20dB of headroom, it's a good choice for miking instruments known to produce extremely high SPLs.

ITEM	DESCRIPTION	PRICE
C2000	Large diaphragm cardioid mic,	
	with spider shock mount, battery power supply	199.00
C3000	Large diaphragm cardioid mic	
	with spider shock mount and carrying case	199.00
C4000	Large diaphragm selectable-pattern mic	
	with spider shock mount, foam windscreen	399.00
C4500-BC	Large diaphragm cardioid mic	
	with spider shock mount, windscreen, case	399.00

### (A) audio-technica: always listening...

AUDIO-TECHNICA AT4050 LARGE DIAPHRAGM MULTI-PATTERN CONDENSER MICROPHONE With three switchable polar patterns (omnidirectional, cardioid and figure-8) the AT4050 exhibits a remarkable combination of qualities: high SPL capability with transparent and airy high/ mids complemented by rich low-end qualities. Its two large diaphragms are gold-vaporized and aged for consistent, outstanding performance. A precision-machined, nickel-plated brass acoustic element baffle provides rock-solid element stability and exceptional sensitivity. Ideal for studio use and live sound productions with vocals, piano, strings, drum overheads, guitar amps and more.

PRICE
699.00









## (A) audio-technica

always listening...

### **AUDIO-TECHNICA AT2020 CARDIOID CONDENSER MIC**

A side-address studio condenser microphone featuring high SPL handling and wide dynamic range. Custom-engineered 16mm lowmass diaphragm provides extended frequency response and superior transient response. Cardioid polar pattern reduces pickup of sounds from the sides and rear, improving isolation of desired sound source. Pivoting, threaded stand mount attaches securely for easy and precise placement of the microphone.



ITEM

ITEM	DESCRIPTION	PRICE
AT2020	Cardioid condenser, 20Hz-20kHz, 144dB max SPL	99.00

AUDIO-TECHNICA AT2035/AT2050 Bundled together at a great price, the AT2035 condenser mic is equipped with a switchable 80Hz hi-pass filter and 10dB pad, and comes with a protective pouch and a custom shock mount. The ATH-M20 dynamic headphones features a low-profile, closed-back design, 40mm drivers (each with a neodymium magnet structure), adjustable cushioned headband, gold-plated stereo 1/8" connector with strain relief and snap-on 1/4" adapter, 10' coiled cable with single-side exit.



ITEM	DESCRIPTION	PRICE
AT2035/ATHM20	. Includes AT2035 cardioid condenser mic (20Hz-20kHz) and	
	ATH-M20 closed-back dynamic headphones (30Hz-20kHz)	151.32
AT2050	. Cardioid, omni, figure-8, 20Hz-20kHz,	
	149dB max SPL (mic only)	229.00

### AUDIO-TECHNICA AT4033/CL STUDIO MICROPHONE

Large diaphragm studio microphone with low-noise transformerless electronics (17dB). 80Hz switched filter, smooth response to 20kHz, requires 48V phantom power and includes AT8449 spider type shock mount.

		V 1	
ITEM		DESCRIPTION	PRICE
AT4033	/CL	Studio cardioid	399.00
AT8137		Windscreen	37.54



### AUDIO-TECHNICA AT4040 STUDIO MICROPHONE

This single-pattern large-diaphragm microphone has an extremely low noise transformerless design, wide dynamic range, high SPL capability, and smooth natural sonic characteristics. It features 20Hz-20kHz response, an 80Hz rolloff, 10dB pad, 100-ohm impedance, and 133dB dynamic range. Requires 48V phantom power and includes AT8449 spider-type shock mount.



ITEM	DESCRIPTION	PRICE
AT4040	Studio cardioid microphone	299.00
	Studio pack with AT4040 and AT4041	
	condenser mics in wooden hov	5/19 00

### **AUDIO-TECHNICA 40 SERIES CONDENSER**

MICS High-quality studio condenser microphones with turned brass housings and black chrome plating. Very flat response from 20Hz-20kHz, maximum SPL of 145dB, 48V phantom power and low-cut switch. The AT4041/SP is a matched pair of AT4041 condensers packaged with 2 AT8410A shock



mounts in a wooden box. The AT4021 and AT4022 have 5dB better signal-to-noise ratios and AT4051b and AT4053b are modular and support interchangeable capsules.

ITEM	DESCRIPTION	PRICE
AT4041	Cardioid microphone	. 299.00
	Studio pack with 2x AT4041 mics in a wooden box	
AT4021	Cardioid mic with -10dB pad	349.00
AT4022	Omnidirectional mic with -10dB pad	349.00
AT4051B	Cardioid mic, supports optional hypercardioid capsule	. 599.00
AT4053B	Hypercardioid microphone, supports optional cardioid capsule	. 599.00
AT4051B-EL	. Cardioid capsule	. 249.00
AT4053B-EL	. Hypercardioid capsule	. 249.00
AT8114	Windscreen for AT813, AT814	11.54
AT8407	Replacement stand adapter (clothes-pin universal style)	20.34
AT8415	. Shock mount	52.20




AUDIO-TECHNICA AE5100 CARDIOID INSTRUMENT For overheads, percussion, acoustic guitar and strings. Large diaphragm, 80Hz low cut filter switch, 10dB pad, AT8471 isolation clamp; requires phantom power.

			•	•	
ITEM	DESCRIPTION				PRICE
AE5100	 . Cardioid instrumen	t mic,	20Hz-2	0kHz	 279.00

### (A) audio-technica. always listening...

### AUDIO-TECHNICA AT5040 CARDIOID CONDENSER MIC

Featuring a unique 4-diaphragm capsule, this mic offers high-fidelity performance, depth, and a pure sound. The ultra-thin diaphragms' outputs sum to create A-T's largest-ever element, with a combined surface area over twice that of a 1" circular diaphragm. These characteristics and quick transient response make it ideal for use with string and wind instruments. The advanced internal shock mount decouples the capsule from the mic body, and works in conjunction with the included AT8480 external shock mount to reduce handling noise. This durable, hand-assembled mic has an aluminum and brass housing in a gray finish.



**AUDIO-TECHNICA ATM450 CARDIOID CONDENSER** 

### **INSTRUMENT MIC** This microphone's extended

flat frequency response makes it ideal for high SPLs and for live and amplified acoustic instruments. Sideaddress stick design for endless placement options. Equipped with an 80Hz hi-pass filter and 10dB pad. Includes an isolation clamp.

ITEM	DESCRIPTION	PRICE
	.Cardioid condenser instrument mic, 40Hz-20kHz, 152dB max SPL	249.00

### AUDIO-TECHNICA PRO37 SMALL DIAPHRAGM CARDIOID

**CONDENSER MIC** A low-profile design enables optimal placement, making this mic ideal for acoustic guitar, overheads, piano and group vocals. The low-mass element gives superb transient response and it also excels in high-SPL applications.

ITEM	DESCRIPTION	PRICE
PR037	. Cardioid mic, 30Hz-15kHz, 141db max SPL	136.85



AVANTONE CONDENSER MICS These offer true professional performance and meet or surpass the performance and specs of higher priced mics. The CK-1 and CK-6 are ideal for recording instruments and percussion while the CK-7 can be used for instruments or vocals. The CV-12 is intended for use with vocals while the CV-28 is designed for acoustic instruments. The BV-12 is a "custom" tube mic designed primarily for vocals, but versatile enough to use for acoustic guitar, mandolin, piano or more. All bodies and capsule assemblies

PS-1 power supply and cables .

are made from precision-machined brass.	•
ITEM DESCRIPTION	PRICE
FET Microphones	
CK-1Small diaphragm FET condenser, pad and HPF, includes	interchangeable
capsules (cardioid, hypercardioid and omni), 25Hz-20kH	Z,
padded wooden box and shock mount	149.00
<b>CK-6</b> Large diaphragm cardioid FET condenser, pad and HPF,	
35Hz-20kHz, shock mount and wooden box in metal carr	
CK-7Large diaphragm multi-pattern (cardioid/omni/figure-8) F	
pad and HPF, 20Hz-20kHz, wooden box and shock mount,	metal road case 279.00
Tube Microphones	
CV-12Large diaphragm 9-pattern tube condenser, pad and HP	F,
25Hz-20kHz, wooden box, shock mount, metal road case	499.00
CV-28Small diaphragm tube condenser with interchangeable of	
(cardioid, omni, hypercardioid), pad and HPF, shock mou	
proprietary power supply with cables, wood box, aluminu	
BV-12Large diaphragm 9-pattern tube condenser, pad and HP	F,
20Hz-20kHz, wood box, shock mount, tweed road case,	











COMPUTER AV













































































AUDIX MICROBOOM The MicroBoom is a 24", 50" or 84" carbon fiber boom arm that attaches to any microphone stand. It has a diameter of less than .3" and is only 2.5oz. The upper end features a mini-XLR connector that securely holds the mic in place and also allows for easy access when changing out mics. It can be used either in a horizontal or vertical position, and is designed for use with any of the microphones in the Micros series.

ITEM	DESCRIPTION	PRICE
MICROBOOM-24	. 24" carbon fiber boom and clip only (no mic)	.145.00
MICROBOOM-50	.50" carbon fiber boom and clip only (no mic)	.229.00
MICROBOOM-84	.84" carbon fiber boom and clip only (no mic)	.329.00
MB5050	.MICROBOOM-50 with M1250B cardioid mic,	
	clutch assembly, cable, RFI immunity	.499.00
MB5050-HC	As MB5050, with hypercardioid capsule	.549.00
MB5055	As MB5050, with high-output cardioid capsule	.549.00
MB5055-HC	As MB5050, with high-output hypercardioid capsule	.569.00
MB8450	MICROBOOM-84 with M1250B cardioid mic,	
	clutch assmebly, cable, RFI immunity	.599.00
MB8450-HC	As MB8450, with hypercardioid capsule	.649.00
MB8455	As MB8450, with high-output cardioid capsule	.649.00
MB8455-HC	As MB8450, with high-output hypercardioid capsule	.669.00
STAND-MB	. Heavy-duty pedestal base mic stand (max height 21")	34.95
MC-B00M	Clutch assembly for MicroBoom	19.95

AUDIX MICROS SERIES The smallest, fully-integrated condenser on the market today offers an internal preamplifier, detachable cable, low noise and high sensitivity. Perfect for live, recording, and installation applications, Micros Series microphones do not need an external power supply and are immune to RF interference. M1255B offers higher sensitivity for longerdistance applications. They are available in cardioid, hypercardioid, omnidirectional or supercardioid capsule configurations,

and feature a 25' mini-XLR to XLR cable, stand adapter, hanging clip, windscreen,

and pouch. M1250B and M1255B also available in white.

ITEM	DESCRIPTION	PRICE
M1250B	Cardioid micro, 50Hz-19kHz, 150Ω, max SPL 140dB,	
	requires 18-52V phantom power, 10mV sensitivity, black	
M1250BW	As above, in white with white cable	419.00
	M1250B with hypercardioid capsule	
M1250BW-HC	As above, in white with white cable	439.00
M1250B-0	M1250B with omnidirectional capsule	399.00
M1250BW-0	As above, in white with white cable	419.00
M1250B-S	M1250B with supercardioid mini-shotgun capsule	429.00
M1255B	Cardioid mini, 50Hz-19kHz, 150Ω, max SPL 130dB,	
	requires 18-52V phantom power, extra 12dB sensitivity,	
	32mV sensitivity, black	
	As above, in white with white cable	
	M1255B with hypercardioid capsule	
	As above, in white with white cable	
	M1255B with omnidirectional capsule	
	As above, in white with white cable	
	M1255B with supercardioid mini-shotgun capsule	
	As above, in white with white cable	469.00
M1280B	Cardioid mini, 40Hz-20kHz, 150Ω, max SPL 150dB,	
	requires 18-52V phantom power	
	As above, with omnidirectional capsule	
M1280B-S	As above, with supercardioid mini-shotgun capsule	449.00
Micro Series Acce	ssories	
SMT-MICRO	Shock mounted stand adapter	. 24.95
	Mini gooseneck for rim mounting Micros	
DCLAMP-MICRO	Mini-gooseneck with drum tension lug clamp	. 29.95

### **AUDIX TM1 TEST** AND MEASUREMENT

**MICROPHONE** This 6mm pre-polarized condenser mic with linear response can be used for test/ measurement, real time analyzers, room analysis software programs, or even ambient room miking. Features precision machined brass housings, low noise electronics, replaceable electronics, and capsule. The TM1-PLUS, is a combination kit that



calibrator adaptor and mic calibration data CD...



AUDIX SCX25-A An elegant design with microphones patented capsule suspension system in an intricate machined brass ring which minimizes acoustic reflections and diffractions, delivering a pure open-air sound unlike other mics. A smooth uniform response of 20Hz-20kHz, Cardioid pattern, low 14dBA noise, 48-52V phantom power, 138dB Maximum SPL. Good for vocal and instrumental recording.

ITEM SCX25-A	DESCRIPTION Cardioid microphone	PRICE 695.00
SCX25A-MATCHED-PAIR	. Matched pair of SCX25A	1489.00
SCX25A-PS	Piano system — includes (2) SCX25A, (2 (2) 20' mic cables, and an aluminum fli	



M30

# Earthworks

FW430/TPB

EARTHWORKS FLEXWAND A 30kHz High Definition Microphone™ and a low profile microphone stand with boom as a single unit. It allows the microphone head to be positioned as high as 7' and as low as 10" from the floor, or anywhere in between, depending on the model. Also available in matched pairs.

ITEM	DESCRIPTION	PRICE
FW430	.4.7ft cardioid FlexWand with cast iron base	1239.00
FW430/HC	4.7ft hypercardioid FlexWand with cast-iron base	1239.00
FW430/TPB	.4.7ft cardioid FlexWand with tripod base	1239.00
FW430/HCTPB	.4.7ft hypercardioid FlexWand with tripod base	1239.00
FW730	7ft cardioid FlexWand with cast-iron base	1299.00
FW730/HC	7ft hypercardioid FlexWand with cast-iron base	1299.00
FW730TPB	7ft cardioid FlexWand with tripod base	1299.00
FW730/HC-TPB	7ft hypercardioid FlexWand with tripod base	1299.00
	,	

### EARTHWORKS TIME COHERENT OMNI MICS

VIP50

DC-96B

DC-196

Impulse settling time is faster than any other microphone available, which yields remarkable high frequency detail

definition. These mics handle huge sound pressure levels and have no proximity effect or handling noise. The M30 meets or exceeds ANSI Type 1 and applicable IEC 61094 requirements.

ITEM	DESCRIPTION	PRICE
QTC50	. 3Hz-50kHz response	1399.00
QTC40	. 40kHz response, ideal for acoustic instrument recording	999.00
QTC40MP	. Matched pair of QTC40s, cherry box	2199.00
QTC30	. 30kHz response for less critical applications	799.00
TC25	. For loud sources, 9Hz-25kHz	549.00
TC30	. 30kHz response, for general purpose	769.00
TC20	. 20kHz response, shorter version of TC30	479.00
M30	. Measurement mic, 5Hz-30kHz, 142dB SPL	679.00
	.Matched pair of M30s in wood box (mic clips included)	



### MILAB LARGE DIAPHRAGM CONDENSER

MICS All models feature rectangular, large membrane, shock absorbing rubber-fitted capsules and gold-plated XLR connectors. The DC-96B cardioid provides a full-bodied and exceptionally clean sound with natural brightness. The DC-196 is a variable pattern condenser (cardioid, omni, figure-8)

that features built-in pop protection, -12dB pre-attenuation and is transformerless. The VIP-50 is also transformerless and shares the same polar patterns as the DC-196 plus widecardioid and hypercardioid patterns. It also features 200/500Hz hi-pass filters and -10/-20dB pre-attenuation.

ITEM	DESCRIPTION	PRICE
DC-96B	Cardioid pattern, 20Hz-20kHz	CALL
DC-196	Variable pattern (cardioid, omni, figure-8), 20Hz-20kHz.	CALL
VIP50	Variable pattern (cardioid, omni, figure-8),	
,	wide-cardioid hypercardioid) 20Hz-20kHz	CALL









# Balance of **Power**

Strong enough to lift your choir's sound above the band.

Flexible enough to go where you need it.

Small enough to dissapear.

Be seen and heard with the MicroBoom™ Series from Audix.





800-356-5844 fullcompass.com



The MicroBoom \*\* Series from Audix combines exceptional sound quality with a low profile. Our scalable system and selection of pick-up patterns, output levels and frequency responses mean that we have the right mic for your choir's unique sound. And the mic is just half of the story: the boom arms are made of carbon fiber so they are lightweight, thin and strong. With three models – 24, 50 and 84 inches – capable of adjusting to the angle and position you need, the MicroBoom fits in those hard-to-reach places and then disappears so your choir will be seen and heard.





















































### **BLUE SPARK SOLID STATE CONDENSER MICROPHONE**

A cardioid solid-state condenser mic designed for professional quality recording. Features a custom-designed condenser capsule with Class 'A' discrete electronics resulting

BAING LATMAN UNIVERSAL SLEGRADING in detailed and uncolored output. Ideal for recording vocals, drums, guitars, pianos, brass, woodwinds, etc. A unique focus control provides two different usage modes; Normal mode for increased low frequency sensitivity and Focus mode for greater clarity and detail. Ships with a custom-designed pop filter, shock mount and wood case. Frequency response is 20Hz-20kHz, sensitivity rating is 28 mV/Pa, output impedance of  $50\Omega$ , a max SPL of 128dB and a S/N Ratio of 84dB. Requires +48VDC phantom power.

ITEM	DESCRIPTION	PRICE
SPARK	Cardioid condenser microphone	199.99





BLUE BABY BOTTLE Discrete Class 'A' solidstate circuitry, with a hand-selected gold sput-RALIK LATMON UNIVERSAL ELECTRONICS tered diaphragm. It is perfect for vocal, percus-

sion or acoustic recordings. It boasts 20Hz-20kHz response, cardioid pattern, 133dB SPL, and a 128dB dynamic range with 12dB output. Includes shock mount and pop filter.

ITEM	DESCRIPTION	PRICE
BABY-BOTTLE	. Cardioid, FET	399.99



BLUE BLUEBIRD The Bluebird is a large diaphragm cardioid condenser with Class 'A' discrete circuitry for low distortion and extremely low noise (7.5dB). Bluebird has been engineered to be as versatile as possible, with applications ranging from vocals to electric and acoustic guitars, close-miking of drums, drum overheads, percussion, piano, horns, strings, and any other application where crystal-clear sound quality and detail are of the utmost concern. The Bluebird Accessory Pak includes Blue's high-definition 22AwG Blueberry mic cable, a specially designed shock mount – the BirdCage, and a metal mesh pop filter – the BirdNest.

1		
ITEM	DESCRIPTION	PRICE
BLUEBIRD	Cardioid, 20Hz-20kHz, 50Ω, 138dB S	PL 299.99

### **BLUE REACTOR LARGE-DIAPHRAGM CONDENSER MIC**

A large-diaphragm condenser mic with Class 'A' discrete components and multiple pickup patterns. It features a proprietary preamp for noiseless live switching between cardioid, omni or figure-8 patterns. To facilitate use in multiple mic setups (mid/side, X-Y), its capsule head rotates 90° for perfect positioning in tight spaces and easy pattern adjustability. Its pattern selection is both intuitive and stylish, featuring LED backlighting on the pattern indicators and a magnifying element that compliments its design. Frequency response is 20Hz-20kHz, a sensitivity rating of 19.0mW/Pa at 1kHz, max SPL of 135dB, dynamic range of 128dB, S/N ratio of 88dB-A and on output impedance rating of 50Ω. Requires +48VDC phantom power.

ITEM DESCRIPTION	PRICE
REACTORMulti-pattern, large-diaphragm cond	1denser mic 324.99



Shop fullcompass.com or call 800-356-5844





### BEHRINGER ECM8000 MEASUREMENT MICROPHONE

This specialized condenser mic is designed for use with realtime analyzers in providing an accurate acoustic picture of a behringer room. The ruler-flat frequency response from 15Hz-20kHz and omnidirectional polar pattern delivers a clear, accurate reading of any room's unique sound characteristics. Includes carrying case, mic clip and stand adapter. Requires phantom power.

ITEM	DESCRIPTION	PRICE
ECM8000	Measurement mic, omni condenser, 15Hz-20kHz	59.99



**DPA MICROPHONES D:DICTATE SERIES** 

This series of high-quality reference condenser microphones, capsules and



REFCARD

REFGOLD

ITEM	DESCRIPTION	PRICE
2006C	Compact twin-diaphragm omnidirectional microphone	799.95
2011C	As above, cardioid version	799.95
4006-A	Omnidirectional microphone	1899.95
4006-C	As above, compact version	1759.95
4011-A	Cardioid microphone	1739.95
4011C	As above, compact version	1589.95
4015C	Compact wide-cardioid microphone	1589.95
Capsules		
MMC4006	Omnidirectional microphone capsule	1495.95
	Cardioid microphone capsule	
Preamplifier		
MMP-A	Transformerless microphone preamplifier	489.95



### **MANLEY LABS** REFERENCE **CARDIOID MICROPHONES** These microphones closely replicate how many

of the vintage European tube microphones sounded when they were new. Ideally suited to record guitars, drum overheads, saxophones and especially

vocals. The Reference Cardioid has a center-fixed cardioid-only capsule with a thicker-gauge gold-sputtered diaphragm. The Reference Gold

uses Telefunken's own design of large capsule (1.25" overall, 1" diaphragm diameter) which are executed to precise tolerances made possible by modern micromilling machinery. Its pattern is continuously variable between Omni, Cardioid and Figure 8 patterns. The Gold Reference Stereo is identical to the Reference gold in every way except that it has two carefully matched systems installed in one case. The upper capsule is fixed and the lower capsule is continuously rotatable through 90° for M-S and X-Y Blumlein-style recording techniques.

ITEM	DESCRIPTION	PRICE
REFCARD	Reference cardioid microphone, with power supply	. 2700.00
REFGOLD	Reference Gold microphone, multi-pattern, with power supply	. 4950.00
REFSGOLD	Stereo Reference Gold microphone, multi-pattern, with power supply.	CALL









ii ii ii ii

COMPUTER AV

ACCESSORIES

PRICE



### MXL LARGE DIAPHRAGM **CONDENSER STUDIO MICS**

Studio condenser microphones with low-noise FET circuitry. All models require 48V phantom power and use a gold-sputtered 6-micron diaphragm.



ITEM	DESCRIPTION		PRICE
MXL-2010	Multi-polar (cardioid/figure-8/omni) condenser, FET preamp wit	h	
	bass roll-off switch, shock mount and windscreen, 30Hz-20kHz.	1	79.95
MXL-CUBE	.Drum cardioid condenser, FET-balanced output with mic clip,		
	20Hz-20khz	1	119.95
MXL-V67G	.Vocal cardioid condenser, transformer-balanced output,		
	FET preamp and gold grill, 30Hz-20kHz	1	21.10
MXL-V87	.Instrument cardioid condenser, transformer-balanced output,		
	FET preamp, pop filter and shock mount, 20Hz-20kHz	2	299.95
	603PAIR 604		/67N



### MXL **DIAPHRAGM** SMALL CONDENSER MICS These small diaphragm condenser mics are quiet, sensitive, rugged enough for the road and inexpensive. They are an excellent choice for drum overheads and for close recording of acoustic instru-





### **NEUMANN U891** VARIABLE PATTERN

CONDENSER MIC The U89i offers improved acoustical and electrical characteristics and better high-end response than the U87A. It has a dynamic range of 123dB, 5 polar patterns, a 6dB pad, and a 2-position LF roll-off switch. It has little to no off-axis col-

oration and is	lucai ioi bioaucast oi	studio recording	; аррисацон
ITEM	DESCRIPTION		PRICE
U891-BLACK	Variable pattern mic,	20Hz-20kHz, black	3199.95
U89I-SILVER	As above, in silver		3199.95

NEUMANN TLM103/TLM103D LARGE DIAPHRAGM MICS These are large diaphragm cardioid mics with a transformerless output stage. Designed primarily for vocals, the TLM03 also excels on piano, percussion, and stringed instruments. The TLM103D is a digital version of the mic, designed for home recording and project studios. Its A/D converter receives the output signal directly from the capsule, ensuring that the signal has no coloration and superb transparency. Both mics require 48V phantom power and come with an SG-1 swivel mount and wooden box.

î	ITEM	DESCRIPTION	PRICE
	TLM103-BLACK	Cardioid mic, 20Hz-20kHz, Max SPL for THD (	0.5%
		-138dB, with swivel mount and case, black	1099.95
	TLM103-NICKEL	As above, in nickel	1099.95
)	TLM103-D	Digital version of TLM103, black or nickel .	1599.95
	EA1-BLACK	Elastic suspension mount, black	269.95
	EA1-NICKEL	Elastic suspension mount, nickel	269.95
	WS87	Windscreen	46.95

**NEUMANN** TLM67 LARGE DIAPHRAGM CONDENSER MIC This "Transformerless Microphone" incorporates Neumann's K67 capsule into a circuit design that emulates the U67, without using tubes. Features 3 switchable polar patterns (omni, cardioid, figure-8), selectable 10dB attenuation and

hi-pass filter. The electronic circuit that replaces the transformer in the mic suppresses interference signals and ensures good, common mode rejection. Intended for vocal performance, but suitable for orchestral and individual instrument recordings as well.

		U	
ITEM	DESCRIPTION	F	PRICE
TLM67-SETZ	Multi-pattern mic with K67 ca	apsule,	
	wood box, EA87 mount, WS87	windscreen,	
	IC 3/25 cable	23	99 95



maximum sound pressure level of 144dB, which is good for recording amps, drums, and other loud instruments. Acoustic instruments will benefit from the TLM102's fast transient response. The TLM102 also features a slight boost above 6kHz, making it ideal for voice/ speech applications. Below 6kHz, the frequency response is linear, providing clear bass and little coloration. Features an elastic suspension in the capsule and an integrated pop screen. Ideal for a wide range of applications including home recording and broadcasting.

ITEM	DESCRIPTION	PRICE
TLM102	. Large diaphragm cardioid condenser mic, black	. 699.95
TLM102-NICKEL	. As TLM102, in nickel	. 699.95

### **NEUMANN TLM49 CARDIOID VOCAL MIC**

A large diaphragm transformerless cardioid condenser microphone specially optimized for warm vocals. The acoustic design is focused on the M49 and U47 with a gentle presence boost above 2kHz. In fact, it utilizes the same K47 34mm capsule used in both of those models. The TLM49 comes in nickel finish and includes the EA3 elastic suspension. The microphone can operate at sound pressure levels of up to 114dB without distortion, and provides a dynamic range of 102dB (A-weighted), 48V phantom

dynamic range or	1020D (A-WCIS	incuj. 40 v	phantom.
ITEM	DESCRIPTION		
TLM49	Cardioid vocal	mic	

**NEUMANN U87AI 3-PATTERN MIC** 

A legendary FET large diaphragm transformer-coupled studio mic with omni, cardioid and figure-8 patterns, 10dB pad and low cut filter.

ITEM	DESCRIPTION	PRICE
U87AI	Multi-pattern microphone, no mount or cas	e 3199.95
U87AI/SET-Z	Microphone with shock mount,	
	cable and windscreen	3599.95
EA87	Elastic suspension (with SET-Z)	379.95
	Windscreen	



Featuring a surprisingly fresh design, the TLM107 is a modern, high-resolution sound transducer with excellent reproduction characteristics that enable it to capture the original sound without

coloration, thus ensuring unlimited design freedom in mixing and post-production. It offers omnidirectional, cardioid, figure-8, wide-angle cardioid and hypercardioid polar patterns. Its sound remains balanced with an almost linear reproduction up to 8kHz and a slight boost in the highest frequencies that lends presence and freshness to the voice. The TLM107 has a frequency range of 20Hz-20kHz, a 10dB-A self-noise rating, max SPL rating of 141dB (153dB with Pad engaged) and low cut settings of 40Hz and 100Hz. All microphone functions are controlled via a navigation switch with an illuminated pattern display in the chrome ring and LEDs for Pad and Low Cut status. All switches and indicators are located on the back of the microphone in order to avoid distractions for the performer. Available in black or nickel finish.

ITEM	DESCRIPTION	PRICE
TLM107	Large diaphragm condenser microphone,	
	5 patterns, choose finish	. 1699.95

























































### **NEUMANN KM180 SERIES**

The KM180 series condensers offer the same transformerless circuitry as the KM100s without the 10dB pad. Frequency response is 20Hz-20kHz. The KM183, KM184 and KM185 have SPL handling of 140dB, 138dB and 142dB respectively. 48V phantom power is required.

ITEM	DESCRIPTION	PRICE
KM183	. Omni condenser mic	899.95
KM184	. Cardioid condenser mic	849.95
KM185-SILVER	. Hypercardioid condenser mic	899.95
EA2124A	. Optional suspension mount	299.95
WNS100	. Replacement windscreen	24.95
WS100	. Optional 90mm windscreen	28.95
SKM183-MT	. Stereo mic pair-omni, with case, black	1699.95
SKM183-SILVER	. Stereo mic pair-omni, with case	1699.95
SKM184-MT	. Stereo mic pair-cardioid, with case, black	1599.95
SKM184-NI	. Stereo mic pair-cardioid, with case, nickel	1599.95

### **NEUMANN M149 9-PATTERN TUBE MIC**

The world's first transformerless tube microphone. The capsule is from the M49, includes a tube amplifier from the TLM50 microphone. The M149 Tube has 9 polar patterns and a 7-position high-pass filter. Frequency range is 20Hz-20kHz, sensitivity of 30/44/55 mV/Pa with max output of 101/12dB. Includes a power supply, cables, shock mount and case.

ITEM	DESCRIPTION	PRICE
M149-TUBE	. 9-pattern tube n	nic5049.95



### **RØDE M5 MATCHED PAIR 1/2" CONDENSER MICS**

The M5 is a compact 1/2" cardioid condenser microphone with low noise and full frequency response. Ideal for studio recording and live stage, the M5 is equally at home capturing a range of acoustic instruments, choirs or anywhere else a small diaphragm condenser would be used. It has a frequency response of 20Hz-20kHz, maximum SPL rating of 140dB and an equivalent noise level rating of 19dB-A. This matched pair has been carefully selected to ensure

a variation of no more than 1dB sensitivity between the pair. A premium foiled certificate is supplied to verify the authenticity of the pair. Ships with two WS5 windscreens and two RM5 stand mounts.

ITEM	DESCRIPTION	PRICE
M5-MP	1/2" cardioid condenser microphones, matched pair	199.00

### **RØDE NT1 CONDENSER MICROPHONE**

The NT1 is a revolutionary new 1" diaphragm condenser microphone from Røde. Although the new NT1 closely resembles the NT1-A, it has been completely redesigned from the ground up. The HF6 capsule has a sound signature reminiscent of classic microphones, while at the same time exhibiting very low noise. The NT1 has an internal capsule suspension system which employs patented Lyre technology from Rycote®. This system isolates on the X, Y and Z axes, providing protection that is superior to conventional suspension systems. Its aluminum body is plated with nickel for corrosion resistance before being

coated in an extremely durable ceramic firearm coating that is resistant to scratches and marks. It has a frequency response of 20Hz-20kHz, 123dB max SPL rating, 4dB-A of self-noise and a cardioid nickup nattern. The NT1-KIT includes an SMR shock mount and non-shield

cardioid pickup pa	tiern. The 1411-Kit includes all blank shock inount an	a pop silicia.
ITEM	DESCRIPTION	PRICE
NT1	1" cardioid condenser microphone	249.00
NT1-KIT	As above, with SMR shock mount and pop shield	269.00

### Looking for these brands?

Shop fullcompass.com or call 800-356-5844





RØDE NT1-A CARDIOID MIC World's quietest microphone with an incredible 5dBA self noise figure. 48V phantom power, transformerless output, 137dB max. SPL, fixed cardioid pattern.

ITEM	DESCRIPTION	PRICE
NT1-A-COMPLETE	Anniversary edition, includes:	
	shockmount, pop shield, 20'	cable,
	dust cover, and DVD	229.00





### **RØDE NT2A MULTI-PATTERN LARGE DIAPHRAGM CONDENSER**

MIC Successor to the very popular NT-2 studio condenser mic, the NT2A now has the internally shock mounted HF1 dual 1" capsule, the same as is used in the K2 microphone, and new electronics with extremely low 7dBA self-noise. It has a 3-position variable polar pattern for omni, cardioid, and figure-8 patterns, three positions of selectable attenuation (0dB, -5dB, or -10dB) and low freq. roll-off (flat, 80Hz or 40Hz). The NT-2A comes with a soft pouch and mounting clip.

ITEM	DESCRIPTION	PRICE
NT2A	. Multi-pattern condenser	.399.00

### RØDE NT3 3/4" CARDIOID CONDENSER MICROPHONE The NT3's

end-address 3/4" gold-sputtered true-condenser transducer provides incredible detail on almost any instrument imaginable. Intended for studio, stage and location work, this versatile handheld, stand or boompole mounted microphone will give great results on drums, percussion, acoustic guitar, guitar amps, piano and all acoustic instruments. It also gives detailed voice reproduction when used as a handheld presentation microphone or indoor boom mic. It can be powered via +48V phantom power or a 9V battery.

ITEM	DESCRIPTION	PRICE
NT3	3/4" cardioid condenser microphone	.269.00



### RØDE NT5 AND NT55 CARDIOID CONDENSER MICS

The RØDE NT5 is a true condenser microphone specifically designed for instrument recording. Its discrete size and design allows for effective and subtle positioning, which is crucial when close miking. Requires 48V phantom power. Frequency response is 20Hz-20kHz, max SPL of 143dB, dynamic range >128dB. NT5's are supplied as closely matched pairs (NT5-MP) in a custom carry case with two stand mounts and two windscreens. NT5 is also available as a single mic (NT5-S). The new NT55 model is essentially the NT5 with a two-stage hp (75Hz or 150Hz) filter and a two stage (-10dB/-20dB) pad, and includes a NT45-O omni capsule so that you have the option to operate cardioid or omni by swapping capsules.

		,	 0 1
ITEM	DESCRIPTION		PRICE
NT5-MP	Studio condenser mic, matched pair		 429.00
NT5-S	Single NT5 condenser mic		 219.00
NT55	Mic with two stage hp filter, 2 stage pad,		
	and cardioid and omni capsules		 369.00
WS5	Replacement windscreen for NT5		 19.99







SENNHEISER E614 DRUM

SENNHEISER

**CONDENSER** The e614 has a supercardioid pattern, with a neutral response and moderate sensitivity,

which insures optimum isolation from other instru-

ments on stage. Unobtrusive for precise placement

and powered by external phantom power (P48), the

e614 tolerates extremely high SPLs, precisely captur-

ing cymbals and hi-hats better than other mics in its

price range. 10-year warranty. Frequency response is

.Supercardioid condenser...

SENNHEISER K6 MODULAR ELECTRET MIC **SYSTEM** This rugged system has separate capsules and powering modules that can be combined to produce a wide variety of microphones. A single module and a few capsules can provide the user with flexibility

that would otherwise require investing in a number of

individual microphones. It converts quickly from one

type of microphone to another by simply threading together various system components. All capsules

use back-electret technology for uncompromised quality. Output of all powering modules is balanced,

low impedance (200 $\Omega$ ) and terminates in a standard

K6 Powering Module "Universal" powering module for the system. Powered by a single 1.5V "AA" battery with a life of 150 hours, or phantom power (12-48V). On/off switch with LED indicator, bass rolloff switch

.Powering module battery/phantom..

......Powering module phantom only.....

3-pin XLR connector.

DESCRIPTION

..Omni capsule..

Lapel capsule.

MZW66.....Foam windscreen for ME66.

Cardioid capsule.

. Handheld capsule.

.8.75" shotgun capsule ....

.12.5" shotgun capsule ....

Short electret shotgun system...

.Camera adapter and shock mount

(flat, -11dB).

Capsules for K6

ME66/K6-COMBO

MKE2-60-GOLD

ITFM

Kĥ

K6P

MF62

MF64

ME65

MF66

MF67

M7SK6

DESCRIPTION

Z SENNHEISER GOLD

**OVERHEAD** 

PRICE

.219.95















































for enhanced vocal clarity. The internally suspended capsule features a 33mm beveled collar to increase high frequency directivity and the entire head assembly can be angled +/- 20° for precise positioning. Other features include transformerless output stage, 50Hz-22khz frequency response, 40Hz low cut switch and 79dBA signal-to-noise ratio. Includes wooden case and requires phantom power.

ITEM	DESCRIPTION	PRICE
V4-U	Large diaphragm condenser microphone, for vocals	2999.00

SCHOEPS COLETTE MODULAR MIC SETS Microphones consist of a mic capsule and amplifier. The CMC 6 microphone amplifier converts extremely high-impedance signals from the attached capsule to a very low-impedance signal suitable for transmission via mic cable. It also features a symmetrical Class "A" output stage, free of coupling condensers or an output transformer. They are lightweight, have extremely low distortion, and their very low output impedance helps make them insensitive to electrical interference. The CMC 6 works with both 12V and 48V phantom powering. Matte gray options listed below but also available in nickel. All sets include SG20 stand clamps and B5 popscreens.

ITEM	DESCRIPTION	PRICE
CMC621G-SET	Includes CMC 6 amplifier and MK21 wide cardioid capsule	1796.00
CMC622G-SET	Includes CMC 6 amplifier andMK22 open cardioid capsule	1796.00
CMC64G-SET	Includes CMC 6 amplifier and MK4 cardioid capsule	1698.00
CMC641G-SET	Includes CMC 6 amplifier and MK41 supercardioid capsule	1918.00
CMC641CG-SET	Includes CMC 6 amplifier and MK41 supercardioid capsule, CUT 1 filter	2552.00
CMC65G-SET	Includes CMC 6 amplifier and MK5 omni/cardioid capsule	2265.00
CMC68G-SET	Includes CMC 6 amplifier and MK8 figure-8 capsule	2132.00
	Includes 2 CMC 6s, matched pair of MK2 omnis	
	Includes 2 CMC 6s, matched pair of MK2 H omnis	
UNIVERSAL-OMNI-S-ST	Includes 2 CMC 6s, matched pair of MK2 S omnis	3465.00
WIDE-CARDIOID-ST	Includes 2 CMC 6s, matched pair of MK21 wide cardioids	3519.00
OPEN-CARDIOID-ST	Includes 2 CMC 6s, matched pair of MK22 open cardioids	3519.00
CARDIOID-ST	Includes 2 CMC 6s, matched pair of MK4 cardioids	3299.00
	Includes 2 CMC 6s, matched pair of MK41 supercardioids	
SWITCHABLE-PATTRN-ST.	Includes 2 CMC 6s, matched pair of MK5 omni/cardioids	4454.00

MK41

MK8

40Hz-20KHz.

ITFM

E614

### T<sup>®</sup>SENNHEISER<sup>®</sup>


NEW

### SENNHEISER MK4 LARGE DIAPHRAGM MICROPHONE

A large diaphragm microphone with a cardioid pickup pattern and a nickel colored finish. It has a large 1" diaphragm precisely sputtered with 24-carat gold. It has a sturdy metal housing and the elastically mounted capsule suppresses handling noise. It has a max SPL level of 140dB and a low self-noise level of 10dB(A). It has a frequency response of 20Hz-20kHz, a sensitivity rating of 25mV/ Pa and a dynamic range of 130dB. It requires +48V of phantom power.

ITEM	DESCRIPTION		P	RICE
MK4	 Large diaphragm side	e-address microphone	 29	99.95
MKW4	 Windscreen for MK4			24.95
MKS4	Shock mount for MK4		(	99.95





ITEM DE	SCRIPTION	PF	RICE
	al-diaphragm multi-pattern condenser microphone, puires 48V phantom power. 50Ω	COMING SC	INONI

### For expert advice - call: 800-356-5844

Shop fullcompass.com today!

M-F: 9:00-5:30 Central





















PRICE

249 95

249.95

159 95

169.95

229 95

209.95

199 95

.299.95

369 95

49 95

























































SENNHEISER MKH-SERIES RF-CONDENSER MICROPHONES RF condenser microphones constitute a unique, sophisticated class of condenser microphones. They fulfill the very highest demands made on sound quality and versatility, and are renowned for their high quality, highly accurate sound reproduction, ruggedness, all-weather operation, wide frequency response and extremely low inherent self-noise. RF condenser microphones use a comparatively low RF voltage, modulated by the capacitance changes produced by the capsule diaphragm. Excellent low frequency response can be achieved even with small capsules. RF condenser microphones possess a genuine fully floating, balanced output without having to use an audio frequency transformer. 48V phantom power is required.

ITEM	DESCRIPTION	PRICE
MKH20-P48	. Omnidirectional	1199.95
MKH30-P48	. Figure-8	1249.95
MKH40-P48	. Cardioid	1199.95
MKH8090	. Wide cardioid	1199.95
MKH50-P48	. Supercardioid	1199.95
MKH60-P48	. Short shotgun, supercardioid	1499.95
MKH70-P48	. Long shotgun, lobar	1749.95
MKH800-P48	. Multi-pattern side address, 50kHz response	2999.95
MKH416P48U3	. Short shotgun, hypercardioid	999.95
MKH418S	. Stereo shotgun, M: supercardioid; S: figure-8	1649.95

### SHURE

### SHURE BETA 181 SIDE-ADDRESS INSTRUMENT MICROPHONES

This ultra-compact, small-diaphragm side-address condenser microphone is designed for discrete placement and gives great control in live and studio environments. Features interchangeable capsules for superior versatility. The small diaphragm design provides superior audio with consistent, textbook polar responses and is small enough to use in the tightest conditions. The compact side-address design features an innovative locking ring to provide secure connection between capsule and preamplifier. The 20Hz-20kHz frequency response is tailored for wide dynamic range applications for use in high SPL environments. Ships with stand adapter, windscreen and carrying case which securely protects up to 4 capsules.

ITEM	DESCRIPTION	PRICE
BETA181/C	Cardioid side-address microphone	499.00
BETA181/S	Supercardioid side-address microphone	499.00
BETA181/BI	Bidirectional side-address microphone	499.00
BETA181/0	Omnidirectional side-address microphone	499.00
RPM181/PRE	Preamp for Beta181 microphones	249.00
RPM181/C	Cardioid capsule only	249.00
RPM181/S	Supercardioid capsule only	249.00
RPM181/BI	Bidirectional capsule only	249.00
RPM181/0	Omidirectional capsule only	249.00

**SHURE PG81** This condenser instrument microphone is the perfect choice for instrument recording in the home studio environment. Its condenser element provides high sensitivity and low self-noise, while its extended flat frequency response keeps instruments and samples sounding accurate. The PG81 operates on an internal AA battery or phantom power. Includes padded vinyl carrying case, swivel adapter and AA battery.

	•	_		
ITEM			DESCRIPTION	PRICE
PG81-XLR	₹		 . Cardioid microphone	129.00
A53M			Shock stopper isolation mount	33 25

**SHURE SM81** One of the world's great studio or live mics. Ruler-flat

response 20Hz-20kHz ultra low self-noise. The ultimate in precise, detailed sound reproduction. Excellent for use with acoustic instruments, choirs, overhead cymbal applications. Build in 10dB attenuator and bass cut switch. Phantom power only.

ITEM	DESCRIPTION	PRICE
SM81LC	. Condenser cardioid	349.00
A81WS	. Optional multilayer windscreen	31.92
A53M	. "Shock Stopper" isolation mount	33.25

### Looking for these brands?

Shop fullcompass.com or call 800-356-5844



SAMSON

PG27LC

### SHURI

### SHURE PG27LC AND PG42LC CONDENSER MICS

These mics feature a cardioid pickup pattern, large diaphragm capsules with switchable attenuators. The PG27LC is designed for use with instruments. It has a flat, neutral frequency response of 20Hz-20kHz as well as a high SPL rating of 124dB with pad off and 144dB with pad engaged. It ships with a stand adapter and zippered pouch. The PG42LC is designed for vocals and features a voice-



PG42LC

tailored frequency response of 20Hz-20kHz as well as an SPL rating of 130dB with pad off and 145dB with pad engaged. It also includes a switchable high-pass filter and ships with a shock mount and carrying case. Both models have 3-pin XLR connectors.

ITEM	DESCRIPTION	PRICE
PG27LC	.Side-address cardioid condenser instrument mic, 20Hz-20kHz	149.00
PG42LC	.Side-address cardioid condenser vocal mic, 20Hz-20kHz	199.00

### SHURE KSM32 SINGLE-DIAPHRAGM CONDENSER

MICROPHONE For studio recording and live sound production. The KSM32 offers an extended frequency response of 20Hz-20kHz for an open, natural sound. The Class 'A' transformerless preamp circuitry eliminates cross-over distortion for improved linearity across the full frequency range. An embossed, high-compliance, ultra-thin, gold-layered, low-mass diaphragm provides extended low frequency response and excellent transient response. Other features include a 15dB pad switch, switchable low-frequency filter, integrated 3-stage pop protection, swivel mount and an internal shock mount for reduced handling noise.



ITFM DESCRIPTION PRICE KSM32/CG Studio condenser mic, charcoal finish, carrying case... 499.00 KSM32/SL Studio condenser mic, silver finish, shock mount, aluminum case. 549.00 Elastic-suspension shock mount for the KSM32. 136.28 107.59

### **A32SM A32SC** Locking aluminum carry case for the KSM32 ..... Windscreen for KSM series, black A32WS KSM44A SHURE KSM42 AND KSM44A LARGE

### **CONDENSER MICROPHONES** Premium side-address mics offering a dual-dia-

phragm design with an active front, ultrathin (2.5 micron) 24-karat gold, low mass, 1" Mylar® diaphragm. The KSM42 is ideal for vocal applications with a tailored frequency response and extensive internal and external pop filtering. The single-pattern



design exhibits smooth proximity control and ultra-wide dynamic range. An internal shock mount reduces unwanted handling and stand noise. Prethos<sup>TM</sup> Advanced Preamplifier Technology exhibits extremely low self-noise with superior dynamic range, transient response and ultra-low distortion for transparent recording. The KSM42 includes ShureLock® shock mount, Popper Stopper<sup>TM</sup> magnetic pop filter, aluminum carrying case, and velveteen pouch. The KSM44A adds multiple polar pattern options (cardioid, omnidirectional, bidirectional) and a switchable 15dB pad. A 3-position switchable low-frequency filter helps reduce unwanted handling and stand noise. The KSM44A includes ShureLock® suspension shock mount, ShureLock® stand mount, carrying case, and velveteen pouch.

IIEM	DESCRIPTION	PRICE
KSM42/SG	. Large dual-diaphragm side-address	
	condenser vocal mic, cardioid	. 799.00
KSM44A/SL	. Multi-pattern large dual-diaphragm side-address	
	condenser mic	. 999.00







CU-29

AR-51

AK-47MKII

### SHURI

SHURE KSM PROBE SERIES INSTRUMENT MICS These condenser microphones feature 20Hz-20kHz frequency response, a 3-position pad switch, a 3-position LF filter, and include a windscreen and carrying case. The KSM137 is a single pattern cardioid mic, while the KSM141 is a dual pattern mic (omni and cardioid). Both mics require 48V phantom power.

ITEM	DESCRIPTION	PRICE
KSM137/SL	Cardioid condenser, windscreen, case, champagne finish	200.00
KSM137/SL-STEREO	Stereo matched pair, 2 foam windscreens,	233.00
	A27M stereo mic adapter, case	665.00
KSM141/SL	Dual-pattern condenser, windscreen, case,	000 00
VCM141/CL CTCDCO	champagne finish	399.00
N3W141/3L-31EREU	A27M stereo mic adapter, case	870.00



SHURE SM94LC INSTRUMENT MICROPHONE A unidirectional electret condenser microphone tailored to the needs of professional musicians and sound engineers in both live performance and sound recording. It is equally at home in sound reinforcement systems or in sound studios and motion picture/ TV scoring stages. When used with the optional windscreen, the SM94 can be used by vocalists and speechmakers who desire a wide, flat response with minimum coloration. It runs on either an AA battery or phantom power. Other features include an internal shock mount, wide dynamic range of 119dB, a flat frequency response of 40Hz-16kHz and a uniform cardioid polar pattern.

ITEM	DESCRIPTION	PRICE
SM94LC	Cardioid condenser microphone	170.21
A3WS	Windscreen	12.83



A versatile, flat-response mic for both acoustic and high-volume performance applications. Useful for acoustic guitar, acoustic bass, strings, piano, woodwinds, and orchestral applications. Steel and brass construction with dark gray matte finish and stainless steel mesh grille. Frequency response 40Hz-16kHz.

ITEM	DESCRIPTION	PRICE
SM137LC	Cardioid condenser microphone	179.00



**ELECTRONICS MAGNETO STUDIO** CONDENSER MICROPHONE This cardioid condenser mic was designed for both vocals and acoustic instruments. Its max SPL is 140dB and it has a frequency response of 20Hz-20kHz with a high-sensitivity of -34dB. Runs on 12-48V phantom power. Includes swivel mic clip and

thread adapter.

ITEM	DESCRIPTION	PRICE
MAGNETO	Cardioid condenser microphone	119.00

### **ELECTRONICS** SERIES LARGE DIAPHRAGM CONDENSER MICROPHONES

The new X1 series of cardioid condenser microphones features the same handcrafted capsule as

the classic sE X1. X1-T features a gold-sputtered capsule and adds analog tube circuitry with a hand-selected tube

to achieve a vintage tube sound. Due to its tube circuitry it provides a slight boost to low-mid frequencies as well as high frequency content within the 20Hz-20kHz frequency response. X1-D is an instrument condenser microphone tailored for drums and percussion and features a titanium-sputtered capsule, allowing for an even faster transient response and use in high-SPL applications. Both models also feature a switchable -10dB pad and low-cut filter switch to keep incoming signals under control. X1-T includes multi-region international power supply unit with power cable, 7-pin cable to connect microphone to PSU and microphone clip; X1-D includes a microphone clip and a soft protective storage pouch.

ITI	EM DESCRIPTION	PRICE
X1	-TLarge diaphragm cardioid tube condenser microphone with PSU	399.00
SE	-X1-DCardioid condenser percussion microphone	299.00
	The state of the s	



### **TELEFUNKEN ELEKTROAKUSTIK RFT MICS**

These tube-powered, largediaphragm condenser mics are affordable alternatives to Elektroakustik high-end boutique models.

The AR-51 has a smooth midrange, open top end and solid, well-balanced low-end, making it great for vocals and instruments. It also has 9 switchable polar patterns. The AK47MkII has a highfidelity sound reminiscent of a cross between the classic M49 and U47/48 mics. It also has 9

selectable polar patterns and its superior high-frequency detail with rich, full low-end make it ideal for vocals. The CU-29 "Copperhead" has a warm, well-rounded low-end which is accented by a delicate and

intimate "air" in the high- end, making it equally at home capturing vocal or instrument performances. It has a cardioid-only polar pattern. All models feature NOS tubes, and ship with power supply, shock mount, cable and wooden box.

ITEM	DESCRIPTION	PRICE
AR-51	Tube condenser mics, switchable polar patterns	1895.00
AK-47MKII	Tube condenser mics, switchable polar patterns	1895.00
CU-29	Tube condenser mics, cardioid polar pattern,	
	Lundahl outnut transformer	1295 00

### TELEFUNKEN ELEKTROAKUSTIK ELA M 251 E MULTI-PATTERN TUBE CONDENSER MICROPHONE Hearkening back to classic designs of yesteryear, the ELA M 251 E features an edge-terminated, dualbackplate CK-12 capsule with a 1" gold-sputtered membrane, 20Hz-20kHz frequency response, AC701 tube, European-made Haufe 14:1 ratio output transformer, multiple polar patterns and a SPL-handling capability of up to 132dB. The microphone capsule and amplifier can be field-repaired in less than 1 minute - simply remove the retaining ring on the bottom of the body and slide the metal body tube off to access the internal workings. This microphone includes a dedicated power supply, locking flight case, wooden microphone box, shock mount and 25 foot Accusound quadshielded tube microphone cable with swivel connector.

ITEM	DESCRIPTION
ELA-M-251-E	Large diaphragm multi-pattern tube condenser microphone,
	cardioid/omnidirectional/figure-8 polar patterns

### TELEFUNKEN ELEKTROAKUSTIK U-47 AND U-48 LARGE DIAPHRAGM CONDENSER MICS

Modern designs, based on classic mics that defined the sound of music as we know it, these stunningly high-fidelity mics accent the musicality of your source, whether it's a symphony, classic crooner, or modern rock. Both models are powered by VF-14K vacuum tubes - a "plug 'n' play" replacement for the original VF-14M tubes. They also feature M7 dual-sided, gold-sputtered, center-terminated capsules, 2 polar patterns each, 20Hz-20kHz

frequency response, newly redesigned BV8 output transformer, and can handle SPLs up to 138dB. Both include a dedicated NG-style power supply, locking case, shock mount, and wooden box.

,		
ITEM	DESCRIPTION	PRICE
	Large diaphragm condenser, cardioid/omnidirectional	
U47-STEREO-SET	Matched stereo pair of U47s	CALL
U48	Large diaphragm condenser, cardioid/figure-8	8495.00
U48-STEREO-SET	Matched stereo pair of U48s	CALL

### TELEFUNKEN ELECTROAKUSTIK **C12 TUBE CONDENSER MICROPHONE**

This reissue of the classic C12 variable-pattern condenser combines silky top end with articulate mid-range, and tight, focused low end. It is ideal for recording drum overheads, acoustic guitars, and vocals. Powered by a 6702 vacuum tube, this mic has a CK12 1" dual-sided gold-sputtered membrane, Haufe output transformer, frequency response of 20Hz-20kHz, and can handle SPLs of up to 138dB. The dedicated power supply features an external pattern selector which is polydirectionally variable between omnidirectional and figure-8 polar patterns. Includes a locking flight case, lunchbox-style power supply, and wooden microphone box.

ITEM	DESCRIPTION	PRICE
C12	Tube condenser microphone, variable p	attern 8495.00
C12-STERFO-SI	T Matched stereo pair of C12s	CALL





























PRICE CALL











































COMPUTER AV



































### APOGEE MIC IPAD/IPHONE/MAC MIC

- · A studio quality mic for the iPad, iPhone
- · About the size of an iPhone
- · Record vocals as well as instruments and build tracks right on an iPad with GarageBand.
- · Compatible with iPhone 4S (16GB, 32GB, 64GB), iPhone 4 (16GB, 32GB), iPad2 (16GB, 32GB, 64GB) iPad (16GB, 32GB, 64GB).
- Includes .5m cable for connecting iPad and iPhone, 1m cable for connecting to Mac and a desktop tripod.



### **RØDE IXY/IXY-L** IOS STEREO MIC

- 1/2" cardioid condenser capsules
- Fixed 90° XY near-coincident alignment
- 20Hz-20kHz frequency response
- Up to 24-bit/96kHz quality with RØDE Rec or RØDE Rec LE app · Compatible with iPhone 4S, iPhone 4,
- iPad (3rd generation), iPad 2, iPad and iPod Touch (4th generation, iOS6+)
- · Includes windshield and case

IXY	Cardioid condenser mic, iOS	. 149.00
IXY-L	Lightning version	199.00

NEW



### SAMSON METEORITE **USB CONDENSER MICROPHONE**

- Cardioid USB condenser microphone Great for
- podcasting, iChat, voice recognition software
- Crossplatform plug-n-play operation (Mac/Win/iOS)
- 14mm shock-mounted diaphragm; 16-bit/44.1kHz resolution
- Includes a removable magnetic base and integrated USB cable
- · iPad or USB bus-powered

NEW!





- · Zero-latency monitoring
- 16-bit, 44.1/48KHz
- · Perfect for podcasting, voiceovers and home or field recording
- · Includes pivoting stand mount. tripod desk stand, threaded 5/8"-27 to 3/8"-16 adapter, 10' USB cable and storage pouch



AT2020-USB+ .... USB condenser mic. cardioid. 20Hz-20kHz ... 169.00





### **RØDE NTUSB** CARDIOID CONDENSER USB MIC


- · Side-address cardioid condenser USB mic
- Plug-and-play operation; compatible with Mac/ Windows, also works with iPad via optional Camera Connection Kit
- Captures audio at 16-bit/48kHz quality
- Built-in headphone amplifier and 1/8" headphone output for direct monitoring
- · Direct Mix Control dial allows for selection between microphone and source input monitoring
- · Includes tripod desk stand, ring mount, 20 ft. USB cable, pop filter and storage pouch







- **DIAPHRAGM USB CONDENSER MIC**
- designed for podcasting and vocal recording
- · Hand-crafted construction and gold-sputtered capsule based on sE's X1 microphone
- · Cardioid polar pattern, 20Hz-20kHz frequency response
- USB 2.0/3.0 connection is compatible with Windows and Mac OSX
- USB-B to USB-A cable



299.00

PG27USB PG42USB



### **AUDIX USB12 HIGH DEFINITION GOOSENECK CONDENSER MICROPHONE**

- · Record directly to computer via USB
- · Sleek, low-profile desktop design
- No additional preamp or interface needed
- 16-bit/48kHz sampling rate
- 12mm high-resolution condenser capsule
- · Push-to-talk includes choice of "steady on" or "momentary on"
- Includes bass roll-off filter and headphone jack for monitoring
- · Excellent for use with voice recognition



### *SAMSON* SAMSON CO1U PRO USB

### STUDIO CONDENSER MICROPHONE

- · Hypercardioid USB condenser microphone
- · Great for music recording,
- voice-over, Skype and FaceTime • Crossplatform plug-n-play operation (Mac/Win)
- 19mm shock mounted diaphragm;
- 20Hz-18kHz frequency response · Includes an tripod desk stand and mic
- · Connects to iPhone/iPad via Lightning to USB connection kit (sold separately)

CO1U-CONDENSER-MIC ........ USB condenser microphone ....... 77.99 LIGHT-USB-CAM-ADP.....Lightning to USB adapter kit ..... 29.00



### SE ELECTRONICS SE X1 USB LARGE

- · Studio-quality USB condenser microphone
- -10dB pad and low-cut filter switches
- Includes microphone clip and 1.5 meter

condenser microphone.

169.00

### SHURE SHURE PG SERIES USB

### SIDE ADDRESS CONDENSER **MICROPHONES**

- Large diaphragm capsules
- · USB plug-and-play interconnect with 1/8" headphone jack for zero-latency monitoring, monitor mix control for blending mic and playback audio
- Cardioid pickup pattern
- Integrated preamp with microphone gain control
- Pad switch (15dB on the 42, 20dB on the 27)
- USB-powered, 500mA maximum 20Hz-20kHz frequency response

PG27USB. .USB multi-purpose condenser mic. 144dB max SPL..

.USB vocal condenser mic, 135dB max SPL... 249.00





- For use with internet conferencing programs like SkypeTM
- 3-capsule boundary mic design with 180° coverage
- · Built-in custom circuitry
- · Built-in headphone/speaker monitoring jack 6ft USB cable
- · Automatic gain control · Comes with leatherette zipper case



LIGHT-USB-CAM-ADP..... Lightning to USB adapter kit....



- **PORTABLE USB CONDENSER MICROPHONE** Cardioid/omnidirectional USB
- condenser microphone · Great for business travelers,
- Skype and students
- Crossplatform plug-n-play operation (Mac/Win/iOS) • 20Hz-18kHz frequency response; 16-bit/44.1kHz resolution
- · Includes acoustic beam software to eliminate keystrokes and other ambient interference
- · Connects to iPhone/iPad via Lightning to USB connection kit (sold separately)





PG42USB.

### SHURE X2U XLR TO USB MIC ADAPTER

- · Plug-and-play USB connectivity
- · Compatible with Windows Vista Business, XP Pro/Home SP1 or later, 2000 Pro, and Mac OSX
- 10.1 or later, requires 64MB RAM or better Includes 3m/9.8' USB cable,
- and padded zipper carrying pouch
- · Monitor mix control for blending mic wand playback audio · Headphone jack with volume control for monitoring with zero-latency
- Integrated pre-amp provides +48V phantom power and mic gain signal control
- 16-bit up to 48kHz sample rate, 20Hz-20kHz +/- 1dB frequency response Peak signal LED indicator

X2U ......XLR-to-USB signal adapter with headphone output ... 99.00









AC-404.......Web conferencing boundary mic, 40Hz-16kHz......103.50











Portable USB condenser mic



always listening...

AUDIO-TECHNICA BP4027 AND BP4029 M-S STEREO SHOTGUN MICS Designed for broadcasters, sound recordists and videographers, these phantom-powered models feature independent linecardioid and figure-8 elements configured in an M-S




(Mid-Side) arrangement. Each provides a switch-selectable internal matrixing system offering a selection of wide and narrow stereo (L/R) output or M-S output. A switchable low frequency roll-off filter helps minimize the pickup of unwanted low frequency noise. The models differ from one another primarily in length (the BP4027 is 15 in. long and the BP4029 is 9 in. long); they both feature a lightweight rugged design and sleek black color scheme, ideal for on-camera use.

ITEM	DESCRIPTION	PRICE
BP4027	. 15" stereo shotgun microphone	. 771.36
BP4029	. 9" stereo shotgun microphone	. 700.12

AT8022

### AUDIO-TECHNICA AT8022 & BP4025 X/Y STEREO MICROPHONES Ideal for video-

cameras, stereo field recording, interviews and home recording.



ITEM	DESCRIPTION	PRICE
AT8022	.X/Y stereo condenser microphone, battery or phantom powered,	
	20Hz-15kHz, includes 2 cables (dual 3-pin XLRM-type & 3.5mm TRS)	399.00
BP4025	.X/Y stereo condenser microphone, phantom power only,	
	20Hz-17kHz, includes 1 cable (dual 3-pin XLRM-type)	649.00

### **AUDIO-TECHNICA ATR6250 STEREO** CONDENSER VIDEO/RECORDING MIC

An extremely affordable, high-quality stereo pickup in a single microphone. Its compact design is ideal for use with video cameras and portable audio recorders. Includes 1/8" stereo female output connector, 1/8"-1/8" stereo camera cable, 1/8" stereo to 2x1/8"



mono recording cable, camera mount, interchangeable mic stand base, windscreen, two 1/8" to 1/4" mono adapters and AA battery.

ITEM	DESCRIPTION	PRICE
ATR6250	. Stereo condenser video microphone	43.29



### DPA D:MENSION 5100 MOBILE SURROUND MIC

A versatile mobile surround mic that can be mounted, flown or held via a hand grip. It is equally suitable for studio or location



highly resistant to inclement weather conditions. Five miniature pressure transducers exhibit extremely low sensitivity to wind and mechanical noise, low distortion, highly-consistent low frequency response and large dynamic range. Appropriate channel separation and directionality are achieved through a combination of DPA's proprietary DiPMic™ (Directional Pressure Microphone) technology, which mounts interference tubes on L/C/R omni capsules, and the use of acoustic baffles that further preserve the accuracy of levels between the discrete analog output channels. A multi-pin Lemo connector carries six electronically balanced channels, while an enclosed five-meter (16 ft), six-pair Mogami cable breaks out to six Neutrik XLR-M connectors. Includes thread adapter and outdoor cover.

ITEM	DESCRIPTION	PRICE
5100	. d:mension mobile surround microphone with breakout cable	. 3399.95

**DPA D:MENSION MATCHED SURROUND** MICROPHONE KITS These surround kits consist of 5 select microphones, factory-matched to extremely low tolerances for consistent, pristine audio. The 4006A microphones are matched within ±0.5dB for both frequency response and sensitivity; 4011A and 4015A sets are matched to  $\pm 1$ dB. All microphones are matched from the mean of the set and for a maximum phase response difference of 5°. Each kit has been assembled for specific applications and include a sturdy Peli<sup>TM</sup> case, holders and windscreens. 5006-11A consists of (3) 4006A and (2) 4011A, selected for use as a Decca

Tree front + cardioids rear; 5006A contains (5) 4006A mics, perfect for Decca Tree + rear omnidirectional surround array; 5015A is (5) 4015A mics ideal for A/B, Decca Tree or surround main array use.

ITEM		PRICE
5006-11A	. (3) 4006A/(2) 4011A surround mic kit	CALL
5006A	. (5) 4006A surround microphone kit	CALL
5015A	. (5) 4015A surround microphone kit	CALL
Accessories		
SB0400	. Modular stereo boom with shock mounts	240.00
UA0836	. Stereo boom	729.95
SM1500	. Modular shock mount	135.00



capture the true ambience of the recording space, while offering a high level of rear rejection and low noise. Both offer 9V battery operation, LED battery status indicator, hi-pass filter switch, and -10dB pad switch. SVM-Pro features cardioid mics, ergonomic form factor, and integrated shock mount. DECODIDATION

IIEM	DESCRIPTION	PRICE
STEREO-VIDEOMIC	Stereo video microphone, for environmental and	
	ambient sounds	. 249.00
STEREO-VIDEOMIC-PRO	Stereo video microphone, for dialogue and	
	directional sounds	. 299.00
RØDE NT4 SINGLE PO	INT STEREO MIC The RODE NT4 is a studio grade	40

condenser microphone, but is perfect for location recording. It utilizes two 1/2" capsules in a 90°, XY arrangement. It comes with a case with a stand mount. windscreen and custom stereo cables, which include both XLR and mini-jack connectors. Requires 48V phantom power but can also use a 9V battery. Frequency response is 20Hz-20kHZ, max SPL of 143dB, dynamic range >128dB.

-			
ITEM	DESCRIPTION		PRICE
NT4	 Single point stereo mic		 529.00
WS4	 Replacement windscreen for NT	4	 19.99

# MITRA MT-3D 3D MICROPHONE

Record professional and immersive 3D sound with this unique binaural microphone. Ideal for audio engineers, musicians and videographers. Its lifelike sound is captured by the patent-pending SHEM audio processing system which mimics the perception of human hearing. Two

9V batteries provide up to 12 hours of use and the 1/4" tripod mount, two gold-plated XLR and single microphone level phono outputs ensure easy connection to your camera or recorder of choice.

ITEM	DESCRIPTION	PRICE
MT-3D	. Binaural microphone	. 995.00

### SHURE

SHURE VP88 STEREO CONDENSER The VP88 incorporates a forwardfacing cardioid mid-capsule, a perpendicular bidirectional side capsule and a built-in stereo matrix to provide wide, natural, uncolored response for optimal stereo imaging. Yet it's 100% mono compatible. Perfect for reinforcement, live music recording, drum overhead miking, and ambient studio miking. Frequency response 40Hz-20kHz. A88SM shock mount for stand mounting.

ITEM	DESCRIPTION	PRICE
VP88	Stereo condenser	723.14
A88SM	Shock mount for stand mounting	192.38
C110	25' extension cable	72.38









































































































**AUDIO-TECHNICA AT SERIES SHOTGUN MICS** The AT875 is a 6.9" long electret condenser operating from 11-52V phantom power with 127dB SPL. The AT897 is an 11" long shotgun ideal for camera-mounted use. The 14.5" AT8035 has an acceptance angle of 60° and the 18" AT8015, 40°. The AT897, AT8015 and AT8035 will operate over 3000 hours on a single AA cell or 11-52V of phantom power and have a switch to roll off low frequencies. All come with a windscreen, protective case, and mic clip.

	DESCRIPTION	PRICE
AT875R	Short shotgun, 6.9" long, 90Hz-20kHz, phantom power only	200.84
AT897	Short shotgun, 11", 20Hz-20kHz	264.33
AT8035	Medium shotgun, 14.5" long, 40Hz-20kHz	275.88
AT8015	Long shotgun, 18" long, 40Hz-20kHz	298.97
AT8405A	Replacement stand adapter	14.86
	Shock mount system (universal)	



**AUDIO-TECHNICA ATR6550 CONDENSER SHOTGUN MIC** Crisp & intelligible pickup — far away or up close. In its "Tele" range setting, this cardioid condenser is engineered to pick up dialogue and sound effects at a distance, while bypassing ambient noise. Designed especially for use with video cameras. Includes camera mount, mic stand clamp, windscreen, 1/4" adapter and AA battery.

ITEM	DESCRIPTION	PRICE
ATR6550	70Hz-18kHz, 3' long output cable with 1/8" plug	69.26

### ▲AZDEN

### AZDEN SGM SERIES SHOTGUN MICROPHONES

The SGM-PDII has an electret condenser and an 8.15" long supercardioid barrel. The SGM-1X features an

11.8" long supercardioid barrel, while the SGM-2X features an 8.4" long omnidirectional barrel with an extension that creates a 16" long supercardioid. The phantom powered SGM-3416 has a 7" long supercardioid barrel while SGM-3416L has a 9.75" barrel. The SGM-1000 has a 12.2" Long supercardioid barrel and is phantom powered. The SGM-DSLR has an 8.34" supercardioid barrel designed for use with DSLR cameras. Also for DSLR's, the SGM-990 is a supercardioid mic with a 6" barrel and selectable pattern width (narrow or wide). All feature an integrated shock mount/ shoe camera mount and windscreen and carrying case.

ITEM	DESCRIPTION	PRICE
SGM-PDII	Supercardioid condenser, phantom powered, 80Hz-18kHz	199.00
SGM1X	Supercardioid condenser, switchable low cut filter,	
	XLR out, 80Hz-18kHz	179.00
SGM2X	Omni with extension condenser, switchable low cut filter,	
	XLR out, 40Hz-20kHz	229.00
SGM1000	Supercardioid condenser, phantom powered,	
	switchable low cut filter, XLR out, 80Hz-20kHz	249.00
SGM-3416	Supercardioid condenser, phantom powered, 30Hz-20kHz	499.00
SGM-3416L	As above, with 9.75" barrel	599.00
SGM-DSLR	For use with DSLR cameras, supercardioid,	
	1/8" mini-jack, 80Hz-18kHz	175.00
SGM-990	For use with DSLR cameras, supercardioid,	
	1/8" mini-iack. 150Hz-18kHz	85.00

### **KLOVER PRODUCTS**

### KLOVER PRODUCTS PARABOLIC MICROPHONE SYSTEM

Available in three different sizes, these true parabolic microphone systems are a staple in the broadcast industry and are also used in military, police and rescue applications. The KM-26 features a 26" dish that can pick up normal conversation levels (~60dB) from up to 500 feet away. The 16" KM-16 was designed for use in confined spaces and works up to 200 feet from the source. KM-09 features a 9" dish that con-



verts a lavalier microphone for use as a lobar microphone, and can be mounted on top of a camera or concealed in a corner, making it ideal for EFP or ENG applications.

ITEM	DESCRIPTION	PRICE
KM-26	26" parabolic microphone system	2250.00
KM-16	As above, but 16"	1450.00
KM-09	. As above, but 9"	450.00



Owe Audie

### QUE AUDIO SHOTGUN MICROPHONE LOCATION KIT

A flexible, professional multiapplication shotgun mic kit, perfect for the on-the-go videographer needing a variety of solutions. Features include 3 types of shotgun



barrels providing a variety of polar patterns, high SPL-handling capabilities and high rear and side rejection to maximize the source audio. Kit contains (1) QLM1 9" shotgun barrel. (1) QLM2 12" shotgun barrel, (1) QLM3 17" shotgun barrel (all 3 with windscreens), (2) QLM-PSU power supplies, (2) QSM2 shock mounts, (1) QMM2 dual mic bar, and (1) aluminum case with foam insert.

ITEM	DESCRIPTION PRI	CE
QLOC	Location recording kit with 3 mics, 2 mounts and case	.00

### **SENNHEISER**°

SENNHEISER MKE SERIES SHOTGUN MICROPHONES The MKE400 has all-metal housing, maximum side-noise rejection, switchable sensitivity, integral shock mount, a 1/8" TRS connector with coiled cable and is

MKF-600

powered by a single AAA battery (included). The MKE600



replaces the switchable sensitivity with a low-cut filter and adds the ability to accept phantom power or power by a single AA battery. It includes a shock mount and has an XLR connector. Both models include a foam windscreen.

I I E IVI	DESCRIPTION	PRICE
MKE400	. 5.1" compact shotgun mic, 1/8" connector	. 199.95
MKE-600	. 10.1" shotgun mic, XLR connector	. 329.95
	3 ,	
Comment of the last of the las	MKIICO	



**SENNHEISER MKH SERIES SHOTGUN MICS** Interference tube microphones with supercardioid/lobar (>2kHz) patterns with high directivity throughout the whole frequency range. Very lightweight with exceptionally low inherent self-noise and high sensitivity. MKH416 is a pressure gradient receiver with short interference tube. MKH60 and MKH70 include switchable roll-off filter and treble emphasis, along with switchable pre-attenuation.

ITEM	DESCRIPTION	PRICE
MKH60-P48	. 11.02" short shotgun, 50Hz-20kHz	. 1499.95
MKH70-P48	. 16.14" long shotgun, 50Hz-20kHz	. 1749.95
MKH416P48U3	. 9.84" short shotgun, 40Hz-20kHz	999.95







COMPUTER AV



**RØDE VIDEOMICS** These supercardioid condenser shotgun microphones with integrated shock mounts are designed to connect directly to consumer video cameras and DSLRs via a standard hot-shoe mount. The microphones feature 1/8" stereo mini-jack output (dual mono), rugged ultra-lightweight ABS housing, and 9V battery power with up to 70 hours of battery life. The Pro version adds 2-step high-pass filter (flat, 80Hz),

3-position level control (-10dB, 0, +20dB), internal shock mount and includes a DeadCat VMP furry windshield. The Go version weighs only 2.5 oz, offers 96dB of dynamic range, includes a Rycote® Lyre® suspension for shock isolation and receives plug-in power via a 3.5mm connector — no batteries required (please ensure your camera supports plug-in power).

ITEM		PRICE
VIDEOMIC-R	Shotgun microphone, 9V, powered, with Rycote shock mount	149.00
	As above, but plug-in powered	
	As above, with HPF filter, level control,	
	internal shock mount and furry wind shield	229.00
Accessories		
VXLR	Female mini to XLR-M adapter for VideoMic	9.99
VC1	10' extension cable for VideoMic	. 10.99
WSVM	Replacement windscreen for VideoMic	. 11.99

### ALSO SEE SVM STEREO VIDEO MICROPHONE IN STEREO MIC SECTION.

RØDE NTG SERIES SHOTGUN MICS The NTG-1, NTG-3, and NTG-8 operate on 48V phantom, while the NTG-2 can operate from phantom or internal AA battery. The moisture-resistant NTG3 and humidity-resistant NTG-8 both include a weatherresistant aluminum storage cylinder and also use RF-bias technology for a high level of RFI immunity. All mics include a zip pouch, clip or shock mount (NTG-8), and windscreen suitable for outdoor recording.

ITEM	DESCRIPTION	PRICE
NTG1	. 48V phantom only, 8.5", black	249.00
NTG2	. 48V phantom or AA battery, 11", black	269.00
NTG3	. 48V phantom only, moisture-resistant, 10", silver	699.00
NTG8	. 48V phantom only, humidity-resistant, 22", black	999.00
DEADCAT	. Wind muff for NTG1/NTG2	39.00
WSVM	. Replacement windscreen for NTG1/NTG2	11.99



### SHURE

SHURE VP83 & VP83F LENSHOPPER™ CAMERA-MOUNT CONDENSER MICROPHONE These ultra-compact supercardioid shotgun microphones provide an all-in-one solution for capturing detailed, high-definition audio with DSLR cameras and camcorders. Easily accessible controls for low-cut filter and threeposition gain enable adjustments for different recording environments. Features detailed high-definition audio with full low end, high sensitivity and low self-noise, wide frequency range for natural audio reproduction and superior RF immunity to avoid unwanted audio artifacts from cellular and RF devices. The VP83F features flash recording with SD cards and playback with .wav file capture at 24-bit/48kHz and headphone audio output. Both include an integrated professional-quality Rycote® Lyre® shock mounting system, standard-size shoe mount with 1/4" threaded base for on-camera or stand use, detachable 1/8" goldplated audio cable and foam windscreen. Two AA batteries included.

1		
ITEM	DESCRIPTION	PRICE
VP83	.LensHopper™ camera-mount condenser microphone	. 229.00
VP83F	LensHopper™ camera-mount condenser microphone	
	with built-in digital recorder	. 349.00

### SHURE VP82/VP89 MODULAR SHOTGUN MICS

The VP89 and VP82 shotgun mics provide exceptional audio quality for broadcast/media production venues. The VP89 has 3 interchangeable capsules – long, medium and short. These are used when critical sound capture is required. The VP89L is ideal for sporting events/field recording as it targets sources of high volume over long distances. The VP89M offers a wider target for higher ambience, suited for audience response, talk shows and live concerts. The VP89S is perfect for camera mounting and features a wide pickup angle for high ambience. The VP82 is compact & lightweight, offering excellent off-axis rejection for sound capture and reinforcement in camera-mounted AV media productions. It includes an integrated preamp design for exceptional performance.

ITEM	DESCRIPTION	PRICE
VP89L	Long shotgun, with RPM89L capsule	999.00
VP89M	Medium shotgun, with RPM89M capsule	899.00
VP89S	Short shotgun, with RPM89S capsule	699.00
VP82	Non-modular shotgun mic for camera mount,	
	includes zipper pouch and windscreen	299.00
RPM89L	15.21" long capsule for VP89 systems	725.00
RPM89M	9.41" medium capsule for VP89 systems	625.00
RPM89S	6.41" short capsule for VP89 systems	425.00
	•	

### SONY

SONY SHOTGUN MICROPHONES Lightweight, unidirectional mics for Sony camcorders. The ECM673/9X, ECM674/9X and ECM678/9X use mono electret condenser capsules, have a supercardioid polar pattern, a 40Hz-20kHz frequency response and a low-cut filter switch. The ECM674/9X offers battery power as well as phantom power. The ECM680S is an MS stereo shotgun has a 50Hz-20kHz frequency response and comes with an XLR 5-pin cable. All mics listed include a windscreen.

ITEM	DESCRIPTION	PRICE
ECM673/9X	7-7/8" condenser mic, supercardioid, phantom power	. 309.88
ECM674/9X	10-5/8" condenser mic, supercardioid, battery/phantom power	. 389.73
ECM678/9X	9-7/8" condenser mic, supercardioid, phantom power	. 714.80
ECM680S	9-7/8" stereo MS condenser mic, phantom power, 5-pin XLR cable	914.00

HEM DESCRIPTION	PRICE
VP83LensHopper™ camera-mount condenser microphone	229.00
<b>VP83F</b> LensHopper™ camera-mount condenser microphone	
with built-in digital recorder	349.00







**ECM678** 

CAMERA NOT

















































### AUDIO-TECHNICA AT8004L LONG-HANDLE OMNIDIRECTIONAL DYNAMIC MICROPHONE

Ideal for interviews and sports broadcasting, with an extended-length handle (AT8004L) that provides ample room for a microphone flag. Provides natural reproduction of surrounding ambience. Rugged housing with hardened-steel grille stands up to field use, while internal shock mounting minimizes handling and cable noise. Includes stand clamp and protective pouch.

ITEM	DESCRIPTION	PRICE
AT8004L	Omnidirectional, 80Hz-16kHz,	
	extended handle, 9.43" long	102.73
AT8004	Shorter handle version of AT8004L,	
	5.93" long	91.20
AT8101	Optional windscreen for	
	AT8004/AT8004L	9.38



### **CONDENSER MICROPHONE**

Ideal for interviews, group vocals, or acoustic guitar, the AT8010 fea-

tures an omnidirectional polar pattern that provides maximum ambient pickup. It gives a very smooth, extended response on- and off-axis and has a low sensitivity to popping and overload. Operates on battery or phantom power. Stand clamp, windscreen, battery and soft pouch included.

ITEM	DESCRIPTION	PRICE
AT8010	Omnidirectional condenser	
	mic, 20Hz-20kHz	152.36

### beyerdynamic))))

**BEYERDYNAMIC M-58** This is an omnidirectional high output moving coil or dynamic microphone that has significant reduced handling noise because of its internal shock mounting. Its extended frequency response puts it into a class by itself for the sole purpose of announcing, interviewing, or ENG. The rugged construction, non-reflective finish and slim profile make it the perfect mic for on camera use. The smooth, natural response also makes it less susceptible to feedback where a PA is being used.

ITEM	DESCRIPTION	PRICE
M58	.Omnidirectional microphone	.259.00
WS58	Foam windscreen	17.90
MKV8	Replacement stand adapter	19.90

### **BEYERDYNAMIC MCE58 CONDENSER MIC**

A highly accurate electret-condenser omni interview microphone with integrated shock mount and pop shield for in-field broadcasting. Powered by internal AA cells and provides a high-balanced output level for broadcast equipment.

	1 1	
ITEM	DESCRIPTION	PRICE
MCE58	Condenser mic	399.99



ITEM	DESCRIPTION	PRICE
635A	Omni, gray finish	139.00
635A-B	Omni, black finish	139.00
300-BLACK	Optional windscreen	5.99

EV RE50 DYNAMIC OMNI A shock isolated version of the Electro-Voice 635A to reduce unwanted handling noise. Offers experienced and novice alike mechanical noise free audio. The "infield" mic of choice used by professionals

proressionais.		
ITEM	DESCRIPTION	PRICE
RE50-BLACK	Dvnamic omni	
RE50N/D-BLACK		
900-BLACK	Ontional windscreen	6.25





RØDE REPORTER INTERVIEW MICROPHONE An omnidirectional dynamic mic especially tailored for voice reproduction to maximize intel-

ligibility and deliver crisp, clear results in almost any condition. Features a durable die-cast aluminum alloy body coated with matte black anti-glare finish and multi-layer mesh basket to cut down environmental noise. Includes zip bag and "branding" flag.

ΓEM	DESCRIPTION	PRICE
EPORTER	Omni interview microphone	129.00


MD42

**MD46** 

F115B


### "SENNHEISER"

SENNHEISER ENG MICROPHONES High-quality microphones optimized for rough use in live reporting and broadcasting environments. The design of the mics helps block wind and noise. Mic bodies are refined steel with black finish. Does not include mic clip.



### SHURE

\$ \$ \$



ITEM	DESCRIPTION	PRICE
SM63L	Omnidirectional dynamic, champagne finish	137.09
SM63LB	Omnidirectional dynamic, black finish	137.09
SM63	Short handle version	113.09

SHURE VP-64 Shure's VP-64 is rugged and engineered to withstand nearly any kind of abuse. Its neodymium magnet structure maximizes signal-to-noise ratio and helps cut through background noise. Built-in pop/blast filter and shock mounted capsule keeps wind and handling noise at a minimum

mounted capour	e keeps while and handling holde at a himmani.	
ITEM	DESCRIPTION	PRICE
VP64A	Omnidirectional dynamic microphone	
<b>157F</b>	Renlacement stand adapter	7 92

### SONY

### SONY F112 AND F115B INTERVIEW MICROPHONES

High-quality handheld dynamic microphones designed for field production and newsgathering applications. These mics are equipped with a newly developed omnidirectional microphone capsule for clear voice pick-up from all directions. The metal body is rugged with an ergonomic design for a stable grip. The F112 offers a flat-and-wide frequency response of 60Hz-17kHz. The F115B offers a special rubber at the core of the microphone for reducing shocks and vibrations. The F115B's microphone cable is resistant to water, ensuring no deterioration of internal parts and has a frequency response 40Hz-12kHz.

IIEM	DESCRIPTION	PRICE
F112	Omnidirectional dynamic	CALL
F115B	Omnidirectional dynamic, weather-resistant	CALL







### AKG C562CM FLUSH-MOUNT BOUNDARY MIC

The C562CM has been designed specifically for permanent, "invisible" mounting in ceilings, walls, tables, stage props, etc. The C562CM is a perfect

tool for surveillance or live recording since a single microphone can

cover an entire room. The supplied XLR phantom power adapter connects to the microphone cable through a miniature connector so installation holes can be smaller than the diameter of the phantom power adapter.

ITEM	DESCRIPTION	PRICE
C562CM	Low-profile boundary mic, omni (hemispherical), 20Hz-20kHz.	299.00

# (A) audio-technica. always listening...

### AUDIO-TECHNICA UNIPOINT BOUNDARY MICS

UniPoint boundary condenser mics feature superior off-axis rejection and maximum gain-before-feedback, on- and offaxis response, 80Hz filter which reduces pickup of unwanted low-frequency ambient noise, and a heavy die-cast case with non-slip bottom pads. UniGuard® technology offers unsurpassed immunity from radio frequency interference. PivotPoint® provides a unique rotating output connector that allows the cable to exit form either the back or the bottom of the microphone (except for U841A). The U891R, U891RW, and U891RC boundary mics are equipped with programmable switches and LED status indicators.



ITEM		PRICE
U841A	Omnidirectional with battery or phantom power	249.00
U851A	Cardioid with battery or phantom power	269.00
U851R	Cardioid with phantom power only	269.00
U851RW	As U851R, with white finish	219.00
U891RX	Cardioid with phantom power, touch-sensitive	
	3-position built-in switch	299.00
U891RWX	As U891RX, in white	299.00
U891RCX	As U891RX, with provision for local or remote switching	319.00

### AUDIO-TECHNICA PRO42/PRO44 CARDIOID **CONDENSER BOUNDARY MICROPHONES** Both these mics feature a low-profile design for limited visibility, half-cardioid polar pattern, wide-range condenser ele-



ITEM	DESCRIPTION	PRICE
PR042	Miniature boundary mic, 70Hz-14kHz,	
	25ft permanently-attached cable	97.51
PR044	Boundary mic, 70Hz-16kHz, 25ft detachable cable	104.31

### beyerdynamic)))

BEYERDYNAMIC CLASSIS BOUNDARY INSTALLATION  $\begin{tabular}{ll} \textbf{MICROPHONES} & These & condenser & boundary & microphones \\ \end{tabular}$ are designed for flush mounting into tabletops or ceilings, and applications such as teleconferencing, videoconferencing, recording or amplification of round table discussions - wherever the microphone needs to be as unobtrusive as possible. The high sensitivity guarantees a constant output level even



from long distance sources. Elastic bearing rings achieve mechanical isolation and offer effective sound isolation. All have a 3-pin XLR connector. The Classis BM 32 and 34 have a half-cardioid polar pattern, which increases the gain-before-feedback and decreases the amount of diffuse ambience. The BM 34 adds a bass roll-off filter. The Classis BM 33 has a half-spherical polar pattern making it ideal for large rooms.

	DESCRIPTION PRICE
BM32-E	Half-cardioid, black, no preamp
BM32-B	Half-cardioid, 50Hz-18kHz, black
BM32-SE	As BM32B, in silver metallic
BM32-W	As BM32B, in white
BM33-B	
BM33-SE	As BM33B, in silver metallic
BM33-W	As BM33B, in white
BM34-B	Half-cardioid, 150Hz-18kHz with bass roll-off filter, black 134.99
BM34-SE	As BM34B, in silver metallic
BM34-W	As BM34B, in white



### CAD AUDIO BOUNDARY

MICS The 220VP and 2220VP are continuously variable polar pattern, button-style, condens-



er boundary mics, designed for surface installation. These mics are made to resist interference from cell phones and RF devices. The 80Hz, 12dB/octave highpass filter removes unwanted low-frequency energy to improve intelligibility. The mics are terminated with a standard 3-pin XLRM-type connector recessed in the body of the mic. The 2220VP has remote polar control through a Digital Signal Processor (DSP).

ITEM DESC	RIPTION		PRICE
220VPBoun	dary mic, 90Hz-17kHz,	120Ω, black	239.00
220VPWAs all	oove, in white		239.00
2220VPBoun	dary mic, 90Hz-17kHz,	120 $\Omega$ , DSP compatible, black	299.00
2220VPWAs al	oove, in white		299.00

CAD AUDIO 901VP BOUNDARY MICROPHONE For use on conference tables or stage floors, this boundary mic features an all-metal body, rugged rubber bottom, Variable Pattern Control, and a DSP-controlled continuously-variable polar pattern. The improved RF immunity greatly reduces susceptibility to radio interference from GSM-based cell phones, PDA/cell phones and wireless devices.

ITEM	DESCRIPTION	PRICE
901VP	40Hz-20kHz, RF-resistant, condenser boundary microphone	199.00



**AUDIX ADX60 BOUNDARY CONDENSER MICROPHONE** The ADX60 is a pre-polarized condenser microphone designed to handle a wide variety of recording and live sound applications as well as permanent installations. With a smooth, uniform response over a frequency range of 50Hz-18kHz, the ADX60 provides a warm, full-bodied sound not typical of microphones this size. It is housed in

a heavy-duty zinc die-cast base with a low reflective black e-coat finish. It is supplied with a an inline preamplifier and 25' of shielded cable. Requires phantom power, optional power supply is available.

ITEM	DESCRIPTION	PRICE
ADX60	Cardioid boundary microphone	219.00
ADX60-OM	Omnidirectional boundary microphone	239.00
APS-911	Phantom power supply	57.00



### **CROWN PCC-160**

Surface-mounted, supercardioid condenser mic intended for stage floors, lecterns, conference tables, and news desks. Features excel-



lent gain-before-feedback, room noise and rear sound rejection. Surface mounting results in a "half-supercardioid" polar pattern with increased directivity and sensitivity. The low profile and black finish make the PCC160 almost invisible in most applications. Phantom power only.

ITEM	DESCRIPTION		PRICE
PCC160	. Supercardioid microphone,	black	. 449.00












































































































### **CROWN PZM10 LOW PROFILE MICROPHONES**

Features a cylindrical design for ceiling, wall or tabletop installations. Intelligibility is excellent, with low frequencies below the voice range rolled off to reduce the pickup of HVAC rumble. It has an XLR connector and

is phantom powered. The PZM-10LL has line-level output featuring pigtail connectors and is powered by 12-14V DC (not phantom power).


ITEM	DESCRIPTION	PRICE
PZM10	. Low profile mic, 80Hz-20kHz, -52dBm/Pa,	
	12-48V phantom powered	169.00
PZM10LL	Line level version, 100Hz- 20kHz, +8dBm/Pa,	
	12-14VDC powered	199.00

CROWN PZM-11 This low-cost microphone mounts on a standard wall plate, for surveillance and conference room applications. It resembles a light switch rather than a microphone. Electronics on the rear of the plate offer screw terminals, eliminating the need



11LLWR is the weather-resistant version.			
ITEM	DESCRIPTION	PRICE	
PZM11	Boundary mic, phantom required	119.00	
PZM11LL	Line level boundary mic	139.00	
P7M11II_WR	Weather-resistant line level houndary mic	179 00	

CROWN PZM30D AND PZM6D The PZM (Pressure Zone Microphone) is ideal for recording critical music or voices. The PZM-



30D has integral XLR output connector, the PZM-6D has hard wire output. Both have flat or rising response switchable. Phantom power only.

ITEM	DESCRIPTION	PRICE
PZM30D	Boundary microphone, XLR output	399.00
PZM6D	Boundary microphone, hard-wired output	399.00

CROWN PZM-185 An inexpensive version of the PZM-30 and PZM6 with XLR output, can be phantom or battery powered.

		•		
ITEM	DESCRIPT	ION		PRICE
PZM185	. Microphon	e	2	229.00

CROWN SOUND-GRABBER-II A less expensive version of the PZM-185. Battery powered only with attached cable. 1/4" and mini plugs included.

ITEM	PRICE
SOUND-GRABBER-II	119.00

### SENNHEISER®

SENNHEISER E900 SERIES HALF-CARDIOID BOUNDARY MICROPHONES Pre-polarized condenser microphones with a half-cardioid pickup pattern and internal preamp electronics in rugged low-profile housings. The e901 is especially well-suited for kick drum and grand piano. The e912 is designed for picking up speech, vocals and acoustic instruments. Max SPL is 136dB. A rub-

ber plate on the underside reduces unwanted vibrations and mounting slots allows the microphone to be securely fastened on a stage, a conference table or lectern.

			0 /	
ITEM	DESCRIPTION			PRICE
E901	.Boundary mic for	kick drum or gi	rand piano	239.95
E912	.Boundary mic for	speech and ac	oustic instruments,	black or white 299.95

### SHURE

### SHURE CENTRAVERSE™ BOUNDARY MICS

These fit seamlessly within any design aesthetic. They offer low profile, discreet placement for corporate facilities, houses of worship, government institutions, and

more. They feature Commshield® Technology to guard against unwanted RF interference. Their 70Hz-16kHz frequency response makes these mics ideal for capturing fast transients in a wide variety of locations, including podiums and desktops. Both versions come with attached 12ft XLR cable.

ITEM	DESCRIPTION	PRICE
CVB-B/C	Cardioid condenser boundary microphone, 12' cable, black	99.00
CVB-B/0	Omnidirectional condenser boundary microphone, 12' cable, black	99.00

### SHURE

### SHURE BETA91A HALF-CARDIOID CONDENSER MIC

Designed for use with kick drums, as well as other low-frequency applications including piano. It features an updated microphone capsule, integrated preamp, XLR connection and a 20Hz-20kHz frequency response. The Beta 91A combines superior attack and punch for studio-quality sound, even at extremely high sound pressure levels (SPL). A 2-position contour switch maximizes attack and clarity depending on application; flat response for



natural sound, or low-mid scoop for a strong low-frequency punch with ample higher frequency attack. Requires no external mounting or accessories.

ITEM	DESCRIPTION	PRICE
BETA91A	Half-cardioid condenser kick-drum mic	239.00

### SHURE MX391 MINIATURE CONDENSER BOUNDARY MICS

The low-profile design of the MX393 at half the size! The smooth, widefrequency response and high sensitivity are perfect for boardrooms, houses of worship and courtrooms. Other features include interchangeable capsules, dent-resistant steel grilles, mounting holes, bottom cable exit and attached 12' cable and preamp. Also available in a white finish.



ITEM	DESCRIPTION	PRICE
MX391/C	Cardioid, detachable preamp with XLR, requires phantom power	156.43
MX391/S	Supercardioid, detachable preamp with XLR, requires phantom power	161.93
MX391/0	Omnidirectional, detachable preamp with XLR, requires phantom power	144.32

### SHURE MICROFLEX BOUNDARY

MICS Perfect for altars, boardrooms and distance learning centers. Features programmable, silent membrane switches, logic inputs/outputs and LED indicators. Like all microflex



models, 3 interchangeable condenser cartridges are available. The MX393s feature a 10' tiny QG-to-XLR cable, a paint mask, skid-resistant feet and a keyhole slot for rigid mounting. The MX690 has an integrated wireless transmitter, programmable mute, bi-color status indicator, requires SLX4 or SLX4L receiver.

ITEM	DESCRIPTION	PRICE
MX393/C	Cardioid with XLR cable	197.18
MX393/S	Supercardioid with XLR cable	203.80
MX393/0	Omnidirectional with XLR cable	186.17
MX690	Wireless boundary microphone cardioid condenser	451.07

SHURE MX395 LOW PROFILE BOUNDARY MICS Perfect for meeting rooms, these microphones deliver exceptional sound pickup while barely being noticed. Choose from a selection of colors and pickup patterns for customized table installations. They feature logic inputs for remote LED control, bi-color status indicators, a wide dynamic range and smooth frequency response, and are only 1.25" in diameter.



	(female connector included), in black	156.0
MX395B/0	. Omni, 3-pin XLR, in black	135.6
MX395B/O-LED	. Omni, remoteable LED, 5-pin XLR	
	(female connector included), in black	149.2
MX395AL/0	Omni, 3-pin XLR, in brushed aluminum	135.6
MX395W/0	. 3-pin XLR, in white	156.0
MX395B/BI	. Bi-directional, 3-pin XLR, in black	161.6
MX395AL/BI	. Bi-directional, 3-pin XLR, in brushed aluminum	161.6
	. Bi-directional, remoteable LED.	
	5-pin XLR, in black	172.9

### SHURE MX396 MULTI-ELEMENT BOUNDARY

MIC These mics come in 2-or 3-element configurations, combining the coverage of multiple microphones into one compact package. They feature end of table (300°), center of table (360°), or cross table (bi-directional) coverage patterns, individual control of each element, bi-color status indicator, programmable mute switch, back or bottom exit cable, logic input/output for



remote LED and mute control. The MX396/C-DUAL features a 0-180° dual-element while the MX396/C-TRI features a 90-0-90° tri-element adjustable to 120-120-120°.

ITEM	DESCRIPTION	PRICE
MX396/C-DUAL	Cardioid boundary dual-element	340.39
MX396/C-TR	Cardioid boundary tri-element	417.50







### CHM99 HANGING CONDENSER MIC

When suspended from the ceiling or a beam, this mic is a simple solution for recording choirs. Includes an integrated spring steel clamp for optimum alignment and 33ft cable. Use two in an XY or ORTF stereo configuration.

.,	· ·	
ITEM	DESCRIPTION	PRICE
CHM99-BLACK	Cardioid, 70Hz-18kHz, in matte black	149.00
CHM99-WHITE	As above, in white	149.00



### 

always listening...

AUDIO-TECHNICA PRO45 PROPOINT HANGING MIC A widerange condenser cardioid hanging mic with a 25' cable terminated in an XLR connector. Phantom powering from 9-52V is required. Ideal for choirs and theatre. A foam windscreen and wire hanger are standard. Response from 70Hz-16kHz.

ITEM	DESCRIPTION	PRICE
PR045	. Cardioid condenser microphone	100.72
AT8153	. Replacement foam windscreen	10.16
AT8451	. Replacement steel hanger	13.30

AUDIO-TECHNICA UNIPOINT HANGING MICS Cardioid condenser hanging mics featuring UniGuard<sup>TM</sup> technology and offering unsurpassed immunity from radio frequency interference. An 80Hz UniSteep® filter reduces pickup of low-frequency ambient noise. Interchangeable elements offer superior on- and off-axis response, resulting in truly exceptional sonic quality and a choice of angle of acceptance.

ITEM	DESCRIPTION	PRICE
U853A	Cardioid, uses battery/phantom power	259.00
U853AU	As U853A, with 90° pickup pattern	289.00
U853AW	As U853A, in white	259.00
U853AWU	As U853A, with 90° pickup pattern, in white	289.00
	Cardioid, uses phantom with wall/ceiling plate	
U853PMU	As U853PM, with 90° pickup pattern	269.00
U853PMW	As U853PM, in white	209.00
U853PMWU	As U853PM, with 90° pickup pattern, in white	269.00
U853R	Cardioid, uses phantom power	189.00
U853RU	As U853R, with 90° pickup pattern	249.00
U853RW	As U853R, in white	189.00
U853RWU	As U853R, with 90° pickup pattern, in white	249.00
UE-C	Cardioid element, 120° pickup pattern	73.69
UE-H	Hypercardioid element, 100° pickup pattern	73.69
UE-0	Omnidirectional element, 360° pickup pattern	73.69
UE-UL	UniLine element, 90° pickup pattern	103.41

AUDIX ADX 40 SERIES HANGING MICROPHONES A miniature condenser microphone for overhead hanging applications, with a smooth uniform response of 40Hz-20kHz for full rich sound. It is machined from solid brass and is available in non-reflective black or white, and in a cardioid or hypercardioid pick-up pattern. Has an attached 30' cable, and operates on 9-53V phantom power with the preamp module APS-910.

ITEM	DESCRIPTION	PRICE
ADX40	Hanging cardioid mic, in black	189.00
ADX40W	Hanging cardioid mic, in white	199.00
ADX40-HC	Hanging hypercardioid mic, in black	209.00
ADX40W-HC	Hanging hypercardioid mic, in white	229.00
APS-910	Phantom power preamp module	36.00

### **AUDIX M1255 MICRO SERIES HIGH-OUTPUT HANGING MICS**

A miniature condenser mic with an integrated preamp and detachable cable. With unmatched high-output and extremely low-noise electronics, it's the perfect choice for choir, ceiling and recording from a distance. It has great RFI immunity and natural hi-pass filter frequency response of 80Hz-20kHz. Available in black or white as well as a choice of pick up patterns.

ITEM	DESCRIPTION	PRICE
M1255B	High-output hanging cardioid mic, in black	409.00
M1255BW	Cardioid mic, in white	429.00
M1255B-HC	Hypercardioid mic, in black	429.00
M1255BW-HC	Hypercardioid mic, in white	449.00
M1255B-0	Omnidirectional mic, in black	409.00
M1255BW-0	Omnidirectional mic, in white	429.00
M1255B-S	Supercardioid (mini-shotgun) mic, in black	449.00
MC-HANGER	Hanging clip, transparent	19.95

### 0M302-US beyerdynamic)

### BEYERDYNAMIC CLASSIS **INSTALLATION MICROPHONES** Classis

Series installation microphones combine an unobtrusive design with high gain before feedback. Innovative new Scudio<sup>TM</sup> technology eliminates mobile wireless interference via a shielded capsule - ensuring optimum audio quality and speech intelligibility.

DESCRIPTION

Overhead gooseneck for ceiling-mount

<b>OM304-US</b> As a	above, with 26' cable
	CAD VARIABLE OVERHEAD MIC
AUDIO	able polar patters

0M302-US

**CAD VARIABLE PATTERN CONDENSER OVERHEAD MICS** The continuously vari-

able polar pattern of these mics can be ASTATIC COMMERCIAL changed with the remote control and allows the user to precisely adjust the shape of the pick-up pattern for the best performance from a remote location. Utilizing a 2-conductor shielded cable between the mic head and the pattern box, the user

Cardioid condenser, white, for US sockets

can adjust the polar pattern in real time w/o changing capsules or mic positions. Both models include rackmountable remote box. The 2600VP and 2700VP are both controlled through a Digital Signal Processor (DSP).

ITEM	DESCRIPTION	PRICE
1600VP	Hanging condenser mic, variable pattern, 40Hz-20kHz, with	
	30' cable terminated to TA3F and XLR-M, steel hanger, remote box	499.00
1700VP	As above, includes MB-1 mini boom in place of steel hanger	599.00
MB-1	Carbon fiber 56" mini boom, fits standard 5/8" thread mic post	. 98.72
2600VP	Hanging condenser mic, variable pattern, 40Hz-20kHz, with 30'	
2700VP	cable terminated to TA3F and XLR-M, steel hanger, DSP compatible As above, includes MB-1 mini boom with clutch rotation	449.00
2100¥F	in place of steel hanger, DSP compatible	549.00

# **COUNTRYMAN ISOMAX II-H**

### HYPERCARDIOID HANGING CHOIR MICROPHONE

Designed to pick up the entire choir evenly while eliminating unwanted ambient noise. The polar pattern reduces the number of microphones necessary to capture the whole choir. These tiny, lightweight microphones are easy to place, position and control. Supplied with windscreen, 50' cable on a spool and phantom-powered XLR preamp.

ITEM	DESCRIPTION	PRICE
M2HP4FF50B/ISOMAX-2	. Hypercardioid choir microphone, 40Hz-18kHz, in black	. 200.52
M2HP4FF5NW/ISNMAX-2	As above in white	200 52

### SHURE

### SHURE CENTRAVERSE™ OVERHEAD CONDENSER MICS

Professional low-profile cardioid electret condenser mics designed for overhead sound reinforcement applications. An integrated wire-aiming hanger allows optimal and discreet placement above choirs and other ensembles. Features Commshield® Technology to guard against unwanted RF interference. The tailored frequency response captures fast transients above choirs and other ensembles. Includes attached 25ft XLR cable and snap-fit windscreen.

ITEM	DESCRIPTION	PRICE
CVO-B/C	.Overhead condenser microphone,	
	25' cable, cardioid, in black	. 89.00
CVO-W/C	.As above, in white	. 89.00

SHURE MICROFLEX OVERHEAD MICS These mini-condenser overhead mics are perfect for choirs and stages. Comes with in-line or plate-mount preamps, with choice of one interchangeable condender mic cartridge. Also includes: 4" gooseneck with 30' cable, snap fit windscreen. Available in black or white.

ITEM	DESCRIPTION	PRICE
Models with in-	-line preamps	
MX202B/C	Cardioid, in black	160.52
MX202B/S	Supercardioid, in black	166.18
MX202W/C	Cardioid, in white	160.52
MX202W/S	Supercardioid, in white	166.18
Models with 1-	gang wall plate type preamp	
MX202BP/C	Cardioid, in black	160.52
MX202BP/S	Supercardioid, in black	166.18
MX202WP/C	Cardioid, in white	160.52
MX202WP/S	Supercardioid, in white	166.18



0M304-US

PRICE

168.99

168.99

1600VF



































































































GM315

GM314-S

GM303-S



always listening...

### **AUDIO-TECHNICA PROPOINT GOOSENECK MICS**

All models operate only from 9-52V of phantom power. Four models in two different lengths and two mounting styles. The PRO47 has a 5/8" thread mount and a 9' cable terminated with an XLR connector.

ITEM	DESCRIPTION	PRICE
PR047T	. 12.4" thread mount	.130.40
PR047TL	. 15.8" thread mount	.130.40
PR049Q	. 13" quick XLR mount	.117.93
PR049QL	. 16.4" quick XLR mount	.117.93
	Replacement foam windscreen	

### **AUDIO-TECHNICA UNIPOINT GOOSENECK MICS**

Cardioid condenser gooseneck mics with UniGuard™ technology (except U855QL/U859QL). Unsurpassed immunity from radio frequency interference, and 80Hz UniSteep® filter that reduces pickup of unwanted low-frequency ambient noise. New interchangeable elements (hypercardioid, cardioid, omnidirectional and super-directional UniLine® line cardioid) offer an angle of acceptance from 90° through 360° and superior on- and off-axis response for exceptional sonic quality. A 2-stage foam windscreen yields outstanding resistance to plosives and other breath noises. The U855QL is a cardioid talk-back, paging and dispatch cardioid dynamic gooseneck mic. Interchangeable elements are for U857 mics only.

	<b>DESCRIPTION</b> .17.64" cardioid, XLR mount, without UniGuard™ .16.58" cardioid, 5/8" mount, uses phantom or	<b>PRICE</b> 109.00
U857Q	battery power, includes power module, windscreen, flange and pass-through adapter	
	includes foam windscreen and shock mount	
	.19.17" UniLine® line-cardioid, XLR mount, includes foam windscreen and shock mount	
	. 18.90" cardioid, XLR mount, phantom only, without UniGuard™, includes windscreen	
UE-H	.Cardioid element, 120° pickup pattern .Hypercardioid element, 100° pickup pattern .Omnidirectional element, 360° pickup pattern	. 73.69
UE-UL	.UniLine® element, 90° pickup pattern	103.41

AUDIO-TECHNICA AT808G SUBCARDIOID DYNAMIC CONSOLE MICROPHONE A quality talk-back microphone for entertainment, commercial and industrial applications which features a versatile gooseneck for unlimited positioning. Custom-tailored frequency response ensures excellent intelligibility in environments with excessive ambient noise.

ITEM	DESCRIPTION	ON			PRICE
AT808G	Dynamic, su	ubcardioid,	200Hz-5kHz,	3-pin XLR	125.82

### beyerdynamic))) **BEYERDYNAMIC CLASSIS SERIES CONFERENCE MICROPHONES**

Gooseneck microphones with an extremely small head and thin matte black neck, these microphones will blend into any design aesthetic. Its improved cardioid polar pattern ensures maximum volume due to a high-gain before feedback with excellent intelligibility. Beyerdynamic's exclusive Scudio<sup>TM</sup> technology provides absolute RFI immunity.

ITEM	DESCRIPTION	PRICE
Goosened	k Microphones	
GM303-S	12" gooseneck podium microphone,	
	XLR-M, on/off switch	195.99
GM306	24" gooseneck podium microphone, XLR-M .	244.99
GM304	16" gooseneck podium microphone, XLR-M .	167.99
GM304-S	As above, with on/off switch	182.99
GM314-S	16" gooseneck podium microphone,	
	LED ring, XLR-M, on/off switch	296.99
GM315	20" gooseneck podium microphone,	
	LED ring, 5-pin XLR-M	261.99
CM215 C	As above with on/off switch 3 pin VIP M	205.00



CAD GOOSENECK MIC The Astatic 920B is a low-noise, cardioid, condenser

gooseneck mic that provides natural, articulate and transparent sound. The cardioid polar pattern minimizes

feedback when used close to sound reinforcement speaker and monitors. Has durable matte-black non-reflective paint. Foam windscreen included.

	DESCRIPTION Cardioid gooseneck mic. 150Hz-20kHz. 20-7/16" long	PRICE 139.00
GSM1	Shock mount for 920B	64.98
FM-1A	Flange with 3-pin XLRF stem mount	27.50
FM-2A	Locking flange mount with 3-pin XLRF	14.66

### COUNTRYMAN ISOMAX 4 RF GOOSENECK MICS The lowest noise podium mic features improved RF rejection of

interference from cell phones, wireless devices, and active noise cancellation to eliminate mechanical noise from either touching

the mic or the surface it is attached to. The base is a standard XLR male connector, the output is balanced transformerless, a minimum of 9VDC phantom power is required. The matte black extension tube may be bent repeatedly.

ITEM	DESCRIPTION	PRICE
M4HP5RF18EB/ISOMAX-4	18" Isomax 4RF mic, hypercardioid,	
	70Hz-18kHz, black	299.81
M4HP5RF24EB	24" Isomax 4RF mic, hypercardioid,	
	70Hz-18kHz, black	299.81
M4CP5RF18EB/ISOMAX-4	18" Isomax 4RF mic, cardioid,	
	70Hz-18kHz, black	299.81
M4CP5RF24EB/ISOMAX-4	24" Isomax 4RF mic, cardioid,	
	70Hz-18kHz, black	299.81
A4STAND	Isomax 4RF stand clip	20.73
A4CDM	Isomax 4RF desk mount	20.73
A4WSB	Replacement windscreen, black	13.03

### **EARTHWORKS IML SERIES** Earthworks GOOSENECK INSTALLATION **MICROPHONES**

NEW!

The IML Series of gooseneck microphones are designed for installations such as teleconferencing systems, distance learning, boardrooms, government facilities and surveillance. These microphones feature a cardioid polar pattern, wide frequency response (30Hz-30kHz), fast impulse response, programmable LumiComm<sup>TM</sup> touch ring and programmable dual-color LED light ring. Available in 4 different lengths and are supplied with either a 5-pin RJ45 connector or a 5-pin Phoenix connector. Speak with your Sales Pro for more information.

	DESCRIPTION	PRICE
IML3-B	3" gooseneck installation microphone, black finish,	
	red and green LEDs, touch sensor output	899.00
IML6-B	As above, with 6" gooseneck	939.00
IML10-B	As above, with 10" gooseneck	959.00
IML12-B	As above, with 12" gooseneck	969.00

### EARTHWORKS FLEXMIC™ SERIES PODIUM MICROPHONES

These mics offer exceptional intelligibility, impressive impulse response, diaphragm settling time and sound quality not usually found in podium microphones. Patented cardioid or hypercardioid polar patterns, as well as smooth off-axis response, allow an orator to move up to 90° off-axis and still be heard. The flexible neck allows the mic to be repositioned with no handling noise. While intended for podium use, these can also be used as hanging choir mics. They are also suitable for piano, acoustic instruments or even drums. Frequency response is flat from 50Hz-20kHz within +2dB at 6", up to 145dB SPL.

ITEM	DESCRIPTION	PRICE
FM360	13" cardioid	. 529.00
FM360HC	13" hypercardioid	. 529.00
FM500	19" cardioid	. 529.00
FMR500	19" cardioid with rigid center and flex on both ends	. 589.00
FM500/HC	19" hypercardioid	. 529.00
FMR500/HC	19" hypercardioid with rigid center and flex on both ends	. 589.00
	27" cardioid with rigid center and flex on both ends	
FMR720/HC	27" hypercardioid with rigid center and flex on both ends	. 589.00

### SAMSON SAMSON CM SERIES GOOSENECK MICS

These mics feature miniature cardioid condenser elements, XLRM connectors at their base, onboard high-pass filter at 100Hz, a dual-stage, rippled windscreen, and they function on 9-52V phantom power. They include a FMS1 standard flange mount for installation, and a WS15 windscreen.

ITEM	DESCRIPTION	PRICE
CM15P	.15" cardioid condenser, 60Hz-16kHz, 127dB SPL, black	89.99
CM20P	.20" cardioid condenser, 60Hz-16kHz, 127dB SPL, black	99.99



Earthworks IML6-B

Introducing the Earthworks IML Installation Series of High Definition Microphones<sup>™</sup> featuring the LumiComm<sup>™</sup> Touch Ring. Seamlessly integrated into the microphone, the LumiComm<sup>™</sup> Touch Ring consists of a dual-color LED light ring and a touch sensor output—providing integrators complete freedom to assign function and LED color.

The IML microphones feature a near-perfect cardioid polar response, a flat frequency response, and an incredibly fast impulse response; allowing the speaker to maintain high intelligibility at the front, sides, top and bottom of the microphone without a reduction in sound level or loss of high frequencies. What does this mean for your sound? More clarity, detail and intelligibility than any other microphone can deliver.

Contact your Full Compass Sales Representative to discover how the IML Installation Microphones featuring the LumiComm™ Touch Ring can dramatically improve your next sound installation.




### Intelligently Engineered

- Simple installation
- Shielded against wireless RF
- · Choice of 3, 6, 10 or 12 inch gooseneck
- Engineered for a wide supply voltage range from 7 to 28 VDC regulated supply



### **High Definition Audio**

- High speech intelligibility
- Near-perfect polar response
- Extended, flat frequency response
- More gain before acoustic feedback



### LumiComm Touch Ring

- Touch sensitive
- Dual-color LED indicator
- Electronic system control compatibility























































oid, supercardioid and hypercardioid). Available in 12- or 18-inch lengths, and XLR, flange mount, or PolarChoice Plus which features a push button on top of the mount and status LED.

ITEM	DESCRIPTION	PRICE
PC12/FL	. 12" multi-pattern gooseneck mic, flushmount	456.00
PC12/XLR	. 12" multi-pattern gooseneck mic, XLR-mount	370.00
PC18/FL	. 18" multi-pattern gooseneck mic, flushmount	456.00
PC18/XLR	. 18" multi-pattern gooseneck mic, XLR-mount	370.00
PC-PLUS-12	. 12" multi-pattern with base switch and LED	442.00
PC-PLUS-18	. 18" multi-pattern with base switch and LED	442.00

EV RE90P ARCHITECTURAL PODIUM MIC The RE90P is an unobtrusive podium microphone designed to pickup sounds distant or near. Dual gooseneck points allow for quick and reliable microphone positioning. Available in 12" or 18" length.

ITEM	DESCRIPTION	PRICE
RE90P-12	12" length, cardioid	311.00
RE90P-18	18" length, cardioid	311.00
CPSM	Shock mount hardware	40.00

POLAR CHOICE SATELLITE WIRELESS PODIUM MICROPHONE The PolarChoice Satellite brings the benefits of wireless to the podium. It is a freestanding gooseneck style microphone, firmly anchored in place by its base. This low-profile foundation hides PolarChoice Satellite's most powerful feature - space for a wireless transmitter. Turn the base over to reveal the specially designed compartment for housing a required Electro-Voice body pack transmitter (sold separately). Connect the microphone to the body pack, set up the wireless channel, and place the PC Satellite anywhere an easy-to-use microphone is required. It features switchable polar patterns, mute switch, and is available in 3 length options.

ITEM	DESCRIPTION	PRICE
PC-SATELLITE-5	5" wireless condenser gooseneck mic, 50Hz-20kHz	582.00
PC-SATELLITE-12	12" wireless condenser gooseneck mic, 50Hz-20kHz	582.00
PC-SATELLITE-18	18" wireless condenser gooseneck mic, 50Hz-20kHz	582.00
BPU-2-71887X1	RE2 series UHF body pack transmitter, A-band	264.50
RE2-71883X1	RE2 series UHF receiver, A-band	484.50

### SHURE

### SHURE CENTRAVERSE™ **GOOSENECK CONDENSER MICS**

Featuring Commshield® Technology, which protects against RF interference from portable wireless devices and other intense radio signals, these mics are ideal for use in houses of worship or corporate facilities. The cardioid polar pattern is combined with a frequency response (70Hz-16kHz) tailored for speech and fast transient response which provides clarity. The rugged dual-section gooseneck allows for easy, precise placement. Both mics include an inline preamp and flange mount, and integrate with the optional CVD-B desktop base.

	DESCRIPTION  12" Centraverse™ gooseneck mic	
Accessories	Desktop base for Centraverse mics	

SHURE 515SB-G18X All metal impact resistant screen/grille provides extra ruggedness. Momentary push to talk switch makes this the standard gooseneck microphone for the fast-food industry and applications such as supermarkets, etc. Includes 18" gooseneck/ flange mount.

ITEM	DESCRIPTION	PRICE
515BSM	With cable, push-to-talk switch, low	
	impedance, for handheld use	102.82
515SB-GX	With push-to-talk switch, low	
	impedance, gooseneck not included	65.11
515SB-G18X	18" gooseneck, push-to-talk	
	switch, low impedance, with A13HD flange	79.97
515SB-G18XF	18" gooseneck, push-to-talk	
	switch, low impedance, with A12 flange	76.54
515SDX	Dual-impedance, switch selectable,	
	for handheld use, no cable	49.13
A1WS	Foam windscreen (gray)	4.92

### SHURE MX405/MX410/MX415 MINIATURE GOOSENECK MICS

These models are available in 5", 10" or 15" desktop, mounted base, wired, or wireless versions, with interchangeable capsule options. Desktop models have a programmable mute switch. CommShield<sup>TM</sup> technology ensures the MX models to be highly resistant to intense nearby radio signals. The MX890 desktop base allows you to interface these mics with compatible Shure SLX wireless systems.

ITEM	DESCRIPTION	PRICE
MX405/C	5" cardioid, bi-color indicator, with surface mount preamp	223.83
MX405/S	5" supercardioid, bi-color indicator, with surface mount preamp	229.49
MX405R/N	5", no cartridge, light ring indicator, with surface mount preamp	186.54
	5" cardioid, bi-color indicator, less preamp	
MX405LP/S	5" supercardioid, bi-color indicator, less preamp	172.97
MX405RLP/N	5", no cartridge, light ring indicator, less preamp	130.00
	10" cardioid, bi-color indicator, with surface mount preamp	
MX410/S	10" supercardioid, bi-color indicator, with surface mount preamp	229.49
MX410R/N	10", no cartridge, light ring indicator, with surface mount preamp.	186.54
MX410LP/C	10" cardioid, bi-color indicator, less preamp	167.31
MX410LP/S	10" supercardioid, bi-color status indicator, less preamp	172.97
MX410RLP/N	10", no cartridge, light ring indicator, less preamp	130.00
MX415/C	15" cardioid gooseneck, includes surface mount preamp,	
	bi-color status indicator	235.13
MX415/S	15" supercardioid gooseneck, includes surface mount preamp,	
	bi-color status indicator	240.79
	15" cardioid gooseneck, less preamp, bi-color status indicator	178.61
MX415LP/S	15" supercardioid gooseneck, less preamp,	
	bi-color status indicator	184.27
MX415R/N	15", no mic cartridge, gooseneck,	
	includes surface mount preamp, light ring	
	15", no mic cartridge, gooseneck, less preamp, light ring	
	Desktop base for MX405 and MX410 models	
	Wireless desktop base, compatible with SLX series	
	Surface mount preamp for MX405 and MX410 models	
	UHF body pack option for MX890 base only (specify band)	
SLX4	UHF receiver option for MX890 base only (specify band)	380.00

SHURE MICROFLEX GOOSENECK MICROPHONES Ideal for lectern, pulpits and conference tables. These mini-condenser gooseneck mics offer a variety of heights and mounting styles, high sensitivity and wide frequency range. The D versions include a desktop base with built in programmable switching capability. Other features include: interchangeable cardioid, supercardioid and omnidirectional mic cartridges, a rigid center tube for easy positioning and transformerless output for maximum immunity to electromagnetic hum and RF interference even over long cable runs.

ITEM	DESCRIPTION	PRICE
Models with	XLR at bottom, no cable	
MX412/C	12" cardioid	178.61
MX412/S	12" supercardioid	184.27
MX412S/S	12" supercardioid with switch and LED	202.36
MX418/C	18" cardioid	178.61
MX418/S	18" supercardioid	184.27
Models with	10ft. cable	
MX412D/C	12" cardioid, desktop base	237.40
MX412D/S	12" supercardioid, desktop base	243.05
MX412SE/C	12" cardioid, side exit cable	191.06
MX412SE/S	12" supercardioid with side exit cable	196.70
A412MWS	Locking metal windscreen	17.91
A400SM	Shock mount systems	22.61
RK100PK	In-line preamp	114.00
RK412WS	Snap-fit windscreen (4-pack)	18.53
A412B	Desktop microphone base	63.37
R183	Omni replacement cartridge	38.28
R184	Supercardioid replacement cartridge	61.85
R185	Cardioid replacement cartridge	53.01

SHURE 503BG DYNAMIC GOOSENECK MIC Developed for computer voice recognition applications, this microphone offers excellent voice fidelity while reducing background noise. Also useful in other close-talking applications such as paging and talkback. It has a low-impedance, moving coil transducer with an integral humbucking coil and attached 2-conductor shielded cable with built-in strain relief. It has a frequency response of 100Hz-7kHz with constant output voltage over the voice spectrum when used close to the sound source. It has a black finish and mounts to a gooseneck (not included), a fixed pipe or a microphone stand using a standard 5/8"-27 thread.

ITEM	DESCRIPTION	PRICE
503BG	Cardioid dynamic mic, for gooseneck mounting	85.68
G27B	27" gooseneck, black	23.28
G18	18" gooseneck, chrome	16.00







### BOGEN

COMMUNICATIONS, INC.

**BOGEN DDU250 DYNAMIC DESKTOP MICROPHONE** Compact desktop microphone with gooseneck. Excellent speech and intelligibility to cut through the noisy backgrounds of live situations and large gatherings. Features a push-to-talk switch, push-to-lock switch, hard-wired 10ft cable (5-conductor), and wire-mesh wind filter. Table stand with on/off switch.

ITEM DESCRIPTION PRICE DDU250 . Cardioid, 100Hz-12kHz..... 126.95

BOGEN MBS1000A DESKTOP PAGING MICROPHONE This dualimpedance desktop microphone uses a simple push-to-talk bar (lockable) or lift-to-talk operation (defeatable) for activating the microphone and any external equipment. Features 7ft of 4-conductor shielded cable, an impedance selector switch, and 4 molded non-skid feet.

ITEM	DESCRIPTION	PRICE
MBS1000A	Cardioid mic, dynamic, 45Hz-15kHz	. 141.31



XIBI.

### **CAD 878HL-2 OMNI PAGING MIC**

This dual impedance, omnidirectional dynamic mic offers modern styling and features in a ASTATIC COMMERCIAL rugged housing for industrial and commercial public address and paging applications. A slight rise above 200Hz gives

it a natural and highly intelligible sound. Offers a long life DPDT leaf switch with 3 types of switch activation; a momentary push bar, a locking on/off switch and lift-to-talk operation. It has 4 non-skid, shock isolation "feet" on the base and a high/low impedance selector switch on the bottom of the microphone. Supplied with 7ft of 4-conductor cable wired normally open for relay control. Can be easily rewired in the field for line-shorting switch function.

	ů .	
ITEM	DESCRIPTION	PRICE
878HL-2	.Omni paging mic with dual impedance, HiZ 40k $\Omega$ and LoZ 400 $\Omega$	73.73



ITEM	DESCRIPTION	PRICE
CSPM-1	.1-zone, PTT, paging microphone	119.95
CSPM-2	As above, 2-zone version	129.95
CSPM-4	As above, 4-zone version	139.95

### SHURE

SHURE 104C INDOOR/OUTDOOR COMMUNICATION MICROPHONE A small, pressure actuated, diaphragm-type, carbon microphone that fits comfortably in the hand. Features include a heavy-duty PTT switch, a high impact ARMO-DUR case,

and a long life, rubber-jacketed coil cord cable and frequency response of 300Hz -4kHz specifically for voice communications. Recommended for all types of outdoor/ indoor communication activity, such as mobile and fixed station use, police, fire, utility, forestry and transportation services, industrial applications, and public address.

ITEM	DESCRIPTION	PRICE
104C	Indoor/outdoor communication microphone	85.68

SHURE 514B HANDHELD MIC WITH SWITCH A low impedance, dynamic, handheld microphone designed for paging and public address systems. It offers clear, natural voice response and high intelligibility. It connects to microphone inputs rated at 19-300ohms. It can be used in applications that require long cable lengths, or where severe hum conditions are present. The 514B microphone is provided with a 4-conductor (2 shielded) coiled cable and a "Million-Cycle" leaf-type switch. It fits comfortably in the hand and is not affected by heat or humidity. The exclusive ARMO-DUR case resists mechanical shocks and vibration, and is impervious to oil,


ITEM	DESCRIPTION	PRICE
514B	Handheld microphone with switch	68.54

fumes, salt spray, ultraviolet radiation, and corrosion. It has a frequency response of

### SHURE

### SHURE 577B HANDHELD DYNAMIC MICROPHONE

Designed for communications and paging applications that require highly intelligible, low noise output. The 577B represents a significant improvement over most microphones with anti-noise features. Shaped frequency response, directionality, and distant sound discrimination contribute to total noise reduction. A mounting bracket is supplied to provide convenient hang-up when the microphone is not in use. It has a frequency response of 100Hz-5kHz, and an output level of -66dBV/Pa (0.5mV). Other features include a rugged ARMO-DUR case, leaf-



### SHURE 596LB OMNI HANDHELD DYNAMIC PUSH-TALK MIC

A compact, handheld low-impedance communications mic with a 200Hz-5kHz frequency response. An economical mic compatible with many popular paging amplifier inputs and its tailored frequency response provides clear, intelligible operation. Fits comfortably in the palm of the hand and has a long-life push-to-talk switch, and a durable coiled cable (5ft) for years of

reliable performan	ce.
ITEM 596LB	<b>DESCRIPTION</b> . Omnidirectional handheld push-talk mic

SHURE 450-II PAGING DISPATCH MIC Designed for high-speed intelligibility and reliable paging and dispatching. Features an omnidirectional pattern, low to high impedance switch, press to talk switch, sturdy high impact base, and an external relay or control circuit. Its frequency response of 200Hz-5kHz is tailored for optimum speech intelligibility. Includes case and 7ft cable.

ITEM	DESCRIPTION	PRICE
450-II	Desktop paging microphone, omnidirectional	. 137.09

SHURE 522 DESKTOP MICROPHONE Designed for radio communications, paging, and dispatching systems, this dynamic base station mic features a cardioid pattern that suppresses background noise. It also reduces feedback in public address paging applications, includes a press to talk switch, and external relay or control unit. Dual impedance (19-300 ohms or High). Frequency response 60Hz-11kHz. Sturdy high impact base. Includes case and 7' cable.

ITEM	DESCRIPTION	PRICE
522	Desktop paging microphone, cardioid	137.09

SHURE 527 SERIES HANDHELD MICROPHONES Extremely reliable dynamic microphones well-suited for ham radio, mobile FM transmission, and top-quality paging systems. Omnidirectional pattern, neoprene jacketed cord, million-cycle leaf switch.

neoprene jaci	icted cord, mimon cycle icai switch.	
ITEM	DESCRIPTION	PRICE
527B	Low impedance 300Hz-5kHz response	85.68
527C	Built in amplifier — up to 100ft	
	unshielded cable, 300Hz-5kHz response	85.68



### TOA PM660U DESKTOP PA/PAGING MICROPHONE

Ideal for use in restaurants, warehouses, transportation terminals, dispatch centers, or entertainment facilities. It features a cardioid polar pattern,  $600\Omega$  balanced output, 8.2', four-conductor cable with stripped wire ends. Conductors are shielded and are dedicated for the microphone signal. The other two unshielded conductors connect to an auxiliary, normally-open switch contact, used to activate external

muting, priority or relay control circuits. The auxiliary switch contact is closed by using the push-to-talk bar, which also turns on the microphone by opening a second set of contacts that normally short the mic element. A locking lever is provided to keep the push-to-talk bar in the "on" position when the microphone must be kept open for an extended period.

ITEM	DESCRIPTION	PRICE
PM660U		
	push-to-talk bar, 100Hz-10kHz	CALL

















PRICE




































100Hz-6kHz and an output level of -36.5dB.

















































A DESIGNS REDDI TUBE DIRECT BOX Ideal for basses, guitars, synths, and electronic instruments that require a direct box for

recording. Features include: vacuum tube design, level control, ground lift, Neutrik Combo input connectors, XLR outputs, zero feedback loop, custom wound output transformers, a 6NI-P tube, and a 1/4" through jack. It

has a frequency res	ponse of 10Hz-60kHz.	
ITEM	DESCRIPTION	PRICE
REDDI	Tube direct box	. 745.00



ART PDB4 FOUR-CHANNEL PASSIVE DIRECT BOX With four fully transformerisolated direct boxes in a 1RU chassis, the PDB4 has switchable input attenuation and ground lift on each channel. Input jacks are unbalanced 1/4" TS and output jacks are balanced XLR-M.

ITEM	DESCRIPTION	PRICE
PDB4	4-channel passive direct box	79.00

X-DIRECT

AVDIBOX

### AR' [cessories"

ART DI BOXES Convert high-impedance inputs to 600ohm balanced outputs. All models feature 1/4" TRS/XLR combo inputs (AVDIBOX has 1/4" TRS and RCA inputs), XLR outputs, switchable ground lift, and aluminum case. The XDirect<sup>TM</sup> models are active, can be phantom or 9V battery powered, and include switchable input attenuation (-30dB). The ZDirect™ models have a passive transformer design, switchable input attenuation (-20dB, -40dB), low pass filter and phase invert. The 2-channel dADB is same as the XSeries, with discrete controls per channel. The dualRDB is a 2-channel reamping box with variable level controls for connecting line level signals to XLR or 1/4" instrument level inputs. The AV Direct is used to connect stereo MP3 players, DVD players, consumer stereo or video equipment to a single mic level XLR input

equipment to a sin	510 IIIIC ICVCI ALIN IIIPUL.	
ITEM		PRICE
X-DIRECT	. Single-channel active direct box	40.00
Z-DIRECT	Single-channel passive direct box	25.00
DUAL-X-DIRECT	. 2-channel active direct box	55.00
DUAL-Z-DIRECT	. 2-channel passive direct box	40.00
DADB	. 2-channel active direct box	65.00
DUAL-RDB	. 2-channel reamping box	79.00
AVDIROX	Direct hox for consumer media players	55.00

### AVALON (1) DESIGN

### **AVALON DESIGN U5** MONO INSTRUMENT

DI The U5 includes a variable gain Class 'A' preamplifier, six passive EQ curves, a high-cut switch, headphone monitor amp and uses twin DC coupled Class "A" output amplifi-



ers for direct to tape/disc recording. Switched 3dB steps, a maximum gain of +30dB, 3,000,000Ω unbalanced input, +24dBu unbalanced-400W speaker input, 2 x XLR outputs-+30dBu DC coupled, balanced  $600\Omega$ .

ITEM	DESCRIPTION	PRICE
U5	. Mono-instrument DI	620.00



### behringer

**BEHRINGER DI BOXES** The DI100 allows direct connection of amplifier



shut-off when phantom power is connected. The DI20 converts 2 unbalanced 1/4" inputs into 2 balanced XLR outputs. The DI400P/600P are single-channel transformercoupled passive DI boxes with switchable ground lift.

ITEM	DESCRIPTION	PRICE
DI100-ULTRA-DI	Direct box	39.99
D120	2-channel direct box/splitter, powered by	
	9V battery or 48V phantom power	24.99
DI400P-ULTRA-DI	Passive DI with ground lift switch	19.99
DI600P-ULTRA-DI	Passive DI with switchable 30dB pad and 7.5kHz filter	29.99



BEHRINGER DI4000/DI800 ULTRA-DI PRO DIRECT BOXES A choice of either four or eight professional DI channels in one rack space. An XLR and a 1/4" TRS input, and a balanced XLR and 1/4" TRS output per channel. Up to 40dB of switchable attenuation and up to 20dB of gain. Allows direct connection to speaker outputs at up to 3000W. Includes phase reverse and ground lift switches.

ITEM	DESCRIPTION	PRICE
DI4000-ULTRA-DI-PRO.	4 DI channels in	1RU99.99
DI800-ULTRA-DI	8 DI channels in	1RU119.99



BSS AR133 An active direct box that has switchable input attenuation capable of handling a wide-range of output levels from the output of guitar pickups



and normal line level signals, to the output of amplifiers. Sounds outstanding on acoustic guitar and bass guitar pickups, suitable whenever it is critical to match levels and impedances, sources needing isolation, or with long cable runs.

ITEM	DESCRIPTION	PRICE
AR133	Active direct box	161.97



Connect guitar pickups, contact mics or electric instruments to a recording or PA console without loss of level or increased distortion. Has recessed connectors and switches, battery or phantom power, internal pad for speaker bridging, true ground isolation, RF filtered. Both models have a rugged extra thick DT85S





aluminum housing material and are virtually indestructible and static free. The DT10 adds lights to monitor battery or phantom power performance.

ITEM	DESCRIPTION	PRICE
DT85	FET direct box, 20Hz-20kHz, ground lift switch,	
	pickup/speaker switch	158.70
DT85S	As above, with 2 channels	262.67
DT10	DI with battery and phantom LED indicators,	
	10Hz-50kHz, -15dB/-30dB pad, ground lift	198.83
DT10S	As above, with 2 channels	365.75







### **DBX DB12 AND DB10 DIRECT BOXES**

Utilizes custom metal-shielded audio HARMAN transformers, high-quality Neutrik connectors, and low-noise circuitry to preserve the sonic integrity and true characteristics of the signal source. Both boxes include a pad switch that accommodates instrument, line





### KLARK-TEKNIK DN100 & DN200 ACTIVE **DIRECT BOXES** Both feature a high-impedance,

transformer-isolated inputs on XLR connectors and (2) twin 1/4" linked input connectors (Two 1/4" Link Thru, Left and Right on the DN200), and a low-impedance active balanced XLR output. Both utilize 24V to 48V phantom power. The DN100 has a switchable 30dB input pad & switchable 15dB output attenuation while the DN200 has a global 20dB input



pad and ground lift switches. The DN200 also has (2) RCA phono inputs, a sum switch that optionally routes both inputs to both outputs and a split switch that optionally routes left input to both outputs.

ITEM	DESCRIPTION	PRICE
DN100	Active direct box	79.00
DN200	Active stereo direct box	139.00







box and re-amping tool featuring a high-quality buffered direct box input (phantom power required via XLR in) or passive direct box inputs; both with ground lift and phase reverse capabilities. Compare the direct and re-amped signals with a single button. It is expandable for daisy chaining to other Red Eyes to feed multiple amps or pedals. (2) 1/4" instrument inputs (1 active, 1 passive), XLR in, XLR out and (1) 1/4" re-amp output.

ITEM	DESCRIPTION	PRICE
RED-EYE-3D	Passive direct box/re-amp box with phantom power	290.00

### ® PRO CO

PRO CO CB-1 DIRECT BOX Affordable and versatile. Features 1/4" Hi-Z input and loop-through output, a Lo-Z output and a ground-lift switch. Packaged in a durable 16-gauge steel box.



ITEM DESCRIPTION PRICE

### PRO CO INTERFACE BOXES DB-1 DIRECT BOX

1/4" phone jack input, 1/4" phone jack parallel output. SPKR/ INST switch (-20dB pad). FILTER/FLAT switch (six dB/octave low pass), XLRM isolated output with GND/LIFT switch.



ITEM DESCRIPTION PRICE Passive direct box 90 63

PRO CO DB-2 STEREO DIRECT BOX This low-noise direct box has a high dynamic range and features two 1/4" inputs with parallel 1/4" outputs, a -30dB pad for each input, and 2 XLRM balanced outputs with a ground lift switch. Suitable for any high impedance instrument, it uses two DBT-1 transformers and MU metal cans for optimal RF/EMF rejection. When using a single input, this direct box will act as a transformerisolated split that provides 2 balanced outputs from a single in.



ITEM	DESCRIPTION	PRICE
DB-2	. Stereo direct box	165.06

ROLLS DB25 MATCHBOX The DB25 is a transformer-balanced, passive direct box. It features a ground lift switch for hum elimination, and an attenuator switch for padding the



input signal by 20dB, or 40dB. Padding the input signal provides a way to connect the DB25 to a line-level signal, even a speaker level signal and connecting it to a balanced line or mic input on a mixer. The two 1/4" inputs are paralleled for guitarists to "passthrough" their input signal to a tuner, pre amp, etc.

TEM	DESCRIPTION	PRICE
)B25-B	Matchbox, polarity + pin 2 hot (XLR),	
	fregency response 50Hz-15kHz ±3dB	. 25.20

**ROLLS DB325 ACTIVE INSTRUMENT PREAMP/DIRECT** BOX The DB325 is a Class-A FET active direct box that is designed to take input signals from instruments such as guitars, bass or keyboards and run them in to a computer or tablet via the 1/8" stereo output or to any analog input via the 1/4" mono ( $1000\Omega$ ) or balanced XLR outputs  $(600\Omega)$ . The direct box can operate on a 9V battery or with

ITEM DESCRIPTION DB325 Active instrument preamp/direct box, 20Hz-20kHz



the included AC adapter.

### SM PRO AUDIO TRANZ WIRELESS STEREO DI

signal wherever it's needed.



ITEM	DESCRIPTION	PRICE
SMP-TRZ-R	Receiver, wireless DI	139.99
SMP-TRZ-T	Transmitter, wireless DI	139.99

### Switchcraft







SWITCHCRAFT DIRECT BOXES These boxes convert the output of high impedance line level audio devices and musical instruments to low impedance, balanced and isolated mic level signals that can be connected to audio consoles, mic pres, effects processors, and other equipment with 3-pin XLR inputs. The SC700 and SC700CT feature RCA inputs and are designed for use with sources like MP3 players and turntables. The SC800 and SC800CT are designed for use with instruments. The SC900 and SC900CT are also for instrument use and feature Phantom Lift technology which allows the ground lift function to be operated remotely using +48V phantom power from the console. All models feature throughputs, high quality I/O jacks, -20dB pad, and Pin 1 ground lift. Built by hand in the USA.

DESCRIPTION	PRICE
A/V direct box with Jensen transformer	179.99
A/V direct box with custom transformer	99.99
Instrument DI box with Jensen transformer	179.99
Instrument DI box with custom transformer	84.99
Instrument DI box, Jensen transformer, phantom lift	199.99
	USSCRIPTION AVV direct box with Jensen transformer. AVV direct box with custom transformer. Instrument DI box with Jensen transformer. Instrument DI box with custom transformer. Instrument DI box, Jensen transformer, phantom lift Instrument DI box, with custom transformer, phantom lift.

































































































RADIAL ENGINEERING DIRECT BOXES No-compromise DIs for both studio and live applications. They use ultra-high quality/low distortion components for transparency and a clear signal with amazing frequency response. Available in a variety of configurations. All RADIAL ENGINEERING DIRECT BOXES No-compromise DIs for both studio and live applications. They use ultra-high quality/low boxes feature heavy-duty 14-gauge steel boxes, XLR or XLR-1/4" TRS and unbalanced connectors and are covered by a 3-year warranty.

ITEM	DESCRIPTION	PRICE
J33	Combo phono preamp and direct box	199.99
J48-MK2	Transformerless DI, 15dB pad, 48V phantom power,	
	ground lift, mix-merge, 10Hz-40kHz	199.99
JDX	Guitar amp DI, ground lift, polarity switch	199.99
JDI-MK3	Passive DI, ground lift, Jensen transformer, 10Hz-80kHz	199.99
JDI-DUPLEX	Stereo version of the JDI-MK3, US-made transformer	349.99
JD6	6-channel rackmount version of the JDI-MK3,	
	with Eclipse transformer	899.99
JD7	Guitar level distribution to feed up to 7 amps simultaneously,	
	with push button selection, Jensen transformer, balanced I/O	. 1099.99
J-RAK-8	Chassis (2RU) for up to 8 DIs, drivers or splitters	139.99
JPC	2-channel active/transformer DI with 1/8", 1/4" and RCA inputs	
	to interface with computers/consumer audio gear	199.99
PRODI	Mono transformer-coupled passive DI	99.99
PROD2	Stereo transformer-coupled passive DI	149.99
	Active DI for Orchestral Piezo Pickups	

ITEM	DESCRIPTION	PRICE
TWIN-ISO	2-channel line-level isolation box with Jensen transformers,	
	15dB pad and separate ground lifts	259.99
JS2	Mic splitter, 1-in/3-out	
	As JS2, with input, thru and 2 transformer-isolated outputs	
	Active direct box, compact design	
	Single-channel AV DI box, 1/4", 1/8", RCA, XLR inputs	
	Passive stereo multimedia DI with RCA, 3.5mm, XLR, 1/4"	
PROD8	Passive 8-channel DI, Radial trasformers, 1RU	799.99
	Active acoustic DI, compact	
	Passive DI for bass and keys	
	Active DI for orchestral piezo pickups, compact	
STAGEBUG-SB5-		
	Passive stereo DI for laptops, 1/8" TRS connector	99.99
STAGE-DIRECT	Active DI with mute switch and tuner out	
USB-PRO	Digital DI, USB	229.99
	DD040	



cert stages where wireless guitar systems, acoustics, effects and multiple amplifiers are used simultaneously. Its 4 inputs employ Radial's unique Class 'A' buffering with 100% discrete components throughout. Inputs A and B have Drag™ Control load correction that lets you dial in the perfect load on the pickup for the most natural tone. Inputs B and C are equipped with a trim level that lets you quickly balance signal levels when using wireless systems or active guitars. It has 2 effects loops, one is a 'local' loop for a drawer full of pedals or multi-effects processors. The second loop is a long-haul balanced interface that provides a noise-free RADIAL ENGINEERING FIREFLYTM connection for distances up to 328' when combined with a stand-alone Radial SGI-44 interface. A built-in direct box functions as an output to the PA or as a dry feed for TUBE DI This DI has a 100% discrete recording. Up to 6 amplifiers may be used at once. Outputs 1 and 2 are single while Class 'A' front end with no circuit-staoutputs 3 and 4 are doubled-up to drive multiple stacks. All outputs are transformerbilizing pagative feedback for a more open cound. It also has a Drag Control load isolated and have 180° polarity reverse switches. Amp selection can be done via the

> PRICE 599.99

bilizing negative recuback for a more open sound. It also has a brag control load
correction which allows adjustment for any magnetic pickup. With the Drag Control
bypassed Firefly jumps to 4 megohms, great for use with piezo pickups. A 12AX7 tube
provides for extra warmth and detail.
provides for extra warmth and detail.

FIREFLY	Tube direct box		Į.
RADIAL	ENGINEERING J+4™	BALANCED	
SIGNAL	<b>DRIVER</b> A stereo interface	designed to	

accept unbalanced low output level devices such as instruments, computers or CD players and boost the signal to a balanced +4dB level for easy manipulation in professional situations. It is built of 100% discrete components. The combination of active signal buffering with transformer isolation eliminates noise, delivering better than 95dB signal-to-noise ratio. Controls are minimal, consisting of a stereo

level control, hi- pass (low cut) filter and ground lift. Inputs consist of a stacked set of 1/4" jacks for DJ mixers or keyboards, RCA jacks for CD players and a 1/8" TRS jack for MP3 players. Outputs are a pair of 3-pin XLR connectors.

ITEM	DESCRIPTION		PRICE
J+4	 . Balanced signal	driver	 229.99

Follow Us!

front panel or by u	sing the optional JR5 remote control.		
ITEM	DESCRIPTION	PR	ICE
JX44	Guitar signal manager	1499	.99
JR5	Remote control for the JX44	. 249	.99
SGI-44	Stand-alone interface, for JX44	. 339	.99

RADIAL ENGINEERING JDVTM ACTIVE DI This DI is able to handle any type of instrument and reproduces sound with accuracy and little-to-no coloration. It has 100% discrete Class 'A' circuitry which eliminates zero-cross distortion. Rather than using phase-cancelling negative feedback loops to stabilize the circuit, the JDV employs a tube-like configuration with proprietary stabilizers. A Drag Control enables you to correct the load of the instrument as if connected directly to an ampli-

fier. For piezo instruments, the input can be switched to 4megohms to eliminate squawk. The 30V internal rails ensure digital samplers and active basses are handled with ease. It also features separate outputs for the PA, monitors, amps and tuner.

ITEM	DESCRIPTION	PRICE
JDV	. Active direct box	399.99

### ProAV2 MultiMedia DI



### JCR Studio Reamper



The original Reamp™ lets you play a recorded track back through amps or effects until they sound just right.

### PZ-DI Variable Load DI



lezo optimized D) for acoustic & orchestral instruments produces wide frequency response for more natural tone.

### **ProMS2 Mic Splitter**



High performance transformer coupled passive mic splitter with aux output to feed 3 audio systems at once!

### H-Amp Headphone Driver



Converts any speaker level source to a mono headphone output for personal monitoring.

### J+4-10 to +4dB Line Driver



Stereo preamp lifts low output unbalanced signals to 4dB line level for pro audio system connectivity.

### USB-Pro Stereo USB DI



High performance 24bit/96kHz converters with transformer isolated outputs and built-in neadphone amp.

### StageBug SB-5 Stereo DI

Super compact passive direct box Built-in cable with storage cleat for easy interface with laptops.

# Thank You....

# ...for making Radial the number one DI in pro touring!

AC/DC Adele Adrian Belew Aerosmith Alice Cooper Alicia Keys Alison Krauss Alter Bridge America American Idol Anberlin Ani DiFranco Animal Collective Annihilator Antoine Dufour Audioslave Avenged Sevenfold Avril Lavigne Backstreet Boys The Band Barbra Streisand Bare Naked Ladies Barry Manilow Beach Boys Beastie Boys Beck Béla Fleck Ben Harper Bette Midler Billy Idol Billy Joel Billy Ray Cyrus Billy Sheehan Bjork The Black Crowes Black Eyed Peas The Black Keys Blue Man Group Bob Dylan Bon Jovi Bonnie Raitt Bootsy Collins Boston Pops **Brad Paisley** Bruce Hornsby Bruce Springsteen Bruno Marz Bryan Adams Buddy Guy Butch Walker Cannibal Corpse Carly Rae Jepson Casting Crowns CeCe Winans

Chick Corea Chayanne Chris Comell The Chieftains Chuck Leavell Chuck Rainey Cyndi Lauper Cirque Du Soleil Clint Black Coldplay Colin James The Corrs Creed Crosby, Stills, Nash Crowded House Damien Rice Dandy Warhols Daniel Lanois Daryl Stuermer Dave LaRue Dave Matthews Davy Knowles The Decemberists Def Leppard Derek Trucks Destiny's Child Devin Townsend Diana Krall Dimmu Borgir Disney Dixie Chicks Dolly Parton Donna Summer Donny Osmond Doobie Brothers The Doves Dream Theater Duke Robillard Duran Duran Dwight Yoakam The Eagles Econoline Crush Edgar Winter Elton John Eminem Emmylou Harris Enrique Iglesias Eric Clapton Eric Johnson Erykah Badu

Flogging Molly Foo Fighters Foreigner Frank Gambale Franz Ferdinand Garbage Gavin DeGraw Genesis Gino Vanelli Godsmack Gomez Goo Goo Dolls Good Charlotte Gov't Mule Grand Ole Opry Great Big Sea Gregg Allman The Guess Who Guns & Roses Gwen Stefani Hall & Oates Herbie Hancock Him Hoobastank Hot Hot Heat House of Blues Hunter Hayes INXS Iron Maiden James Taylor Jamie Cullum Jamiroquai Janet Jackson Jars of Clay Jay Leno Show Jeff Beck Jennifer Lopez Jerry Douglas Jet Jethro Tull Jewel Jimmy Buffett Joe Jackson Joe Nichols Joe Satriani

Joe Walsh Joey DeFrancesco Lou Reed John Frusciante John Hiatt John Jorgensen John Mayer John Patitucci John Petrucci John Rzeznik Johnny A Johnny Hallyday Joni Mitchell Josh Groban Josh Turner Journey Juanes Justin Bieber Justin Timberlake Kaiser Chiefs Kanye West Kasabian kd Lang Koh' Mo Keith Urban Kellie Pickler Kenny Chesney Kenny Loggins Kerry King The Killers Kings of Leon Kirk Hammett Kitaro Klaxons Kom KT Tunstall Lady Antebellum Lady Gaga Lamb of God LeAnn Rimes Lee App Womack Letterman Show Lenny Kravitz Leo Kottke Leonard Cohen

Lucinda Williams Macy Gray Manhattan Transfer Manowar Marcus Miller Mariah Carey Marillion Marilyn Manson Mark Egan Mark Knopfler Mark Tremonti Maroon 5 Marty Stuart Matchbox 20 Meatloaf Megadeth Melissa Etheridge Metallica Michael Buble Mötley Crüe Motorhead Mumford & Sons Muse My Morning Jacket Nathan East The National Neil Young Nelly Furtado The Neville Brothers Nickelback Nine Inch Nails Oak Ridge Boys The Offspring One Direction Pat Metheny Paul McCartney Paul Simon Peter Gabriel Pink Floyd

The Police Porcupine Tree Prince The Prodigy Queensryche Radiohead Randy Bachman Randy Travis Rascal Flatts Ravi Shankar Razorlight R H Chili Peppers Rick Wakeman Rickie Lee Jones Ricky Skaggs Rihanna Ringo Starr Robert Randolph Rod Stewart Roger Waters Rolling Stones Rush Ryan Adams Sam Roberts Sammy Hagar Santana Sarah McLachlan Seal Sevendust Shakira Shania Twain Sheryl Crow Shinedown Sigur Rós Skunk Anansie Slayer Slipknot Snow Patrol Sonic Youth

Steely Dan Steve Earle Steve Lukather Steve Miller Steve Morse Steve Stevens Steve Vai Steve Winwood The Stills Sting Stone Temple Pilots Styx Sum 41 System of a Down Taylor Swift Ted Nugent Three Doors Down **Timbaland** Tom Waits Tommy Emmanuel Tommy Lee Tony Levin Toots & The Maytals Tragically Hip Travis Tritt U2 Usher Van Halen Vanessa Williams Victor Wooten Vince Gill Weezer White Stripes The Who Will Lee Will I Am Wyclef Jean Xavier Rudd Yellowjackets Zac Brown





Soundgarden

...true to the music

FULL COMPASS

PRO AUDIO VIDEO LIGHTING MUSICAL INSTRUMENTS

800-356-5844 fullcompass.com

Fleetwood Mac The above is a partial list of artists and sound companies that use or have used Radiol pookusts. No endocement is offered or implied by being listed here. Sorry if we've raissed you – let us know and we'll include you out time

The Flecktones

Evanescence

Extreme

Faith Hill

Celine Dion

Cheap Trick















































# whirlwind

WHIRLWIND DI2 PASSIVE DUAL DIRECT BOX This hardwired version of the Director2 DI makes it easy to keep your stage clean and eliminates the need for piles of mic cables. Features include 1/4" parallel in/out jacks, ground lift, Snakeskin fanout, and color coding. Comes in standard lengths of 15', 25', and 50', and uses TRHLM transformer. Replace the XX in the part number with the color of your choice: BK - black; WH - white; BL - blue; YL - yellow; and VT - violet (YL, VT, and BL shown at right).

vi violet (12, vi, and DE	onomi di rigite).	
ITEM	DESCRIPTION	PRICE
D12-050-XX	.Passive, hardwired, dual-channel direct box, 50ft length	218.81
DI2-025-XX	.As above, 25ft length	178.19
DI2-015-XX	.As above, 15ft length	167.19

WHIRLWIND DIRECT-JT A top-of-the-line passive DI featuring the Jensen JT-DB-EPC:200k:1.5k transformer for wide frequency response and superior noise rejection. The 1/4" input jacks can be used as "INPUT/THRU" or they may be combined with the "COMBINE" pushbutton to safely sum stereo feeds to a single channel. The "FILTER/OFF" button engages a filter that emulates the frequency response of a microphone placed in front of a 12" speaker. The "PAD" button engages 15dB pad for reducing hot input levels. Also includes reverse phase and ground lift buttons. THD @ 1kHz: less than 0.001%

ITEM	DESCRIPTION
DIDECT_IT	Passive direct how in aluminum housing



SERIES DIRECT BOXES A premium direct box that

converts a line, instrument or speaker level signal to a low impedance mic level. The input is Hi-Z bridging. Features include a 30dB pad



	TRHL-M transformer.	
ITEM	DESCRIPTION	PRICE
DIRECTOR	Passive, TRHL-M transformer, direct box	65.34
DIRECTOR+	. Passive, Dlmax transformer, direct box	117.50
MULTIDIRECTOR	Passive, 4 Director DI's in 1RU package	259.59

WHIRLWIND HOT BOX This top-of-the-line DI is an active direct box that operates from battery or phantom power. The Hot Box provides super-clean front-end circuitry that delivers the widest frequency response that you'll find in any direct box. There is a ground-lift switch, useful for eliminating ground-loop hum problems even with phantom power, and a switch that allows you to

with phantom j	power, and a switch that allows you to	
switch between	instrument, line, or amplifier inputs.	•
ITEM	DESCRIPTION	PRICE
HOTBOX	Active direct box	128.61
HOTBOX-QUAD	1RU 4-channel active DI	476.60

WHIRLWIND IMP2/IMP JT **DIRECT BOXES** An economical Direct Box that converts a line or instrument level unbalanced signal to a low impedance balanced signal. The input is Hi-Z bridging and the

output is provided with a ground lift switch. IMP JT features a Jensen transformer, IMP2 utilizes the TRHL transformer.

ITEM	DESCRIPTION	PRICE
IMP2	Passive, TRHL transformer, direct box	43.55
IMPJT	Passive, Jensen transformer, direct box	145.85

### WHIRLWIND PODMIX AND PODDI DIRECT

**BOXES** The podMIX is a passive mixer and direct box that combines a mic source with a stereo

PRICE

line level audio source for connection to a single channel input of a sound system. It accepts stereo line inputs via 1/8" stereo jack or dual RCA phone jacks and sums them with a mic signal into a single balanced XLR mono output. Works with dynamic and condenser mics and passes phantom power from the output to the mic input. The podDI accepts stereo inputs and sums them into a single balanced XLR mono output. A variable attenuator on each input allows level matching between left and right inputs, making the podDI a passive mixer in split track audio applications. Signal input is via 1/8" stereo TRS jack or color coded RCA phono jacks, and features a balanced male XLR output. Also be used as a single input DI box. Both feature a ground lift switch for eliminating hum and buzz.

PODMIX

484.22

ITEM	DESCRIPTION	PRICE
PODMIX	Mic/Line passive mixer and direct box	127.07
	Single input/output summing direct box	

# PCDIQ

WHIRLWIND PCDI AND PCDIQ DIRECT BOXES The PCDI is designed to interface your unbalanced stereo line sources with professional balanced low impedance equipment. Features 2 separate DI's, Inputs; 1-3.5mm (1/8") mini TRS stereo jack or 2 sets of color coded RCA in/thru. Output; color coded XLRs. Also features a mono/stereo switch, ground lift and a 20dB pad. The PCDIQ also features a stereo mix buss to combine any combination of channels into a stereo mic level, balanced output. Perfect for interfacing with the

outputs of C	D players, computer sou	nd cards, tape de	cks, etc.
ITEM	DESCRIPTION		PRICE
PCDI	Dual-direct box		134 93

WHIRLWIND EDB1 An economy direct box offering rugged construction while maintaining exceptional sound

PCDIQ ...... Quad-direct box......

Input impedance: $20k\Omega$ ; output impedance: $150\Omega$ .	
quality. 1/4" in and through jacks, pad switch, and ground l	ш.







# whirlwind

If it connects, adapts or solves your problem, chances are it's Whirlwind.



With over 35 years of rock solid, touring grade, audio interface, Whirlwind is proud to partner with Full Compass. It's just another way we can keep you connected, and serve you better.



### SHOWN ABOVE

- Mini 12 and Mini 6 dropsnakes
- Imp 2 direct box
- Director direct box
- Line Balancer Splitter
- pcDI direct box
- EDB1 direct box
- podDI direct box
- Split 6 splitter
- Splitter 1x2 and 1x3
- Little Imp transformer
- Imp Pads

















































### whirlwind

WHIRLWIND SPLIT 6 Use this handy box when you need to split a line level signal up to 6 times. Features 1 female XLR input wired to 6 male XLR outputs. Note: It is not recommended that the SPLIT 6 be used to split a microphone level signal to more than two outputs.

ITEM DESCRIPTION SPLIT6... ..Line-level signal splitter...

WHIRLWIND IMP COMBINER 2-TO-1 MIC **COMBINER** This versatile box combines 2 microphone signals into 1 signal, and is built with the premium TRSP-2 transformer for optimum durability. Features a phase reverse switch which flips the polarity of Input #2.

ITEM DESCRIPTION PRICE IMP-COMBINER... ... Mic combiner



Frager) are control of	17	
ITEM	DESCRIPTION	PRICE
ISO-XL	Inline isolation transformer	43.83
ISOPOD	Inline 1/8" stereo - XLR mono transformer	52.50



### RADIAL ENGINEERING MIC ACCESSORIES

INADIAL LITUIT	EERING MIC ACCECCONIEC	
ITEM	DESCRIPTION	PRICE
JR-1L	Compact latching footswitch remote with XLR and 1/4"	89.99
JR-1M	Compact momentary footswitch remote	
	with XLR and 1/4"	89.99
SB-48	StageBug power bar 48V phantom power supply	129.99
JS2	Jensen transformer mic splitter with XLR input, thru,	
	and isolated monitor output +4th output with ground lift	219.99
8CX	Mic splitter, 8 channels on frame mount for install,	
	radial transformers	699.99
HOTSHOTABI	Dual-to-single XLR source selector	99.99
HOTSHOTABO	Single-to-dual XLR source selector	99.99
DM1-HOTSHOT	Passive mic mute and signal redirector,	
	momentary switch with ground lift	99.99
CHERRY-PICKER	Passive mic preamp selector with phantom power	349.99
GOLD-DIGGER	4-channel mic selector with trim adjust on each channel	349.99

**ROLLS PB224 PHANTOM POWER**  $\textcolor{red}{\textbf{SUPPLY}} \hspace{0.1cm} \textbf{Perfect for any condenser}$ 

microphone, the PB224 powers even the high-current draw microphones. The unit features a rock solid 48 volts of clean phantom power. It can operate

from two internal 9	V batteries or from the Rolls PS27S AC adapter.	
ITEM	DESCRIPTION	PRICE
PB224	2-channel phantom power supply	81.00
PS27S	AC adapter	18.36





### **VU VU-ATTEN ADJUSTABLE IN-LINE ATTENUATOR**

Enables balanced low-impedance microphones to connect to low- to mid-impedance inputs in high-SPL applications. Adjusts via a -10dB, -20dB or -30dB switch to match the mic output to the input of mixers, portable recording devices, and more. Prevents input overloading due to high-level signals and is compatible with phantom power.

•			0	•	•	•
ITEM	D	ESCRIPTION				PRICE
VU-ATTEN	A	djustable in-l	ine attenu	ator, XLRF to XLRM.		22.38

### SHURE



### SHURE PROBLEM SOLVERS

ITEM	DESCRIPTION	PRICE
A15AS	.Switchable mic attenuator, (15, 20, 25dB), passes	
	phantom, requires use of balanced signals	45.60
A15BT	.Bridging transformer, in-line XLRF to XLRM,	
	33kΩ primary, $600\Omega$ or $7.5$ kΩ secondary	51.30
A15HP	.High pass filter, in-line XLRF to XLRM, roll off of 12dB	
	below 100Hz, requires use of balanced signals	54.15
A15LA	Line adapter, converts balanced line level signals to mic level	
	(50dB attenuation), in-line XLRF to XLRM configuration	41.33
A15PRS	.Switchable phase reverser, requires balanced signals, XLRF to XLRM	71.25
A15RF	.RF Filter, XLR in/out, passes phantom power	49.88
A15TG	.Tone generator, 700Hz mic level signal, XLRM output	143.90
A85F	.Transformer, Lo-Z, XLRF to Hi-Z 1/4" phone plug, may be used in reverse	18.75
A95U	.Transformer, Lo-Z, XLRM to Hi-Z Amphenol MC1M	
	with 1/4" jack adapter, may be used in reverse	48.72
A95UF	.As A95U, with XLRF low impedance connector	
	.Transformer, Lo-Z XLRF to medium impedance mini plug	
	on attached 2' cable	62.64
A120S	.In-line on/off switch (no connectors, requires soldering)	

### Switchcraft

SWITCHCRAFT RMAS1 SINGLE CHANNEL MIC SPLITTER Passive 3-way transformer isolated mic splitter with XLRF input, XLRM 1-direct and 2-isolated, with ground lifts, -40dB pad. The direct out passes phantom power.





### **SWITCHCRAFT AUDIOSTIX**

These problem-solving adapter boxes can be used in a variety of situations. The 318 converts 1/8" TRS jack to balanced mono 3-pin male XLR mic-level output

with volume control and ground lift swtich. The 319 converts 1/8" TRS jack to balanced mono 3-contact terminal block line-level output with

pad and lift switches. The 366R is an AES/EBU adapter which converts female XLR 110 $\Omega$  to BNC 75 $\Omega$ . The 367R is an AES/EBU adapter which converts BNC 75 $\Omega$  to male XLR  $110\Omega$ .

ITEM	DESCRIPTION	PRICE
318	Adapter, 1/8" TRS to 3-pin XLRM	64.92
	Adapter, 1/8" TRS to terminal block	
366R	Adapter, AES/EBU, XLRF to BNC	35.02
367R	Adapter, AES/EBU, BNC to XLRM	35.02







S8 8-CHANNEL MIC SPLITTERS Splits 8 mic signals into 16 (8 direct XLR outs, 8 transformer-balanced XLR outs). Direct outputs pass phantom power from the main mixer to the mics. Includes a ground lift switch on each isolated output and an attenuator pad switch on each input.

ITEM DESCRIPTION PRICE 2-way 8-channel mic splitter, 16 XLR outs... S8-AR1



ART S8-3-WAY 8-CHANNEL MIC SPLITTER An 8-channel 3-way mic splitter suitable for recording, broadcast, or live sound scenarios where microphone and XLR balanced line level input signals need to go to multiple locations. Each channel has 1 XLR input; 1 direct XLR output with 2 additional transformer isolated XLR outputs for a total of 3 balanced outputs from each mic input signal.

ITEM	DESCRIPTION	PRICE
S8-3-WAY	. 3-way 8-channel mic splitter	. 279.00

### **ART**cessories

ART SPLITCOM PRO MIC SPLITTER/ **COMBINER** Used to split or combine balanced low impedance microphone signals. It provides 1 direct-coupled output and 1 isolated output from a single microphone,




or 1 output from 2 microphone inputs. Phantom power passes through each output to their respective input. Includes phase invert and ground lift.

ITEM	DESCRIPTION	PRICE
SPLITCOM-PRO	Mic splitter/combiner	35.00

### (A) audio technica. always listening...

### **AUDIO-TECHNICA UNIMIX MIC COMBINER**

The Uni-Mix is a 24V-48V phantom-powered 2-1 microphone combiner with balance control. Its



ITEM	DESCRIPTION	PRICE
AT8681	2-1 mic combiner with balance control	56.90

AUDIO-TECHNICA AT8801 PHANTOM POWER

**SUPPLY** The AT8801 is a line-powered device that provides 48V phantom power for a single microphone. This highly regulated power supply provides a constant voltage source, even with a heavily loaded input. The regulator IC is internally protected to prevent overheating even if shorted. The rugged



steel case is finished in enamel and provides shielding from electrostatic interference. It includes a plug-in power module (wall wart) that attaches to the electronics module with a 6' cable.

ITEM	DESCRIPTION	PRICE
AT8801	1-channel 48V phantom power supply	69.21



### KLARK-TEKNIK SQUARE ONE SPLITTER

Features 8 channels of Midas XL8-inspired preamps, 9-position rotary gain switches, 30Hz hi-pass filter, duplicate inputs on the front and back, 48V phantom power per channel, transformer-isolated outputs, and more. I/O consists of 8 XLR mic/lin ins (front and back), 8 XLR outs on front panel, 16 XLR outs on the rear panel and 1 headphone out on 1/4" TRS.

ITEM	DESCRIPTION	PRICE
SQUARE-ONE-SPLITTER	8-channel splitter	499.00

PRO CO UTILITY MICROPHONE **MUTING BOXES** These problem solvers help in a variety of situations. Check out the Full Compass website for more detailed specs. The "Cough Drop" provides noiseless instantaneous muting for those "emergency" situations. The "Short Stop" is for temporarily muting a dynamic or condenser mic by pressing and holding the switch. Releasing the switch resumes the signal. The "Sign Off" works the







same way except that you don't need to hold the switch down to mute. You push once to mute, again to resume the signal. The "Power Mute" combines the functions of the "Short Stop" and the "Sign Off" into one unit. The "Panic Button" is for when you actually need to switch your signal from front of house, to an alternate location (i.e. backstage to request a different guitar, etc.)

ITEM	DESCRIPTION	PRICE
COUGHDROP-SHORTSTOP	.Shortstop momentary muting switch	77.79
COUGHDROP-SIGNOFF	.Sign-off latching muting switch	77.79
COUGHDROP-PANICBUTTN	.Panic button A/B switch	161.38
COUGHDROP-POWERMUTE	.Shortstop and Sign-off in one unit	140.06

PRO CO AUDIO VISUAL INTERFACE BOXES 1/4" phone, RCA phono and 3.5mm mini-jack inputs (all parallel). HIGH/LOW switch (-20dB pad). 1/4" phone jack line output. XLR male isolated mic-level output with ground lift switch.

ITEM	DESCRIPTION	PRICE
AV1A	Mobile interface box	104.73
AVP-1STS	A/V interface with steel wallplate/mountable	95.19
AVP-1VSTS	A/V interface with volume control	119.46

PRO CO MS-2/MS-3 MIC SPLITTERS Female XLR input, XLR male 1-direct and 1-isolated (with ground lift) output (MS-2), or 1-direct and 2-isolated (with ground lift) outputs (MS-3), both use the Pro Co MBT-1 transformer.

ITE	M	DES	CRIPTI	ON		PRICE
MS:	2	1x2	mic sp	litter	 	 .81.71
		1x3				

PRO CO MS42A/MS43A RACKMOUNT MIC SPLITTERS These split mic signals for 2 or 3 mixers. 4-female XLR mic inputs, 2 outputs (MS42A) or 3 outputs (MS43A), 1 direct and 1 or 2 isolated (with ground lift) XLR outputs.

	,		•		
ITE	M	DESCRIPTION			PRIC
MS	12A	 . 4x2 rackmount	splitter		 267.0
		. 4x3 rackmount			
		 	- p	 	 

**PRO ANNOUNCER** CO **SPORTS** SWITCHES These rugged, desktop push-totalk mic switches are designed specifically for sports event announcers but equally suitable for any application where a desktop push-totalk device is required. Offers clean reliable performance with any balanced or floating

low-impedance (150ohm nominal) mic or signal source. Designed for either condenser or dynamic mics. XLRF input and XLRM outputs standard. SAS3 has 1 XLRF mic input on



the gooseneck as a direct connect and an additional XLRF input on the back (both inputs run parallel and controlled by switch.)

ITEM	DESCRIPTION	PRICE
SAS1	Push-to-talk switch, (1) XLRF in, (1) XLRM out,	
	magnetically shielded	. 127.88
SAS2	. Push-to-talk switch with 6" gooseneck (mic and adapter not	
	included), (1) XLRF in, (1) XLRM out, magnetically shielded	. 166.43
SAS3	Push-to-talk switch with 6" gooseneck XLRF in,	
	(1) XLRF in, (1) XLRM out, magnetically shielded	. 188.13

**Looking for USB** adapters? See page 58























































