



MUSIC itiit COMPUTER AV VIDEO LIGHT: ACCESSORIES

Shop fullcompass.com today!

For expert advice - call: 800-356-5844 M-F: 9:00-5:30 Central







AKG DMM SERIES AUTOMATIC MICROPHONE MIXERS

These automatic mixers have functions for level, treble, bass, low cut, limiting, compression, automixing (yes/no), priority (ducking), pan/balance, routing to REC, routing to out 1, and routing to out 2. The DMM6 includes 6 mic or line inputs, with DSP offering up to 60 channels of mixing by cascading up to 10 DMM6s and is designed for spoken word applications. The DMM12 offers 12 mic/line inputs, 120 channels via cascading and is

more suited for large meetings and conferences. The DMM12 BC is similar to the DMM12, but adds one AES-EBU output, two additional stereo audio outputs and a 12-band graphic EQ on the 2 main outputs.

ITEM	DESCRIPTION	PRICE
DMM6	6 mic/line in automatic mixer	1666.00
DMM12	12 mic/line in automatic mixer	2249.00
DMM12BC	12 mic/line in automatic mixer with AES-EBU out	2799.00



AUDIO-TECHNICA SMARTMIXERS® AUTOMATIC MIXERS These automatic mixers are ideal for meetings, seminars, teleconferencing, worship services, radio and TV broadcasting and AV applications. All switching is under microprocessor control with proprietary algorithms for instant, seamless operation. An individual priority pre-select switch for each balanced mic/line input channel allows choice of one-channel-at-a-time operation, all channels active, or any mix of moderator override. The last microphone on stays on so that ambient sound is never muted. Plus, SmartMixers can be linked to create a system for large multi-mic installations. The priority control system extends throughout the entire chain. The AT-MX381 is compatible with Crestron and AMX systems and includes a RS232 port for PC connection with included SmartMixer software.

ITEM	DESCRIPTION	PRICE
ATMX341B	4-channel auto mixer with 12V phantom	619.00
ATMX351A	4-channel, 1 aux input auto mixer with 48V phantom	829.00
ATMX381	8-channel auto mixer with 48V phantom	1392.34



DATAVIDEO AD-200 AUDIO DELAY/MIXER

Synchronize audio and video with this 1RU device that features a unique two-piece design allowing the remote control to be placed near the operator while the I/O is easily accessible for cable changes. Each input channel offers up to 3 seconds of audio delay and level adjustments. I/O includes (4) balanced XLR inputs, (2) selectable mic/line aux inputs, (4) balanced outputs and (2) unbalanced outputs. ITI

ITEM	DESCRIPTION	PRICE
AD-200	3-second audio delay	





BEHRINGER RX1202FX MIC/LINE MIXER This versatile and multi-purpose 12-channel rackmount mixer has been designed as a submixer for your keyboard and drum setup, multi-track monitoring or as a line mixer in fixed audio/video installations. It features 8 IMP "Invisible" Mic Preamps with ultra-low noise and transparent audio quality. The mixer also features a 24-bit digital stereo FX processor with 100 presets, switchable +48V phantom power for condenser microphones and offers a 2-band EQ with clip LED for each channel. Other notable features are 4 high headroom line inputs, 2 aux sends per channel, 1 pre fader for monitor applications, and 1 post fader for internal FX or as an external send, and separate control room, phones, and stereo CD/tape outputs. Balanced main mix outputs are provided with XLR connectors. DESCRIPTION ITEM PRICE

RX1202FX	12-channel mic/line mixer, 3RU
	URORACK PRO
	ଶ୍ୱତ୍ରଶ୍ୱଣ୍ଡର୍ଶ୍ୱର୍ଥ୍ଣର୍କ୍ଷ୍ୟ 🚟 ଟ 🗖 🚈
BEHRINGER R	X1602 EURORACK This 16-input line mixer can be used as a flexible

keyboard and multi-purpose submixer, multi-track monitoring mixer, level translator, FX return submixer, and more. Its ultra low-noise ULN design assures the highest possible headroom and ultra-transparent audio. It features dedicated balance and level controls plus +4/-10 level selection per channel, and monitor/FX send control on each section with global master send control for flexible monitoring, recording, or effects applications. Monitor/FX signals are assignable to phones output for added flexibility. An illuminated double-function "mute" button on each section with additional "clip" indication provides comfortable input source/level information. The unit's high-quality detented rotary controls and the rugged construction ensure long-term life and reliability under the most demanding conditions.

ITEM	DESCRIPTION	PRICE
RX1602-EURORACK	.16-input line mixer	149.99





AUDIO OVER FIREWIRE







LECTROSONICS DM SERIES DIGITAL MATRIX PROCESSORS The DM Series provides digital audio processing, mixing and routing for sound reinforcement and conferencing with multiple microphones and loudspeaker configurations. They have auto mic mixing with proportional gain and AutoSkew[™] at the matrix crosspoints. They feature 6 filter stages plus compressor, ADFE and delay on each input, 9 filter stages plus compressor, limiter and delay on each output, 128 global macros available with up to 64 commands per macro. The USB and RS232 interface is for setup and control, and uses LecNet2 or $\widetilde{AMX^{\odot}}$ and CRESTRON^{{}^{\mathrm{TM}}} control systems. The 3 available models are the same except for the number of inputs and outputs. They can be stacked in a master/ slave configuration to expand the number of inputs for any size system.

ITEM	DESCRIPTION	PRICE
DM812	Digital matrix audio processors, 8-in/12-out	CALL
	Digital matrix audio processors, 16-in/12-out	
DM1624F	Digital matrix audio processors 16-in/24-out	CALL





RADIO DESIGN LABS ST-UMX3 3X1 UNIVERSAL **AUDIO MIXER**

This 3-channel unit combines mic- or line-level signals to a single mic/line output. Each input features a separate preamp circuit, isolating it from the other inputs. The output amplifier includes a dual-LED VU meter. Flexible switching between mic and line signals allows installers to address a wide variety of mixing solutions with only one product. Power supply not included. Must use ST-MPA2 adapter if using phantom power.

ITEM	DESCRIPTION	PRICE
STUMX3	. 3x1 Universal Audio Mixer, requires PS24AS power supply	. 132.39
STMPA2	. Phantom power adapter, requires PS24AS power supply	88.53
PS24AS	. Power supply, 24Vdc, 500mÅ, 100-240 VAC	22.23





AUTOMIX® CONTROL 8

An automatic mixer with 8 transformer-balanced mic/ line inputs. Each channel provides a gain control, 48V phantom power, low-cut filter, activity/clipping LED, an aux send control and choice between manual or auto-

matic operation. Each channel also provides a defeatable insert point, 5 V TTL status output and can be muted individually or multiple channels can be muted simultaneously via an assignable mute bus. In addition, channels 1 and 2 provide an adjustable priority control. The master section provides a gain trim control, three 1/9-octave sweepable notch filters, a downward expander, transformer-balanced outputs (main and aux), and remote volume connections. Multiple units may be linked together to form a single mixer with many more inputs (16, 24, 32, etc).

ITEM	DESCRIPTION	PRICE
AUTOMIX-CONTROL8	8-channel automatic mic/line mixer	859.48

RADIO DESIGN LABS AUDIO MIXERS

For expert advice - call: 800-356-5844 M-F: 9:00-5:30 Central

This series offers gold-plated RCA in/ out jacks, plus headroom that accommodates high input level. Both models offer a dual-LED VU meter for each



channel, 1 line input on MINI or RCA jacks, and unbalanced out on MINI (except for EZ-MX4ML) or RCA jacks. EZ-MX4L offers 4 channels and 3 unbalanced line inputs on RCA jacks. EZ-MX4ML offers 2 mic and 2 line inputs. It also has 2 balanced mic ins on XLR and one unbalanced line in on RCA jacks. Mic inputs provide phantom voltage. The RUMX4T has 4 channels with expansion capability. It offers XLR mic ins, phono jack line ins, mic/line XLR out (switchable), unbalanced line out and direct in, switchable 24V phantom per mic input, and switchable compressor/limiter.

ITEM	DESCRIPTION	PRICE
EZ-MX4L	4-channel stereo line-level audio mixer	. 152.93
EZ-MX4ML	2-mic and 2-stereo line audio mixer	162.23
RUMX4T	4-channel mic/line mixer with phantom power, mic/line out	. 331.98



RANE AM1 AND AM2 RACKMOUNT AUTOMIXERS Both models act as

gain-sharing automatic mixers, a stand-alone mic mixer (AM2, or stand-alone mic/line mixer (AM1). The AM1 also can be used as a USB audio I/O device and a manual line mixer. The AM1's 4 XLR mic inputs and the AM2's 8 XLR mic inputs feature front panel level controls and a front panel mic mix level control, while the rear panel features 3-position switches for each input. Both also feature fixed 100Hz to 7kHz bandpass filters, 3 aux inputs (dual RCA, 1/8", USB), and signal and overload indicators on mic and aux inputs. Both units' XLR main output can be set to mic or line level to feed a mic snake or +20 dBu max balanced input. Using the RAD port, either unit can transport its main mix to a CobraNet network via a Rane Mongoose. Up to seven AM2 units can be cascaded into an AM1 unit, creating a total of 60 gain-shared mic inputs.

		'	0	0	1
ITEM	DESCRIPTION				PRICE
AM1	4-channel automix	er with U	SB audio	I/O	
AM2	8-channel automix	er			
MONGOOSE	Remote audio Cobr	aNet inte	rface		

Shop fullcompass.com today!



ITEM	DESCRIPTION	PRICE
MLM42S	. 4x2 mic/line mixer, 1RU	
MLM82S	. 8x2 mic/line mixer, 1 RU	439.00
MLM103	. 10x3 mic/line mixer, 3RU	839.00

MUSIC ihidh COMPUTER AV

VIDEO

LIGHTS

ACCESSORIES

COMPUTER AV

VIDEO

0

LIGHTS

ACCESSORIES

RACK / UTILITY MIXERS

RANGE 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	-
• <u></u> = = = = = = = = = = • • • • •	-

RANE MLM65 MIC/LINE MIXER Features 6 mic/line XLR inputs with front panel pan and fader lever control, rear panel screw-driver gain trims, overload indicators, 12V phantom power, and mic/line switches. Also features selectable aux input with fader level control on the front panel, 5 RCA inputs on the rear panel with screw-driver gain trims. Aux 1 features a 1/8" TRS jack input as well as a USB charge port, aux 4 includes a phono/line switch and a phono ground lug for integrating turntables, and aux 6 is a USB audio port. 1/4" and 1/8" headphone jacks on front panel receive audio from the Cue button and feature rotary level control and dedicated meters with peak hold. The main front panel fader and peak hold meter only affects the main stereo XLR outputs. Digital audio outputs include S/PDIF, TOSLINK, and USB.

RANE CP64S COMMERCIAL PROCESSOR/ZONE MIXER A single space rackmount mixer/processor with 4 line inputs and 4 level priority assignable to 2 zone outputs with 7-band EQ 2 independently assignable mic/line page inputs with defeatable ducking. Has remote controls available for page assign (PR 2) and source/volume (ZR 1), RCA line inputs. I/O also includes euroblock page inputs, remote, and zone outputs.

ITEM CP64S	DESCRIPTION Zone mixer	PRICE 759.00
	Single-zone version	

RANE CP66 COMMERCIAL PROCESSOR/MIXER This multiple-input processor with paging support is designed for use in multi-zone environments. With 6 Program inputs, 6 linkable Zone outputs, Page input, and support for the Rane PAGER2, DR1, and DR3 Digital Remotes, a multitude of system configurations are possible. It can be configured using its front panel controls, and easily set up by a technician in any location without a computer. Included Windows® software (connected through USB) provides the additional ability to save and load pre-configured settings for easy deployment, and also allows custom Zone and Group naming.

	DESCRIPTION	PRICE
CP66	Commercial processor	
	. Level remote	
DR3	. Source and level remote	
PAGER2	. Paging station	

RANE SM26S LINE MIXER/SPLITTER A combo 6-in/2-out mixer and 2-in/6out splitter in one. Can be configured to perform mixing and splitting combos simultaneously. Features mix/pan and level controls with 12dB gain for each channel, and can also operate as a multi-effects mixer/splitter for a guitarist or as a distribution amp/line booster/zone level controller.

ITEM	DESCRIPTION
SM26S	Line mixer/splitter

Certified Repair by Experienced Technicians

Full Compass is a factory-authorized repair center for many of the major brands we carry.







AUDIO OVER

PRICE 379.00







SHURE SCM262/SCM268 MIXERS The SCM262 has 2 XLR mic inputs, 3 stereo unbalanced aux inputs (RCA), defeatable ducking, jukebox mute and 12V phantom power. Other key features include bass and treble controls on the master output, 1 unbalanced stereo aux level output (RCA) and 1 balanced stereo mic/ line output (1/4" TRS). loops. The SCM268 has 4 transformer-balanced XLR mic level inputs, 1 transformer-balanced XLR mic/line output and 1 internal toroidal power transformer making this mixer perfect for many types of applications. Other key features include 5 unbalanced aux level inputs (RCA), an LED peak output meter, 12V phantom power, built-in low-cut filters on mic inputs and 1 unbalanced aux level output.

ITEM	DESCRIPTION	PRICE
SCM262	. Stereo mixer	
SCM268		000.000

SHURE 000000 0 C

SHURE SCM410, SCM800 AND SCM820 MIXERS The SCM410 is a 4-channel auto-mixer in a half-rack chassis with 4 mic level XLR ins, 1 balanced XLR mic/line out and 1 balanced RCA aux out. The SCM800 is an 8-channel manual mixer with 8 mic ins on terminal block connections, send/receive 1/4" per channel, 48V phantom power per channel, terminal block line out, 2 aux ins that feed one channel, headphone out, and more. The SCM820 is an 8-channel digital auto mixer with enhanced I/O connectivity options. It features per-channel direct outs, mix A and B outs, individual channel control, and more. The standard version SCM820 has phoenix type connectors for inputs and outputs and RJ45 for networking. Please call for a full listing of connection options.

ITEM	DESCRIPTION	PRICE
SCM410	4-channel auto mixer	728.83
SCM800	8-channel manual mixer	655.20
SCM820	8-channel IntelliMix® digital automatic mixer	1999.00
RKC800	Rackmount XLR connector panel for the SCM800	218.03

Solid State Logic

SOLID STATE LOGIC **SIGMA ANALOG** SUMMING ENGINE

Offering the ease of ITB mixing using the DAW of your choice, this 100% analog summing mixer provides 16 flexible



MUSIC

ihidh

COMPUTER AV

VIDEO

LIGHTS

ACCESSORIES

channels, switchable between stereo and mono for up 32 channels at mixdown. MDAC control technology reads your DAW's automation to drive the SuperAnalogue mix engine feeding 2 stereo mix buses with individual stereo inserts for parallel compression or printing of post-processed stems. All channels offer direct outputs, and Mix Bus B can be injected into Mix Bus A; both Mix Bus inserts include an insert sum feature. Remote control can be accessed via standard MIDI hardware control surfaces, including MIDI learn for easy setup; dual-action front panel push/hold buttons or a footswitch can be assigned to switching functions as well. MIDI-over-Ethernet allows for control and connection to a cross-platform software interface, and the Sigma can also be remote controlled via an iOS device.



TUDIO

STUDIO TECHNOLOGIES 742 AUDIO MIXER LOGIES Expressly designed for use in electronic-newsgathering (ENG) vehicles and small production

truck applications. Offers a flexible monitor section, setup oscillator with dedicated output, all operator controls on the front panel, single rack-space mounting and internal power supply. It also provides 4 mic/line and 4 line-only inputs, 2 compressors and two 10-segment LED meters.



SYMETRIX ZONE MIX 761 ZONE PAGING MIXER A complete zone mixing, paging, and music management solution designed to save integrators time and money. Perfect for restaurants, hospitality establishments, nightclubs and more. A Graphic User Interface provides a familiar hardware-like layout allowing for a low learning curve and quick use. From elegant remote controls to a simple 3rd party control protocol, the Zone Mix 761 is all about integration. Includes (8) mono-summed stereo inputs on RCA, (4) balanced mic/line ins on terminal blocks, and (6) outs on terminal blocks.

ITEM	DESCRIPTION	PRICE
761	12-in/6-out zone mixer	1699.00

For expert advice - call: 800-356-5844 M-F: 9:00-5:30 Central

