















































ALTO PROFESSIONAL TRUESONIC SERIES PA SPEAKERS These lightweight speakers combine a modern Class 'D' power PROFESSIONAL amplifier with super-efficient drivers to create accurate, transparent sound. All models feature lightweight polypropylene trapezoidal enclosures (suitable for either vertical or floor use), 1" tweeter, integrated 36mm pole socket, M10 fly points (10" models have 4, 12" models have 5, 15" models have 6), carrying handles, 2 parallel Speakon NL4 connections for input and pass-through, over-excursion/thermal/driver protection, clip/limit indicator LED and offer 80°/100° horizontal and 60° vertical coverage. Wireless models have onboard Bluetooth® A2DP wireless technology, allowing you to stream audio wirelessly from any Bluetooth-compatible device and even stream your stereo signal to discrete left and right speakers. Active models include 2 mic/line combo inputs with independent volume controls, contour switch for increased EQ control, and ground lift. The TS115-VIBE provides an easy solution for playing backing tracks or intermission music, with its ability to stream MP3, WMA, or AAC music files directly from a USB flash drive or microSD card and includes ID3 tag support as well as rear panel navigation, transport, and search controls.

ITEM	DESCRIPTION	PRICE
	. Active loudspeaker, 800W, 2-Way 12"/1", 65Hz-19kHz, Bluetooth® connectivity Active loudspeaker, 800W, 2-Way 15"/1", 53Hz-19kHz, Bluetooth® connectivity	
Passive Models	, , , , , , , , , , , , , , , , , , , ,	
TS-115	.Passive, 800W, 2-way 12"/1", 52Hz-18kHz	
	.Active loudspeaker, 600W, 2-way 10"/1", 70Hz-19kHz	
TS-115A	Active loudspeaker, 800W, 2-way 12"/1", 65Hz-19kHz	349.99
Subwoofers	Active loudspeaker, 800W, 2-Way 15"/1", USB media player	
TS-SUB-15	Active subwoofer, 600W, 12", 47Hz-125Hz	599.99
TS-SUB-18	Active subwoofer, 1200W, 18", 37Hz-125Hz	699.99
	. 16GB USB 2.0 flash drive, black (by Transcend)	





# **ALTO PROFESSIONAL** STEALTH WIRELESS STEREO WIRELESS SYSTEM FOR ACTIVE LOUDSPEAKERS

The Stealth Wireless system is designed to add wireless audio capabilities to any powered loud-

speaker systems. The system is comprised of a dual-channel transmitter and (2) single-channel receivers. The receivers each feature an XLR output that connects directly to the input of the powered speaker, and the transmitter features two XLR combo jack inputs allowing for connections from a sound source to the transmitter. The UHF system has 16 selectable channels ensuring clear transmission from up to 200 feet away and the adjustable squelch on the system helps eliminate potential interference. Includes (1) Stealth Wireless transmitter, (2) Stealth Wireless receivers, (3) power supplies, (2) XLR cables, (2) M10 screws, (2) machine screws and (2) velcro strips.

ITEM	DESCRIPTION	PRICE
STEALTH-WIRELESS	Stereo UHF wireless audio system for active loudspeakers	399.99



SPEAKERS Two-way, horn-loaded, weather-resistant speakers feature extremely high output and outstanding pattern control for indoor and outdoor applications. All models feature bottom-mounted Speakon connectors.

ITEM	DESCRIPTION	PRICE
AH54-15-BSG	With 15" LF, 50° X 40°, 75Hz-14.5kHz, 250W RMS	. 1352.50
AH94-15-BSG	With 15" LF, 90° X 40°, 75Hz-14.5kHz, 250W RMS	. 1352.50
AH66-15-BSG	With 15" LF, 65° X 65°, 75Hz-14.5kHz, 250W RMS	. 1352.50
AH99-12T-BSG	With 12" LF, 90° X 90°, 80Hz-15kHz, 200W RMS	. 1068.50
AH66-12T-BSG	With 12" LF, 65° X 65°, 80Hz-14kHz, 200W RMS	. 1068.50
AH99-8ST-BSG	With 8" LF, 90° X 90°, 90Hz-10kHz, 100W RMS	706.50
AH-94-BSG	With 8" LF, 90° X 40°, 90Hz-10kHz, 100W RMS	706.50
AHSUB15S	15" subwoofer, 55Hz-120Hz, 250W RMS	. 1638.50

15" wo handles newer loudspo sound throw applications.

AKER	END TIME ALIGN® TA5000 LOUDSPEAKER
Steel	ofer and 1" titanium driver with 90° horn. Steel
is the	s and grille (on portable models). The TA5000 is the
gned®	version of the Bag End 15" 2-way, Time Aligned®
natural	eaker, and provides even more precise and natural
onger)	reproduction for short to medium (and longer)

ITEM	DESCRIPTION	PRICE
TA5000-R	Black RO-TEX finish	1197.00
PTA5000-R	As above, powered version	2038.00
TA5000-I	Install, black painted finish, with flying hardware	1333.00
PTA5000-I	As above, powered version	2174.00
P-versions include	the built-in Minima One amplifier. It features 1000	W @ $4\Omega$ . and

BAG END TA6002-R Compact, portable speech-range loudspeaker system offering high fidelity and high efficiency in a rugged 27lb. birch plywood package. Has 95dB SPL, 80° horiz and 60° vert dispersion and a 600W peak capacity. Contains (2) 6.5" cones, a 1" compression driver in a radial horn. C an be combined with the ELF subwoofer for higher powered applications, and uses the Bag End time aligned system. Connectors are 1-dual Banana, (2) 1/4" phone, and 2 Neutrik speakons. Mount hardware is a 35mm rigging point.

automatically adapts to any voltage between 88V and 275V.

	00 0.	
ITEM	DESCRIPTION	PRICE
TA6002-R	Birch plywood Ro-tex finish	739.00
TA6002-S	Birch plywood coated with black	textured paint 739.00
TA6002-I	Black painted installation finish	701.00



# BAG END \$18E/D18E/D12E/\$12E **EXTENDED LOW FREQUENCY** SUBWOOFER ENCLOSURES

These subwoofers offer unheard of flat, Time Aligned<sup>TM</sup> response to as low as 8Hz-18Hz and can be used with any INFRA® processor. Portable models include durable carpet covering, vinyl coated steel grille, plastic corners (for easy stacking), large steel handles, pole

mount adapter (on D12 and D18 models), and recessed input plate with dual Speakon and banana input connectors for versatility. Installation enclosures feature flat black painted finish (with unfinished as an option), "barrier strip" screw terminal inputs, vinyl-coated steel grille (with cloth grille option), vertical flying hardware (with an option for horizontal hardware), and white painted models with white cloth grilles as an option. All models also available as active speakers - speak with a Sales Pro for more information.

ITEM		PRICE
D10E-I	Dual 10" (install)	823.00
D12E-DA	Low profile dual-12" Sub, only 9" tall	1159.00
D12E-I	Dual 12" (install)	931.00
D18E-AD	Low profile dual-18" Sub, only 15" tall	2394.00
D18E-R	Dual 18" (RO-TEX)	2240.00
D18E-I	Dual 18" (install)	1838.00
\$10E-I	Single 10" (install)	491.00
\$12E-I	Single 12" (install)	598.00
\$18E-I	Single 18" (install)	931.00
S18E-R	Single 18" (RO-TEX)	982.00
\$21E-I	Low profile 21" Sub, only 24" tall (install)	1806.00
S21E-R	Low profile 21" Sub, only 24" tall (RO-TEX)	1857.00
INFRA-MXB	System controller with stereo hi pass	972.00









# **BEHRINGER EUROLIVE D SERIES POWERED PA SPEAKERS**

These speakers feature integrated DSP as well as Ultra-Low Noise (ULN) mic/line inputs with volume control plus a dedicated 2-band EQ. Connections include XLR and 1/4" servo-balanced inputs and an XLR link output. All models have integrate 1-3/8" pole mount sockets and may be tilted on their sides to be used as a floor monitor. All have Class 'D' amplifiers for even more power in a lightweight package.

ITEM B208D-EUROLIVE	DESCRIPTION 8" 2-way, Class 'D' active, 1.35" aluminum	PRICE
B208D-WH-EUROLIVE	compression driver, 135W, 113dB, 65Hz-20kHz, 14.7lbs As above, in white	
B210D-EUROLIVE	. 10" 2-way, Class 'D' active, 1.35" aluminum	
B040B WW EUBOLINE	compression driver, 135W, 113dB, 65Hz-20kHz, 18.8lbs	
	. As above, in white	229.99
	compression driver, 280W, 125dB, 65Hz-20kHz, 31.9lbs	
	. As above, in white	299.99
	compression driver, 280W, 126dB, 55Hz-20kHz, 45.2lbs	
	. As above, in white	349.99
D12000	. 12" 2-way, Class 'D' active subwoofer, 500W, 122dB, 45Hz-180Hz	299.99



### **COMMUNITY VERIS2 INSTALLATION SPEAKERS**

These 2nd-generation install speakers offer a range of 2-way, 3-way and subwoofer designs ideal for small and medium-sized venues. All models offer improved crossovers (64° models' crossovers are individually voiced), new grille design and 1" exit HF drivers. All 6.5" and 8" models are also available with a built-in autoformer for 70V/100V applications. All models listed are in black; white also available. Please speak with your Sales Pro to configure your system today!

ITEM	DESCRIPTION	PRICE
VERIS2-6-BLACK	100W, 8Ω, 2-way, 6.5" LF/1" HF, 110Hz-16kHz, up to 118dB SPL	CALL
VERIS2-8-BLACK	150W, 8Ω, 2-way, 8" LF/1" HF, 100Hz-16kHz, up to 120dB SPL	CALL
VERIS2-26-BLACK	200W, 4Ω, 2-way, (2)6.5" LF/1" LF, 90Hz-16kHz, up to 121dB SPL	CALL
VERIS2-28-BLACK	300W, 4Ω, 2-way, (2)8" LF/1" HF, 90Hz-16kHz, up to 125dB SPL	CALL
VERIS2-1264-BLACK	200W, 8Ω, 2-way, 12" LF/1" HF, 90Hz-16kHz, up to 127dB SPL	CALL
VERIS2-1564-BLACK	200W, 8Ω, 2-way, 15" LF/1" HF, 80Hz-16kHz, up to 128dB SPL	CALL
VERIS2-3264-BLACK	200W, 8Ω, 3-way, 12" LF/6.5" MF/ 1" HF, 80Hz-16kHz, up to 129dB SPL.	CALL
VERIS2-3564-BLACK	200W, 8Ω, 3-way, 15" LF/ 6.5" MF/1" HF, 70Hz-16kHz, up to 129dB SPL.	CALL
VERIS2-210S-BLACK	300W subwoofer, 4Ω, (2) 10" LF, 50 - 150Hz, up to 96dB SPL	CALL
VERIS2-212S-BLACK	300W subwoofer, 4Ω, (2) 12" LF, 50 - 125Hz, up to 129dB SPL	CALL
VERIS2-215S-BLACK	400W subwoofer, 4Ω, (2) 15" LF, 50 - 1000Hz, up to 129dB SPL	CALL





**COMMUNITY MX8/MX10 COMPACT COAXIAL MONITORS** Using Community's proprietary coaxial drivers and DYNA-TECH™ driver protection system, these compact monitors provide professional performance at affordable prices. Their coaxial design means that all of the sound emanates from the same point source. These features reduce feedback, improve intelligibility, and provide uniform coverage exactly where it's needed.


	DESCRIPTION	PRICE
MX8-B	8", 2-way monitor, 150W RMS @ 8Ω, black	CALL
MX8-W	As above, in white	CALL
MX10-B	10", 2-way, 200W RMS @ 8Ω, black	CALL
MX10-W	As above, in white	CALL
MX-Y8B	Wall/ceiling yoke for MX8, black	CALL
MX-Y8W	Wall/ceiling yoke for MX8, white	CALL
MX-Y10B	Wall/ceiling yoke for MX10, black	CALL
MX-Y10W	Wall/ceiling yoke for MX10, white	CALL

**COMMUNITY R.5SUB** This system is engineered to provide quality low frequency reproduction in a variety of outdoor and indoor environments. Its compact size and weather-resistant properties allow for easy inclusion in a wide variety of environm in

n	nents. An available input transformer provides impedance match-	
ing to 70V or 100V lines. 5-year limited warranty.		1323
-11	EM DESCRIPTION	PRICE
R	.5-SUB Compact subwoofer, 200W @ 6Ω	CALL
R	.5-SUBT As above, with 70V transformer	CALL

# **COMMUNITY R.25 HORN LOUDSPEAKERS** These 2-way,

horn loaded coaxial speakers are highly weather resistant for outdoor applications, but appropriate for indoor use as well. They offer exceptional voice clarity and sound projection. They feature a roto-molded UV enclosure, weather-treated drivers and crossovers, zinc-rich epoxy dual-layer powder coated steel grille and yoke and integral mounting points. They have a



ITEM	DESCRIPTION	PRICE
R.25-94Z	. 2-way weather-resistant speaker, white	CALL
R.25-94BZ	. As above, in black	CALL
R.25-94TZ	. 2-way weather-resistant speaker, 70V/100V, white	CALL
R.25-94BTZ	. As above, in black	CALL

COMMUNITY R.5, R.5-COAX The R.5 series of 2-way, fullrange loudspeakers is engineered to provide quality full-range sound projection in a variety of outdoor and indoor applications. Its wide range, smooth frequency response and high efficiency ensures both high fidelity music reproduction and superb projection of clear intelligible speech with very low distortion. All R.5's feature a 12" 200W LF driver, with 90Hz-16kHz frequency response,

and a UC1 1" exit non-metallic Ferrofluid cooled high frequency compression driver. "T" versions include an input transformer with 4 switchable tap settings to provide impedance matching to 70V or 100V lines. 5-year limited warranty.

ITEM	DESCRIPTION	PRICE
R.5-66Z	.50°H x 50°V, 200W RMS, 500W PGM, 8Ω	CALL
R.5-66TZ	As above, with 120W/70V transformer	CALL
R.5-94Z	.90°H x 40°V, 200W RMS, 500W PGM, 8Ω	CALL
R.5-94TZ	As above, with 120W/70V transformer	CALL
R.5-99Z	.90°H x 90°V, 200W RMS, 500W PGM, 8Ω	CALL
R.5-99TZ	As above, with 120W/70V transformer	CALL
R.5-COAX-66	.60°H x 60°V, 200W RMS, 500W PGM, 8Ω	CALL
R.5-COAX-66T	As above, with 200W/70V transformer	CALL
R.5-COAX-99	.90°H x 90°V, 200W RMS, 500W PGM, 8Ω	CALL
R.5-COAX-99T	As above, with 200W/70V transformer	CALL















































































































DAS AUDIO ACTION SERIES SPEAKERS This series offers outstanding performance, absolute reliability, and unparalleled convenience. Good for both high-profile venues or on-stage for major events. They feature rugged birch plywood construction, environmentally-friendly paint finish, Class 'D' 1000W biamplified electronics, versatile I/O options, and are pole-mountable or stackable on Action series subwoofers. All powered versions have XLRF inputs, loop-thru XLRM and male IEC power inputs (except the 218A has PowerCon NAC 3 FCA inputs for power.) All passive versions have 2 NL4 speakon connectors.

ITEM	DESCRIPTION	PRICE
Powered		
ACTION-12A	. 12", 500W	629.00
ACTION-M12A	. 12", 500W, floor monitor version	729.00
ACTION-15A	. 15", 500W	729.00
	. (2) 15", 500W	
	. 18" subwoofer, 750W	
ACTION-218A	. (2) 18" dual subwoofer, 1250W	1469.00
Passive		
ACTION-12	. 12", 300W RMS@8Ω	429.00
ACTION-M12	. 12", 300W RMS@ 8Ω, floor monitor version	499.00
ACTION-15	. 15", 350W RMS@8Ω	499.00
	. (2) 15", 700W RMS@4Ω	
ACTION-18	. 18" subwoofer, 600W RMS@8Ω	679.00
ACTION-218	. (2) 18" dual subwoofer, 1200W RMS@4 $\Omega$	999.00



**EAW VF SERIES PASSIVE LOUDSPEAKERS** 

The VF Series leverages EAW's core technologies to deliver an unprecedented level of fidelity, output and pattern control for cost-sensitive applications, both mobile and permanently installed. All models feature a rotatable waveguide as well as NL4 4-terminal and barrier strip connectors. Models listed below are black, white installationonly models are also available. Shop fullcompass.com or call a Full Compass Sales Pro for more information.

ITEM	DESCRIPTION	PRICE
VFR159I-BLACK	15" 2-way, 90x60, 8Ω	1127.00
VFR129I-BLACK	12" 2-way, 90x60, 8Ω	991.00
VFR109I-BLACK	10" 2-way, 90x60, 8Ω	856.00
VFR891-BLACK	8" 2-way, 90x50, 8Ω	721.00
VFR691-BLACK	6" 2-way, 90x50, 8Ω	586.00
VFS220-BLACK	(2) 12" subwoofer, 4Ω	1217.00
VFS250-BLACK	(2) 15" subwoofer, 4Ω	1442.00
VFM109-BLACK	10" 2-way floor monitor, 90x60, 8Ω	856.00
VFM129-BLACK	12" 2-way floor monitor, 90x60, 8Ω	991.00
VFM159-BLACK	15" 2-way floor monitor, 90x60, $8\Omega$	1127.00



### **EV ZXA1 AND ZXA1-SUB COMPACT POWERED LOUDSPEAKERS**

Powered by an amp module from EV's Tour Grade series, this light-

weight portable loudspeaker system is well suited for clubs, houses of worship, and other concert venues. The 800W ZXA1 features a biamplified design with transducer protection, an 8" high-output LF transducer, 1" exit true compression driver, selectable high-pass filter, XLR/TRS combo line and XLR mic inputs, and a built-in pole mount. ZXA1-SUB is a 700W 12" subwoofer, featuring DSP with low-end boost and polarity control, dual XLR stereo inputs and outputs, and pole mount.

ITEM	DESCRIPTION	PRICE
ZXA1-90B-120V	8", 800W, 123dB max. SPL, 90° x 50°	499.00
ZXA1-SUB-120V	12", 700W, 126dB max. SPL, omnidirectional	599.00

EV ZX1 SERIES All models have steel grille construction, weatherized 8" LF drivers, 60Hz-20kHz frequency response, 200W continuous power handling, and DH2005 1" exit compression drivers. The ZX1 portable model features integral pole mounting, and dual NL4 Speakon connections. The ZX1i installation models feature Phoenix connectors and an integrated QuickSAM  $^{\mathrm{TM}}$  mounting bracket system, and same horn rotation capability as the portable series. The ZX1iT models have an  $8\Omega$  bypass position to allow

constant voltage operation with multiple tap settings (6.5, 12.5, 25, 50, and 100W), and 100°x100° horn coverage. Call for 100°x100° model numbers (ZX1I-100xx).

ITEM	DESCRIPTION	PRICE
ZX1-90	8" speaker, 90°x50° horn, portable use, NL4, black	299.00
ZX1I-90	8" speaker, 90°x50° horn, install, Phoenix, black	491.00
ZX1I-90W	8" speaker, 90°x50° horn, Phoenix, white	491.00
SB122	12" passive subwoofer, 400W power handling	489.00
AB-ZE	Array bracket for 2 or 4 ZX1i speakers	136.50
CB1-EV	Padded carry case for ZX1	113.50
SC-ZX1	Slip cover	57.15
MP1-B	Mounting plate	125.00
TC-ZX	Terminal cover for ZX1 series	28.60
TCA-7X1	Truss clamn	75 00

EV TOUR X SERIES SPEAKER SYSTEMS These high-performance speakers feature EV's SMX woofers, for extraordinarily low levels of distortion without sacrificing sensitivity. The backbone grille design is aesthetic and damage-resistant, and the input panels and handle are ergonomically designed for maximum comfort. Steep slope analog crossovers with elliptical filters provide up to 36dB per octave slopes, reducing acoustic transducer interaction for better sound and higher power handling. Floor monitors feature a patent-pending

SST (Signal Synchronized Transducers) design which utilizes a split baffle layout, allowing the enclosure to be more compact and yield near-perfect driver phase summation. All models feature parallel Neutrik®NL4 inputs.

TX1122

ITEM	DESCRIPTION	PRICE
TX1122	12" 2-way, passive, 90°x50° horn, 60Hz-20kHz, 500W, 8Ω	729.00
TX1152	15" 2-way, passive, 60°x40° horn, 55Hz-20kHz, 500W, 8Ω	887.00
TX2152	Dual 15" 2-way, passive, $60^{\circ}$ x $40^{\circ}$ horn, $55$ Hz- $13$ kHz, $1000$ W, $4\Omega$	1249.00
TX1181	18" subwoofer, 50Hz-160Hz, 500W, 8Ω	749.00
TX2181	Dual 18" subwoofer, 50Hz-160Hz, 1000W, 4Ω	1199.00
TX1122FM	12" 2-way vertical floor monitor, passive, 90°x50° horn, 500W, 8Ω	729.00
TX1152FM	15" 2-way vertical floor monitor, passive, 90°x50° horn, 500W, 8Ω	749.00
TX-W1	Wheel kit for TX1181 and TX2181, black	301.50
	<u> </u>	



TX2152









# Now you can...

event

line array series by D.A.S

event 210A

event 208A

From large scale concerts and arenas to small venues and even house parties; D.A.S. Audio – is one of the most respected names in the business.

Now you can afford to own gear used by professional touring companies and installers world wide. Proudly made in Spain, but enjoyed globally!

If your sound matters... **D.A.S. has you covered!** 

event 218A

# action

See our 7 products in the Action family which includes a 2500W Peak Dual 18" Subwoofer and 1000W Peak Dual 15"



FULL COMPASS

FRO AUDIO VIDEO LIGHTING MUSICAL INSTRUMENTS

800-356-5844 fullcompass.com

action 12/12A

action 18/18A

action 215/215A action 8/8A

action 218/218A

action 15/15A action M12/M12A





















































EV LIVE X LOUDSPEAKERS These speakers are built to meet exacting power-handling specs and have high-frequency titanium compression drivers, rugged solid wood construction, SPL output up to 134db, frequency response up to 20kHz, and up to 1000W power-

handling. Powered versions have 700W or 1000W Class 'D' high-efficiency amplifiers that run cool without fans and have 2 XLR/TRS combo jacks, 1 Stereo RCA input, and 1 XLR link output. Cabinets are designed to pole-mount or stack with Live X subwoofers.

ITEM	DESCRIPTION	PRICE
Passive Speakers		
ELX112	12" 2-way, 250W continuous and 1000W peak	299.00
ELX115	15" 2-way, 400W continuous and 1600W peak	399.00
ELX215	(2) 15" 2-way, 600W continuous and 2400W peak	599.00
ELX118	18" subwoofer, 400W continuous and 1600W peak	499.00
Powered Speakers	•	
ELX112P	12" 2-way, 1000W Class 'D' amplifier	599.00
	15" 2-way, 1000W Class 'D' amplifier	
	18" subwoofer, 700W Class 'D' amplifier	



### **EV ZLX SERIES SPEAKERS**

Available in passive or active versions these speakers cut through the competition with the most complete and innovative package of features in their class. Features include LCD



display and unique single-knob DSP control with presets, input level meters and independent amplifier control, EV-engineered components matched with a custom-built Class 'D' amp. Both passive and powered speakers are made of durable composite construction with unique hi/lo grip design for effortless pole mounting and portability and a patented split-baffle design for superior driver time alignment and enhanced sonic impact and intelligibility.

ITEM	DESCRIPTION	PRICE
ZLX-12P-US	12" powered 2-way loudspeaker, 1000W	399.99
ZLX-15P-US	15" powered 2-way loudspeaker, 1000W	499.99
ZLX-12	12" passive 2-way loudspeaker, 250W continuous	299.99
ZLX-15	15" passive 2-way loudspeaker, 250W continuous	399.99
Accessories		
ZLX-12-CVR	Padded cover for the ZLX-12 models	87.48
ZLX-15-CVR	Padded cover for the ZLX-15 models	104.98
ZLX-BRK	Wallmount bracket for the ZLX series	137.50

EV ZX3 12" 2-WAY LOUDSPEAKER Features the DVX3121 12" woofer and the ND2 neodymium compression driver. Provides 600W continuous power in passive mode and 500W (LF)/40W (HF) in biamp mode. Includes 2 Speakon NL4 connectors. Available in white, substitute "W" for "B" at the end of the part number.

		•	
ITEM	DESCRIPTION		PRICE
ZX3-90B	90° x 50° horn, b	lack	899.00
ZX3-90P1	90° x 50° horn, v	veatherized, bla	ck 1392.00
ZX3-60B	60° x 60° horn, b	lack	899.00
ZX3-60PI	60° x 60° horn, v	veatherized, bla	ck 1392.00



EV ZX4 15" 2-WAY PA SPEAKER ZX4 is designed with main mix and monitor duties in mind. It features an integrated pole mount, and for varying stage depths is capable of 45° or 55° angles via integrated retractable monitor feet. The DH3 compression driver with its pure titanium diaphragm, coupled with the Zx4's large 90° x 50° horn allows for tremendous intelligibility and pattern control. The EVS15-SF 15" LF delivers tight, low bass and 400W continuous power handling (1600W peak), sensitivity is 100dB and max SPL is 132dB.

ITEM	DESCRIPTION				PRICE
ZX4	. 15" 2-way speaker,	400W,	44	.5 lbs	699.00

### **EV ETX SERIES PORTABLE PA SPEAKERS**

These versatile speakers use advanced technology to create clear, powerful, accurate sound, 2000W (1800W for subs) Class 'D' power amps with onboard DSP are matched with lowdistortion transducers and EV's patented SST waveguide



(custom-designed for each model) for consistent coverage with any configuration. Two-way models offer a smooth-sounding 1.25" titanium compression driver for high frequencies and 90°x60° coverage pattern (60°x40° for ETX-35P). FIR-Drive uses Finite Impulse Response technology to optimize transducer linearity while limiter algorithms prevent signal and/or thermal overload. The onboard LCD screen provides an easy-to-read display for adjustment of DSP parameters: EQ presets, limiter status, input meters and level controls and master volume control. Subwoofer models include a preset for true cardioid performance. Other features include 13-ply birch cabinet construction, (2) XLR/TRS combo jacks and XLR link output (2 link outputs on sub models), attractive and durable EVCoat finish, 8 fly points on two-way models, and custom die-cast polemount cups, handles and hardware.

ITEM	DESCRIPTION	PRICE
ETX-10P	10", 2-way, 65Hz-20kHz, 134dB peak, 1.7kHz x-over	1099.00
ETX-12P	12", 2-way, 55Hz-20kHz, 135dB peak, 1.6kHz x-over	1199.00
ETX-15P	15", 2-way, 48Hz-20kHz, 136dB peak, 1.5kHz x-over	1299.00
ETX-35P	15"/6.5", 3-way, 48Hz-20khz, 134dB peak,	
	700Hz/2.9kHz x-over	1499.00
ETX-15SP	15", subwoofer, 37Hz-150Hz, 134dB peak	1399.00
ETX-18SP	18", subwoofer, 33Hz-150Hz, 135dB peak	1499.00

EV ZX5 AND ZXA5 The Zx5 is a 15", 2-way cabinet with a lightweight, high-impact composite enclosure, featuring a 500W, forced-air cooled woofer with 3" voice coil, and a 2" neodymium compression driver. It's rated for 600W long-term power handling (2400W peak) and can produce 132dB SPL with very smooth 58Hz-15kHz frequency response. With two available coverage patterns (60°x60° or 90°x50°) and 2 adjustable monitor angles (45° or 55°). Ten built-in rigging and suspension points allow for a variety of mounting accessories. The ZXA5 active speaker effortlessly delivers a continuous 250W into the HF and 1000W into the



LF for an unprecedented power-to-weight ratio, and performance that is unmatched by powered systems costing twice as much. ZX5 portable versions are available in white as well - substitute "W" for "B" in part number.

ITEM	DESCRIPTION	PRICE
ZX5-60B	15" 2-way speaker, 60°x60°, 600W, 8Ω, Speakon, black	999.00
ZX5-60PI	As above, permanent install version, black only	1521.00
ZXA5-60B	Active 15" 2-way speaker, 60°x60°, 1000W LF,	
	250W HF, XLR and 1/4" TRS, black	1699.00
ZX5-90B	15" 2-way speaker, 90°x50°, 600W, 8Ω, Speakon, black	1229.00
ZX5-90PI	As above, permanent install version, black only	1521.00
ZXA5-90B	Active 15" 2-way speaker, 90°x50°, 1000W LF,	
	250W HF, XLR and 1/4" TRS, black	1699.00





Electro-Voice ETX Powered Loudspeakers

The new ETX Powered Loudspeaker family builds upon the industry-leading innovation and 85-year heritage of Electro-Voice audio engineering to offer the most advanced professional-grade products for an array of applications.

- . State-of-the-art components deliver the legendary EV sound quality and reliability the pros trust: 1800 W (subs) & 2000 W (full-range) Class-II power amplifiers with integrated USP graduce high SPLs utilizing high-sensitivity, lowdistortion transducers (including DVX & SMX series wooders and precision DH3-8 HF titurium compression drivers).
- . Eightweight, ergonomic, durable and compact 18-mm, 13-ply birch plywood enclosures finished with EVCoat, Eight mounting points for permanent installations (full-range models). Costom die-cast aluminum pole cups, handles and hardware.





Performance beyond the reach of the competition.

# BRAINER

Intelligent technology. innovative design.





- EV's FIR-Drive utilizes the latest Finite Impulse Response (FIR) filter technology to optimize transducer linearity. Advanced limiter algorithms for independent peak and thermal transducer protection.
- Complete full-function DSP control via a single-knob interface. LCD screen for easy system set-up and monitoring: location/application EQ presets (e.g. tripod, mounted, suspended, live, music, speech), limiter status, input level controls/meters and master volume control to ensure optimal gain structure. Parametric EQ allows for more precise configuration. Subs feature a preset for true cardioid performance.
- EV-patented Signal Synchronized Transducers (SST) waveguide design provides precise and consistent coverage across all system configurations. Waveguides are custom-designed and optimized per model.

10 = 12 = 15 = 15 3-way = 15 sub = 18 sub

