



LINE 6

LINE 6 STAGESOURCE SERIES LOUDSPEAKER SYSTEM

These 3-way, tri-amped loudspeaker systems are optimized for a variety of performance scenarios. A combination of on-board accelerometers and pole-mount sensors automatically detect speaker orientation and set the DSP-based Smart Speaker modes accordingly. Other features include integrated 12-band feedback suppression, multifunction design, and (4) M10 fly points. L6 LINK™ digital networking support allows for automatic self-configuration, Smart Speaker mode adjustment, system-wide optimization and connectivity to the StageScape M20d 20-input 7" touchscreen-based mixer. When networking StageSource speakers with the M20d, total system optimization is a snap, with the M20d doing all the heavy lifting automatically, setting up monitor mixes, panning and speaker modes quickly and effortlessly. For use as a stand-alone PA, L3t adds an integrated 2ch mixer with EQ, effects, and acoustic guitar modeling. The L3M/L3T models each have (1) XLR-1/4" balanced line in, (1) stereo RCA in and (1) L6 LINK™ XLR. The L3S sub has (1) XLR-1/4" balanced line in and the L6 LINK™ XLR.



ITEM	DESCRIPTION	PRICE
STAGESOURCE-L3M	Dual 10", 3-way, 1400W, active speaker	899.99
STAGESOURCE-L3T	As above, with DSP and 2-channel mixer	999.99
STAGESOURCE-L3S	Dual 12", 2-way, 1200W, active subwoofer	1199.99
STAGESCAPE-M20D	20-input mixer with 7" touchscreen and L6 LINK digital networking	1499.99

GALAXY AUDIO HOTSPOT MINI SPEAKERS

The PA6S is a compact PA 2-way system featuring a 6.5" LF neodymium woofer and a 1.5" HF neodymium tweeter. It has a built-in compressor/limiter and an XLR pass thru on channels 1 and 2. The HOT-SPOT-VC-7 (HS7) is engineered for near-field vocal monitoring and has two Neolite 5" drivers and an 18dB stepped attenuator volume control. Both models include an integrated handle and mounting point for a mic boom.



ITEM	DESCRIPTION	PRICE
PA6S	2-way powered PA, 170W @ 4Ω, 80Hz-18kHz	299.99
HOT-SPOT-VC-7	Vocal monitor, passive, 200W, 150Hz-18kHz	139.99

GALAXY AUDIO NANO SPOT POWERED MONITOR

The NSPA has a 3" driver, 25W amplifier, 2-band EQ, built-in compressor and can provide 24V phantom power. Inputs consist of (1) XLR, (1) 1/4" TRS and (1) 1/8" TRS jack. It is stand/bracket-mountable and ships with a bracket. Power supply is included.



ITEM	DESCRIPTION	PRICE
NSPA	Nano Spot powered monitor, 25W	139.99



GALAXY AUDIO MS5 MICROSPOT® SPEAKER

Created to solve the problem of musicians and public speakers not being able to hear themselves while performing, the MS5 efficiently reproduces crucial vocal range frequencies. It can be attached to a microphone stand using the included yoke bracket kit, is capable of handling up to 100W and is equipped with a passive volume control. Input connection is made via two parallel 1/4" jacks. The MS5 has an impedance rating of 16Ω.

ITEM	DESCRIPTION	PRICE
MS5-GALAXY	Microspot monitor speaker, passive, with volume control	139.99

JBL CONTROL®1 PRO/CONTROL® 5 SPEAKERS

Combining high performance, compact design and rugged construction, the Control Series offers unprecedented versatility. The Control® 1 Pro has a 5.25" woofer and a 0.75" polycarbonate dome tweeter. An updated crossover network design provides steeper crossover slopes for improved sonic performance and consistency throughout the listening area. A wall-mount bracket is included. The Control® 5 features a 6 1/2" woofer and 1" titanium tweeter. Both models feature magnetically shielded transducers, making them well-suited for use near video monitors. Inputs on each model are spring-loaded terminals. Mounting brackets are included with both models. Priced as each, but sold in pairs.



ITEM	DESCRIPTION	PRICE
CONTROL-1-PRO	5.25" 2-way speaker, 80Hz-20kHz, 150W, 4Ω	82.00
CONTROL-1-PRO-WH	As above, in white	82.00
CONTROL-5	6.5" monitor loudspeaker, 75Hz-20kHz, 175W, 4Ω, black	169.00
CONTROL-5-WHITE	As above, in white	169.00
5-0100	Ultra-duty mount bracket for Control-1-Pro	64.00

JBL CONTROL 29AV-1 An upgraded version of the Control 29AV loudspeaker, featuring re-voicing advancements in the crossover network. Developed in conjunction with Walt Disney Imagineering, the re-voicing provides a flatter frequency response with more natural midrange sound character, while extending the bass response. The result is improved clarity on speech and vocals with a more natural sound and wider frequency response for music.

ITEM	DESCRIPTION	PRICE
C29AV-1	8" 2-way speaker, 300W program	387.00

JBL CONTROL 30 A 10" 3-way speaker featuring a 5-1/4" mid-range and compression driver HF and 120x110 deg coverage. Has an integral 70V transformer, a weather-resistant finish, and Sonic Guard overpower protection.

ITEM	DESCRIPTION	PRICE
CONTROL-30	10" 3-way speaker, black	681.00
CONTROL-30-WHITE	10" 3-way speaker, white	681.00



Follow Us!

We Stock Thousands of Common and Hard-to-Find Parts!
Search for Parts on our website: fullcompass.com/parts



JBL JRX200 SERIES Delivers the performance and prestige JBL is known for at an affordable price point. Features include 900x400 Progressive Transition Waveguide for best horn performance, non-resonant steel handles, hexagon perforated steel grille, SonicGuard protection, 3/4" MDF wood construction and dual-angle pole socket (JRX212 and JRX215) for better coverage. Connections are both Neutrik Speakon and 1/4" phone sockets.

ITEM	DESCRIPTION	PRICE
JRX212	12" 2-way stage monitor, 250W @ 8Ω	249.99
JRX215	15" 2-way, 250W @ 8Ω	299.99
JRX225	15" dual 2-way, 500W @ 8Ω	449.99
JRX218S	18" subwoofer, 350W @ 8Ω	499.99



JBL PRX400 SERIES PASSIVE PORTABLE SPEAKERS Provides sensitivity, frequency response, and power handling of well-designed speakers, tailored for demanding audio environments. All models feature tough DuraFlex™ surfaces, 16ga. screen-backed steel grille, suspension points, and professional connectors. All except PRX418S use a 90° x 50° nominal coverage pattern.

ITEM	DESCRIPTION	PRICE
PRX412M	12" 2-way, 300W, 65Hz-16kHz, 8Ω, stage monitor and loudspeaker	499.00
PRX415M	15" 2-way, 300W, 75Hz-16kHz, 8Ω, stage monitor and loudspeaker	549.00
PRX425	15" dual 2-way, 600W, 75Hz-16kHz, 4Ω, loudspeaker	749.00
PRX418S	18" 2-way, 800W, 52Hz-120Hz, 8Ω, subwoofer	749.00

JBL PRX700 SERIES ACTIVE LOUDSPEAKERS

JBL's PRX700 series offers high-power, tour-tested, ultra-lightweight loudspeakers designed to withstand the rigors of professional-level touring sound applications. All models feature JBL's patented Differential Drive® woofers which reduce weight while maximizing power amp efficiency. Smooth, consistent 90°x50° dispersion (100°x60° on the 710 model) eliminates hot spots. PRX700 series models are driven by 1500W Class-D amplifiers, which provide ample power and accurate dynamics. I/O consists of balanced XLR-1/4" combo inputs, unbalanced RCA inputs (HF models only) and XLR THRU. Other features of the HF models include switchable EQ curve, two channels, Speaker Select switch, Thru select switch, mic/line switch (channel 1) and ground lift switch (channel 2). The LF models feature a Polarity Button, Pass Thru button for Hi Pass or Full Range, Signal and Limit LED indicators. Cabinets are built from a combination of 25mm and 18mm poplar plywood covered with JBL's DuraTex™ finish. 16 gauge steel grilles and light-weight glass-filled nylon handles are standard.



ITEM	DESCRIPTION	PRICE
PRX710	10" 2-way powered speaker, 50Hz-19.6kHz	749.00
PRX712	12" 2-way powered speaker, 45Hz-19.6kHz	849.00
PRX715	15" 2-way powered speaker, 43Hz-19.5kHz	949.00
PRX725	2x15" 2-way powered speaker, 42Hz-18.5kHz	1299.00
PRX735	15" 3-way full-range powered speaker, 35Hz-18.5kHz	1299.00
PRX715XLF	15" powered subwoofer, 37Hz-113Hz	1149.00
PRX718XLF	18" powered subwoofer, 30Hz-103Hz	1399.00

JBL EON SERIES SPEAKERS

The EON-300 Series models feature Speakon and 1/4" input connectors, SonicGuard™ HF protection and lightweight composite enclosures. The EON 500 Series add a 3-channel mixer, Differential Drive® LF drivers, neodymium HF drivers and Selectable Pre-engineered EQ settings. The new EON-600 Series feature high-powered 1000W amplifiers, JBL's Advanced Waveguide Technology, JBL designed and manufactured transducers and convenient, wireless remote control of onboard DSP parameters via Bluetooth. This total redesign of the EON platform leverages the latest technologies in cabinet materials, acoustic science, transducer design and user-friendliness.



ITEM	DESCRIPTION	PRICE
EON-305	15" 2-way, passive, 250W, 100°x60°, 50Hz-18kHz, 33lbs	379.00
EON-315	15" 2-way, active, 220W/LF, 60W/HF, 100°x60°, 50Hz-18kHz, 35lbs	299.99
EON-510	10" 2-way, active, 220W/LF, 60W/HF, 100°x60°, 70Hz-17kHz, 17lbs	299.00
EON-518S	18" subwoofer, active, 500W, 42Hz-100Hz, 65lbs	699.99
EON-610	10" 2-way, active, 1000W, 90°x50°, 46.8Hz-20kHz, 26lbs	399.00
EON-612	12" 2-way, active, 1000W, 90°x50°, 46.8Hz-20kHz, 33lbs	449.99
EON-615	15", 2-way active, 1000W, 90°x50°, 46.8Hz-20kHz, 39lbs	499.99
GPA-712LG	Gator Cases rolling speaker bag for EON 515XT	149.99



JBL VP7212/95DP POWERED SPEAKER

A biamplified 12" 2-way integrated loudspeaker system with 1100W of power and JBL DrivePack® technology. It has a 12" Differential Drive® low-frequency driver and a 4" titanium-damped diaphragm high-frequency driver. The enclosure is 5/8" multi-ply exterior grade Baltic birch with internal bracing and black DuraFlex® finish. Other features include a 90° x 50° rotatable waveguide, RJ45 network connector, XLR input and loop through connectors, Neutrik Powercon connectors, M10 and fly-track suspension points and a powder-coated perforated steel grille.

ITEM	DESCRIPTION	PRICE
VP7212/95DP	12" 2-way powered speaker, 63Hz-18kHz	CALL



JBL STX800 SERIES These speakers offer high performance in a portable, truck-friendly package. Full-range boxes in this series feature JBL's PT™ Waveguide that create a smoother frequency response and eliminate harmonic distortion. The LF drivers all have Vented Gap Cooling™ which helps reduce heat and provides the full output capacity of the speaker even after long hours of use. Series subwoofers have even more significant reductions in heat and compressions thanks to Super Vented Gap™ technology. All STX800 speakers are covered in rugged DuraFlex™ and have 14-gauge steel grills. Connections are all NLA.

ITEM	DESCRIPTION	PRICE
STX812M	12" 2-way, 800W, 8Ω, 50Hz-20kHz	1199.00
STX815M	15" 2-way, 800W, 8Ω, 41Hz-20kHz	1499.00
STX825	Dual-15" 2-way, 1600W, 8Ω, 34Hz-20kHz	1999.00
STX835	Dual-15" 3-way, 1600W, 8Ω, 32Hz-20kHz	2599.00
STX818S	18" subwoofer, 1000W, 8Ω, 35Hz-25kHz	1199.00
STX828S	Dual-18" subwoofer, 2000W, 8Ω, 32Hz-25kHz	1999.00



MACKIE®



MACKIE DLM SERIES POWERED SPEAKERS

Ridiculously lightweight and loud, these ultra-compact powered loudspeakers meld efficient Class 'D' power amps with proprietary TruSource® DSP to deliver 2000W of clear, full fidelity audio in a system that fits inside nearly any car. The DLM8 and DLM12 feature the integrated DL2 digital mixer – a powerful one-touch mixer offering 2 versatile channels with discrete EQ/FX controls, 16 channel FX, XLR/TRS combo and RCA dual connectors. They also offer an integrated kickstand (for use as a personal monitor), multi-band feedback destroyer, 6 speaker voicing modes, and can be pole mounted on a tripod or atop a DLM12S using the SPM300 speaker pole, flown via standard M10 rigging hardware, or wallmounted via the SWM300 articulated arm. All models offer alignment delay up to 300ms, 3 memory locations for instant recall, rugged metal grille and Smart Protect DSP amp/driver protection. The DLM12S is a 12" powered subwoofer featuring DLP digital processing, a digital crossover with presets for use with DLM and SRM series speakers, and 6 XLR connections to meet all your I/O needs (2 line level, 2 full-range, 2 hi-pass).

ITEM	DESCRIPTION	PRICE
Speakers		
DLM8	Active, 8" woofer, 1-3/4" tweeter	699.99
DLM12	Active, 12" woofer, 1-3/4" tweeter	849.99
DLM12S	Active 12" subwoofer	999.99
Speaker Covers		
DLM8-BAG	Bag for DLM8	64.99
DLM12-BAG	Bag for DLM12	79.99
DLM12S-COVER	Cover for DLM12S	79.99
Accessories		
SPM300	Pole mount for DLM8 and DLM12	44.99
SWM300	Wall mount for DLM8 and DLM12	99.99



MACKIE HD SERIES POWERED LOUDSPEAKERS The HD1221, HD1521, HD1531 feature Class 'D' Fast Recovery™ amplification, precision crossovers, time correction and patented acoustic correction in order to provide high-definition clarity and superior performance. All 3 speakers feature custom EAW transducers and the HD1521 and HD1531 have an integrated user-adjustable 3-band EQ with sweepable mid. All 3 are flyable as well as pole-mountable and have a compact but rugged birch plywood cabinet. The HD1501 and HD1801 subwoofers also have Class 'D' amplification and feature internal crossovers, tuning filters, phase alignment with loudspeakers, a hi-pass output, and protection circuitry.

ITEM	DESCRIPTION	PRICE
HD1221	12" 2-way active speaker, 500W/LF, 100W/HF, 55Hz-20kHz, 90°H x 50V°, 133dB Max SPL, XLRf in, XLRm loop out, 50lbs	799.99
HD1521	15" 2-way active speaker, 700W/LF, 100W/HF, 50Hz-18kHz, 80°H x 50V°, 135dB Max SPL, XLRf in, XLRm loop out, 80lbs	999.99
HD1531	15" 3-way active speaker, 700W/LF, 100W/MF, 100W/HF, 50Hz-18kHz, 90°H x 40V°, 135dB Max SPL, XLRf in, XLRm loop out, 96lbs	1249.99
HD1501	15" powered subwoofer, 600W RMS, 1200W peak, 36Hz-145Hz, 126dB Max SPL, XLRf ins, balanced XLRm outs, 80lbs	899.99
HD1801	18" powered subwoofer, 800W RMS, 1600W peak, 35Hz-145Hz, 133dB Max SPL, XLRf ins, balanced XLRm outs, 106lbs	999.99
FB221	Flybar for HDA and HD1801	1557.00
PA-A2	Eyebolt kit for HD Series speakers	47.99



MACKIE THUMP SERIES PORTABLE POWERED LOUDSPEAKERS

Three models of powered loudspeakers make up the Thump series; THUMP-12 and THUMP-15 are full-range 1000W peak loudspeakers, and THUMP-18S is a 1200W peak powered subwoofer. THUMP-12 features a 12" woofer and a 1.4" titanium compression driver along with a 2-way internal crossover, 3-band EQ with sweepable mid-range, XLR combo jack for direct mic/line connection and multiple mounting options including tripod and pole-mounting. THUMP-15 has all of the features of THUMP-12 but has a 15" woofer for even more bass response. To round out the low end the THUMP-18S subwoofer features an 18" woofer, a precision 140Hz crossover, dual XLR inputs for mono or stereo applications and an all-wood enclosure for rugged durability. Each model in the Thump series utilizes Class D amplification technology to ensure high-power sound output while keeping thermal output to a minimum.

ITEM	DESCRIPTION	PRICE
THUMP-12	12" 1000W peak portable powered loudspeaker, 57Hz-20kHz, 125dB SPL max	299.99
THUMP-15	15" 1000W peak portable powered loudspeaker, 39Hz-20kHz, 126dB SPL max	349.99
THUMP-18S	18" 1200W peak powered subwoofer, 40Hz-120Hz, 130dB SPL max	699.99



SRM SERIES POWERED LOUDSPEAKERS These powerful, yet lightweight powered loudspeakers are ideal for almost any application. The 10" SRM350 and 12" SRM450 feature 1000W peak power and a textured black polypropylene cabinet. SRM1801 is an 18" subwoofer with 1000W peak power and textured black plywood cabinet, and is an excellent companion to the SRM350 and 450. Moving up to the 12" SRM550, 15" SRM650 and dual 15" SRM750 gives you 1600W peak power and all-wood internally braced black painted cabinets. Complementing the all-wood full-range SRM speakers are the 18" SRM1850 and the dual 18" SRM2850 subwoofers, which both feature the same all-wood internally braced cabinets and 1600W peak power. Rounding out the SRM series is the SRM150, a compact, powered 3-channel PA speaker that is designed as a mic-stand-mounted personal monitoring station featuring a 5.25" woofer and 150W peak power. All SRM series speakers feature Class D amplification technology and the full-range speakers have two XLR combo jack inputs, four switchable EQ modes, feedback destroyer and THRU output for daisy-chaining. The subwoofer models each feature two XLR inputs and two sets of XLR outputs, the first being a high-pass output and the second being a full-range output.

ITEM	DESCRIPTION	PRICE
SRM350-V3	10" 2-way powered speaker, polypropylene cabinet, 1000W peak, 50Hz-23kHz (-10dB), 126dB max SPL	399.99
SRM450-V3	12" 2-way powered speaker, polypropylene cabinet, 1000W peak, 42Hz-23kHz (-10dB), 128dB max SPL	499.99
SRM1801	18" powered subwoofer, plywood cabinet, 1000W peak, 35Hz-150Hz (-10dB), 129dB max SPL	799.99
SRM550	12" 2-way powered speaker, poplar cabinet, 1600W peak, 49Hz-20kHz (-10dB), 132dB max SPL	599.99
SRM650	15" 2-way powered speaker, poplar cabinet, 1600W peak, 39Hz-20kHz (-10dB), 133dB max SPL	699.99
SRM-750	Dual 15" 2-way powered speaker, poplar cabinet, 1600W peak, 37Hz-20kHz (-10dB), 135dB max SPL	1199.99
SRM1850	18" powered subwoofer, poplar cabinet, 1600W peak, 35Hz-150Hz (-10dB), 132dB max SPL	899.99
SRM2850	Dual 18" powered subwoofer, poplar cabinet, 1600W peak, 26Hz-145Hz (-10dB), 135dB max SPL	1599.99
SRM150	3-channel 5.25" personal powered PA speaker, 3-band EQ, 150W peak, 60Hz-22kHz (-10dB), 120dB max SPL	249.99



Follow Us!

Commercial Lease-To-Own financing for businesses available!
Contact your Sales Pro for details.

THE NEW 1000W
SRM
SERIES

BIG POWER HIGH OUTPUT



Supercharged and then some, SRMs now feature a powerful new 1000W amp platform so you can reach more people than ever before. Paired with custom high-output drivers and Mackie Smart Protect™ DSP, you've got a powerful, solid PA solution perfect for your high-output application.

Beyond proven, the SRM is the most widely used portable loudspeaker ever designed. Now... with tons of power, new innovative sound tools like a first-in-class feedback destroyer and Mackie HD Audio Processing for unbelievable sound, the SRM450 is ready to deliver on its live sound legacy.



CLASS-D AMPLIFIER

1000W ultra-efficient Class-D amplification



HIGH-OUTPUT TRANSDUCERS

Premium titanium-dome compression driver and high-output woofer



SMART PROTECT™ DSP

Intelligent limiting and system protection



SRM350

SRM450

1000W POWER

HD AUDIO PROCESSING

INTUITIVE SOUND TOOLS

FULL COMPASS

PRO AUDIO VIDEO LIGHTING
MUSICAL INSTRUMENTS

800-356-5844
fullcompass.com



©2014 LOUD Technologies Inc. "Mackie," and the "Running Man" figure are registered trademarks of LOUD Technologies Inc. All rights reserved.