SOUND REINFORCEMENT SPEAKERS



PEAVEY PVX SERIES LOUDSPEAKERS Constructed with a lightweight molded polypropylene exterior, these speakers are ideal for live music or speech applications. All models feature woofers with 2-3/8" voice coils and a 1.4" titanium compression driver coupled to a constant directivity horn. Multiple cabinet fly points, angled sides for use as a floor monitor, and an integrated pole mount allow for flexible speaker placement. Active models feature DDT compression, module bay for future use of expansion modules, balanced XLR and 1/4" TRS combo input, and XLR and 1/4" through outputs. Passive versions can handle 400W program and 800W peak, and utilize parallel 1/4" and 4-pin twist-lock inputs.

ITEM	DESCRIPTION	PRICE
PVXP10	10" 2-way active loudspeaker	299.99
PVXP12	12" 2-way active loudspeaker	349.99
PVX12	. As above, passive version	219.99
PVXP15	15" 2-way active loudspeaker	399.99
PVX15	. As above, passive version	269.99
PVXP-SUB	15" active subwoofer	599.99





PEAVEY PV® SERIES

POWERED LOUDSPEAKERS Both portable powered enclosures are rated at 400W program and feature DDTTM compression, RXTM 14 titanium compression drivers, 15" woofers with 2.375" voice coils, and LED signal present and DDTTM activation indicators. Also has combination 1/4"/XLR inputs, as well as XLR and 1/4" through outputs. Carpet covered with integrated pole mounts



as vriv and 1/	a infough outputs. Carpet covered with integrated	i pore mounts.
ITEM	DESCRIPTION	PRICE
PV115D	Powered loudspeaker with (1) 15" woofer	
PV215D	Powered loudspeaker with (2) 15" woofers	499.99







PEAVEY PR SERIES SPEAKERS Constructed with a lightweight molded polypropylene exterior, these speakers are ideal for live music or speech applications. All models feature woofers with 2.375" voice coils, 1.4" titanium compression driver, a 90°x40° constant directivity horn, top and bottom flying point inserts and a molded pole mount. Each of the PR series speakers can handle 400W program and 800W peak at 8 Ω and feature two 1/4" inputs to allow for daisy-chaining with other speakers. The PRSUB's woofer sports a 2.5" voice coil and has the same power rating as the other PR series speaker models.

ITEM	DESCRIPTION	PRICE
PR10	10" 2-way, passive, 400W, 54Hz-21kHz	184.99
PR12	12" 2-way, passive, 400W, 54Hz-21kHz	209.99
PR15	15" 2-way, passive, 400W, 49Hz-21kHz	249.99
PRSUB	15" passive subwoofer, 400W, 45Hz-3kHz (-10 dB, half space)	239.99

Follow Us!



PEAVEY ELEMENTS™ WEATHER-RESISTANT SPEAKERS

The C Series features composite fiberboard enclosures which remain stable in wet conditions, yet have the resonant properties of wood. The M Series have rugged molded cabinets and feature stainless multi-fly-point hardware. All models are IP45 rated, have weatherproof Black Widow® woofers and RXTM22 2" titanium diaphragm compression driver tweeters (expect the 108C). Can be ordered in 60°x40° or 105°x60° coverage patterns.

ITEM	DESCRIPTION	PRICE
Elements C Series		
108C	. 8" 2-way speaker, 75°x75° horn	. 599.99
112C	. 12" 2-way speaker, Quadratic-Throat Waveguide® rotatable horn	899.99
115C	. 15" 2-way speaker, Quadratic-Throat Waveguide® rotatable horn	999.99
Elements M Series		
108M	. 8" 2-way speaker, Quadratic-Throat Waveguide® rotatable horn	499.99
110M	. 10" 2-way speaker, Quadratic-Throat Waveguide® rotatable horn	699.99
	. 12" 2-way speaker, Quadratic-Throat Waveguide® rotatable horn	
	. 2x12" subwoofer	

PRICES SUBJECT TO CHANGE WITHOUT NOTICE. Call today or shop online!



QSC K SERIES POWERED LOUDSPEAKERS

These lightweight powered loudspeakers feature 1000 Class 'D' power modules and are fitted with identical 1.75" HF transducers (expect for the KSUB). Also features auto-standby mode, XLR and 1/4" TRS mic/line level ins, RCA phono-ins, direct-outs on each channel, a balanced out for daisy-chaining up to three sources and extensive DSP processing. EQ settings for both the high-freq. and low-freq. transducers are adjustable on each unit. LEDs can be set to show when the unit is on or when its clip limiter has been engaged. The extended bass LF setting allows for integration of an external subwoofer into the sound system. The KSUB includes a threaded pole-mount receptacle. The K8/10/12 speakers feature fly-mount options as well as the Tilt-DirectTM pole cup mounting system for 7.5° downward tilt for better sound coverage. Multiple units can be daisy-chained for total gain control from a single remote pot. All units feature steel grills and are housed in an ABS enclosure, except for the KSUB in a birch housing.

	DESCRIPTION .8" LF, 1.75" HF transducers, 105° coverage pattern, 127dB max SPL .10" LF, 1.75" HF transducers, 90° coverage pattern, 129dB max SPL	
K12 KSUB	12° LF, 1.75° HF transducers, 75° coverage pattern, 131dB max SPL. Dual 12° bandpass transducer, 130dB max SPL, with threaded speaker pole Rolling speaker bag for K10/K12.	

QSC KW SERIES LOUDSPEAKERS

Designed to provide the performance of QSC's K Series in a lightweight birch enclosure. Features 1000W Class 'D' power modules (2 x 500W continuous) on all of its models. The series' Directivity Matched Transition[™] technology offers matched LF and HF coverage, eliminating hot or dead frequency zones. The series also offers GuardRail^{™M} protection from clipping and excursion limiting. The 122 and 152 bear tilting pole mount systems, while the 153 is pole-mountable, but cannot tilt. All models feature a four-position mic/line gain switch, mic/line level XLR/1/4" TRS inputs, and RCA phono inputs (except on the KW181). Each channel offers separate direct outs. Up to three audio sources can be internally mixed and summed to a balanced out as well. Preset EQ setting switches are featured on-board.

ITEM DESCRIPTION PRICF KW122 .1000W 2-way active loudspeaker, with 12" LF driver, 1.75" comp. driver.... 1099.00 KW152 1000W 2-way active loudspeaker, with 15" LF driver, 1.75" comp. driver.....1199.00 KW153 1000W 3-way active loudspeaker, with 12" LF driver, 6.5" midrange, 1.75" comp. driver..1439.00 KW181. Eye bolt kit for KW122, 152, 153..... KW-M10-KIT .39.99 KW-SUS-KIT-122 ..Suspension kit for KW122, 152, 153..... 59 99



QSC ACOUSTICPERFORMANCE™ HIGH-OUTPUT INSTALL SPEAKERS

These are professional, 2-way, full-range loudspeakers ideal for installed sound reinforcement applications requiring high power in a stylish enclosure. All models feature a 3" voice coil compression driver combined with high-output woofers to deliver exceptional full bandwidth reproduction. They have M10 mounting points for eye-bolts as well as mount points for an optional yoke bracket, NLA Speakon connectors, covered barrier strip terminals and are biamp/passive switchable. Models below are black but also available in white (except the AP-5122M.).

ITEM	DESCRIPTION	PRICE
AP-5102	10" 2-way speaker, 450W, 8Ω, 105° coverage pattern, 127dB max SPL	
AP-5122		
AP-5122M		
AP-5152		
AP-YM10-BK	Yoke mount for the AP-5102, black	
AP-YM12-BK	Yoke mount for the AP-5122, black	
AP-YM12M-BK	Yoke mount for the AP-5122M, black	





Shop fullcompass.com today!

For expert advice - call: 800-356-5844 M-F: 9:00-5:30 Central



SOUND REINFORCEMENT SPEAKERS



M PreSonus

PRESONUS STUDIOLIVE AI ACTIVE PA SYSTEM

Each of these flexible, powerful PA speakers is powered by Active Integration technology, allowing them to sense, interact and work together either wired or wirelessly via a custom chip that's a full computer containing an OS, wireless/Ethernet communications and RAM. Active Integration doesn't stop at remote control, with the StudioLive Dante upgrade, your StudioLive speakers can be fully integrated into a Dante network – with all of the benefits of Audinate's Dante technology. All models include a combo XLR/TRS line input, XLR microphone input with integrated XMAX® preamp, +12V phantom power, XLR mix output, speaker level control, USB and Ethercon connections, M10 fly points, side handles and angle-adjustable dual-position pole mount sockets.

ITEM	DESCRIPTION	PRICE
STUDIO-LIVE-312AI	12"/8"/1.75",2000W 3-way active speaker	1499.95
STUDIO-LIVE-315AI	As above, but 15"/8"/1.75"	1699.95
STUDIO-LIVE-32-8-AI	As above, but 2x8"/1.75"	1599.95
STUDIO-LIVE-18SAI	18", 1000W active subwoofer	1499.95
SL-DANTE-SPK	Dante option card for StudioLive AI Speakers	199.95





m RENKUS-HEINZ

RENKUS-HEINZ CFX SERIES Ideal for portable or permanent install applications. All models (except CFX61/CFX121M) feature tripod sockets for pole-mounting and 6 UMH attachment points to fly the cabinets using eyebolts. Speakers feature unique Complex Conic horns, designed on the spherical expansion of the acoustic pressure wave. The Complex Conic flare changes smoothly from a narrow diffraction slot, through an oval expansion, to a circular mouth producing smooth pattern control. Passive models are listed here but can be upgraded to active models with an optional Class 'D' amp or RHAON-empowered amps. The resulting RHAON (Renkus-Heinz Audio Operations Network) empowered versions allow you to use Cobranet-based digital audio distribution and control your system via free software for any Windows-based computer, using standard Ethernet hardware and cabling. All CFX passive models are provided with both looping 4-pin Neutrik Speakon type connectors and screw-type terminal strips. Models available in black or white. Call your Sales Pro to order speakers with amp modules factory-installed or find out various mounting options.

Follow Us!

SAMSON

SAMSON RX SERIES PA SPEAKERS

These high-performance two-way passive speakers are perfect for houses of worship, gigging musicians or anyone who needs crystalclear sound from a versatile speaker. All models offer 60°x90° horns (except the RSX118S subwoofer) and Celestion drivers; 1" CDX1-1010 PETP compression drivers on RSX110 & RSX112 and



CDX1-1747 1.75" drivers on RSX115 & RSX215. Other common features include dual Speakon® and 1/4" parallel speaker inputs, 1-3/8" pole mount receptacle, (12) M10 fly points, integrated carrying handle and durable black textured finish. RSX215 features a custom 3-way crossover network.

ITEM	DESCRIPTION	PRICE
RSX110		
RSX112		
RSX115		
RSX215		599.99
RSX118S	600W. 1x18" subwoofer	599.99

OTurbosound

TURBOSOUND MILAN SERIES PORTABLE ACTIVE LOUDSPEAKERS

The Milan series has been designed with flexibility and high performance in mind. All models feature Klark Teknik Class 'D' amplification, and full-range models also feature powerful DSP from Klark Teknik. Full-range models also



feature two separate input channels with XLR/TRS combo jacks, two-band EQ, Mix Out function for system expansion, M10 rigging points, dual-angle pole mount and polypropylene construction. The M10 features a 10" woofer and 1" dome compression driver with total peak output of 600W, M12 features a 12" woofer and 1100W peak power and the M15 features a 15" woofer and 1100W peak power. The M15B and M18B subwoofers provide 2200W of peak power from their respective 15" and 18" woofers. Both subwoofers feature all-birch plywood construction, (2) XLR/TRS combo jack inputs, (2) XLR male thru jacks, switchable 3dB boost for frequencies between 40 Hz and 90Hz and polarity switch for avoiding potential phase issues in multi-sub setups.

ITEM	DESCRIPTION	PRICE
MILAN-M10	10" 600W peak active loudspeaker, 55Hz-18kHz, 126dB SPL max	399.00
MILAN-M12	12" 1100W peak active loudspeaker, 50Hz-18kHz, 128dB SPL max	499.00
MILAN-M15	15" 1100W peak active loudspeaker, 45Hz-18kHz, 130dB SPL max	.599.00
MILAN-M15B	15" 2200W peak active subwoofer, 45Hz-100Hz, 134dB SPL max	799.00
MILAN-M18B	18" 2200W peak active subwoofer, 40Hz-100Hz, 134dB SPL max	899.00

Technomad TECHNOMAD NOHO LOUDSPEAKER

We offer over 700 brands, low prices and outstanding service.

The military-specification Noho offers a remarkable combination of high-output, wide-dispersion, long-throw, and excellent fidelity. An ideal choice for sports facilities, touring sound, military applications, or anywhere you need no-compromises outdoor audio. The Noho features a 1" HF compression driver, on a 120° horn for wide coverage, remarkable throw, and an open, natural



sound. A custom-engineered 12" LF driver delivers astonishing bass. A 3-layer stainless WeatherTechTM grill, self-draining cabinet design, proprietary anti-fungal treatments, and fuse protection circuitry make the Noho virtually "unkillable". Two models are offered: the Install Model for indoor or outdoor installations; and the Tour Model which comes with recessed folding handles and a gasketed clamp-on lid that converts the Noho into an indestructible ATA-III flight case for secure transport. 14 optional colors by special order (upcharge applies). Priced each.

ITEM	DESCRIPTION	PRICE
NOHO-C-INSTALL	12" 2-way speaker, 275W, Neutrik NL4	887.36
NOHO-C-TOUR	12" 2-way speaker, 275W, Neutrik NL4	1218.68

EXAMAHA

YAMAHA DXR AND DXS SERIES ACTIVE LOUDSPEAKERS

The DXR and DXS speakers use custom-designed transducers mated with highly-efficient Class 'D' amplifiers to generate up to 133dB with 700W of power. The DXR series feature an intelligent 3-ch mixer, flexible I/O, custom-designed DXR transducers, and the unique Smart Mixing/Linking function. Durable ABS enclosures can be mounted via rigging points, dual-angle pole socket, or optional U-brackets. DXS subwoofers feature D-XSUB processing and perfectly complement the DXR series.

ITEM	DESCRIPTION	PRICE
DXR8	. 700W, 129dB SPL, 57Hz-20kHz, 8" LFT	549.99
DXR10	. 700W, 131dB SPL, 56Hz-20kHz, 10" LFT	
DXR12	. 700W, 132dB SPL, 52Hz-20kHz, 12" LFT	
DXR15	. 700W, 133dB SPL, 49Hz-20kHz, 15" LFT	799.99
DXS12	. 600W, 131dB SPL, 45Hz-160Hz, 12" LFT	
DXS15	. 600W, 132dB SPL, 45Hz-160Hz, 15" LFT	799.99



YAMAHA CLUB-V PASSIVE LOUDSPEAKERS A best buy in price and performance. Great sounding speakers available in carpet covered, elastomeric spray finished and flyable models. The portable models have heavy-duty handles, pole socket and steel grill. All models are 2-way and powered by true compression drivers. Custom Eminence drivers are used, the horns have a 90x40 constant directivity pattern. Connectors are Neutrik Speakon and Switchcraft 1/4" with two of each connector for easy daisy chaining.

nootor for ouoj du	ioj chaming.	
ITEM	DESCRIPTION	PRICE
	orthy, rugged carpet covered models	
\$112V	12" 2-way, 350W/8Ω, 60Hz-16kHz	339.99
S115V	15" 2-way, 500W/8Ω, 55Hz-16kHz	379.99
S215V	Dual-15" 2-way, 1000W/4Ω, 42Hz-16kHz	599.99
SM10V	10" floor monitor, 250W/8Q, 70Hz-20kHz	299.99
SM12V	12" floor monitor, 350W/8Ω, 60Hz-16kHz	349.99
SM15V	15" floor monitor, 500W/8Ω, 55Hz-16kHz	399.99
SW118V	18" subwoofer, 600W/8Ω, 30Hz-2kHz	459.99
SW218V	Dual-18" subwoofer, 1200W/4Ω, 30Hz-2kHz	649.99
	spray finished models with foamed steel grilles	
C112V	12" 2-way, 350W/8Ω, 60Hz-16kHz	349.99
	15" 2-way, 500W/8Ω, 55Hz-16kHz	
C215V	Dual-15" 2-way, 1000W/4Q, 42Hz-16kHz	699.99
CM10V	10" floor monitor, 250W/8Ω, 70Hz-20kHz	289.99
CM12V	12" floor monitor, 350W/8Q, 60Hz-16kHz	359.99
CM15V	15" floor monitor, 500W/8Q, 55Hz-16kHz	419.99
CW118V	18" subwoofer, 600W/8Ω, 30Hz-2kHz	509.99
CW218V	Dual-18" subwoofer, 1200W/4Q, 30Hz-2kHz	749.99
Flyable Models: in	deal for installations	
C112VA	12" 2-way, 350W/8Ω, 60Hz-16kHz	409.99
C115VA	15" 2-way, 500W/8Ω, 55Hz-16kHz	449.99

YAMAHA BR-SERIES PASSIVE SPEAKERS

BR models are designed to fit the budgets of performing musicians, small churches, and schools. Each model's large steel handles, corner protec-



tors, and built-in pole sockets, assure both durability and flexibility. High-frequency response is also enhanced with a new titanium HF driver and 90° by 40° non-resonant horn. All BR-Series models are covered by a 3-year warranty. With integral protection circuitry built into the passive crossover, you can expect a long life of high output and minimal distortion. Speakers feature dual phone jack inputs.

		,	•	
ITEM	DESCRIPTION			PRICE
BR10	. 10" 2-way speaker, 250W	/8Ω, 65Hz-20	0kHz	209.99
BR12	. 12" 2-way speaker, 300W	/8Ω, 65Hz-20	0kHz	249.99
BR15	15" 2-way speaker 400W/	8Ω, 60Hz-20	lkHz	289.99
BR12M	. 12" floor monitor, 250W/8	Ω		259.99
BR15M	.15" floor monitor, 400W/8	Ω		299.99

YAMAHA DSR SERIES ACTIVE LOUDSPEAKERS These include a combination

of ultra-sophisticated digital sound processing and the latest acoustic technologies, including D-CONTOUR multiband dynamic processing for



consistent clarity at both high and low output levels. Each incorporates high power Class 'D' amplifiers, a/PFC switching mode power supply, and has 3-way fail-safe DSP protection. Advanced digital sound processing includes FIR-X tuningTM for the smoothest possible crossover transitions and high power DSP, plus 24-bit discrete AD and DA converters for maximum dynamic range. Exclusive LTBD (Long Throw, Broad Dispersion) Constant Directivity Waveguide Horn provides 90° horizontal x 60° vertical coverage with full-frequency sound projected all the way to the edges of the coverage area (except DSR118W). The DSR112 and DSR115 are stand and pole mountable with 35mm pole sockets and have M10 rigging points for suspended installation. DSR112 can be tilted for use as a floor monitor and additional monitors can be daisy-chained via the XLR THRU jack on the rear panel. Models feature XLR and 1/4" TRS inputs (DSR118W has XLR only) that accept both mic and line level input. Easy to handle series capable of 1300W power output (DSR118W is 800W).

input Eacy to namale believe capable of 1999 h power output (Dentrien is even).				
ITEM	DESCRIPTION	PRICE		
DSR112	12" 2-way, biamp powered speaker,			
	60Hz-18kHz (-3db), 134dB SPL, 47lbs			
DSR115	15" 2-way, biamp powered speaker,			
	55Hz-18kHz (-3db), 136dB SPL, 62lbs			
DSR215	Dual 15" 2-way, biamp powered speaker,			
	55Hz-18kHz (-3db), 138dB SPL, 110lbs			
DSR118W				
	50Hz-110kHz (-3db), 132dB SPL, 93lbs			



YAMAHA MSR SERIES POWERED SPEAKERS

This series offers compact size, big sound and a range of versatile features. Each model features a flexible input mixer section, integrated amplifiers and rugged polypropylene enclosures. A variety of mounting options allow pole mounting, wall mounting or ceiling suspension.

ITEM	DESCRIPTION	PRICE
MSR100	8" 2-way active speaker, 100W	299.99
MSR250	10" 2-way active speaker, 200W	344.74
MSR400	12" 2-way active speaker, 300W (total)	430.92
MSR800W	15" active subwoofer, 500W	664.85

MUSIC COMPUTER AV VIDEO LIGHTS ACCESSORIES

179

MSR800W

Shop fullcompass.com today!

For expert advice - call: 800-356-5844 M-F: 9:00-5:30 Central

