



INTERSTATE BATTERY VIDEO CAMERA REPLACEMENT BATTERIES

| ITEM | REPLACES | OUTPUT | PRICE |
|------------------|-------------|--------|-------|
| SONY | | | |
| CAM0555 | NPF770 | 3.7Ah | 76.84 |
| CAM0840 | NPF970 | 74.8Ah | 92.73 |
| PANASONIC | | | |
| CAM0239 | VWVBG6PPK | 4.8Ah | 75.59 |
| CANON | | | |
| CAM1011 | BP955 | 4.4Ah | 74.85 |
| CAM1010 | BP975 | 6.6Ah | 77.99 |
| CAM0219 | BP-820 | 1.3Ah | 81.19 |
| JVC | | | |
| CAM0162 | BN-VF823USP | 2Ah | 93.74 |

ANTON BAUER

ANTON BAUER TWIN BATTERY CHARGER Light and small 2-position, 60W simultaneous InterActive® battery charger. The plastic enclosure will stand up to rugged use. Its universal wide range mains input (90-250VAC 50/60Hz) makes it the ideal travel charger. Will charge 2 TrimPacs in 2 hours or HyTRON 50s in 3 hours, 2 ProPacs in 3.5 hours or 2 Dionic 90s in 5.5 hours.



| ITEM | DESCRIPTION | PRICE |
|------|---------------------------------|--------|
| TWIN | 60W, 2-position battery charger | 635.00 |

ANTON BAUER DIGITAL DIONIC LITHIUM-ION The DIONIC HCX has a 124 watt-hour capacity and the ability to sustain a 10 amp draw, allowing it to run a 40 watt camera with a 20 watt light for 2 hours. The motion detection feature incorporates a "deep sleep" setting that reduces battery self-discharge, allowing for extended periods of storage with minimal capacity loss. The battery may be "awakened" by the built in motion sensor. The DUAL 2711 PowerCharger can be switched to a 70W power supply allowing you to charge one battery and power a camera simultaneously.



| ITEM | DESCRIPTION | PRICE |
|------------|---------------------------------------|---------|
| DIONIC-HC | 14.4V, 91WH, 1.8 lbs | 337.00 |
| DIONIC-HCX | 14.4V, 124WH, 2.4 lbs | 473.00 |
| DUAL-2722 | 2 position power charger, LCD readout | 1184.00 |

NEW!

DIGITAL-G150



ANTON BAUER DIGITAL BATTERY SERIES The Digital Battery Series meets the needs of the digital video production, while providing top levels of safety, performance and reliability in a sleek design. The integrated LCD panel reports run-time in hours and minutes when attached to a device. The display automatically changes to show battery charge as a percentage of full when not attached to a device or when no load is placed on the battery. Multiple sensors detect temperature and over-current states to minimize the potential of battery damage. The new dual and quad place chargers offer remote battery management and up to 150W of regulated XLR power.

| ITEM | DESCRIPTION | PRICE |
|---------------------|---|---------|
| DIGITAL-G90 | Gold-mount DIGITAL Battery, 14.4 volts, 89 w/h | 379.00 |
| DIGITAL-G150 | Gold-mount DIGITAL Battery, 14.4 volts, 156 w/h | 530.00 |
| DIGITAL-G190 | Gold-mount DIGITAL Battery, 14.4 volts, 194 w/h | 650.00 |
| PERFORMANCE-DUAL-GM | Gold-mount Dual position charger, w/75W PS | 500.00 |
| PERFORMANCE-QUAD-GM | Gold-mount Quad position charger, w/150W PS | 1300.00 |

bescor

BESCOR PSA-124 12V POWER SUPPLY A light-weight, 12V, 4amp power supply (110 or 220V). The 6' power cord has a 4-pin female XLR connector. Weighs 1.2 lbs.



| ITEM | DESCRIPTION | PRICE |
|--------------|---------------------|--------|
| PSA124 | Power supply | 146.72 |
| XL4M-XL4F-10 | 10' extension cable | 46.80 |

EMPIRE VIDEO CAMERA REPLACEMENT BATTERIES AND CHARGER

| ITEM | DESCRIPTION | OUTPUT | PRICE |
|------------------------|---|--------|-------|
| SONY | | | |
| BLI153-6.6C | NPF970 | 6.6Ah | 97.60 |
| BNH109-2.1 | NP66/77/98 | 2.1Ah | 31.27 |
| EPP114-2.3 | NP1SB | 2.3Ah | 80.85 |
| PANASONIC | | | |
| EPP100C | PVBP80/88, AGBP202/212 | 2.3Ah | 33.01 |
| EPP130C | PVBP50, AGBP20 | 2.0Ah | 34.65 |
| UNIVERSAL MODEL | | | |
| VBC-3UN | Universal charger for NiMH, NiCAD, 6V Sony, Panasonic, JVC, Canon | | 52.72 |

I·D·

IDX ENDURA V-MOUNT LITHIUM ION POWERLINK™ BATTERIES

Lithium-Ion V-mount batteries offer the highest energy capacity at a minimal size and weight. The PowerLink™ system allows you to stack 2 V-Mount batteries together on a camera back. This makes using on-camera lights possible without needing a battery belt. The Digi-View™ feature displays accurate battery capacity in the camera viewfinder of many new cameras. Batteries fit directly onto new cameras that have the wedge style V-Mount already built-in, are fully compatible with Sony® V-shoe attachments, can adapt to Anton Bauer Gold Mount™ systems using the optional A-AB2E adaptor plate, or may affix directly to other cameras by adding the P-V or P-VS adaptor plate. These plates have a D-Tab 2-pin connector to allow use of on-camera lights and the P-VS plate supports Syncron, an energy-saving function which activates on-camera lights when recording is engaged and deactivates when the recording is paused.



| ITEM | DESCRIPTION | PRICE |
|--------|--|--------|
| ELITE | 14.8V 142Wh/9.6Ah, air transportable, 2.76 lbs | 664.02 |
| E-HL9 | 14.4V 88Wh/10Ah, PowerLink capable, 5-LED status, supports Digi-View and new Digital Battery Management System, 1.63 lbs | 409.00 |
| E-HL9S | 14.4V 88Wh/6.15Ah, no PowerLink™ or Digi-View™, 3-LED status and limited i-Trax™, 1.59 lbs | 282.00 |
| E7S | Same capacity as E7, no PowerLink™ or Digi-View™, 3-LED status and limited i-Trax™, 1.16 lbs | 259.00 |
| A-AB2E | Adaptor plate to fit ENDURA batteries to 3-stud camera mounts | 156.00 |
| P-V2 | V-Mount camera plate for ENDURA batteries | 91.00 |
| P-VS2 | V-Mount camera plate for ENDURA batteries, includes Syncron | 102.00 |

IDX AC POWER SUPPLIES

The 2-output IA-200a with 100W of power will easily power 2 cameras, a camera and monitor combination, or one very power-hungry camera. You can pull up to 100W from one channel, or any combination equaling 100W from the two outputs. The IA-60a is a 1-output 60W power supply suitable for worldwide operation. Both models have automatic 100-240V sensing and include 1 XLR cable.



| ITEM | DESCRIPTION | PRICE |
|--------|--|--------|
| IA60A | 1-output, 60W, AC 100-240V 50/60Hz power supply | 266.00 |
| IA200A | 2-output, 100W, AC 100-240V 50/60Hz power supply | 467.00 |

IDX ENDURA SYSTEM V-MOUNT CHARGERS

The VL2Plus is 2-channel sequential charger with a built-in 60W power supply and charges (2) E-50 batteries in less than 5 hours. The VL-4S is a 4-channel simultaneous quick charger with a lightweight high-impact molded case and is multi-chemistry capable, charges 4 batteries in 3 hours. The VL-4Si charges 4 batteries simultaneously and includes a LCD display that shows charging information and advanced digital information from ENDURA System E-10/E-80/E7/E50 batteries when connected to the charger. A USB connector is available on back of the charger to connect to your PC.



| ITEM | DESCRIPTION | PRICE |
|---------|---|---------|
| VL2PLUS | 2-channel quick charger/power supply | 441.00 |
| VL4S | 4-channel simultaneous quick charger | 868.00 |
| VL4Si | 4-channel simultaneous quick charger with LCD display | 1043.00 |
| AE2NP | NP type battery to Endura V mount adapter for VL2Plus/VL4S chargers | 247.00 |

Shop fullcompass.com today!

For expert advice - call: 800-356-5844

M-F: 9:00-5:30 Central

