

















COMPUTER AV































# Canon



# CANON POWERSHOT SX280 HS DIGITAL COMPACT CAMERA • 12.8MP 1/2.3" size CMOS sensor

- \*3" TFT color LCD, real-image zoom viewfinder

  Lens & Zoom: 4.5 (W) 90.0 (T) mm
  (35mm film equivalent: 25-500mm), 20x optical zoom, 4x digital zoom, Optical Image Stabilization

  • Digic 6 image processor for faster shooting and auto-focus

  • Uses SD/SDHC/SDXC cards

- · Built-in WiFi and GPS
- AW out, USB 2.0 (mini-B), HDMI out (w/ cables)
  Video includes Full HD @ 1920x1080: 60/30 fps:
- HD @ 1280x720: 30fps, SD @ 640x480: 30fps

POWERSHOT-SX280HS-KT	Compact digital camera	279.99
NB6LH	Replacement battery pack	54.05
TS32GSDHC4	Transcend 32GB Class 4 SDI	HC17.56



# CANON EOS REBEL T51 DIGITAL SLR CAMERA

- 18MP APS-C size CMOS sensor
- · 3" Vari-angle touch screen Clear View LCD monitor II
- SD/SDHC/SDXC memory cards (UHS-I compatible)
- USB, (1) video out terminal (NTSC/PAL selectable),
   (2) mini-HDMI outs (type C auto resolution switching, CEC compatible), hot shoe, 1/8" stereo audio/mic input, built-in mono mic, wired remote terminal, wireless remote control via RC-6
- 9-point Movie Servo AF for continuous focus tracking of moving subjects; records Full HD @ 1920x1080: 30p/24p/25p, HD @ 1280x720: 60p/50p, SD @ 640x480: 30p/25p, MOV file (H.264 image data and Linear PCM stereo audio)

EOS-REBEL-T51-KIT	. Digital SLR camera, no lens	699.99
	. Digital SLR camera w/18-55mm lens	
EOS-REBEL-T5I-18-135	. Digital SLR camera w/18-135mm lens	1049.00
	. Rechargeable Li-ion battery pack	
TS16GSDHC10	.Transcend 16GB Class 10 SDHC, 20MB/s	9.60



# CANON EOS 5D MKIII DIGITAL SLR CAMERA

- · 22.3MP High-sensitivity full frame CMOS sensor
- 3.2" TFT color LCD monitor
- Uses CF Cards (Type I), compatible with UDMA CF cards, uses SD, SDHC, and SDXC memory cards
- Features USB, (1) video out (NTSC/PAL selectable) Features USB, (1) video out (NTSC/PAL selectable) with stereo audio out, (1) mini-HDMI out, hot-shoe, 1/8" stereo audio/mic in, built-in mono mic, 1/8" headphone jack, wired remote terminal, wireless remote control via RC-6, wireless file transmission WFT-E7A, GP-E2 connection for GPS options Video includes full HD at 1920x1080; 30p/24p/25p, 110x + 1920x709 SD = £40x480; 30x59
- HD at 1280x720, SD at 640x480: 30p/25p,

MOV file (H.264 image data and Linear PCM stereo audio) EOS-5DMKIII-24-105KT. Full frame DSLR camera kit with 24-105mm f/4L IS USM AF Lens.





# CANON EOS M MIRRORLESS DIGITAL CAMERA • 18MP APS-C size CMOS sensor

- · 3" TFT color, liquid-crystal monitor with Touch Panel LCD
- Uses SD/SDHC/SDXC memory cards
  Features USB, (1) video out terminal
  (NTSC/PAL selectable), (2) mini-HDMI outs,
  hot shoe, built-in stereo mic

  Uses SD/SDHC/SDXC memory cards

  Features USB, (1) video out terminal
  (NTSC/PAL selectable), (2) mini-HDMI outs,
  hot shoe, built-in stereo mic
- not snoe, bull:-in stereo mic

  Has full HD at 1920x1080: 30p/24p/25p,
  HD at 1280x720: 60p/50p,
  SD at 640x480: 30p/25p, MOV file
  (H.264 image data and Linear PCM stereo audio)

EOS-M-KIT-22 Digital single-lens non-reflex,	
mirrorless AF/AE camera with 22mm lens59	9.99
LP-E12Replacement battery pack	2.37
TS32GSDHC10Transcend 32GB Class 10 SDHC, 20MB/s	8.19



### **CANON EOS-60D DIGITAL SLR CAMERA**

- 18MP APS-C size CMOS sensor

- 3" TFT color flip-out liquid crystal monitor
   SD/SDHC/SDXC memory cards
   USB, (1) video out terminal (NTSC/PAL selectable),
   (1) mini-HDMI out, hot shoe, 1/8" stereo audio/mic input, built-in mono mic, wired remote terminal,
- wireless remote control via RC-6/RC-1/RC-5
   Full HD at 1920x1080: 30p/24p/25p,
  HD at 1280x720: 60p/50p, SD at 640x480: 60p/50p,
  MOV file (H.264 image data and Linear PCM stereo audio)

EOS-60D/EF/18-135-KT Digital SLR camera with 18-135mm lens 1199	0.00
EOS-60D/EF/18-200-KT Digital SLR camera with 18-200mm lens. 1299	.00
LP-E6Spare battery pack83	.16
TS16GSDHC10 Transcend 16GB Class 10 SDHC 20MB/s 9	160



- CANON EOS GD DSLR CAMERA

   20.2 Megapixel Full-Frame CMOS Sensor
   3.0-inch Clear View TFT LCD monitor
   Uses SD, SDHC, SDXC memory cards (UHS-I compatible)
   Remote control via EOS smartphone app
   On-board Wi-Fi@ transmitter and built-in GPS receiver
   USB, Video Out Terminal (1) AV stereo OUT terminal: NTSC/
  PAL selectable, (2) mini-HDMI OUT terminal (Type C)
   11-point AF with high-precision center cross-type AF point with
  EV-3 sensitivity for focusing in extreme low-light conditions
   Continuous shooting up to 4.5 fps
   Image formats. Still. IPPG, RAW (14-bit, Canon original),
  RAW+JPEG, Video: MOV(H/264, Audio: Linear PCM) Full
  HD@1920x108u30x25x24, 1280x720x5060, SD@640x480x25x60
   Includes eyecup, neck strap, battery and charger, AV cable,
- Includes eyecup, neck strap, battery and charger, AV cable, USB cable EOS-6D-KIT.. . 20.2 MP DSLR camera body without lens .. 1899.00

64GB class 10 SDXC memory card (by Transcend). 33.37



# CANON EOS REBEL T31 EF-S DIGITAL SLR

- 18MP APS-C size CMOS sensor

- The color flip-out liquid crystal monitor
   SDSDHCSDXC memory cards
   USB, (1) video out terminal (NTSCPAL selectable),
   mi-HDMI outs (type C auto resolution switching, CEC compatible), hot shoe, 1/8" stereo audio/mic input, built-in mono mic, wired remote terminal, wireless remote control via RC-6
   Full HD at 1920x1080: 30p/24p/25p,
- HD at 1280x720: 60p-50p., HD at 1280x720: 60p-50p., SD at 640x480: 30p/25p, MOV file (H.264 image data and Linear PCM stereo audio)

EOS-REBEL-T31-	-18-55 Digi	tal SLF	? came	ra with	18-55mr	n lens .	599.99
LP-E8	Replacemer	nt rech	argeal	ole Li-io	on battery	pack.	62.37
TS16GSDHC10.	Transcend	16GB	Class	10 SD	HC, 20MI	3/s	9.60



### **CANON EOS-70D DIGITAL SLR CAMERA**

- 20.9MP APS-C size CMOS sensor
- 3" Vari-angle touch screen Clear View LCD monitor II
   SD/SDHC/SDXC memory cards (UHS-I compatible)
- WiFi built-in
- USB, (1) video out terminal (NTSC/PAL selectable),
   (1) mini-HDMI out, hot shoe, 1/8" stereo audio/mic input, built-in mono mic, wired remote terminal, wireless remote control via RC-6
- . 19-point dual pixel Movie Servo AF for continuous 13-point dual pixel involve Serva i for Commonds focus tracking of moving subjects; records Full HD @ 1920x1080: 30p/24p/25p, HD @ 1280x720: 60p/50p, SD @ 640x480: 30p/25p, MOV file (H.264 image data and Linear PCM stereo audio)

	0		-
EOS-70D-KIT	Digital SLR c	amera	1199.00
EOS-70D-EF-S1	8/135MM Digital SLR c	amera w/18-135mm	lens 1549.00
EOS-70D-EF-S	18/55MMDigital SLR c	amera w/18-200mm	lens 1349.00
LP-E6	Spare batter	y pack	83.16
TS16GSDHC10	Transcend 16	ốĠB Class 10 SDHC, 2	20MB/s9.60



### **CANON EOS (SLR) LENSES**

Standard Zoom
9517A002EF-S 17-85mm f/4-5.6 IS USM (Not for 35mm
film/full frame sensors, APS-C size only) 586.3
<b>5175B002</b> EF 24-70mm f/2.8L II USM
0344B002EF 24-105mm f/4L IS USM
Telephoto Zoom
9322A002EF 28-300mm f/3.5-5.6L IS USM
9321A002EF 70-300mm f/4.5-5.6 DO IS USM
Wide-Angle
2510A003EF 28mm f/1.8 USM
Standard and Medium Telephoto
2515A003EF 50mm f/1.4 USM
2519A003EF 85mm f/1.8 USM
Super Telephoto
2526A004EF 400mm f/5.6L USM
Macro
4657A006EF 100mm f/2.8 Macro USM











# PANASONIC LUMIX FZ1000 4K QFHD/HD 16X LONG ZOOM DIGITAL CAMERA

- Macro Photography to 3cm
   1" 20.1MP MOS sensor
- 5-AXIS Correction / Tilt Correction (excluding 4K)
- Bright Leica DC lens 25-400mm (16x optical zoom),
- Super-fast LUMIX Depth From Defocus (DFD) Auto-Focus technology

  Integrated smartphone WiFi for geotagging,
- and remote viewing/shooting
- In-camera playback screen grabs from 4K video for 8-megapixel (3840 x 2160) hybrid photography stills

DMC-FZ1000......LUMIX 4K QFHD/HD digital camera ......899.99

### **Panasonic**



### PANASONIC DMC-GH4 **LUMIX MIRRORLESS DSLR BODY (NO LENS)**

- 16MP Live MOS sensor, micro four thirds
- interchangeable lens mount
   Uses SD/SDHC/SDXC memory cards
- Supersonic wave filter image sensor dust reduction
- system • 3" OLED Live View finder (2,359K dots) with static touch
- control • USB, HDMI, MicroHD TypeD, WiFi support, 3.5mm input
- for external microphone, on-board stereo mic
   Still Image formats: 4:3/3:2/16:9 aspects: up to 4608x3456,
- Still aspect: up to 3456x3456
   Video formats: MOV (up to 4096x2160/24.00p), MP4 (up to 4096x2160/24.00p), AVCHD (up to 1920x1080/59.94p)

DMC-GH4KB0DY	.LUMIX 4K DSLR body, no lens	1699.99
DMW-BGGH3	.Battery grip	219.74
DMW-BLF19	.Battery	79.95
DMW-MS2	.External stereo/shot gun	
	switchable microphone	349.95
DMW-FL500	.External flash	599.95
TS64GSDXC10	.64GB Class 10 SDXC Card	33.37

## SONY



- SONY α6000 DIGITAL E-MOUNT CAMERA
   24.3MP Exmor APS HD CMOS sensor + BIONZ X image processor
- 3" tiltable LCD screen & OLED Tru-Finder electronic
- 0.06 second autofocus, takes 11 photo/sec
   Full 1080 HD AVCHD or MP4 video recording at 60p, 24p, H.264 compression
- Multi interface shoe, HDMI micro Type D, USB 2.0 Hi-Speed
- One-touch sharing over WiFi or NFC (Near Field Communication) with PlayMemories Mobile app
- Communication) with Flayweinteries whome app (not included)
   Uses SD/SDHC/SDXC cards (UHS-I compliant) and Memory Stick PRO Duo/PRO-HG Duo/XC-HG Duo Audio Dolby Digital (AC-3) 2ch, Dolby Digital Stereo Creator for AVCHD, MPEG-4 AAC-LC 2ch for MP4

ILCE-6000/B	. Compact	digital SLR	camera, b	ody only	CALL
ILCE-6000L/B	. As above	with SELP1	1650 lens		CALL
TS32GSDHC10	Transcen	d 32GR Clas	s 10 SDHO	20MR/s	18 19

ILCE-6000/B Compact digital SLR camera, body only	CAL
ILCE-6000L/B As above, with SELP1650 lens	CALI
TS32GSDHC10 Transcend 32GB Class 10 SDHC, 20MB/s	18.19

# **Panasonic**



### PANASONIC DMC-GM1KS

### COMPACT DIGITAL SLR CAMERA

- 16MP Live MOS sensor, micro 4/3" interchangeable lens mount
- USB 2.0 digital interface, MicroHDMI TypeD,
- USB 2.0 tingtial interface, microribini 19peb,
   WiFi compliant, built-in stereo mic
   AVCHD (Audio format: Dolby Digital 2 ch); Full HD at 1920x1080: 60i, HD at 1280x720: 60p, MP4 (Audio format AAC 2 ch); Full HD at 1920x1080: 30fps: HD at 1280x720: 200x 1280x1080 30fps, SD at 640x480: 30fps

DMC-GM1KS Digital SLR camera with	
12-32mm lens kit (in silver)	49.99
DMW-BLH7Replacement battery pack	59.95
TS64GSDXC10 64GB Class 10 SDXC memory card	33.37

HFS100300

HF008

## SONY



- SONY DSC-RX100 CYBER-SHOT® DIGITAL CAMERA 20.2MP, 1" Exmor™ CMOS sensor 3" TFT color LCD
- Carl Zeiss® Vario-Sonnar lens, 3.6x optical zoom
   (4:3 ratio 35mm film equivalent: 30-108mm zoom may differ slightly for Movie mode), 20x digital zoom, Optical Steady Shot mode option • Uses Memory Stick Duo, Memory Stick PRO Duo, Memory Stick PRO Duo (High Speed), Memory Stick
- PRO-HG Duo, SD/SDHC/SDXC memory cards
- Micro USB, Hi-Speed USB (USB2.0), Micro HDMI
   AVCHD Full HD at 1920x1080: 60p;

MP4 - HD at	1440x1080, 30fps,	SD at 640x480:	30fps
SCRX100/B	Cyber-shot digital	camera	(

DSCRX100/B	. Cyber-shot digital camera	CALL
NPBX1	Replacement battery pack	48.04
TS32GSDHC10	.Transcend 32GB Class 10 SDHC, 20MB/s	18.19



# SONY $\alpha 7S$ 35MM full frame mirrorless E-mount camera

- 12.2MP sensor for 4K and low light video
- 35mm Exmor CMOS large pixel sensor w/ 15.3 stops of
- Fast Intelligent AF with low light sensitivity down to -4EV
   Outputs uncompressed QFHD 4K video (3840x2160) in 8-bit 4:2:2 via HDMI
- 3" tiltable LCD screen, OLED Tru-Finder electronic
- viewfinder One-touch sharing/remote via WiFi or NFC
- AVCHD 1080/60p recording @ 28Mbps, MP4 1080/30p recording @ 12Mbps
- Multi interface shoe and USB 2.0 hi-speed
   Uses SD/SDHC/SDXC cards (UHS-I compliant) and Memory Stick PRO Duo/PRO-HG Duo/XC-HG Duo

ILCE7S/B...... 35mm full frame mirrorless E-mount camera, body only.

# **Panasonic**



PANASUNIC LUMIX MICRU 4/3" LENSES	
Standard Lenses	
HH014Lumix G 14mm/F2.5	399.9
HX025Lumix G 25mm/F1.4	629.99
HF008Lumix G Fisheye 8mm/F3.5	799.9
HESO45 Leica DG Macro-Elmarit 45mm/F2.8	899.9
3D Lens	
HFT012 Lumix G 12.5mm/F12	249.9
Zoom Lenses	
HF007014Lumix G Vario 7-14mm/F4.0	1199.9
HFS14140KLumix G Vario HD 14-140mm/F4.0-F5.8.	699.99
HFS045200Lumix G VARIO 45-200mm / F4.0-5.6	329.9
HFS100300Lumix G Vario 100-300mm/F4.0-5.6	599.9

# SONY





### SONY CANON EF & EF-S SLR LENSES

E-MOUNT LENSES (FOR A6000)

SEL16F28	E 16mm F2.8	CALL
SEL35F18	E 35mm F1.8 OSS	CALL
SEL50F18/B	E 50mm F1.8 OSS	CALL
SEL1018	E 10-18mm F4 OSS	CALL
SEL55210	E 55-210mm F4.5-6.3 OSS	CALL
SEL1670Z	Vario-Tessar T* E 16-70mm F4 ZA OSS	CALL
E-MOUNT FUL	L FRAME LENSES (FOR A7 SERIES)	
SEL2470Z	Vario-Tessar T* FE 24-70mm F4 ZA	CALL
SEL2870	FE 28-70mm F3.5-5.6 OSS	CALL
SEL35F28Z	Sonnar T* FE 35mm F2.8 ZA	CALL
SEL55F18Z	Sonnar T* FE 55mm F1.8 ZA	CALL
CEL 70200C	EE 70 200mm E4 C 000	CALL

# SONY NEWi

### SONY α7 SERIES E-MOUNT CAMERAS

- Full frame 24.3MP resolution (36.4MP on the 7R) with 14-bit RAW recording
- Fast Hybrid AF with phase detection, Fast Intelligent AF optimized for full-frame sensor
   3" tiltable LCD screen, XGA OLED Tru-Finder electronic viewfinder

  | Company |
- AVCHD Full HD up to 1080/60p, MP4 up to 1080/30p
   Uses Memory Stick Pro Duo/PRO-HG Duo/XC-HG Duo and SD/SDHC/SDXC (UHS-I compliant) cards
   Multi interface shoe, HDMI Type D micro, USB 2.0 hi-speed, built-in WiFi

body only.....

• •	
ILCE7/B24.3MP a7 full frame mirrorless camera,	
body only	CALL
ILCE7K/B As above, with 28-70mm full frame lens	
ILCE7R/B36.4MP a7 full frame mirrorless camera.	















































.....FE 70-200mm F4 G OSS .....






















































GIOTTOS VGR CLASSIC TRIPODS It's a tripod and monopod in one. One leg of the tripod combined with the center column converts to a monopod that can be expanded up to 68". The legs are made of carbon fiber or aluminum and feature Giotto's SDL dust-proof locking system with 1/8" turn leg locks. They also feature rubber feet with metal spike (on some models), bubble level and retractable hook. The included quick-release ballhead has bubble levels and is Arca-compatible. Every kit also includes a carrying bag.

TECH SPECS	VGR8255	VGR8265	VGR9254	VGR9255	VGR9264	VGR9265
LOAD CAP	8.8 lbs	13 lbs	8.8 lbs	8.8 lbs	13 lbs	13 lbs.
MAX HEIGHT	65"	67.3"	61"	65"	65"	67.3"
MIN HEIGHT	10.6"	11.2"	11.2"	10.6"	11.7"	11.2"
WEIGHT	2.8 lbs	3.7 lbs	3.3 lbs	3.3 lbs	4.3 lbs	4.3 lbs.
STAGES	5	5	4	5	4	5
MATERIAI	CF	CF	ΔΙ	ΔΙ	ΔΙ	ΔΙ

ITEM	DESCRIPTION	PRICE
VGR8255-S2N	. Carbon fiber tripod/monopod with quick-release ballhead	425.99
VGR8265-M2N	. Carbon fiber tripod/monopod with quick-release ballhead	499.99
VGR9254-S2N	. Aluminum tripod/monopod with quick-release ballhead	259.99
VGR9255-S2N	. Aluminum tripod/monopod with quick-release ballhead	305.99
VGR9264-M2N	. Aluminum tripod/monopod with quick-release ballhead	299.99
VGR9265-M2N	. Aluminum tripod/monopod with quick-release ballhead	305.99
MH646	. QR plate replacement for VGR8265, VGR9264, VGR9265	29.99
MH645	. QR plate replacement for VGR8255, VGR9254, VGR9255	27.99

GIOTTOS CLEANING SUPPLIES Keep your camera or other electronic device clean with the CL1001 cleaning kit. It contains the Rocket-Air blaster, which provides a powerful stream of air to blow dust away and a special air valve to prevent it from breathing in dust. The multipurpose cleaning solution is suitable for all cameras, lenses, computers screens and LCD monitors. The kit contains a retracting two-position goat's hair brush, white microfiber cloth, small Rocket-Air blaster, 30 ml of cleaning



# gepe

CL3614

GEPE CARDSAFE The CardSafe holders feature 3 or 4 multi-card compartments made with an anti-static inner material and are shock-resistant, dust and weatherproof and float. The CardSafe Extreme is also crushproof,

Micro fiber cloth, 15"x11"

watertight and ha	s an ergonomic lock and reinforced	
hinge. Available in	black or neon yellow.	
ITEM	DESCRIPTION	PRICE
3861E	Fits CF, SD, MMC, Memory Stick and Smart Media cards, black	34.99
3862E	As above, neon yellow	34.99
	Fits SD, MMC, Memory Stick Duo, SD-Mini, XD, black	
3854	As above, neon yellow	21.99

# ikan

**IKAN EV2 ELEMENTS** The EV2 Elements Series from ikan is a lightweight solution for DSLRs and camcorders. These modular systems are easy to assemble and disassemble. The DragonFly, DeluxeFly EV2 and SuperFly EV2 offer instant stability in a 2

handled solution with multiple mounting options for accessories like ikan monitors and LED lights. The ikan Stealth is a premium shoulder stabilizer for camcorders with an adjustable baseplate mounted on a 15mm rod system, with multiple mounting options including an optional battery plate for Anton Bauer, V-Mount or DV type batteries.

ITEM	DESCRIPTION	PRICE
ELE-DRGFLY	DragonFly camera support rig	134.00
ELE-EV2DF	DeluxeFly camera support rig kit, base plate,	
	two 12" rods, 2 long arms, 2 utility grips	161.00
ELE-EV2SF	SuperFly camera support rig kit, two 12" 15mm rods, base plate,	
	cheese plate, 2 long bar hand grips, 4 extra long handle arms	224.00
ELE-STLH-ENG	Stealth Rod-based shoulder mount kit, two 12" 15mm rods,	
	Elements handle arm, double cheese plate	629.00

# ikan

**IKAN FLYWEIGHT SYSTEM** The Flyweight system from ikan uses the existing EV2 Elements series, with a new lightweight shoulder stock and new heavy-duty, rubberized-hand grips. Both the Flyweight DSLR (utilizing ikan's EV2 DSLR adjustable baseplate), and Flyweight Camcorder (utilizing ikan's EV2 full size camcorder adjustable baseplate), ship with key components

weight bag is included, which can be filled with weights of your choice, allowing you to customize the balance of your system. By using industry standard 15mm rods and components, the Flyweight system can easily be expanded to fit your needs.

pre-assembled and baseplates that offer vertical and lateral adjustability. A soft

	1	,		0						
ITEM			DESCRI	PTION	V					PRICE
ELE-FLW	/CAM		Flyweig	ht Ca	mcord	er rig kit,	large bas	se plate,		
									clip	449.00
ELE-FLW	/DSLR		Flyweig	ht DS	LR rig	kit, two 1	.8" 15mm	rods,		
			cheese	plate.	weigh	nt bag an	d clip			359.00



### Manfrotto

### MANFROTTO PHOTO-MOVIE CARBON FIBER TRIPOD KIT

Kit includes MH055M8-Q5 photo video head and 755CX3 tripod. Head is made of magnesium and features a repositionable pan bar, photo-movie selector switch, adjustable friction control, independent pan lock, adjustable counterbalance, and a single tilt/portrait orientation lock. The head's fluid cartridge offers high precision and control of movement.



8 1	
TECH SPECS	755CX3-M8Q5
LOAD CAPACITY	15.43 lbs.
MAX HEIGHT	69.98"
MIN HEIGHT	23.62"
WEIGHT	7.08 lbs.
STAGES/MATERIAL	2-stage, carbon fiber

- [	TEM	DESCRIPTION				PRICE
7	55CX3-M8Q5	2-stage carbon	fiber tripod	and photo/video	head	799.99



KT1500U

(3)

11.00

### SMITH-VICTOR THRIFTY LIGHT KITS

Designed to fulfill basic lighting requirements at an exceptionally affordable price. Each kit features two 32" shoot-thru white umbrellas, two UM-6 umbrella mounts, 5/8" light stand adapters and Raven RS8 8' light stands.



(3) 12" Hand-Spun Aluminum Reflectors	(2) 12" Reflectors
Socket and Cordsets with 5/8" Stand Mounts	(1) 5" Reflector
3) Raven RS8 8 ft. Aluminum Light Stands	(3) Socket and Cordsets with St
(3) ECT 500-Watt 3200K Photoflood Lamps	(2) UM-6 Umbrella Mor
(3) UM-6 Umbrella Mounts	(2) 32" White Umbrell
(2) 32" White Umbrellas	(2) ECT 500-Watt Photofloo
(1) Smith-Victor Imaging with Light Guide	(1) ECA 250-Watt Photofloo
	(3) Raven RS8 8' Aluminun
	(3) DC-1 Dimmer and Lamp

Stand Mounts m Stands (1) Smith-Victor Imaging with Light Guide

KT900
(2) 12" Reflectors with punch-out hole
(1) 5" Reflector
(3) Socket and Cordsets with 5/8" Stand Mounts
(2) UM6 Umbrella Mounts
(2) 32" White Umbrellas
(2) ECT 500-Watt Photoflood Lamps
(1) ECA 250-Watt Photoflood Lamp
(3) Raven RS8 8' Aluminum Light Stands
(1) MB110 Mini Boom-Arm
(1) SoftCase on Wheels
(1) Smith-Victor Imaging with Light Guide

ITEM	DESCRIPTION	PRICE
KT1500U	. 1500W 3-light thrifty intermediate kit	177.00
KT800U	. 1250W 3-light thrifty advanced kit	221.00
KT900	. 1250W 3-light thrifty essential advanced kit	275.00
ECA	. 250W photoflood lamp	4.07
	. 500W photoflood lamp	

### SMITH-VICTOR ECONOMY SOFTBOX LIGHT KITS These kits are

a great way to take advantage of soft box lighting at reasonable prices. Soft boxes are designed for maximum brightness while diffusion provides smooth, even light. Fluorescent or tungsten bulbs can replace the included photoflood bulbs.



KSB-500	KSB
(1) SBL-2432 Economy SoftBox Light	(2) SBL-2432 Ec
(1) 500W ECT 3200k Photoflood Lamp	(2) 500W ECT 32
(1) Raven RS8 8' Black Aluminum Light Stand	(2) Raven RS8 8' Bla
(1) Smith-Victor Imaging with Light Guide	(1) Smith-Victor Im

-1000 onomy SoftBox Light 200k Photoflood Lamp ick Aluminum Light Stand naging with Light Guide

(2) SBL-2432 Economy SoftBox Light(tm) (1) SBL-1236 Economy SoftBox Light(tm) (2) 500W ECT 3200k Photoflood Lamp (1) 250W ECA 3200k Photoflood Lamp (1) MB110 Mini Boom-Arm (1) Smith-Victor Imaging with Light Guide

ITEM	DESCRIPTION	PRICE
KSB-500	. 500W 1-light economy softbox light kit	171.00
KSB-1000	. 1000W 2-light economy softbox light kit	409.00
KSB-1250	. 1250W 3-light economy softbox light kit	585.00
ECA	. 250W photoflood lamp	4.07
	. 500W photoflood lamp	





