SENNHEISER EVOLUTION G3 UHF WIRELESS SYSTEMS

The receivers commonly feature 1/2 rack width metal housings, true diversity operation, 42MHz bandwidth with 1,680 switchable frequencies, LCD displays, AutoScan for frequency selection, sound check mode to check audio and RF signal during setup, HDX compander, wireless sync of transmitters via infrared interface, integrated EQ, XLR and 1/4" TS output jacks. The compact transmitters have integrated charging contacts (for use with optional charging accessories), use AA cells and will operate up to 8 hours. Frequency response is 25Hz-18kHz. Backwards compatible with G1/ G2 series.

EVOLUTION 100 SERIES-G3 The EM100-G3 receiver has a SN ratio of >110dB, and has up to 12 compatible frequencies per bank. It also has a built-in guitar tuner and cable emulation.

EVOLUTION 300 SERIES-G3 The EM300-G3 receiver has a SN ratio of >112dB, an ethernet port that allows you to control settings via a computer, and has up to 24 compatible frequencies per bank. No guitar tuner or cable emulation. Body pack transmitters have configurable mute modes and switchable RF output power (10/30mW).

EVOLUTION 500 SERIES-G3 The EM500-G3 receiver shares the features of the 300 series but improves to a SN ratio of 115dB and has 32 compatible frequencies per bank. The 500 series handheld transmitters feature 900 series Sennheiser capsules. Like the 100 series, the receivers have a built-in guitar tuner and cable emulation.

ORDERING INFO: A Range, TVCH 21-28

EW145-G3.....

EW165-G3.....

OPERATES IN THIS RANGE:

G Range, TVCH 30-37		566.000-608.000MHz	
B Range, TVCH 40-47		626.000-668.000MHz	
ITEM DESCRIF	PTION		PRICE
100 Series Sets with I	ackmounta	able EM100 receiver	
(GA3 rack ears not inc	luded)		
EW112-G3Presentation set with SK100-G3 body pack & ME2 omni lapel mic 649.95			
EW122-G3Presentation set with SK100-G3 body pack & ME4 cardioid lapel mic . 649.95			
EW152-G3Head wo	rn set with S	SK100-G3 body pack & ME3 ca	rdioid,
condens	er headset		649.95
EW172-G3Instrume	ent set with	SK100-G3 body pack & Ci1 ins	trument cable 499.95
EW135-G3Vocal set with E835 handheld cardioid dynamic mic			

..Vocal set with E845 handheld supercardioid dynamic mic..

.Vocal set with E865 handheld supercardioid condenser mic............. 749.95

100 Series Sets with portable EK100 receiver (for camera use) - includes Ci1 1/8" output cable, CL100 XLR unbalanced output cable, CA2 camera mount

......Rackmount kit for wireless receiver

EW100ENG-G3ENG set with SK100-G3 body pack, ME2 omni lapel mic,	
& SKP100 plug-on transmitter (no phantom power)79	99.95
EW112P-G3ENG set with SK100-G3 body pack, & ME2 omni lapel mic	29.95
EW122P-G3ENG set with SK100-G3 body pack, & ME4 cardioid lapel mic	29.95
EW135P-G3ENG set with SKM835 handheld transmitter, cardioid dynamic mic 5	99.95

300 Series Sets with rackmountable EM300 receiver (GA3 rack ears included)

EW312-G3	Presentation set with SK300-G3 body pack & ME2 omni lapel r	nic 849.95
EW322-G3	Presentation set with SK300-G3 body pack & ME4 cardioid lapel	mic . 849.95
EW352-G3	Head worn set with SK300-G3 body pack and	
	ME3 cardioid condenser headset	899.95
EW335-G3	Vocal set with E835 handheld cardioid dynamic mic	849.95
EW345-G3	Vocal set with E845 handheld supercardioid dynamic mic	899.95
EW365-G3	Vocal set with E865 handheld supercardioid condenser mic	999.95

500 Series Sets with rackmountable FM500 receiver (GA3 rack ears included)

EW512-G3Presentation set with SK500-G3 body pack & ME2 omni lapel mic 1049.95
EW572-G3Instrument set with SK500-G3 body pack & Ci1 instrument cable 849.95
EW500/935-G3Vocal set with E935 handheld cardioid dynamic mic
EW500/945-G3Vocal set with E945 handheld supercardioid dynamic mic
EW500/965-G3Vocal set with E965 handheld switchable cardioid or
supercardioid condenser mic



SENNHEISER XS SERIES WIRELESS SYTEMS XS Wireless delivers renowned Sennheiser sound to small venues, conference rooms or houses of worship. Truediversity reception offers worry-free operation. It features 24MHz switching bandwidth, 8 frequency banks containing 12 coordinated channels each and 960 available frequencies which are tunable in 25kHz steps. The powerful scan function identifies available channels while the new Remote Channel sync allows components to be synchronized at a distance. Transmitters will operate up to 10hrs on 2 AA batteries. Operates at ranges up to 250'.

ORDERING INFO		OPERATES IN THIS RANGE:	
A Range		548.000-572.000MHz	П
B Range		614.000-636.000MHz	
ITEM DES	SCRIPTION	PRIC	CE
		20 body pack, EM10 receiver,	
		399.	95
		SK20 body pack, EM10 receiver,	
ME:	3 headset mic		95
XSW-35 Har	ndheld system with SI	KM35 HH dynamic	
car	dioid transmitter, EM	110 receiver	95
XSW-65 Har	ndheld system with SI	KM65 HH condenser	
		er, EM10 receiver 449.	95
XSW-72 Inst	trument system with	SK20 body pack, EM10 receiver,	
		399.	95

SENNHEISER 2000 SERIES UHF WIRELESS SYSTEMS Series features include backwards compatibility with Evolution G1/G2/G3 transmitters, true diversity operation (rackmount receivers only), built-in Ethernet port for linking to PCs, switching bandwidth between 42-75MHz in 25kHz

steps, and up to 64 compatible presets per band. The rack mount receivers (EM2000/EM2050) feature integrated power supply, and active splitter (up to 8 receivers may be linked w/out using additional splitters);

transformer balanced XLR and 1/4" outputs, scan feature for compatible frequency selection, 4 selectable EQ presets, HDX compand-



er, built-in guitar tuner, Soundcheck mode for monitoring transmission conditions, and IR sync with compatible transmitters. ODDEDING INFO.

ORDERING INFO:	OPERATES IN THIS RANGE:	
A Range, TVCH 21-28	516.000-558.000MHz	
G Range, TVCH 28-40	558.000-626.000MHz	
B Range, TVCH 40-51	626.000-698.000MHz	
ITEM DESCRIPTION	PRICE	
EM2000Single-channel UHF wire	less receiver, 1RU	
EM2050Dual-channel UHF wirele	ss receiver, 1RU2799.95	
EK2000Camera-mount UHF wire	less receiver	
SK2000XP UHF body pack transmitter only (no mic)		
SKM2000-BLACK Handheld transmitter, black (note: no capsule included)		
SKP2000 Plug-on transmitter, 10/30/50/100mW RF output,		
supplies phantom power,	, 3-pin Lemo socket	

Please call for info on accessories and capsules for handheld transmitters!















COMPUTER AV

















































































SENNHEISER 5000 SERIES PROFESSIONAL WIRELESS SYSTEMS

This system centers around the EM3732-II dual-channel receiver (except the BP-PACKAGE-4) and transmits across the UHF spectrum. They have up to 184MHz of switching bandwidth and are capable of integrating with 2000 Series systems. An integrated antenna splitter allows daisy chaining of up to 8 units for 16 channels of audio. The integrated Ethernet port allows for remote control via Wireless System Manager Software. Transmitters have switchable output power and a Low Intermodulation mode which allows larger numbers of transmitters to operate in congested RF environments. Transmitters are available in Nickel, Black or Steel Blue and you must also indicate frequency range when ordering.

SMK5200-II NICKEL	SMK5200-II STEEL BLUE
	EM3732-II
COL MINNE &	B THERE'S BOLD
	0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0
ORDERING INFO:	OPERATES IN THIS RANGE:
L	470-638MHz 614-698MHz



OPERATES IN THIS RANGE

470.000-558.000MHz 550.000-638.000MHz 630.000-718.000MHz 710.000-798.000MHz

7	SKM9000-NI
W	SKM9000-BI
	SKM9000-NI
	ME9002
	ME9004

SENNHEISER DIGITAL 9000 SERIES WIRELESS SYSTEM

This system has been developed for professional users in broadcast studios, theaters and live performance situations who are unwilling to compromise on sound. Its unique uncompressed digital audio transmission offers artifact-free sound with superb dynamics. The use of extremely narrow filters allows a very narrow set-up of the respective radio frequencies within the available range without risking intermodulation. The EM9046 receiver offers 328MHz of switching bandwidth from 470 to 798MHz. Its modular design can support up to 8 receiver modules with modules for analog and digital output. Its intuitive icon-based user interface is displayed via a large TFT display, which can also be used to view the built-in graphical spectrum analyzer and RF level recorder. The SK9000 body pack transmitter is lightweight and durable with magnesium housing and a 3-pin Lemo connector for lavalier microphones, guitars and instruments. The SKM9000 handheld transmitter is available with 4 new capsule choices and is also compatible with Neumann, Sennheiser Evolution and 2000 series capsules. For more information about this system please call your Sales Pro.

ITEM	DESCRIPTION	PRICE
EM9046-SU	. Modular receiver system, multi-channel (up to 8)	CALL
EM9046-DRX	. Digital receiver module	2000.00
EM9046-DA0	. Digital audio output module	2000.00
EM9046-AA0	. Analog audio output module	4500.00
SK9000	. Body pack transmitter	2600.00
SKM9000-BK	. Handheld transmitter, black	2600.00
SKM9000-NI	. As above, in nickel	2600.00
SKM9000-BK-COM	. Handheld transmitter with command button, black.	2995.00
SKM9000-NI-COM	. As above, in nickel	2995.00
ME9002	. Omnidirectional capsule, condenser	600.00
ME9004	. Cardioid capsule, condenser	600.00
ME9005	. Supercardioid capsule, condenser	600.00
MD9235	. Supercadioid capsule, dynamic – available in black	ί,
	nickel or combination finishes	550.00





ORDERING INFO:



















NEW!

QLXD14/85



























WIRELESS STSTEW	
This series offers	
Shure's patented Audio	
Reference Companding	
technology. Utilizing	
Auto Frequency	
Selection and Auto Transmitter Setup,	
the system scans the wireless land-	
scape and identifies a clear channel	
instantly. With over 960 operating fre-	
quencies across 24MHz of UHF band-	
width, users can easily set up to 20	
systems (across multiple bands) in a	
given location. Each rugged metal SLX Wireless receiver uses diversity technology to	

889.00

systems (across multiple bands) in a given location. Each rugged metal SLX \ improve reception and minimize dropouts. The receiver is outfitted with rackmount hardware, detachable 1/4-wave antennas, a backlit LCD display, 1/4" and XLR output connectors, frequency and power lockouts, an inline power supply and a rear-panel volume control. SLX's handheld and body pack transmitters have a 300ft operating range, and run on 2 AA batteries for 8 hours of continuous use.

> OPERATES IN THIS RANGE 494.000-518.000MHz, TVCH 17-22

WIRELESS SYSTEM This series offers Shure's patented Audio Reference Companding

H5	518.000-542.000MHz, TVCH 22-25
J3 L4	572.000-596.000MHz, TVCH 31-34
L4	638.000-662.000MHz, TVCH 42.45
ITEM DESCRIPTION	PRICE
SLX14Body pack system — SLX1/	SLX4 with WA302 instrument cable, no mic 559.00
SLX14/93Lavalier system — SLX1/S	SLX4 with WL93 omni lavalier mic 599.00
SLX14/84Lavalier system — SLX1/SI	LX4 with WL184 hypercardioid lavalier mic 659.00
SLX14/85Lavalier system — SLX1/S	SLX4 with WL185 cardioid lavalier mic 659.00
SLX24/58Handheld system — SLX4	with SLX2/58 HH transmitter599.00
SLX24/BETA58Handheld system — SLX4	with SLX2/BETA58 HH transmitter 639.00
SLX24/BETA87AHandheld system — SLX4	with SLX2/BETA87A HH transmitter 729.00
	with SLX2/BETA87C HH transmitter 729.00
SLX24/86Handheld system — SLX4	with SLX2/86 HH transmitter

SLX124/85/58Combo system - SLX4 with SLX1, WL185 lavalier mic

and SLX2/SM58 HH transmitter.



SHURE ULX SERIES WIRELESS SYSTEMS These are frequency agile UHF wireless systems with 1400 user-selectable channels and auto frequency selection. Up to 60 systems are simultaneously compatible within the 3 frequency groups (up to 20 per band). ULX Transmitters feature a 3-segment battery gauge, on/off switch lockout and frequency lockout. Other features include 8hr battery life, and a -20dB pad on the ULX1 body pack. ULX standard receivers feature RF presence LED, 5-segment audio meter, 3-segment battery gauge, detachable 1/4 wave antennas, plastic chassis, XLR and 1/4" outputs, mic/line switchable. Rack hardware not included. Components shown are in the G3 band – for alternate bands replace the "G3" with bands shown below on chart, or call a Full Compass Sales Pro for assistance.

OPERATES IN THIS RANGE

G3 – Note: some metro areas have	
Public Safety Channels in this band –	
call your Sales Pro for assistance with G3	470.000-506.000MHz, TVCH 14-20
J1	554.000-590.000MHz, TVCH 28-33
M1	662.000-698.000MHz, TVCH 46-51
ITEM DESCRIPTION	PRICE
ULXS4-G3 Standard receiver, plast	ic chassis, no rack hardware included 446.00
JLX1-G3 Body pack transmitter 193.0	
ULX2/58-G3 Handheld transmitter wi	ith SM58 head253.00
ULX2/87-G3 Handheld transmitter wi	ith SM87 head 363.00
ULX2/BETA58-G3 Handheld transmitter with Beta58 head	
JLX2/BETA87A-G3 Handheld transmitter with Beta87A head	
JLX2/BETA87C-G3 Handheld transmitter with Beta87C head	
UA506 Rack hardware for singl	e ULXS4 receiver
	ULXS4 receiver

TEK AND HEADINICS FOR SHOKE BODY PACKS	
DESCRIPTION	PRICE
nhones	
Omni subminiature lav mic, condenser, matte black, TQG	199.00
As MX150B/O-TQG, cardioid version	199.00
Omnidirectional micro-lavalier mic, condenser, black	68.54
As WL93, in tan	68.54
As WL93, with 6' cable	73.11
As WL93T, with 6' cable	73.11
Cardioid lavalier mic, condenser, black	107.24
phones	
As WBH53B, in tan	299.00
QLXD14/SM35	
	DESCRIPTION shones Omni subminiature lav mic, condenser, matte black, TQG

With streamlined setup and operation, QLX-D delivers incredibly efficient, agile RF performance at a price point that accommodates the budgets of mid-sized venues. These systems offer the most efficient use of available on-air channels than any other system in its class, with 17 compatible systems per 6MHz TV channel. Automatic channel scan and IR sync allow for easy location and assignment of open frequencies and AES-256 encryption is standard for all system configurations. Networked control capabilities are available via ShurePlus Channels for iOS devices and Wireless Workbench 6.10 and third-party systems including AMX and Crestron. Shure's intelligent rechargeable battery technology allows for up to 10 hours of continuous use. Individual components are also available, shop fullcompass. com or call a Sales Pro for more information.

SHURE QLX-D DIGITAL WIRELESS SYSTEMS

J50	632.000-696.000MHz, TVCH 31-41
L50	632.000-696.000MHz, TVCH 41-51
ITEM DESCRIPTION	PRICE
Single-Channel Systems	
QLXD14Instrument syst	tem with QLXD1 bodypack and instrument cable 973.00
QLXD14/SM35 Headworn syste	em with QLXD1 bodypack and SM35 microphone 1073.00
QLXD14/83Lavalier system	with QLXD1 bodypack and WL183 microphone 1053.00
QLXD14/84Lavalier system	with QLXD1 bodypack and WL184 microphone 1083.00
QLXD14/85Lavalier system	with QLXD1 bodypack and WL185 microphone 1076.00
QLXD14/93Lavalier system	with QLXD1 bodypack and WL93 microphone 1048.00
QLXD24/B58Handheld syste	m with QLXD2 transmitter and Beta58 microphone 1055.00
QLXD24/B87AHandheld syste	m with QLXD2 transmitter and Beta87A microphone . 1136.00
QLXD24/SM58 Handheld syste	m with QLXD2 transmitter and SM58 microphone 999.00
	with QLXD1 bodypack with WL185 lavalier
microphone an	d QLXD2 transmitter with SM58 microphone1439.00
Looking for	FP3

ORDERING INFO:

OPERATES IN THIS BAND: 534.000-598.000MHz, TVCH 14-24 572.000-636.000MHz, TVCH 24-35

ORDERING INFO:







WIRELESS MICROPHONES

GLXD24/B87A SHURE GLX-D DIGITAL WIRELESS SYSTEMS Featuring LINKFREQ automatic frequency management for easy frequency location, these 2.4GHz digital wireless systems are rugged and available in a variety of configurations to match your performance needs. All systems include a power supply, rechargeable battery, USB charge cable or wall charger and carrying case. ORDERING INFO: OPERATES IN THIS BAND: DEFAULT BAND ITEM DESCRIPTION PRICE Complete Systems GLXD14 Guitar system - GLXD1, GLXD4, WA302 instrument cable ... 449.00 GLXD16 Guitar pedal system - GLXD1, GLXD6, WA305 locking instrument cable GLXD14/B98 Instrument system - GLXD1, GLXD4, WB98H/C instrument clip-on condenser. 589.00 GLXD14/PGA31 . Head worn system — GLXD1, GLXD4, PGA31 head worn condenser.. 519.00 . Lavalier system — GLXD1, GLXD4, WL185 Microflex® GLXD14/85 549.00 lavalier with windscreen/tie clip GLXD14/93 Lavalier system, GLXD1, GLXD4, WL93 omnidirectional micro-lavalier with windscreen/tie clip. 519 00 GLXD24/B58 Vocal system - GLXD2/B58, GLXD4, mic clip. 549.00 GLXD24/B87A Vocal system - GLXD2/B87A, GLXD4, mic clip 589.00 GLXD24/SM58 Vocal system — GLXD2/SM58, GLXD4, mic clip...... 499.00 GLXD24/SM86 Vocal system - GLXD2/SM86, GLXD4, mic clip....... 549.00 Components GLXD1 Body pack transmitter... 229.00 GLXD2/B58 Handheld transmitter with Beta 58 microphone 329.00 GLXD2/B87A As above, with Beta 87A microphone 389.00 GLXD2/SM58 As above, with SM58® microphone ... 279.00 GLXD2/SM86 As above, with SM86 microphone... 329.00 GLXD4 Wireless receiver, with PS42US power supply. 219.00 GLXD6 Guitar pedal receiver, with PS23US power supply... 219.00 Accessories 29 99 SB902 Rechargeable Lithium-ion battery SBC-USB-MICROB.. USB wall charger for GLXD1/GLXD2... 14 99 Car charger for GLXD1/GLXD2 ... SBC-CAR SBC-902 Battery dock charger for SB902..... SHURE PGX-D SERIES DIGITAL WIRELESS SYSTEMS This series uses 24-bit/48kHz digital technology at the 900MHz frequency range to avoid interference from TV signals. It offers true digital diversity, frequency response of 20Hz-20kHz, (±2dB), an operating range of up to 200', and the ability to use up to 5 systems simultaneously. The PGXD4 receiver features an automatic scan and sync system for easy setup, durable ABS housing, padded carrying case, and 1/4" and XLR audio outputs. Body pack and handheld transmitters operate on 2 AA cells, yielding up to 9 hours (handheld models), or 10 hours (PGXD1 body pack) of operation. ORDERING INFO: OPERATES IN THIS RANGE: Default Band - X8 902.000-928.000Mhz ITEM DESCRIPTION PRICE Single-Channel Systems PGXD14.. Instrument system - PGXD4/PGXD1, with WA302 (1/4" to TA4-F) guitar cable 429 00 PGXD14/85 Lavalier system - PGXD4/PGXD1, with WL185 cardioid lav mic 499.00 PGXD14/93. Lavalier system - PGXD4/PGXD1, with WL93 omni lav mic... 469 00 PGXD14/BETA98H . Instrument system - PGXD4/PGXD1, with Beta98H/C clip-on mic .. 549.00 PGXD14/PGA31.... Head worn system - PGXD4/PGXD1, with PGA31 cardioid condenser mic PGXD24/PG58 Handheld system - PGXD4 with PGXD2/PG58 transmitter..... 429.00 PGXD24/SM58 . Handheld system - PGXD4 with PGXD2/SM58 transmitter... 449 00 PGXD24/BETA58.... Handheld system - PGXD4 with PGXD2/BETA58 transmitter..... 499 00 PGXD24/SM86...... Handheld system - PGXD4 with PGXD2/SM86 transmitter... 499.00 Individual Components PGXD4. Single-channel digital receiver only. 251 00 PGXD1 248 00 Body pack transmitter only Handheld transmitter only, with PG58 cardioid head... PGXD2/PG58 228 00 PGXD2/SM58 Handheld transmitter only, with SM58 cardioid head. 248 00 PGXD2/BETA58..... Handheld transmitter only, with BETA 58 supercardioid head. 318 00 PGXD2/SM86...... Handheld transmitter only, with SM86 condenser cardioid head...



LIGHTS

ACCESSORIES







PGXD14/PGA31

BLX® Wireless Systems

WIRELESS FREEDOM, MADE SIMPLE.

LEGENDARY SOUND, RIGHT OUT OF THE BOX.

Shure BLX Wireless Systems combine professional quality sound with simple setup and an intuitive interface, for performance you can trust right out of the box. Available in single, dual and half-rack mountable receiver options in a variety of handheld, lavalier, instrument and headset configurations, it's the most accessible way to own the stage.



BLX4R RACK MOUNT WIRELESS RECEIVER SYSTEMS

- Simple setup and operation
- · One-touch QuickScan frequency selection quickly locates the best frequency
- Removable antennas for quick antenna distribution
- LCD display with detailed RF and audio metering
- Rugged metal construction, with rack mount hardware included



PRO AUDIO VIDRO LIGHTING MUSICAL INSTRUMENTS

800-356-5844 fullcompass.com

LEGENDARY PERFORMANCE"

C 2014 Shure Incorporated

















































These systems offer uncompromising audio clarity and extremely efficient RF performance with rugged, intelligent, encryption-enabled hardware. The 24-bit/48kHz digital audio delivers a clear and accurate reproduction of the source material. It features up to 64MHz overall tuning. Over 60 compatible channels are available on one frequency band.

Proprietary Gain Ranging optimizes the system's dynamic range, eliminating the need for transmitter gain adjustments. Optimized scanning automatically finds and deploys the cleanest frequencies available. Ethernet networking ability allows for streamlined setup across multiple receivers, Wireless Workbench® 6 integration and AMX/Crestron control. Advanced Li-Ion rechargeable batteries and intelligent Shure battery circuitry give 12+ hours of life and zero memory effect. Other features include interference detection with alerts, upgraded LCD screens and rugged metal housing on transmitters and receivers. A quad receiver is also available, please shop fullcompass.com for details. Models listed are in the G50 band - for alternate bands replace the "G50" with a band listed

in the chart below, or call your Sales Pro for assistance.

ITEM	DESCRIPTION	PRICE
System Compoi	nents	
ULXD10	Bodypack transmitter	445.00
ULXD40	Receiver, single, with power supply, antenna and rackmoun	t kit 875.00
ULXD4D0	Receiver, dual, with power supply, antenna and rackmount	kit 2505.00
ULXD4Q0	Receiver, quad, with power supply, antenna and rackmount	kitCALL
ULXD2/B58	Handheld transmitter with Beta 58A capsule	554.00
ULXD2/B87A	Handheld transmitter with Beta 87A capsule	630.00
ULXD2/B87C	Handheld transmitter with Beta 87C capsule	630.00
ULXD2/SM58	Handheld transmitter with SM58 capsule	474.00
ULXD2/SM86	Handheld transmitter with SM86 capsule	554.00
ULXD2/SM87	Handheld transmitter with SM87 capsule	630.00
ULXD2/KSM9	Handheld transmitter with KSM9 capsule	1050.00
	Handheld transmitter with KSM9HS capsule	

ORDERING INFO:	OPERATES IN THIS RANGE:
G50	470.000-534.000MHz, TVCH 14-24
H50	534.000-598.000MHz, TVCH 24-35
J50	572.000-636.000MHz, TVCH 31-41
L50	632.000-696.000MHz, TVCH 41-51

ITEM Accessories	DESCRIPTION	PRICE
UA864US	Wideband antenna, wall-mounted	440.28
WA305	Instrument cable, with locking TQG connector	33.87
SB900	Rechargeable battery, lithium-ion	100.80
SB900-8	As above, 8-pack	655.20
SBC800-US	Battery charger, 8-bay	453.60
SBC200	Battery charger, dual-docking, no power supply	172.03
	As above, with power supply	





ORDERING INFO:	OPERATES IN THIS RANGE:
Band G1, TVCH 14-24	
(Note: some metro areas have Public	
Safety Channels in this band – call for	
assistance if using this band)	470.000-530.000MHz
Band H4, TVCH 22-31	518.000-578.000MHz
Band J5, TVCH 32-41	578.000-638.000MHz
Band L3, TVCH 42-51	638.000-698.000MHz

SHURE UHF-R SERIES WIRELESS MICS A UHF series with 2400 selectable frequencies spanning across 60MHz bandwidth. Up to 40 preset compatible systems per band and up to 160 systems with multiple bands. Stores six 60-channel custom frequency groups. Has a multi-function bit-mapped backlit LCD and includes Wireless WorkbenchTM software for PC management of networked wireless systems with USB and Ethernet network options. Models shown are components in the G1 band – for alternate bands replace the "G1" with bands shown below on chart, or call for assistance.

ITEM	DESCRIPTION	PRICE
UR4S+-G1	Single-channel receiver, with 2 half-wave antennas,	
	accessory cables, power supply	1954.00
UR4D+-G1	Dual-channel receiver, with 2 half-wave antennas,	
	accessory cables, power supply	2889.00
UR5-G1	Portable ENG body pack receiver with TA3M jack, camera	
	shoe mount, stand strap mount, 1/8" headphone out	1199.00
	Handheld transmitter with SM58 head	
UR2/SM86-G1	Handheld transmitter with SM86 head	1039.00
UR2/SM87-G1	Handheld transmitter with SM87 head	1159.00
UR2/BETA58-G1	Handheld transmitter with Beta 58 head	1039.00
	Handheld transmitter with Beta 87A head	
UR2/BETA87C-G1	Handheld transmitter with Beta 87C head	1159.00
UR2/KSM9/BK-G1	HH transmitter with KSM9 condenser head, black	1799.00
UR2/KSM9/SL-G1	HH transmitter with KSM9 condenser head, champagne	1799.00
	Body pack transmitter with threaded TA4-F connector	799.00
UR1M-G1	Micro body pack transmitter, 10mW or 50mW RF power,	
	TA4-F conn	1699.00
	As UR1M, with Lemo connector	
UR3-G1	Plug-on transmitter for XLR mics	999.00

SHURE WIRELESS ANTENNAS & ANTENNA DISTRIBUTION ACCESSORIES

Antennas and receivers must be from the same band. Please call a Sales Pro for assistance choosing the correct part for your system.

IIEW	DESCRIPTION	PRICE
SLX/ULX Se	ries	
UA844SWB	Wideband UHF 4-way active antenna splitter & power distr for SLX/ULX	
	series, 470-952MHz, external PS, includes power antenna cables	437.65
UA830USTV	Inline RF amplifier for UA844SWB (470-698MHz)	175.23
UA860SWB	1/2-wave omni wideband antenna SLX/ULX (470-1100MHz)	278.30
UA400B	Replacement 1/4-wave antenna (470-752MHz)	23.56
UA221	Passive antenna/splitter combiner kit for 2 receivers	148.72
UA505	1/2-wave antenna remote mount kit hardware	
	(requires antenna, not included)	22.09

ITEM UA440	DESCRIPTIONFront mount antenna kit with (4) BNC-BNC 2' coax cables,	PRICE
	(4) Bulkhead adapters	111.91
UA806	Coaxial antenna cable, 6'	22.09
UHF-R Serie	es	
UA845SWB	Wideband UHF 5-way active antenna & power distr, 470-952MHz,	
	internal switching power supply (NOTE: not for use with ULX)	787.51
UA830USTV	Inline RF amplifier for UA845SWB (470-698MHz)	175.23
UA600	Front mount antenna kit for U4S/U4D receivers	47.12
UA874US	Active directional antenna (470-698MHz)	353.78
PA805SWB	Passive directional wide-band antenna (470-870MHz)	254.02
UA860SWB	1/2-wave omni wideband antenna UC/UHF-R (470-1100MHz)	278.30
UA505	1/2-wave antenna remote mount kit hardware	
	(requires antenna, not included)	22.09







interference), CD-quality 50Hz-20kHz frequency response, built-in rechargeable battery for up to 8hrs of talk time after a full charge, and 128-bit encryption for security.

ITEM	DESCRIPTION			PRICE
01-HDEXEMIC-11	Wearable lapel style m	ic, rotatable clip,	with earbud, lanyard	1 349.00
01-HDTBLMIC-OM-11	Tabletop mic, omnidire	ctional		349.00
01-HDTBLMIC-DR-11	Tabletop mic, unidirect	tional		349.00
01-HDXLRMIC-11	XLR plug-on transmitte	er for dynamic mi	cs only (no phantom)	349.00
01-HDCOMAN-11	HD microphone adapte	r for Countryman	E6 or	
	B6 style microphones			349.00
B6W4FF05BRV	Countryman B6 omni n	nini-lav mic, blac	k, for Revolabs	293.16
E610W5B2RV	Countryman E6i omni l	neadset mic, blac	k, for Revolabs	337.82
E610W5L2RV	Countryman E6i omni l	neadset mic. ligh	t beige, for Revolabs	337.82

REVOLABS SINGLE/DUAL CHANNEL HD WIRELESS MIC

SYSTEMS These systems use the same high definition audio, and DFS20TM technology found in the HD Executive series. They have some audio processing EQ and mixing capability, eliminating the need for external equipment in most cases. Each system ships with a charger base

(1- or 2-mic charging docks) and a base station. Mics are purchased separately. The HD Single Channel System has an analog input and output (1/8" TRS), and the HD Dual Channel System has 2 of each, plus the ability to mix both outputs into one. All outputs can be line or mic level. This provides maximum flexibility to use the HD Single/Dual Channel System wherever a wired microphone can be used, making the system perfect for videoconferencing, voice lift and PA applications. Other features include 128-bit encryption, 2hr charge time, and 65' operating range.

71	,
ORDERING INFO:	OPERATES IN THIS RANGE:
Default Band	1.92GHz-1.93GHz (UPCS North America)
ITEM DESCRIPTION	PRICE
02-HDSGL-NM HD wireless mic system,	single-channel, analog I/O, no mics 395.00
02-HDDUAL-NM HD wireless mic system,	2-channel, analog I/O, no mics 595.00



The M80 features a low-mass capsule build with a super-thin Mylar membrane coupled to a pro-

prietary step-up transformer, offering superior clarity and extended high frequency response. Designed to withstand the daily abuse of touring bands, these capsules offer another capsule choice for those using Shure wireless systems.

ITEM	DESCRIPTION	PRICE
M80-WH	. Capsule for Shure handheld transmitters, chrome grille	249.00
M80-WH-BLACK	As above, with black grille	249.00

Looking for these brands?

Shop fullcompass.com or call 800-356-5844























































