




APOGEE
APOGEE DUET

- 2 channels 24bit/96kHz audio in/out
- 2 balanced XLR inputs, with selectable 48V phantom power on each input
- 2 unbalanced high impedance instrument inputs
- High-level stereo headphone output
- 2 unbalanced -10dBV line outputs for powered speakers
- Multi-function controller knob for volume and input gain control and assignable MIDI control
- Multi-segment LED meters to display input or output levels
- FireWire 400, compatible with Mac OSX Core Audio
- Control functions built directly into Apple's Logic Pro, Soundtrack Pro and GarageBand
- Compatible with any Core Audio-compliant audio application
- Apogee Maestro software for advanced control & mixing

DUET 2-channel FireWire audio interface (Mac only) 495.00



APOGEE
APOGEE ENSEMBLE FIREWIRE INTERFACE

- 18x18 24bit/48kHz analog/digital I/O
- Or 14x14 @ 24bit/96kHz, 8x8 @ 24bit/192kHz
- 4 XLR w/ phantom and 1/4" inserts
- 4-in/8-out balanced 1/4", 2x 1/4" headphones
- Optical ADAT, coaxial S/PDIF, and word clock I/O
- 2x 6-pin FireWire ports
- Complete integration & control w/ Logic Pro
- CoreAudio support
- Mac OSX compatible
- Stand-Alone Mode – use as high-end converter & mic pre, independent of the computer

ENSEMBLE 18-in/18-out FW interface 1950.00



AVID
MBOX PRO

- 8x8 simultaneous channels of I/O
- 4 mic inputs with 48V phantom power and high pass filter (2 XLR/DI combo, 2 XLR)
- 4x 1/4" TRS line inputs
- 2 unbalanced Alt line inputs (2 RCA, 1 mini 1/8")
- 6x 1/4" TRS balanced line outputs
- Stereo S/PDIF digital I/O
- 1 MIDI input, 1 MIDI output
- 2 discrete 1/4" stereo headphone outputs with separate volume controls
- Word clock I/O
- Monitor control section with Mono, Mute, Dim, Alt Source, and Speaker A/B/C switching controls

MBOX-PRO 8-in/8-out FW production system ... 719.00
MBOX-PRO+PROTOOLS9 . . . Same as above w/ Pro Tools 9 999.00



behringer
BEHRINGER F-CONTROL AUDIO FCA202

- 2x2 @ 24-bit/96 kHz analog I/O
- 2-in/2-out unbalanced 1/4" TRS
- Stereo Headphone out w/ dedicated Level control
- Dual high-bandwidth FireWire connectors for absolute flexibility
- Powered via FireWire bus or included power adapter for use with 4-pin FireWire PCs
- DAW software included (Ableton Live Lite 4 Behringer Edition, Kristal, Audacity)
- Power and FireWire status LEDs on front panel
- Standard port for Kensington security lock provided
- Ultra-low latency drivers for Win XP & Mac OS X included

FCA202 2-in/2-out FireWire audio interface 87.99



ECHO
ECHO AUDIOFIRE4/2 PORTABLE FIREWIRE INTERFACES

- 24bit/96kHz analog/digital I/O
- AudioFire4 has 2 XLR/TRS mic/line combo w/phantom, 2-in/4-out balanced 1/4"
- AudioFire2 has 2-in/2-out balanced 1/4"
- 1/8" headphone out
- Coaxial S/PDIF and MIDI I/O
- Two 6-pin bus powered FireWire or external PSU
- Includes Traktion (version 2.2)
- ASIO 2, WDM, GSIF 2.0, CoreAudio/MIDI support
- Windows XP, Vista and Mac OSX compatible

AUDIOFIRE4 6in/6out FireWire audio interface 299.00
AUDIOFIRE2 4in/4out FireWire audio interface 199.00



ECHO
ECHO AUDIOFIRE 8 FIREWIRE INTERFACE

- 16x16 @ 24bit/48kHz or 12x12 @ 24bit/96kHz
- 2 auto-sensing universal inputs (mic/guitar/line)
- Meters, trim knobs, phantom power, & channel inserts
- 6-in/8-out balanced 1/4" TRS
- 2 unbalanced 1/4" channel inserts
- S/PDIF (coaxial and optical) I/O at 24-bit/96kHz
- Optical ADAT, coaxial S/PDIF and MIDI I/O
- Stereo headphone output with volume knob
- Sync via word clock, S/PDIF or ADAT
- On-board DSP processing
- Near zero latency hardware monitoring

AUDIOFIRE8 16-in/16-out FireWire audio interface 499.00



ECHO
ECHO AUDIOFIRE PRE8 FIREWIRE INTERFACE

- 16x16 24bit/96kHz analog/digital I/O
- Auto-sensing universal inputs featuring Echo's Brilliant™ preamp technology
- 8 balanced 1/4" TRS outputs (back)
- MIDI, wordclock I/O
- S/PDIF I/O (coax and optical) at 24-bit/96 kHz
- ADAT I/O, 2x 1/8" headphones out
- 2 full featured mic/line/instrument combo inputs (front)
- 6 XLR/TRS mic/line combo w/ phantom outputs (back)
- Two 6-pin bus powered FireWire or external PSU
- Software console controls mixing and monitoring
- ASIO 2, CoreAudio/MIDI support
- Windows 7, XP, Vista and Mac OSX compatible

AUDIOFIRE8-PRE ... 16-in/16-out FireWire audio interface 699.00



ECHO
ECHO AUDIOFIRE12 FIREWIRE AUDIO INTERFACE

- 12x12 24bit/192kHz analog I/O
- 12-in/12-out balanced 1/4"
- MIDI and word clock I/O
- 2 FireWire ports with 15' cable
- Near zero latency hardware monitoring
- Includes Traktion (version 2.2)
- ASIO2, GSIF 2.0, CoreAudio/MIDI support
- Windows XP, Vista and Mac OSX compatible

AUDIOFIRE12 12-in/12-out FW interface 599.00



Focusrite
FOCUSRITE SAFFIRE PRO 14 FIREWIRE AUDIO INTERFACE

- 8x6 24-bit/96kHz analog/digital I/O
- 2 XLR/TRS mic/line mic-pre combos w/phantom
- 2 line 1/4" TRS (channels 3-4) on rear panel
- Two Hi-Z instrument inputs
- 4 TRS 1/4" outputs
- 1/4" headphone out
- 1 x 6-pin bus powered FireWire or external PSU
- Coaxial S/PDIF, MIDI I/O
- Includes Saffire MixControl 18x6 DSP mixer
- Plug-in Suite provides compression, reverb, gating and EQ
- VST/AU plug-ins
- Includes Ableton Live Lite, Novation's Bass Station soft-synth, over 1 gig of royalty-free Loopmasters samples
- Windows and Mac OSX compatible

SAFFIRE-PRO-14 8-in/6-out FireWire audio interface ... 249.99



Focusrite
FOCUSRITE SAFFIRE PRO 24 FIREWIRE AUDIO INTERFACE

- 16x8 24bit/96kHz analog/digital I/O
- 6 TRS 1/4" outputs
- 2 XLR/TRS mic/line mic-pre combos w/phantom
- Optical ADAT, coaxial S/PDIF, MIDI I/O
- 1/4" headphone out
- 1 x 6-pin FireWire socket
- 12V DC power input connector for use with external PSU
- DSP model adds extra phones output and onboard DSP for Virtual Reference Monitoring and plug-ins
- Includes Ableton Live Lite 7, full-fledged soft-synth, Focusrite FX Suite, royalty-free loops and samples
- Windows XP, Vista, and Mac OSX compatible

SAFFIRE-PRO-24 16-in/8-out FireWire audio interface . 299.99
SAFFIRE-PRO-24-DSP . . . Same as above, DSP version 399.99



Focusrite
FOCUSRITE SAFFIRE PRO 40

- 18x18 @ 24bit/48kHz analog/digital I/O or 14x14 @ 24bit/96kHz
- 8 award-winning Focusrite pre-amps
- 8 XLR/TRS inputs, 8 TRS outputs
- 2x 6-pin FireWire ports
- Optical ADAT, coaxial S/PDIF and MIDI I/O
- High quality A-D/D-A conversion and JetPLL™ jitter elimination technology
- Includes a suite of all-new Focusrite compression, reverb, gating and EQ VST/AU plug-ins
- Zero-latency DSP mixer/router provides an 18x16 mixer with the flexibility to route any input signal or DAW output to any of the 20 outputs
- 2 separate headphone buses for independent monitor mixes

SAFFIRE-PRO-40 18-in/18-out FireWire interface 499.99

AUDIO PRODUCTION SOFTWARE



steinberg

SEE PAGES 277-278

PLEASE ALWAYS CONSULT MANUFACTURER'S WEBSITE FOR MOST CURRENT SYSTEM REQUIREMENTS!

LEGEND: AUDIO OVER FIREWIRE AUDIO OVER USB PCI CARD PCI EXPRESS CARD MIDI INTERFACE M-POWERED COMPATIBLE ETHERNET



Focusrite
FOCUSRITE LIQUID SAFFIRE 56 FIREWIRE INTERFACE

- 24bit/192kHz FireWire interface
 - 2 Liquid Pre-amps - 10 different classic pre-amp emulations, with an 11th "flat" option
 - 6 high-quality award-winning Focusrite pre-amps
 - 8 XLR mic inputs, 8-in/8-out balanced 1/4"
 - Dual S/MUX ADAT, coaxial S/PDIF, MIDI, and wordclock I/O
 - 2 separate headphone buses
 - 2x 6-pin FireWire ports
 - Saffire Mix Control zero-latency 18 x 16 DSP mixer/router
 - Front panel 5-LED metering
 - Suite of Focusrite VST/AU plug-ins including Focusrite Compression, Reverb, Gating and EQ VST/AU plug-ins
 - Independent phantom power & a hi-pass filter on every channel
- LIQUID-SAFFIRE-56**..... 28-in/28-out FireWire interface, w/ 2 Liquid preamps..... 999.99



M-AUDIO
M-AUDIO PROFIRE 2626 FIREWIRE AUDIO INTERFACE

- 26 x26 simultaneous analog/digital I/O
 - 8-XLR/TRS mic/line combo with Octane™ preamp technology
 - 2x 1/4" TS instrument inputs on front
 - 8-out 1/4" TRS balanced line output
 - Two 1/4" TRS headphone outputs
 - 2x optical ADAT I/O (S/MUX II/IV modes)
 - Coaxial S/PDIF, MIDI, wordclock I/O
 - User-assignable master volume knob
 - Functions as stand alone 8-channel mic pre/8-channel A/D-D/A converter
 - Flexible on-board DSP mixer - create up to 8 stereo mixes
 - Up to 24bit/192kHz for high-definition audio
 - JetPLL jitter elimination technology
- PROFIRE-2626**..... 26-in/26-out FireWire audio interface..... 699.00
- PROTOOLS-MPOWERED-8**.. Optional DAW software, includes iLok..... 249.95



METRIC HALO
METRIC HALO MOBILE I/O ULN-2 FIREWIRE AUDIO INTERFACE W/DSP

- 24bit/96kHz analog/digital I/O
 - 2 XLR mic/line combo w/ phantom and 1/4" inserts
 - 4-out balanced TRS, 1/4" headphones w/ volume knob
 - Wordclock, AES/ S/PDIF Digital I/O with selectable SRC
 - 8 channels all new ADAT I/O with switchable TosLINK support
 - 4-pin XLR power port for location battery systems
 - 2x 6-pin bus powered FireWire ports or external PSU
 - DSP on-board processing for Metric Halo plug-ins
 - v.5 Configurable mixer for near-zero latency mixing & routing
 - OS X drivers (with multibox support in OS X)
 - Ships with rack kit & 4-pin locking world ready power supply
- ULN2-EXPANDED+DSP**.. 12-in/12-out FW interface w/ DSP... 2394.00
- ULN2-EXPANDED**..... 12-in/12-out FW interface w/out DSP. 1695.00



LEXICON
LEXICON IONIX FW810S FIREWIRE INTERFACE

- Features 8 channels of premium dbx mic pre's and dbx dynamics
 - Lexicon's signature reverbs (included in the newly updated Pantheon II plug-in)
 - Type IV conversion which eliminates clipping and emulates tape saturation
 - Onboard DSP powered dbx dynamics including EQ, gate, compressor and limiter
 - 8 XLR/TRS combo inputs (2 on front panel)
 - 8 1/4" TRS outputs with stereo main outs
 - S/PDIF and MIDI I/O
 - 2 FireWire 400 ports
 - Front panel level/headphone control
 - 8 gain control knobs w/ +48V indicator LEDs
- FW810S**..... 8-in/10-out FW interface w/DSP..... 699.95



METRIC HALO
METRIC HALO LIQ-8 FIREWIRE INTERFACE

- 8 channels of Archival Grade 192k A/D and D/A converters
 - 2 channels of Archival Grade 192k D/A converters with integrated headphone amp
 - 2 channels of DI inputs (front of unit)
 - 8 channels of 192k capable AES inputs and outputs via DB25
 - 8 channels of 192k capable analog inputs & outputs via DB25
 - 8 balanced sends via DB25
 - High resolution 15-segment precision front panel metering
 - Integrated surround monitor controller
 - Dedicated internal clock sources for all rates
 - MIDI, wordclock and SMPTE LTC I/O
 - Integrated mixing and instantiable DSP Processing
- LIQ-8**..... 8-in/8-out FireWire audio interface (Mac only)..... CALL



MOTU
MOTU 8PRE FIREWIRE AUDIO INTERFACE

- 16x12 24bit/96kHz analog/digital I/O
 - 8-XLR/TRS mic/line combo
 - Individually switchable 48-volt phantom power
 - 8-channel 96kHz ADAT I/O (dual SMUX)
 - MIDI I/O
 - CueMix DSP, 1/4" headphone output
 - 2x 6-pin FireWire ports
 - Includes AudioDesk software for Mac only
 - ASIO, WDM, Wave, GSIF, Core Audio and Core MIDI support
 - Windows XP, Vista and Mac OSX compatible
- 8PRE**..... 16-in/12-out FW interface..... 549.00



MACKIE
MACKIE ONYX BLACKBIRD 16X16 FIREWIRE RECORDING INTERFACE

- 16x16 24bit/96kHz analog/digital I/O
 - 2 XLR/TRS mic/line combo Onyx mic pre w/48V phantom on front panel
 - Switchable line/Hi-Z inputs (built in DI), 80Hz low-cut switches
 - 6 XLR/TRS combo inputs w/phantom
 - 6-out 1/4" balanced/unbalanced
 - 2x optical ADAT I/O (S/MUX II)
 - Wordclock I/O (JetPLL™ jitter elimination technology)
 - 2x 1/4" headphone outputs with independent level control
 - 2x FireWire 400
 - Includes powerful Blackbird Control DSP Matrix Mixer
 - Includes Traktion 3™ Music Production Software
 - WDM, ASIO 2.0, CoreAudio support
- BLACKBIRD**..... 16-in/16-out FireWire audio interface..... 499.99



METRIC HALO
METRIC HALO ULN-8 FIREWIRE AUDIO INTERFACE

- 8x8 24bit/192kHz analog/digital I/O
 - 8 Channels of Archival Grade 192k A/D D/A converters
 - 8 Channels of Exceptional Remote Controllable Ultra-Low-Noise Clickless Preamps
 - Fully clickless remote controlled Monitor outputs for flexible monitoring applications from stereo to 7.1 surround
 - DB-25 I/O w/ 8-channels of mic-in, line-in, line-out, balanced sends, and AES/EBU
 - 2x 1/4" monitor outputs, 1/4" headphone
 - Word clock, SMPTE and MIDI I/O
 - Comprehensive, High Resolution 15 Segment Precision Front Panel Metering
 - 2x 1/4" DI suitable for instrument or turntable inputs
 - Integrated Mixing and Deep Instantiable DSP Processing (Includes Full +DSP License)
- ULN8**..... 8in/8out FireWire Interface..... CALL



MOTU
MOTU 828MK3 FIREWIRE/USB2 INTERFACE

- 28x30 24-bit/48kHz analog/digital I/O
 - Or 20x24 @ 24-bit/96kHz, 10x10 @ 24-bit/192kHz
 - (2) XLR/TRS (mic/guitar) combo w/ phantom
 - XLR right/left main outputs
 - 8-in/8-out unbalanced 1/4", 2x 1/4" headphones
 - 2x FireWire type B ports, USB2.0, 1/4" SMPTE I/O
 - 2x optical ADAT (SMUX), coaxial S/PDIF, word clock & MIDI I/O
 - 1/4" footswitch, 2x 1/4" sends
 - CueMix FX digital mixer with built-in effects
 - Includes AudioDesk workstation software (Mac only)
 - ASIO2, WDM, Wave, GSIF 2, CoreAudio/ MIDI support
 - Windows XP, Vista and Mac OSX compatible
- 828MK3-HYBRID**... 20-in/22-out FireWire/USB2.0 interface..... 749.00



M-AUDIO
M-AUDIO PROFIRE 610 FIREWIRE INTERFACE

- 6x10 simultaneous analog/digital I/O
 - 24bit/192kHz audio throughout signal path
 - 2 XLR/TS mic/line combo w/ phantom
 - 2-in/8-out balanced 1/4" TRS
 - 2 1/4" TRS headphone outputs
 - S/PDIF and MIDI I/O
 - 2x 6-pin FireWire ports
 - 2 preamps with award-winning Octane™ technology
 - Flexible onboard DSP mixer
 - User-assignable master volume knob
 - Standalone 2-channel mic pre/2-channel A/D-D/A converter
- PROFIRE-610**..... 6-in/10-out FireWire interface..... 399.00
- PROTOOLS-MPOWERED-8**.. Optional DAW software, includes iLok..... 249.95



METRIC HALO
METRIC HALO MOBILE I/O 2882 FIREWIRE AUDIO INTERFACE WITH DS

- 18x18 24bit/48kHz analog/digital I/O or 14x14 @ 24bit/96kHz
 - 4 XLR mic/line combo w/ phantom
 - 4-in/8-out balanced TRS, 1/4" headphones
 - 8 channels of ADAT I/O (switchable to TosLINK)
 - Coaxial S/PDIF, AES and wordclock I/O
 - Full front-panel metering, remote level control on all channels
 - 2x 6-pin bus powered FireWire ports or external PSU
 - DSP on-board processing for Metric Halo plug-ins (2882+DSP only)
 - OS X drivers (with multibox support in OS X)
 - Ships with rack kit & 4-pin locking world ready power supply
- MIO2882-EXP+DSP**..... 18-in/18-out FW interface w/ DSP.... 2594.00
- MIO2882-EXPANDED**.... 18-in/18-out FW interface w/out DSP. 1895.00



MOTU
MOTU 896MK3 FIREWIRE INTERFACE

- 28x32 24bit/48kHz analog/digital I/O
 - Or 20x24 @ 24bit/96kHz, 10x10 @ 24bit/192kHz
 - 8-XLR/TRS mic/line combo w/phantom
 - 8 XLR outputs, stereo XLR main outputs
 - 2x 1/4" headphone out (1mirrors main out)
 - 2x ADAT optical w/ SMUX I/O and Toslink
 - AES/EBU, coaxial S/PDIF and wordclock I/O
 - CueMix FX flexible 28-input/16-bus mixer with DSP effects
 - Standalone mix operation
 - Front panel metering, clip protection limiter
 - Includes AudioDesk workstation software
 - ASIO, WDM, Wave, GSIF, Core Audio, and Core MIDI support
- 896MK3**..... 28-in/32-out FireWire audio interface..... 995.00



PLEASE ALWAYS CONSULT MANUFACTURER'S WEBSITE FOR MOST CURRENT SYSTEM REQUIREMENTS!

Quick Purchase: 800-476-9886
M-F: 8:30-5:30 CST



FULLCOMPASS.COM

Full Service: 800-356-5844
M-F: 9:00-5:30 CST



- AUDIO
- COMPUTER AV
- VIDEO
- LIGHTS
- MUSIC
- ACCESSORIES

MOTU

MOTU TRAVELER MOBILE FIREWIRE INTERFACE

- 28x30 24bit/48kHz analog/digital I/O
- 4x8 @ 24bit/192kHz
- 4-XLR/TRS mic/line combo w/ phantom
- 4-in/8-out unbalanced 1/4", 1/4" headphones
- Two 6-pin bus powered FireWire ports, (external/battery power option)
- Optical SMUX ADAT, coaxial S/PDIF, AES/EBU stereo and word clock I/O
- Flexible 28-input/16-bus mixer with on-board DSP effects
- Includes classic reverb with sends/returns, plus modeled EQ and vintage compression on every input and output
- Includes AudioDesk 3 workstation software (Mac only)
- ASIO, WDM, Core Audio, and Core MIDI support
- Windows XP, Vista and Mac OSX compatible

TRAVELER-MK3 28-in/30-out FireWire audio interface 849.00
TRAVELER-BAG Bag for Traveler 89.00

PreSonus

PRESONUS FIRESTUDIO MOBILE AUDIO INTERFACE

- 10x6 24-bit/96kHz analog/digital I/O
- 2 XMAX™ PreSonus preamplifiers w/ 48V phantom
- 8-in/2-out balanced 1/4" TRS
- Stereo S/PDIF and MIDI I/O via DB9 breakout cable
- Headphone output with gain control
- 2x 6-pin bus-powered FireWire ports or external PSU
- Software router/mixer
- DICE II Chipset and JetPLL™ - jitter-elimination technology
- Studio One Artist™ multitrack-recording software included
- ASIO2, WDM, CoreAudio/MIDI support
- Mac and Windows compatible
- FS Mobile Studio bundle adds (2) SD7 condenser mics, Stereo XY Mic-stand adapter & XLR cables, HD7 headphones

FIRESTUDIO-MOBILE 10-in/6-out FireWire interface 299.95
FS-MOBILE-STUDIO-BUN FireStudio Mobile bundle 509.40

steinberg

STEINBERG MR816 CSX & MR816 X FIREWIRE INTERFACES

- No latency, DSP-powered FX and full Cubase Control Room support w/ independent Studio mixes
- Direct access from Cubase with no additional software mixing or external windows required
- 8-XLR/TRS mic/line combo Class A analog "D-Pre" preamps w/phantom
- Switchable phantom power per channel
- Digital ADAT and S/PDIF I/O
- Instant routing of inputs to Cubase channels from the hardware with the push of a button
- Up to 8 simultaneous onboard DSP-powered Sweet Spot Morphing Channel Strip w/ compressor, EQ & REV-X reverb
- Includes Cubase AI4 software

MR816-CSX .16-in/16-out FireWire interface w/built-in DSP FX ... 999.99
MR816-X 16-in/16-out FireWire interface 699.99

MOTU

MOTU ULTRALITE-MK3 MOBILE FIREWIRE/USB INTERFACE

- 10x14 24bit/96kHz analog/digital I/O
- Or 8x8 24bit/192kHz
- 2 XLR mic/line combo w/phantom
- 6-in/10-out balanced TRS, 1/4" headphones
- Coaxial S/PDIF and MIDI I/O
- USB2 and 6-pin FireWire port, bus powered or external PSU
- On-board DSP effects including reverb w/ sends/returns
- Standalone operation, tweak w/back-lit LCD and controls
- Includes AudioDesk workstation for Macintosh
- ASIO, WDM, Wave, GSIF, Core Audio, and Core MIDI
- Windows XP, Vista and Mac OSX compatible

ULTRALITE-MK3-HYBRID .. 10-in/14-out FireWire/USB2 interface .. 549.00

PreSonus

PRESONUS FIRESTUDIO PROJECT FIREWIRE RECORDING INTERFACE

- 10x10 24bit/96kHz analog/digital I/O
- 8-XLR/TRS mic/line combo w/ phantom
- 2-in/8-out balanced 1/4", 1/4" headphones
- 2x 1/4" return and sends
- Coaxial S/PDIF and MIDI I/O
- 2x 6-pin FireWire ports
- Zero-latency monitoring w/ DSP mixer/router
- ASIO2, WDM, CoreAudio/MIDI support
- FREE PreSonus Studio One Artist recording and production software
- Mac and Windows compatible

FIRESTUDIO-PROJECT 10-in/10-out FireWire interface 499.95

t.c. electronic

TC ELECTRONIC IMPACT TWIN FIREWIRE INTERFACE

- 24bit/192kHz analog/digital I/O
- 2 XLR mic/line combo w/ phantom - Impact III™ Technology
- 4-in/4-out balanced TRS, 2x 1/4" headphones
- Optical S/PDIF (4ch SMUX @ 96 kHz), coaxial S/PDIF and MIDI I/O
- 2x 6-pin bus powered FireWire ports or external PSU
- 2x headphones out (front panel)
- Onboard EQ, Compressor and De-esser
- Includes M40 Studio Reverb, Assimilator, ResFilter effects
- Includes Ableton Live Lite 8 TC Electronic Edition
- WDM, ASIO, and Core Audio support
- Windows XP and Mac OSX compatible

IMPACT-TWIN 14-in/14-out FireWire interface 399.00

PHONIC

PHONIC FIREFLY 302 PLUS FIREWIRE INTERFACE

- 24-bit/96kHz FireWire stream I/O (3 x 2)
- Microphone input with +48V phantom power
- 2 analog inputs with 1/4" phone and RCA jacks
- S/PDIF in and out (44.1kHz to 96 kHz sampling rate)
- Headphone output with dedicated level control
- 16-channel MIDI I/O
- Zero-latency hardware direct monitoring
- Two built-in high-bandwidth FireWire ports
- Powered through FireWire bus or DC power supply
- Latency-free ASIO drivers
- Compatible with Mac and Windows operating systems

FIREFLY-302-PLUS .. 3-in/2-out FireWire audio interface 149.99

RME

RME FIREFACE 400 192KHZ AUDIO INTERFACE

- 18x18 24bit/48kHz analog/digital I/O
- 14x14 @ 24bit/96kHz or 10x10 @ 24bit/192kHz
- 2-XLR mic/line combo w/ phantom
- 6-in/6-out analog balanced 1/4", 1/4" headphones
- Optical ADAT/ S/PDIF, coaxial S/PDIF, word-clock and 2x MIDI I/O
- (2) 6-pin bus-powered FireWire ports or external PSU
- ASIO2, MME, GSIF 2, WDM, CoreAudio/MIDI support
- Windows 2K, XP/XP64, Vista and Mac OSX compatible

FIREFACE-400 18-in/18-out FireWire interface 1299.00

t.c. electronic

TC ELECTRONIC DESKTOP KONNEKT 6

- 24bit/192kHz sampling rate
- IMPACT™ mic preamp with 48V phantom power
- True Hi-Z guitar inputs, balanced stereo outputs
- Headphone-out with separate level control and separate source
- M40 studio sound reverb (monitor mix and as VST/AU compatible plug-ins)
- Big volume control, tracking reverb level control
- Direct monitor control with input/DAW control
- DIM switch for convenient speaker EQing
- High-resolution meter, Instant scene recall
- Cubase LE4 included
- FireWire 1394, bus powered
- WDM, ASIO and CoreAudio support

KONNEKT-DESKTOP-6 4-in/2-out FireWire interface w/DSP .. 199.00

PHONIC

PHONIC FIREFLY 808 UNIVERSAL FIREWIRE & USB 2.0 AUDIO INTERFACE

- 24bit/192 kHz sampling rate
- 18 simultaneous inputs/outputs
- 8 mic pres w/ trim and individual phantom
- 8 analog line inputs w/ 2 instrument inputs
- 8 channels of optical ADAT I/O (4 ch via 96k dual SMUX)
- S/PDIF I/O, AES/EBU I/O, MIDI I/O and word clock I/O
- Headphone output and Main output with volume control
- 2x 6-pin FireWire ports
- Instrument input, pad switch, balanced TRS send jacks on Inputs 1 and 2
- Compatible with Mac OSX and Windows XP, Vista & 7
- Steinberg Cubase LE 4 DAW software included

FIREFLY-808-UNIVERSL .. 18-in/18-out FireWire/USB2 interface .. 499.99

RME

RME FIREFACE 800 192KHZ AUDIO INTERFACE

- 35 sources into 28 discrete x 30 24bit/48kHz analog/digital I/O
- Or 20x22 @ 24bit/96kHz, 16x18 @ 24bit/192kHz
- 4 separate XLR and TRS w/ phantom
- 8-in/8-out analog balanced 1/4", 1/4" headphones
- 2x optical ADAT/ S/PDIF, coaxial S/PDIF, word clock & MIDI I/O
- A 6-pin and two 4-pin FireWire ports
- Time Code option insert slot
- ASIO2, MME, GSFI 2, WDM, CoreAudio/MIDI support
- Windows XP, Vista and Mac OSX compatible

FIREFACE-800 56-channel FireWire interface TCO-FF Time Code card (word clock, LTC sync) .. 1699.00
TCO-FF Time Code card (word clock, LTC sync) 499.00

t.c. electronic

TC ELECTRONIC STUDIO KONNEKT 48

- 30x28 24bit/48kHz simultaneous I/O
- 22x20 24bit/96kHz simultaneous I/O
- 12x12 24bit/192kHz simultaneous I/O
- 4 XLR/TRS mic/line combo w/ phantom
- 8in/8out 1/4" balanced, stereo XLRs main out
- 2x ADAT I/O (8 channels, 96 kHz SMUX)
- 2x headphone outs (1 discrete)
- Coaxial S/PDIF, MIDI and word clock I/O
- Built-in DSP effects -Fabrik C/R, Reverb 4000
- Studio Kontrol remote w/ built-in talkback
- ASIO2, WDM, CoreAudio/MIDI support
- Windows XP and Mac OSX compatible

STUDIO-KONNEKT-48 .30-in/28-out FireWire interface, no remote .. 799.00
STUDIO-KONNEKT-BUNDL 30-in/28-out FireWire interface, w/remote 999.00

PLEASE ALWAYS CONSULT MANUFACTURER'S WEBSITE FOR MOST CURRENT SYSTEM REQUIREMENTS!

- LEGEND: AUDIO OVER FIREWIRE AUDIO OVER USB PCI CARD PCI EXPRESS CARD MIDI INTERFACE M-POWERED COMPATIBLE ETHERNET



Elevate recording.



Pro Tools Mbox Pro | 8 x 8 24-bit/192 kHz* FireWire recording system

Meet the next-generation Pro Tools Mbox recording systems

The original Mbox[®] revolutionized home recording—now take your music to new heights with the third generation of the world's most popular personal recording systems. With completely redesigned analog signal paths, premium studio-grade converters, and technology from our Pro Tools|HD systems, the new Mbox interfaces deliver sound that's so pristine, you'll want to use Mbox with all your music software. And now, all-new drivers ensure ultra-stable performance with the included Pro Tools[®] software and other recording applications.

* Up to 96 kHz sample rates supported with Pro Tools LE software.



Pro Tools Mbox Mini | 2 x 2 24-bit/48 kHz USB recording system



Pro Tools Mbox | 4 x 4 24-bit/96 kHz USB 2 recording system

Contact Full Compass to learn more about the Mbox product family.



800-356-5844
fullcompass.com

© 2010 Avid Technology, Inc. All rights reserved. Product features, specifications, system requirements, and availability are subject to change without notice. Use of the enclosed software is subject to a related license agreement. Avid, the Avid logo, Mbox, Pro Tools, and Pro Tools LE are trademarks or registered trademarks of Avid Technology, Inc. in the U.S. and other countries. All other trademarks contained herein are the property of their respective owners.