













































DOUG FLEENOR DESIGN

PRODUCTS FOR DMX512

DOUG FLEENOR DESIGN DMX ISOLATED SPLITTERS The DMX512 isolated splitter / amplifier is available with 3, 5 or 11 outputs from a single DMX input. Each output is



electrically isolated from the input and from every other output using 2500V optical couplers. Each output has its own line driver and associated power supply.

1	•	11 0
ITEM	DESCRIPTION	PRICE
123	DMX isolation amp and 3X splitter	 463.50
125	DMX isolation amp and 5X splitter	 661.75
1211	DMX isolation amp and 11X splitter	 1347.20

DOUG FLEENOR DESIGN DMX TO MICROPLEX INTERFACE This interface is capable of converting DMX512 to Sunn, ETA, NSI, Leprecon or Lightronics versions of Microplex. Since each of these manufactures uses unique timings, the DMX to Microplex provides jumpers to configure the output. Common names for conversions the DMX2MPX is capable of handling include DMX to LMX 64, DMX to LMX 128, DMX to Microplex, DMX to Multiple, DMX to Ultraplex.

		-	
ITEM	DESCRIPTION		PRICE
DMX2MPX	. DMX to Microplex converter	 	. 588.42

DOUG FLEENOR DESIGN DMX TO ANALOG CONVERTERS Interfacing to older dimmers, custom controls, animatronics, and motion control are just a few uses of the DMX512 to 0-10V analog converter. Available In 24- or 96-channel versions.

ITEM	DESCRIPTION	PRICE
DMX24ANL	24-channel converter	588.42
DMX96ANL	96-channel converter	1267.36



ELATION EMULATION LIGHTING CONTROL SOFTWARE Emulation Lighting Control Software is used for DMX 512 lighting control for intelligent lights, LED,

dimmers, lasers and various other effects. The software is shipped with a USB-to-DMX



adapter cable, compliant with the new DMX512-A standard. The key to the design of Emulation Lighting Control Software is its intuitive graphical user-interface. It is specifically designed to reduce the amount of time required to learn how to operate the software. Combined with its affordable price, this software package is available to a large audience of lighting users who want easy-to-use, yet powerful lighting control software. Available for Mac OS X and Microsoft Windows.

ITEM	DESCRIPTION	PRICE
EMULATION	. Lighting Control Software	499.99

ELATION SHOW DESIGNER 3 INTELLIGENT LIGHTING CONTROLLER This controller

offers both power and flexibility for all your programming applications. A compact flash drive

makes backing up programs, adding fixture profiles, and updating software a snap.

- 3 DMX Universe, 3- & 5-pin connectors on each output
- Control 48 moving light fixtures and 128 conventional dimmers
- Effect generator creates chase effects
- Scenes, shows, chases and presets can be assigned to the playbacks
- 80-character backlit display for easy programming
- 48 multi-function quick-access buttons
- 8 dedicated playback faders with 32 pages
- Pan/tilt joystick with coarse/fine control
- · Blackout, audio and beat buttons
- · Run 16 chases simultaneously

ITEM	DESCRIPTION	PRICE
SHOW-DESIGNER-3	. Intelligent lighting controller	. 2999.99



ELATION MAGIC 260 INTELLIGENT LIGHTING CONTROLLER The Magic 260 is a 19" rackmount DMX controller ideal



for lighting operators who don't need a big console, but want a compact product with more features. It comes equipped with a large library of pre-installed profiles for moving light fixtures so users don't have to spend time programming their own.

- Pan/tilt joystick
- · 4 data wheels for moving light control and data entry
- 3-pin DMX output
- 260 total moving light channels
- Internal fixture library
- Control up to 24 fixtures (up to 16 channels each)
- 1152 programmable scenes & 264 programmable shows
- · MIDI input and thru

MA

- 80-character backlit LCD display for easy programming
- Audio input and internal microphone
- Go button for manual show triggering
- Master fader for moving light dimmer control
- Separate speed and fade faders
- Effects engine includes circle, figure-8 and pan & tilt movement with wave effect

	engine meradee errere, ngare e and pan a the meremen	it man ouroet	
EM	DESCRIPTION	PRICE	
AGIC-26	1 Intelligent lighting controller.	599.99	

ELATION TRIO SERIES DMX CONSOLES



of conventional lights, moving lights and LEDs. Includes 6 operation modes: single

scene, two scene, sub master moving light, LED and memory playback modes. Features 1152 recordable scenes (24 pages x 48 scenes), 12 built-in FX, LCD display, 20 playbacks x 99 steps in moving light & LED modes, backlit buttons, Grand Master fader, USB, 3-pin DMX in, and two sets of 3 & 5-pin DMX outs. 9-12VDC 2A power supply included

supply illen	ided.	
ITEM	DESCRIPTION PRI	CE
TRIO-1248	. 24 configurable faders, control 12 ML fixtures (up to 40 ch. each),	
	control 12 LED (RGBA) fixtures, 2.75"H x 19"W x 10.4"L, 9 lbs	99
TRIO-2496	. 48 configurable faders, control 24 ML fixtures (up to 40 ch. each),	
	control 24 LED (RGBA) fixtures, 2.75"H x 28.25"W x 10.4"L, 14.33 lbs 1499.	99
TRIO-VGA	Optional 800x600 VGA monitor output	99

ETC ELEMENT LIGHTING

CONSOLE Based on ETC's Eos® control system with a simplified feature set, Element was designed expressly for modest rigs and maximum hands-on control.



Affordable and easy to use, Element packs the fundamentals of lighting control into a compact unit. Element comes in two hardware versions (based on fader count) to suit your needs. Each supports either 250 or 500 channels with two full universes of DMX output. Channel Faders are true Latest Takes Precedence, so you can use them for simple shows directly or to build up looks for use as submasters, cues, or edit levels stored in subs or cues live. Turn a switch and your channel faders become 40 Submasters for simple playback of live shows. Need subs all the time? The Element 60 provides 20 dedicated submaster faders in addition to the 40 switchable channel/submaster faders. Record cues and fade times into Element's cue PRICE for simple playback of more complex shows using a GO button. At the press of a button, the On Demand ML Controls appear on screen with tools designed to control smaller numbers of non-intensity equipment like scrollers, gobo rotators and mirror heads. Color and Gel Picker tools let you apply just the right color to LEDs and color-mixing accessories and fixtures. Intensity, Focus, Color and Beam Palettes let you store commonly-used settings to buttons you can label yourself. Supports two external DVI monitors (which can be touchscreens).

ITEM	DESCRIPTION	PRICE
LMNT-40-250	. 40-fader, 250-channel, Element Console	CALL
LMNT-40-500	. 40-fader, 500-channel, Element Console	CALL
LMNT-60-250	. 60-fader, 250-channel, Element Console	CALL
LMNT-60-500	. 60-fader, 500-channel, Element Console	CALL





ETC SMARTFADE 1248 & 2496

- 48 or 96 channels in normal mode
- 12 or 24 channels in two-scene mode
- DMX input (full universe each)
- USB for software updates
- 24-step sequences (48 available)
- 99-step STACK, playback via crossfaders
- · Manual, timed and rate-override playback
- · LCD menu for configuration and preview

ITEM	DESCRIPTION	PRICE
SF1248	. 48-channel control console	1121.25
SF2496	. 96-channel control console	1421.25

ETC SMARTFADE® ML

SmartFade ML provides palettes, parameter "fan" and



built-in dynamic effects with an easy-to-learn direct-access style of operation. Has a capacity for up to 24 moving lights, an additional 48 intensity channels (dimmers), and the ability to patch to 2 complete universes of DMX512 (1,024 outputs). The keys and built-in LCD displays also provide status feedback without the need for an external monitor.

ITEM	DESCRIPTION	PRICE
SFML	. Moving light controller	2246.25



ETC SMARTBAR 2 SmartBar 2 gives you next-generation dimming for portable or permanent installations without busting budgets. It provides an integrated dimming and fixture-mounting solution for compact, low-power applications such as rentals, industrials, or even small touring productions. Available in 2, 4 or 6 dimmer versions, with each dimmer capable of providing up to 1200 Watts. Each SmartBar 2 is supplied with a 12' SO power cord with bare ends (no connector).

Supplied with c-clamp and color frame

ITEM	DESCRIPTION	PRICE
SB2-10-A	. 2 Circuit SmartBar 2, 1 phase, Edison	659.10
SB2-10-B	. 2 Circuit SmartBar 2, 1 phase, Stage Pin	659.10
SB2-10-C	. 2 Circuit SmartBar 2, 1 phase, Twist-Lok	659.10
SB4-10-A	. 4 Circuit SmartBar 2, 1 phase, Edison	698.10
SB4-10-B	. 4 Circuit SmartBar 2, 1 phase, Stage Pin	698.10
SB4-10-C	. 4 Circuit SmartBar 2, 1 phase, Twist-Lok	698.10
SB4-10X-A	. 4 Circuit SmartBar 2, 2 phase, Edison	776.10
	. 4 Circuit SmartBar 2, 2 phase, Stage Pin	
SB4-10X-C	. 4 Circuit SmartBar 2, 2 phase, Twist-Lok	776.10
SB6-10X-A	. 6 Circuit SmartBar 2, 2 phase, Edison	1322.10
SB6-10X-B	. 6 Circuit SmartBar 2, 2 phase, Stage Pin	1322.10
SB6-10X-C	. 6 Circuit SmartBar 2, 2 phase, Twist-Lok	1322.10
SB6-10Y-A	. 6 Circuit SmartBar 2, 3 phase, Edison	1244.10
SB6-10Y-B	. 6 Circuit SmartBar 2, 3 phase, Stage Pin	1244.10
SB6-10Y-C	. 6 Circuit SmartBar 2, 3 phase, Twist-Lok	1244.10



ETC SMARTPACK CE PORTABLE PACKS These portable dimmers pack professional quality dimming into a rugged 19-inch 2RU rackmount unit. Available with either six 15A dimmers or twelve 10A dimmers. SmartPack has 32 built-in presets and a sequencer for stand alone operation. Features true thyristor reliability based on Sensor[™] technology and include all magnetic circuit breakers. DMX512A compatible.

ITEM	DESCRIPTION	PRICE
SL620 Series: 6 2	OA dimmers	
SL620A	. Edison connectors	1162.50
SL620B	. Stage pin connectors	1162.50
	. GTL connectors	
SL620P	. Powercon connectors	1275.00
SL620V	. 1 multi-pin connector	1462.50
SL620TM	. Terminal strip	1521.00
SL1210 Series: 12		
SL1210A	. Edison connectors	1537.50
SL1210B	. Stage pin connectors	1537.50
SL1210P	. GTL connectors	1537.50
SL1210V	. 2 multi-pin connectors	1725.00
	. Terminal strip	



UNISON DRD DIMMING

SYSTEMS Available in 6- and 12-module enclosures for up to 24 dimmers. Can be cross-bussed from the same main power input, combining enclosures for up to 48 dimmers from a single feed, while only needing one control processor for both enclosures. The Unison DRd supports either a Paradigm or SmartLink Architectural Processor and an optional Station Power Module. The enclosure



supports ETC's Net3™, DMX512A (RS232 serial, and contact-closure interfaces when used with a Paradigm Control Processor). Unison DRd's dimming engine monitors and stabilizes incoming line voltage with minimum and maximum settings. The Unison DRd also features QuickBoot (coming online in just 7 seconds), and the UL924-Listed Bypass Input for even faster emergency lighting use. When it comes to fluorescent dimming, Unison DRd can handle it all: 2- and 3-wire dimming ballasts with standard modules, DALI Ballasts with the DALI Option Board, and 0-10V ballasts with the FLO Option Board. It also does reverse-phase dimming (trailing edge) for electronic low-voltage transformers, and a full range of other loads.

CALL YOUR SALES PROFESSIONAL FOR A QUOTE SPECIFIC TO YOUR APPLICATION

JANDS

JANDS VISTA LIGHTING CONTROLS

Design lightshows visually, without the need for converting a complex series of numbers or spending hours punching in sequences. This console's user interface features a "timeline" that gives a complete picture of your lightshow, with total control over lighting events. The

Vista's new approach to the lighting control user interface makes it incredibly easy to use and its generic fixture model makes changing fixtures easy. The Vista is available as a full-featured console, or as a software option with a variety of control surfaces and channel counts.

ITEM	DESCRIPTION	PRICE
JAVISTAT4-V2	.Console with 30 playbacks	CALL
JAVISTAT2-V2	.Console with 15 playbacks	CALL
JAVISTAS3	.Control surface with 20 playbks (chnl ct. determined by dongle)	CALL
JAVISTAS1	.Control surface with 5 playbks (chnl ct. determined by dongle)	CALL
JAVISTAS1/1024 .	.Compact control surface with 5 playbacks and 1024 chnl dongle	CALL
JAVISTAM1	.Compact playback surface (chnl count determined by dongle)	1045.63
JAVISTAC128	.128 control channel dongle	. 525.00
JAVISTAC256	.256 control channel dongle	1039.50
JAVISTAC512	.512 control channel dongle	1564.50
JAVISTAC1K	.1024 control channel dongle	2614.50
JAVISTAC2K	.2048 control channel dongle	CALL

Leprecon.

FULLCOMPASS.COM

LEPRECON ULD SERIES DIMM dimmer is equipped with dual 25-am magnetic breakers, plus over volt/ove encapsulated chokes come standard operation. Through the display-base channel can be defined as either a fixed intensity level. DMX-512 on 5-pin

ITEM	DESCRIPTION	PRICE
ULD360-STANDARD	Stage pin 6-channel pack w/ single 15-amp breaker	614.25
ULD360-HP	Stage pin 6-channel pk w/ dual 15-amp breakers	696.15
ULD360-DUPLEX	6-channel pk w/ single 15-amp breaker & Edison conn	590.85
ULD360-DUPLEX-HP	6-channel pk w/ dual 15-amp breaker & Edison conn	672.75
ULD340-STANDARD	Stage pin 4-channel pk w/ single 15-amp breaker	573.30
ULD340-HP	Stage pin 4-channel pk w/ dual 15-amp breakers	538.20
ULD340-DUPLEX	4-channel pk w/ single-amp breaker & Edison conn	544.05
ULD340-DUPLEX-HP	4-channel pk w/ dual 15-amp breakers & Edison conn	625.95































































































LEPRECON LPC LIGHTING CONSOLE

The latest console from Leprecon was designed with the intent to be simple enough for volunteer staff, yet powerful enough for any experienced user. Aimed at systems running mostly conventional



lighting, the LPC offers hands-on fader control for dimmers, LED fixtures and moving lights. The dynamic user interface and optional touchscreen control further add to its ease of use making it ideal for schools and houses of worship.

- 1 Scene, 2 Scene Preset, Submaster & Cue Stack operation
- 512 control channels
- 1024 DMX channels
- Fully programmable cue stack (999 Cues)
- Graphical cue timing display Includes: Up and Down, Follow & Wait timing parameters
- Run multiple chases including chase "Blend" mode
- 6 "Quick Look" memories with fade times
- 1000 fixture groups
- · Bump modes include: Solo, Add and Latch w/ Fade

ITEM	DESCRIPTION	PRICE
LPC48V	. 48 channel console	CALL
LPC48V-ELO	. 48 channel console w/ 15" ELO touchscreen	CALL
LPC48V-DMX	. 48 channel console w/ wireless DMX option	CALL
LPC96V	. 96 channel console	CALL
LPC96V-ELO	. 96 channel console w/ 15" ELO touchscreen	CALL
LPC96V-DMX	. 96 channel console w/ wireless DMX option	CALL
ELO-15	. 15" ELO touchscreen	1102.14
ELO-15-CASE	. 15" ELO Touch screen Flight Case	519.48
LPC48V-CASE	.XL style case for LPC-48V with recessed latches	CALL

LEPRECON LP-612/LP-624 CONTROL

CONSOLES Available in 12 or 24 channels, these consoles incorporate full travel faders and a rugged aluminum chassis. Features 2-scene preset mode, soft patch, chase memory, bump



with Add and Solo modes, and a cue stack offering 50 programmable cues with crossfader and "Go" button control. Output via 3-pin Microplex with DMX-512 and analog also available. All three protocols are accessible simultaneously.

ITEM	DESCRIPTION	PRICE
LP612MPX-DMX	12-channel multiplex/digital/analog	735.93
I P624MPX-NMX	24-channel multipley/digital/analog	1262 43

LEPRECON LDS-610

A 6-ch, 1200W per channel distributed dimmer ideally suited for applications with limited space and power available. It can be discretely located throughout venues such as schools, churches and small theaters. Features convection cooling for nearly silent operation, a variety of mounting options, internal phase switching and your choice of output connectors (Edison, Stage Pin, or Twist Lock). Available in black or white.

ITEM	DESCRIPTION	PRICE
LDS610	Stage pin, six channel dimmer	1647.36
LDS610-AUX	Stage pin w/ Aux, six channel dimmer	1805.31
LDS610-DUPLEX	Duplex, six channel dimmer	1502.28
LDS610-DUPLEX-AUX	Duplex w/ aux, six channel dimmer	1659.06
LDS610-TWISTLOCK-AUX	Twist Lock w/ Aux, six channel dimmer	1841.42
LDS610-AUX-DMX	Stage pin w/ Aux, six channel W-DMX dimmer	2197.26
LDS610-DUPLEX-AUX-DM	Duplex w/ Aux, six channel W-DMX dimmer	2051.01
LDS610-DUPLEX-DMX	Duplex, six channel W-DMX dimmer	1894.23
LDS610-WHITE	Stage pin, six channel dimmer, White	1647.36
LDS610-AUX-WHITE	Stage pin w/ Aux, six channel dimmer, White	1805.31
LDS610-DUPLEX-WHITE	Duplex, six channel dimmer, White	1502.28
LDS610-DUPLEX-AUX-WH	Duplex, w/ Aux, six channel dimmer, White	1659.06

LEX

LEX PRODUCTS SLIM DIMMER The Slim Dimmer is an 1800W, 120VAC electronic dimmer with NEMA 5-15 (Edison) connectors. It is a compact, rugged, unfiltered dimmer with onboard fader control. The Slim Dimmer's digital intensity display provides dimming for balancing or matching lights anywhere simple dimming is required, such as television or movie sets.



ITEM	DESCRIPTION	PRICE
LDT1.8K	1800 Watt Slim Dimmer	288.00

LIGHTRONICS

LIGHTRONICS **TL-2448 LIGHTING CONSOLE**

- 1200 scenes
- 36 programmable chases
- Cue stack stores up to 600 scenes
- 48 conventional channels / 8 moving light sub master controllers
- Built in softpatch
- Full go button
- LMX-128 and DMX-512 protocols
- Wireless DMX Option

ITEM	DESCRIPTION	PRICE
TL-2448	Lighting console	1665.00
	Lighting console with Wireless DMX	

LIGHTRONICS TL-5024 CONTROL CONSOLE

- 24 channels
- 192 scenes
- 12 chases
- 240-scene cue PRICE
- Built-in softpatch
- 2-line LED display
- Full go button
- LMX-128 protocol
- 12-channel / 2-scene mode or 24-channel / 1-scene mode
- Optional DMX-512 or wireless DMX

ITEM	DESCRIPTION	PRICE
TL-5024	Lighting control console	596.25
TL-5024-WS-TX	Lighting control console w/ wireless DMX transmitter	1008.75
TL-5024-DMX01	Lighting control console w/ optional DMX 512 output	678.75

LIGHTRONICS XC-42 PORTABLE DIMMER

- 4 channels, 1200W per channel
- Softpatch (each dimmer)
- Dimmer limiting & dimmer curve selection
- Architectural interface
- · AMX/Crestron interface
- DMX-512 protocol, wireless DMX option
- 8 built-in chases
- Relay mode switchable
- · Edison outputs

ITFM	DESCRIPTION	PRICE
IIEIVI	DESCRIPTION	FRIGE
XC42	. Portable dimmer	498.75
XC42-WSRX	. Portable dimmer with wireless DMX receiver	850.50

MARTIN PROFESSIONAL LIGHTJOCKEY PC BASED LIGHTING CONTROL LightJockey 2.7 is a flexible, easy to use Windows-based

controller that is supplied with a USB-DMX Interface. Extremely powerful, LightJockey





includes all the features that have made it the choice of lighting professionals in the club, mobile DJ, touring and special events markets: large fixture library, user friendly graphic functionality, advanced shape generator for fast and intuitive automated movement programming, as well as all the benefits of the Windows environment such as resizing of windows and drag and drop technology. For flexible music capabilities, LightJockey interfaces with Winamp™ to play a multitude of digital audio files including MP3s. LightJockey includes audio CD ROM capability as well. It also supports SMPTE and MIDI timecode with suitable interface.

ITEM	DESCRIPTION	PRICE
LIGHTJOCKEY-II-KIT	PC lighting controller	1430.00



WE'VE GOT YOU COVERED!

From theatres, schools, and houses of worship, to live event productions Leprecon is the answer to all your dimming and lighting control needs.



- · Built to last-the best value for your dollar
- · 100% designed and built in Hamburg, MI since 1980
- · Trustworthy-built to perform as advertised and work as expected
- · Customer safety, convenience, and ease of use is our top priority





....

....

















































MARTIN M1 LIGHTING DESK

The M1's dual-core processor ensures a fast and responsive interface and its user actions immediately translate to its output. Includes a hi-res,16:9, touchscreen that can be adjusted to provide the best viewing angle. An additional monitor can be connected via



VGA or DVI. The M1 has no sub-menus or hidden functions. Fixture parameters can be controlled using the M1's four encoders, its touchscreen, by trackball, or via the

The Playback section has 10 fader playbacks, the Submaster section features 12 faders with flash buttons, as well as an additional 12 flash buttons. Remote controllable via iPhone app (not included) or Maxxyz Manager. Can be fully integrated with other Martin consoles and Maxedia media servers and supports CITP thumbnail and MaxNet protocols. Includes an extensive fixture library and multiple color libraries (LEE, Rosco, GAM). Fixtures can be added to patches and grouped easily. Effects generation gives each parameter its own effect parameter, which tracks through your cuelist just like other device parameters. Multiple effects can be synched together. A cuelist's time scale can be increased or decreased on the M1 in order to accommodate on-the-fly changes made to a given show.

Provides multiple preset groups that allow for customization of all parameter assignments. Control multiple, or individual, parts of a given fixture. Thousands of cuelists, triggerable via SMPTE & MIDI timecode, can be created & stored, each with up to 10,000 cues - each PRICE can be set as chase, override, timecode, submaster, or inhibitive. User settings can be saved to USB stick. External DMX values can be merged into the M1's outputs for external cuelist control & can be captured for programming as cues. RDM compatible. Artnet 2 compliant (4x RJ-45 & expandable). Works with Maxxyz software (PC only, free download) & compatible with show files constructed on Maxxyz consoles. 4x DMX 5-pin XLR, 2x XLR desk lamp connections and 3 pin IEC AC power (cable included).

ITEM	DESCRIPTION	PRICE
M1-TS	. Console / controller	CALL
ETHER2DMX8-BOX	. DMX router / merger / splitter	

LEVITON

LEVITON 1000 SERIES CONTROLLER The

1000 Series can be used both as a 512 channel scene controller and DMX backup controller; offering in both situation recall of recorded scenes. Complete channel level control can be made via the convenient front panel keypad.



Features include 6 sub-masters, one master fader, scene memory (40), and a backup console mode. Operates from included re-chargeable battery or included power supply. 5-pin XLR in/out, DMX output.

ITEM	DESCRIPTION	PRICE
N1000-006	DMX Lighting Controller, 512 channel	359.07
N1RKT-006	19" EIA rack mount ears	32.64

LEVITON PICCOLO SERIES CONSOLES The Piccolo line

of lighting controllers function easily as standard manual/



memory boards with traditional channel capacities and simple user interface components, the line also offers features and capabilities previously unavailable in products in this category. They feature two scene, single scene, and submaster "Theater" operating modes, full access to all channels via faders, 32 attribute channels for automated devices and proportional softpatch to all 512 DMX channels. The user interface includes soft keys, arrow keys, keypad, and a 240x64 display. DMX I/O, ethernet, USB host and device, worklight, MIDI I/O, LT-Link. Power supply and dust cover included.

ITEM	DESCRIPTION	PRICE
PPICO-012	Piccolo 12/48 w/ 48 channels & 32 attributes	2598.37
PPICO-V12	Same as above, w/ VGA video option	3055.37
PPICO-024	Piccolo 24/96 w/ 48 channels & 32 attributes	3068.43
PPICO-V24	Same as above, w/ VGA video option	CALL
PPICO-036	Piccolo 36/144 w/ 48 channels & 32 attributes	CALL
PPICO-V36	Same as above, w/ VGA video option	CALL
PPICO-048	Piccolo 48/192 w/ 48 channels & 32 attributes	CALL
PPICO-V48	Same as above, w/ VGA video option	CALL



NSI D4-DMX PROGRAMMABLE DIMMER PACK

Leviton/NSI combines cutting edge NSI technology and performance with both DMX and Microplex control in the D4-DMX Dimmer Pack. It boasts convenient features



such as resettable circuit breakers in lieu of fuses and 1-button setup of digital DMX addressing via a user-friendly LED panel, eliminating dip-switch settings. Its sturdy metal chassis makes this rugged pack ideal for both stationary and portable applications. In addition to multichannel DMX and Microplex dimming control, these units can also provide a stand-alone chaser function with 16 pre-programmed patterns. Data "in" and "out" provided for easy daisy-chaining of devices. Input is 120V, 60Hz on 15A Edison plug. Output is 120V, 60Hz, 1200W per channel, 2400W maximum.

	•	_	•			•	
ITEM	DES	CRIP	TION				PRICE
D4-DMX-3	4-c	hanne	l dimmer	w/ 3-pin	DMX		 217.35
D4-DMX-5	4-c	hanne	l dimmer	w/ 5-pin	DMX		 217.35

NSI DDS SERIES DIMMERS High-quality UL-rated dimmers with dual SCR circuit, toroidal filtering, soft start, control and channel status LEDs. Available with Edison connectors, stage-pin, patch panel, twist-lock or knock-out chassis. All models have XLR Microplex inputs. DMX512 interface is optional



interface to optione		
ITEM	DESCRIPTION	PRICE
N5600-000	. 4-channel, 600W/ch DDS5600 dimmer with 15-amp	
	power cord, hanging satellite	481.01
N5600-020	DDS5600 dimmer w/ 20-amp power cord	481.01
N6000-000	. 4-channel, 1200W/ch, 2400W max DDS6000 dimmer	
	with 15-amp power cord, wall-mount	589.68
N6000-020	. DDS6000 w/ 20-amp power cord	589.68
N600P-000	. 4-channel, 1200W/channel, 4800W/max DDS6000+	
	dimmer with dual 15-amp AC cords	369.36
N600P-020	. DDS6000 w/ dual 20-amp power cords	646.38
A5512-000	. DMX-512 kit for N5600, N6000	103.95

NSI N7000/7500 SERIES The N7000 Series lighting consoles are simple and flexible with three operating modes. The consoles provide standard 2-scene preset operation, wide mode, single scene operation for double the channel capacity, and memory scene



operation. The N7000 Series is particularly well-suited to small theaters and stage performances. These products are so easy to program and operate, the instructions are printed right on the consoles. Features include individual channel bump buttons, dual dipless crossfaders, user programmable chase and scene memories, and grand master/blackout functions. The 7000 Series has XLR Microplex interface standard with optional DMX512. The 7500 Series has DMX512 standard, soft patching, auto faders, non-volatile memory, audio sync, cue stacking, and MIDI.

ITEM	DESCRIPTION	PRICE
N7008-D00	8-/16-channel, 8-scene memory	447.93
N7016-D00	16-/32-channel, 16-scene memory	665.28
N7516-000	16-/32-channel, 256 scenes	1832.36
N7024-D00	24-/48-channel, 24-scene memory	877.91
N7524-000	24-/48-channel, 384 scenes	2172.56
N7532-000	32-/64-channel, 512 scenes	2692.31
A7512-001	DMX512 adapter for N7008/7016/7024	107.73

NSI DIGITAL DS-SERIES MODULAR DIMMER

PACKS Rackmount dimmer packs with 16-character LCD display and front panel keypad for access to features. Standard interfaces are MicroPlex-XLR, Luma-Net and analog 0-10V. Features include



EEPROM storage, bump buttons, magnetic circuit breakers, voltage regulation, preheat and temperature LED. Knock-out versions available.

ITEM	DESCRIPTION	PRICE
NDS08-1E0	8-channel, 1200W/channel DS812E digital dimmer	
	with Edison sockets	1896.05
NDS08-1S0	Stage-pin version of NDS08-1E0	2192.30
NDS12-1E0	12-channel, 1200W/channel DS1212E digital dimmer	
	with Edison sockets	2369.02
NDS12-1S0	Stage-pin version of NDS12-1E0	2816.00
NDS08-2E0	8-channel, 2400W/channel DS824E digital dimmer	
	with Edison sockets	2249.48
NDS08-2S0	Stage-pin version of NDS08-2E0	2545.73
NDS12-2E0	12-channel, 2400W/channel DS1224E digital dimmer	
	with Edison sockets	CALL
NDS12-2S0	Stage-pin version of NDS12-2E0	CALL

