



MOTU

MOTU HD EXPRESS HDMI COMPACT VIDEO INTERFACE

- Supports Apple ProRes and other popular host-based codecs supported by Apple Final Cut Pro and Adobe Premiere Pro
- HDMI video capture and monitoring for Mac & PC, via PCI Express (tower) or ExpressCard (laptop) connectivity
- Captures and plays uncompressed HD and SD in 10-bit 4:2:2 color depth and up to 1920x1080 resolution
- Capture and monitor analog component HD or SD, plus composite and S-Video
- HDMI and HD/SD component in/out and composite and S-Video inputs only
- HDMI provides up to 8 simultaneous channels of embedded audio, analog RCA outputs for monitoring 5.1 or 7.1 surround sound
- Audio inputs include from HDMI, 2x RCA or S/PDIF, outputs are HDMI, 8x RCA or S/PDIF
- Front-panel headphone jack with dedicated volume control
- Half RU form factor



HD-EXPRESS-HDMIHDMI capturing interface w/PCI Express card495.00
HD-EXPRESS-HDMI-LPTPLaptop version of above w/ExpressCard adapter495.00

MOTU

MOTU HDX-SDI DIGITAL/ANALOG VIDEO PRODUCTION INTERFACE

- Full-raster ProRes workflow with Final Cut Pro
- HD/SD (capture/playback) video interface for Mac and Windows laptops or towers
- Supports Apple Final Cut Pro (Mac) and Adobe Premiere Pro (Windows)
- Capture and play back uncompressed 10-bit HD and SD from all formats
- HDMI output for 1080 HD monitoring
- Supports video reference, timecode & RS422 machine control
- Connect analog device through S-Video, composite or component connectors
- 8 1/4" TRS audio in/out
- IRU form factor, rack ears included
- Windows drivers coming soon

HDX-SDIPCI Express video interface Mac/Windows849.00
HDX-SDI-EXPRESSExpressCard/34 video interface Mac/Windows849.00

MOTU

MOTU V4HD FIREWIRE VIDEO PRODUCTION INTERFACE

- Full-raster ProRes workflow with Final Cut Pro
- HD/SD (capture/playback) FireWire video interface for Mac and Windows
- Supports Apple Final Cut Pro (Mac) and Adobe Premiere Pro (Windows)
- DVCPRO HD capture and play back 720 and 1080 HD over FireWire providing 100 Mb/sec quality and CPU-efficient, frame-based (non-GOP) native editing
- Capture and play back uncompressed 10bit SD from all formats
- HDMI output for 1080 HD monitoring
- Real time SD-to-HD up-convert and HD-to-SD down-convert
- Real-time 2:3 or 2:3:3:2 pull-down insertion and removal
- Connect multiple HD and SD sources and destinations simultaneously. Switch HD/SD sources on the fly while converting to multiple HD/SD destinations.
- Stand-alone operation – converts selected input source to supported output formats with SD-to-HD up-convert, HD-to-SD down-convert and pull-down insertion/removal


V4HDFireWire video interface Mac/Windows1995.00
------	---	--------------

datavideo®



DATAVIDEO CKL-300 SD/HD CHROMAKEY KIT

A perfect solution for standard or high definition video chroma key, without the hassle of paying tedious attention to background lighting. The kit includes the Datavideo LD-1 Dual green/blue LED light ring with a control unit with dimmer, and three 3'x8' RF-1025 retro-reflective screens with Velcro edges. The LED light ring is mounted on the lens of the camera using the included 72mm or 82mm adapter and projects a highly directional green or blue light on the back drop cloth. The cloth's embedded glass beads reflect light back to the camera creating a perfect green or blue background. Connect the screens to together and expand the background to a size that best fits your application. The RF-1025 retro-reflective screens also come with grommets and pole sleeves for studio applications.



ITEM	DESCRIPTION	PRICE
CKL-300HD/SD chroma key studio light kitCALL
LD-1Dual blue/green LED chroma ring with 72/82/58mm adapter rings & control box557.00

DATAVIDEO SE-500 ANALOG VIDEO MIXER/SWITCHER

A 4-channel mixer featuring S-video (Y/C) and composite video inputs. Features include dissolve, fade, wipes, splits, PIP and color processor. Channels are internally synced via a built-in dual-channel TBC 4:2:2 frame synchronizer. Has component (YUV) via breakout cable, S-video (Y/C) or composite video output. The SE-500 uniquely displays all 4 input sources via a single quad output so that the user only needs 2 video monitors – one for all inputs, one for output. The input display will also automatically change to preview the next transition if selected. Unit can be manually operated or via RS232 interface. The HS-500 is a mobile studio that pairs the SE-500 mixer/switcher with the TLM-702 dual 7" 16:9 widescreen monitor unit in a lightweight suitcase with rear access for cables.



ITEM	DESCRIPTION	PRICE
SE-5004-channel video mixer960.00
TLM702Dual 7" 16:9 widescreen monitor unit816.00
HS-500Hand-carried studio with SE-500 switcher & TLM-702 monitor unit2112.00
SE-500-KIT4-channel video mixer with (2) TLM-702 monitors1968.00

DATAVIDEO SE-800 ANALOG VIDEO MIXER/SWITCHER

A 4-input digital audio/video mixer with over 50 built-in digital effects. Full control is provided via the full-sized keypad and control panel. Other features include dual channel time base correction, position control with mosaic effects, and RS-232C remote control compatibility. In addition, the SE-800 features DV I/O and SDI outputs. Kit configuration models include the switcher plus a TLM-404 quad 4" TFT LCD monitor, one TLM-702 dual 7" TFT LCD monitor, an RKM-4N7 monitor bridge, and an RMC-140 tally box. I-Kits add an ITC-100 intercom with red/yellow LED tally lights. The HS-800 adds editing, monitoring, recording and communication capabilities to the SE-800 switcher to create a convenient mobile studio. Includes HDD recorder, intercom kit, quad-screen and dual-screen monitor units, audio monitor, tally lights and more into a sturdy aluminum case.



ITEM	DESCRIPTION	PRICE
SE-800DVDigital video mixer w/ DV I/O & SDI outputCALL
SE-800AVDigital video mixer w/S-video, composite out2496.00
SE-800DV-KITSE-800DV switcher with monitors, bridge, and tally unitCALL
SE-800DV-I-KITSE-800DV switcher with monitors, bridge, tally unit, and intercomCALL
SE-800AV-KITSE-800AV switcher with monitors, bridge, and tally unitCALL
SE-800AV-IKITSE-800AV switcher with monitors, bridge, tally unit, and intercomCALL
HS-800Mobile studio w/ SE-800 switcher, monitors, HDD recorder, intercom kitCALL

PLEASE ALWAYS CONSULT MANUFACTURER'S WEBSITE FOR MOST CURRENT SYSTEM REQUIREMENTS!



MORE INFO AT FULLCOMPASS.COM



APPLE



WINDOWS

FULL COMPASS HIGHLY RECOMMENDS CONSULTING WITH OUR INTEGRATION DEPARTMENT BEFORE PURCHASING VIDEO CAPTURE CARDS!

datavideo® makes live video easier for you.



Ask your friendly
Full Compass sales rep about
Datavideo solutions for:

- Switchers
- Mobile Studios
- Video Recorders
- Monitors
- A/V Converters
- Time Base Correctors
- Teleprompters
- Intercoms



**HS-2000
Mobile
Studio**
(page 294)
combines 1 or 2
DVI-D sources
and 3 or 4
HD-SDI sources

RMC-180 (page 324)
Pan, tilt, zoom camera controller

DN-60 (page 338)
DV/HDV Field Recorder

HDR-40 (page 338)
HD/SD-SDI Hard Drive Recorder



Call a Sales Pro Today! 800-356-5844
Or Visit FullCompass.com

datavideo®

DATAVIDEO HS-2000 MOBILE HD VIDEO PRODUCTION STUDIO/SWITCHER

This unit features a 17" LCD monitor to display multi-view outputs, 1 DVI-D input, 3 HD-SDI inputs and 1 selectable DVI-D/HD-SDI input, a built-in 4-channel audio mixer, a 5-channel wired intercom with belt packs for camera ops. Monitor shows review input, program output, and picture-in-picture preview. Program output allows connection to external digital video recorder, which can be viewed on the unit's screen. Also features lumakey, built-in TBC & frame synchronizers on all inputs, and HD resolutions up to 1920x1080i & 1280x720p. Comes in a protective aluminum case.



ITEM	DESCRIPTION	PRICE
HS-2000	Mobile HD-SDI/DVI video production studio/switcherCALL

DATAVIDEO SE-900 SD SWITCHER SYSTEM

This 8-input SD switcher has an expandable core feature set that includes chromakey cards and PIP. This 2-piece switcher (control panel and rack mounted processor) is ideal for SD venues. The switcher accepts a mix of 8 input cards for DV, SDI, DVI, YUV and composite. Outputs include DV, SDI, composite, component and S-video. Each input has a frame synchronizer and TBC. Preview functions include a YUV/composite multi-image output with "next source" and "next effect" so you can see how it looks before your audience does. The SE-900 caters to DV and SDI formats by including an audio delay for DV, and an optional audio embedder for the SDI stream. The SE-900 is sold as a standalone 2-piece switcher with monitors, monitor racks and cases, or prefigured with different inputs in several different kits (see below). Optional input and function cards are available – call for more details and pricing.



ITEM	DESCRIPTION	PRICE
SE-900	SD switcher system (2 pieces)CALL
SE-900DV-KIT	SE-900 with 1x SDI overlay card, 1x chromakey card, 6x DV input cards, 2x YUV, CV, S input cardCALL
SE-900STD-KIT	SE-900 with 1x SDI overlay card, 1x chromakey card, 4x DV input cards, 4x YUV, CV, S input cardCALL
SE-900SDI-KIT	SE-900 with 1x chromakey card, 6x SDI in card, 1x SDI out card, 1x external genlock cardCALL
MS-900	Configured and wired SE-900 mobile studio – includes SE-900 switcher, TLM-170M dual 7" LCD monitors, intercom set of base station, headsets, body packs and tally light package for eight users, PD-1 AC distribution, DN-300 recorder, RP-17 talkback breakout panel, RP-23 rack mount for DV Bank and DV Deck, Tray for SE-900, CCS-M1 12 RU table-top mobile case, assembled, wired and tested.CALL

Optional Cards:

900-SDI	SDI input card	445.00
900-DV25	DV input card	326.00
900-YUV	YUV, CV, S input card	288.00
900-DVI	DVI input card	384.00
900-SDI-O	SDI output card	307.00
900-DVK	Chromakey card	1920.00
CG100	CG software only – requires Decklink capture card. (Windows only)	979.00
VP445	HD/SD-SDI distribution amplifier, 1-in, 4-out	461.00
TLM170M	17" 16:9 HD-YUV monitor, rackmount	1728.00

DATAVIDEO SE-2000 HD-SDI VIDEO SWITCHER

This unit features 13 transitions with border, 5 individual speed keys (for instant selection with take effect), and the ability to insert up to 14 pre-stored logos. Includes 3 dedicated HD-SDI inputs, 1 DVI-D input and 1 switchable input, a tally output, a DVI-D preview output, and HD-SDI and HD-YUV program output formats. Also features luminance key, PIP, freeze image, memory enough for 5 user presets, RS232 control, and 4-input audio mixer with XLR connectors. 12V DC adapter is included.



ITEM	DESCRIPTION	PRICE
SE-2000	HD-SDI video switcherCALL

datavideo®

DATAVIDEO TBC-5000 TIME BASE CORRECTOR/MATRIX SWITCHER 4-input to 4-output genlock TBC that is matrix switcher controllable via RS232. It has 3 mode settings – 4-in/4-out, 4-in/2-out and 4-in/1-out. You can cascade two TBC-5000s for up to 8 ins/outs. Supports S-Video and composite, NTSC and PAL, is internal/external genlock selectable. 12V AC/DC adapter included and rackmount for up to 2 units.



ITEM	DESCRIPTION	PRICE
TBC-5000	Time base corrector/matrix switcher768.00

FOR.A®
INNOVATIONS IN VIDEO AND AUDIO TECHNOLOGY

FOR.A HVS-300 SERIES PORTABLE HD/SD VIDEO SWITCHER AND CONTROL PANEL

This IRU switcher can be operated via the front control panel, by mini panel or through software control. HD resolutions up to 1080/60i, 4:2:2 10bit processing, 4 HD/SD-SDI inputs and outputs each, (frame synchronizer, up-converter, re-size engine on each input). The HVS-300HS is expandable with I/O card options that include DVI-I, HD/SD analog component and analog composite inputs or outputs. The device's built-in 16-split multi-viewer supports 4-, 10- or 16-split view with tally and title display. Also features dual PIP function, an up-stream keyer and DSK (both with 2d DVE), advanced Chroma Key, a variety of 2D and 3D DVE transitions, 100+ wipe patterns and 2 channels of still stores.



ITEM	DESCRIPTION	PRICE
HVS-300HS-A	1RU HD/SD switcher - remote versionCALL
HVS-300HS-B	1RU HD/SD switcher - standard versionCALL
HVS-300R	Remote unit for HVS-300HS	2100.81
HVS-300U	Operation unit for HVS-300HSCALL
HVS-30GUI	PC Control software for HVS-300HS	962.87
HVS-30HSDI	HD/SD digital input card	2801.08
HVS-30HSDO	HD/SD digital output card	2407.74
HVS-30HSAI	HD/SD analog input card	2407.74
HVS-30HSAO	HD/SD analog output card	2407.74
HVS-30PCIN	PC input card	2407.74
HVS-30PCO	PC output card	2407.74
HVS-AUX8	8-button aux control box	2320.21
HVS-AUX16	16-button aux control box	2495.28

HORITA CHARACTER GENERATOR

A stand-alone video character generator with built-in text editor, that works with a standard PC keyboard (no PC required) to superimpose captions and titles of up to nine lines of 20 characters each, on analog composite video. The horizontal and vertical size and position, black/white, mask on/off, and contrast for the characters is user adjustable. Date and time information can also be automatically inserted in a variety of formats. Up to 25 KCT-50s can be connected and controlled from a single PC keyboard.



ITEM	DESCRIPTION	PRICE
KCT50	Character generator374.97


Gefen PRO MATRIX SERIES

The GefenPro 8x8 DVI Dual Link matrixes 8 DVI sources to any 8 dual link monitors, the GefenPro 8x8 DVI KVM Dual Link also includes USB and audio. The GefenPro 10x4 DVI DL matrixes 10 DVI sources to any 4 dual link monitors. The GefenPro 16x16 DVI routes 16 DVI sources with 16 monitors and comes in a push button control version. The GefenPro16x16 3GSDI routes 16 3G-SDI input sources to any 16 3G-SDI locations. All models feature advanced EDID management, a serial RS232 interface for remote control via computer, support DDWG standards for DVI and are rackmountable with included rack ears and include an IR remote control.



ITEM	DESCRIPTION	PRICE
GEF-DVI-848DL	8x8 DVI Dual Link Pro MatrixCALL
GEF-DVIVM-848DL	8x8 DVI KVM Dual Link Pro MatrixCALL
GEF-DVI-1044DL	10x4 DVI Dual Link Pro MatrixCALL
GEF-DVI-16416	16x16 DVI Pro MatrixCALL
GEF-DVI-16416-PB	16x16 DVI Pro Matrix w/push button controlCALL
GEF-3GSDI-16416	16x16 3GSDI Pro MatrixCALL

- AUDIO
- COMPUTER AV
- VIDEO
- LIGHTS
- MUSIC
- ACCESSORIES



GRASS VALLEY INDIGO SERIES AV MIXERS

The Indigo-SD model offers seamless live switching of standard-def video and audio, as well as computer sources. It also features pre-programmable video layouts with keyers for PIP and other effects, as well as digital effects with 2D & 3D transformations. The Indigo-HR model includes hi-def card (INDG01-HRES-UPG), allowing users to simulcast SD & HD output, as well as upconvert or downconvert multiple video channels into HD or SD video. The Indigo-HR-8 version increases the total number of HD inputs on the HD switcher to 8 HD/SDI inputs (21 total inputs in 2ME mode, 18 total in flat mode) thanks to the addition of the Acappella 8x4 router.



ITEM	DESCRIPTION	PRICE
INDG01-SD	AV mixer w/2D, 3D digital effects	CALL
INDG01-HR	HD AV mixer w/digital effects, SD/HD simulcast, up/down conversion	CALL
INDG01-HR-8	HD AV mixer w/8x4 router	CALL
INDG01-HRES-UPG	High-res upgrade card	CALL
INDG01-AUDIO-CABLE	3M AES/EBU digital audio adapter cable	191.74
INDG01-TALLY-ADAPT	Tally Breakout Adapter w/out cable	837.33
INDG01-TALLY-CABLE	Tally cable for breakout adapter	83.36
INDG01-HR-8-UPG	8x4 router upgrade for Indigo-HD	CALL
INDG01-SDHR-8-UPG	8x4 router upgrade for Indigo-SD	CALL



INTELIX DIGI-HDMI-8X8 HD TWISTED PAIR MATRIX

Combines a professional-grade HDMI matrix with Intelix's extenders. Each system provides 8 HDMI inputs, 8 HDMI outputs, and 8 twisted pair outputs. A built-in touchscreen delivers front panel source selection and matrix routing with ease. It also features 8 pass-through IR channels that distribute remote IR commands from in-room controllers and out of the matrix, allowing complete control of remote sources.



ITEM	DESCRIPTION	PRICE
DIGI-HDMI-8X8	HD twisted pair matrix	CALL

INTELIX HIGH-DEFINITION TWISTED PAIR VIDEO MATRIXES

Features 4 HDMI inputs, HDMI outputs and twisted pair extender outputs (2 each on the 4x2, four each on the 4x4). Both models support 1080i and 1080p video, are HDMI 1.3b and HDCP compliant, and distribute 4 IR signals from remote destinations to local sources. They are rackmountable, include wireless remote and are controllable by the front panel, Ethernet, IR or RS232. Features 4 pass-through IR channels for distributing remote IR commands from in-room controllers via twisted-pair extenders over a maximum of 150ft twisted pair cable



ITEM	DESCRIPTION	PRICE
DIGI-HD-4X2	4 HDMI in/2 HDMI, 2 twisted pair out hi-def matrix	859.96
DIGI-HD-4X4	4 HDMI in/4 HDMI, 4 twisted pair out hi-def matrix	1719.96



JVC KM-H SERIES MULTIFORMAT DIGITAL PRODUCTION SWITCHER

The KMH3000U switcher is compact and versatile for a variety of environments – broadcasting vans, small production studios, or on location. They handle both SD and HD video signals. The KMH3000U features 12 inputs and 3 keys. The switcher also includes high-quality chromakeying and dual-animation play-out capabilities, 4 up/down converters, 6 SD/HD-SDI outputs (2-program, preview, AUX 1, 2 & 3), 2 internal media store sources with animation support, and can be mounted.



ITEM	DESCRIPTION	PRICE
KMH3000U	2-input/3-key SD/HD-SDI multi-level effects switcher	CALL



KRAMER VP-411DS CG VIDEO/STEREO AUDIO STANDBY SWITCHER

This standby switcher will switch to a secondary input when the primary input's signal is lost. Offers computer graphics resolutions of VGA through UXGA and higher (thru 15-pin HD connectors) as well as unbalanced stereo audio signals (through 3.5mm mini-jacks). The VP-411DS features KR-ISP™ Advanced Sync Processing that ensures compatibility with a wide variety of computers by restoring the sync signal waveform. IR remote included. Controllable by RS-232, front panel (which features lockout capability) or contact closure.



ITEM	DESCRIPTION	PRICE
VP411DS	Audio/video standby switcher	556.00



KRAMER ELECTRONICS VP-747 DUAL SCALER & SEAMLESS SWITCHER

A true multi-standard video to graphics scaler and seamless video switcher with 8 universal inputs on 5 BNCs, each of which can accommodate a composite video, S-Video (YC), component video (RGB/YUV), RGBS, or RGBHV signal. Ideal for seamless switching of live productions with internal TBC, picture-in-picture, split-screen, up to 400% zoom, text overlay, cuts, fades and other transition effects. It has dual scalers, one for preview and the other for program output. Both outputs are simultaneously available as DVI-D signals on DVI-I connectors and as RGBHV/YUV signals on both a set of 5 BNC connectors and on HD-15F connectors. It features K-Storm™ Scaling Technology – Kramer's extremely high performance scaling technology for conversion to multiple computer graphics output resolutions, multi-standard SD and HD video, and choice of aspect ratios, including a user-defined output resolution with selectable refresh rates. Has two HDMI/DVI inputs. Flexible control options include front panel buttons, IR remote (with on-screen menus), Ethernet, RS232 & RS485. Includes a worldwide power supply with 100-240V AC.



ITEM	DESCRIPTION	PRICE
VP747	Dual scaler and seamless switcher	CALL
VP727T	Remote control console w/ T-bar, controls up to 4 VP-747s	1596.00
VP727A	8x2.3 companion stereo audio matrix switcher for VP747	1596.00



KRAMER PROSCALE™ VP437XL ANALOG & HDMI SCALER/SWITCHER

This 7-input scaler/switcher scales composite, component video, S-Video, computer graphics video or HDMI signals up/down to a selectable graphics output resolution. Unbalanced stereo audio input is converted to S/PDIF and analog stereo output and embedded in the HDMI out. Other features include 3:2/2:2 pulldown de-interlacing, up to 1080p HDTV output resolutions, audio follow video, and more. Rackmountable and ideal for projection systems, conference rooms and home theater set-ups.

ITEM	DESCRIPTION	PRICE
VP437XL	7-input analog/HDMI scaler/switcher, 1RU	1036.00

Panasonic

PANASONIC AWH550 MULTI-FORMAT LIVE HD/SD SWITCHER

This half-rack unit-wide, 4:2:2 HD/SD live switcher offers 10-bit processing, built-in MultiViewer (4, 9, or 10 images on a single display), chroma keyer, AUX bus with an IP link to Panasonic's AWRP50 remote camera controller, and 1080/29.94PsF support. Other features include picture in picture with dissolve transitions, color correction, linear and downstream keyers, switchable upconversion, auto or manual video transitions, frame memories, and wipe and PinP preset memories. Bears 4 HD-SD-SDI and 1 HD DVI-D inputs – each with 1-bit frame synchronizers, and 2 HD/SD-SDI and 1 scalable DVI-D outputs. The AWH550 also sports a GPI input, camera tally outputs, an Ethernet control interface, and a 4-pin XLR 12VDC input. Also supports 1080/59.94i, 1080/24PsF, and 720/59.94p.



ITEM	DESCRIPTION	PRICE
AWH550	Multi-format live HD/SD switcher	3360.00
AWRP50N	Remote camera controller	1936.00

PANASONIC AG-HMX100 DIGITAL AV MIXER

Integrating a HD/SD video switcher, frame synchronizer, audio mixer and control panel, this compact digital AV mixer offers high quality images via its 12-bit digital processing. Features include a 5.7" LCD screen that displays a 5-row matrix menu, rotary switches, an auto power off function, an AUX output terminal, a DVI-I input, 2 HDMI channels, and 4 SDI (HD/SD switchable) channels. Other features include multi-view function capabilities for single monitor systems, built-in 2D and digital effect functions, chroma and luminance keying, pattern preset, event memory, Panasonic projector control capabilities, and the ability to operate as a 3D video switcher.



ITEM	DESCRIPTION	PRICE
AGHMX100	Digital A/V mixer w/LCD screen	CALL

AUDIO



COMPUTER AV



VIDEO



LIGHTS



MUSIC



ACCESSORIES



- AUDIO
- VIDEO
- COMPUTER AV
- LIGHTS
- MUSIC
- ACCESSORIES

Panasonic

PANASONIC AV-HS300G COMPACT MULTI-FORMAT HD/SD SWITCHER

This compact, multi-format video switcher provides high definition or standard definition switching for live and to-be-recorded events. This high-performance unit features 6 inputs (5 HD/SD SDI and 1 DVI/RGB) and 3 HD/SD SDI outputs, RS422 control, Ethernet connectivity and a built-in, 10-bit, 6-channel frame synchronizer that adjusts automatically (also has external Gen Lock synchronization.) It's easy to operate and includes 9 wipe patterns and 3 directional wipes. A power supply is required for operation.

ITEM	DESCRIPTION	PRICE
AVHS300G	Video switcherCALL
AWPS510AN	Optional power supply627.00
AVHSB300G	HD analog component board (3BNC x 5)1787.40
IA200A-IDX	Optional 100W AC adapter power supply, has (2) 4-pin XLR outputs (by IDX)514.80



PANASONIC AV-HS400A COMPACT LIVE MULTI-FORMAT HD/SD SWITCHER

Multi-format live HD video switcher with standard multi-viewer/multi-image preview, chromakeyer, 3D digital effects, and optional up-conversion of standard definition signals to HD, making it possible to mix HD and SD video. The built-in MultiViewer can output 4, 6, or 10 images from different sources to a single high-resolution display. It comes standard with 4 HD/SD-SDI inputs & 4 HD/SDI outputs, and can be expanded to 8 inputs and outputs via optional boards. A 10-bit frame synchronizer is available on every input, for such sources as Blu-ray, remote feeds, or videotape.

ITEM	DESCRIPTION	PRICE
AVHS400A	HD/SD switcher with MultiViewerCALL
AVHS04M1	HD/SD-SDI input board1932.30
AVHS04M2	Analog component input board1664.40
AVHS04M3	DVI input board1784.10
AVHS04M4	HD analog component output board1031.70
AVHS04M5	DVI/component output board2030.40




Pioneer

PIONEER SVM-1000 PROFESSIONAL AUDIO/VIDEO MIXER

The SVM-1000 allows its user to mix audio and video with its incorporated 11-inch LCD touch panel. Hundreds of video effects, multi-channel video blending, and a still image sampler allow for a large variety of visual options to take place in synchronicity with the music. The audio mixing capabilities of the SVM-1000 are similar to those of Pioneer's DJM-1000 & 800 mixers. AV Beat Effect and Audio video effect functions further integrate the video and audio elements into the SVM-1000 console. Features 96kHz/24bit digital sampling, 32bit DSP, and 600mHz/32bit/4800MPS analog-to-digital converter.

ITEM	DESCRIPTION	PRICE
SVM1000	Audio & video mixing consoleCALL



REFLECMEDIA LITERING CHROMA KEY SYSTEM

The LiteRing features LEDs that are arranged in a circular casing and positioned in front of the camera lens. This provides all the light required to illuminate the Chromatte background for chroma key production. When directional light from the LiteRing hits the Chromatte™ fabric, it is returned on the same path back to the lens – and the camera sees the gray fabric as a perfectly even blue or green background, ideal for keying at any angle. The RM4221 controller allows adjustment of light output for optimum keying. Powered by camera battery or external RM5221 12V power supply. Available in green or blue and 3 sizes each with adapters to ensure compatibility with any lens.



ITEM	DESCRIPTION	PRICE
RM3221	Small blue LiteRing, fits up to 72mm internal filter900.00
RM3222	Small green LiteRing, fits up to 72mm internal filter900.00
RM3231	Medium blue LiteRing, fits 72mm to 105mm internal filter900.00
RM3232	Medium green LiteRing, fits 72mm to 105mm internal filter900.00
RM3241	Large blue LiteRing, Fits up to 147mm internal filter900.00
RM3242	Large green LiteRing, Fits up to 147mm internal filter900.00
RM4221	Intensity controller for LiteRing600.00
RM1125SB	8' x 8' Chromatte curtain, w/ small blue LiteRing kit1500.00
RM1125SG	8' x 8' Chromatte curtain, w/ small green LiteRing kit1500.00
RM1125MB	8' x 8' Chromatte curtain, w/ medium blue LiteRing kit1500.00
RM1125MG	8' x 8' Chromatte curtain, w/ medium green LiteRing kit1500.00

Chromatte Fabrics

RM1201W	12' x 7' Chromatte curtain and bag2200.00
RM1202W	13' x 9.8' Chromatte curtain and bag3200.00
RM1203W	16.4' x 13.1' Chromatte curtain and bagCALL
RM1204W	16.4' x 9.8' Chromatte curtain and bagCALL
RM2201	7' square collapsible screen1000.00

Roland

ROLAND LVS-400 VIDEO MIXER/SWITCHER

A simple, compact 4-channel video switcher for professional video transitions and effects. It offers both BNC & S-Video inputs & outputs, 17 back-lit buttons with time control for transitions, two effect control knobs, preview monitor output, and a T-bar for manual transitions.

ITEM	DESCRIPTION	PRICE
LVS400	Video mixer/switcherCALL



ROLAND V-4 FOUR-CHANNEL VIDEO MIXER

Compact video mixer ideal for portable or fixed installation use in nightclubs, theaters, performance venues, and places of worship. It offers V-LINK for real-time performance control over digital video. Trigger clips, effects, and transitions in real-time when connected to the DV-7PR. It also features MIDI support, TBC / frame synchronizer, digital effects, T-Bar fader, audio/video synchronization, and over 200 transition effects.

ITEM	DESCRIPTION	PRICE
V4	4-channel video mixerCALL



Roland®

ROLAND V-440 HD AND MULTI-FORMAT VIDEO MIXER/LIVE SWITCHER

Combine any 8 video sources (SD, HD even RGB computer signals up to SXGA) through 1 unit and output them at 720p, 1080i or selectable RGB. Featuring built-in, high-quality up-converter and scaler, an array of transitions, Picture-in-Picture, as well as 2 keyers (SD and HD). The units are even remote controllable via V-LINK from any Roland/Edirol musical instruments or use RS232C for computer control.



ITEM	DESCRIPTION	PRICE
V440HD	HD multi-format video switcher	CALL

ROLAND V-8 8-CHANNEL VIDEO MIXER WITH EFFECTS

The internal processing of the V-8 is 4:2:2 full-frame digital with more than 500 lines of video resolution. It has a built-in scan converter, providing direct input of RGB signals (VGA - UXGA) from 2 D-Sub terminals on the rear panel. Using the luminance key or chroma key, enables logos or text from your computer to be keyed over background video enabling the display of lyrics, bottom thirds, and announcements. It includes all your favorite effects like colorize and negative, feedback, afterimage, emboss, and Picture-in-Picture. Customize your transitions between the A and B bus with multiple flavors of simple mix, hard or soft wipes, stretch and slide transitions. It has independent faders on each bus as well as the master output for easy fades and video effects control. The V-8 can be remote controlled from the Roland PR series video presenters as well as the V-4 and can send remote control signals to the new generation of Roland's digital audio mixer, the RSS M-400 (V-Mixer). It includes multiple composite (BNC), S-video and RGB connectivity, plus MIDI in/out/thru for remote control interfaces.



ITEM	DESCRIPTION	PRICE
V8	8-channel video mixer with effects	CALL

ROLAND VR-5 AV MIXER & RECORDER NEW!

An all-in-one solution for live video production, recording and streaming. Use for video switching, audio mixing, video playback, recording, monitor preview or as output for web streaming and more. Features 5-channel video switcher (3 video sources, PC in, video playback), 2 mono and 5 stereo mixable audio channels, scan converter for PC in, dual LCD monitors with touch control, 3 video layers for 2 video sources plus downstream keyer, MPEG-4 player/recorder, USB video/audio class device for web streaming and more. Inputs include BNC x 3 composite in, S-Video x 3, PC-RGB D-Sub 15-pin. Outputs include BNC x 2 composite, S-video x 2, and preview out video BNC x 1 composite. Records to SD (1 to 2GB) and SDHC (max 32GB, class 4 or greater) memory cards. Supports PC-RGB video formats 640x480/120Hz, 800x600/120Hz, 832x624/75Hz, 1024x768/80Hz, 1152x864/80Hz, 1152x870/75Hz, 1280x1024/75Hz, and 1600x1200/60Hz.



ITEM	DESCRIPTION	PRICE
VR-5	AV Mixer & recorder for web streaming	CALL

Roland®

ROLAND V1600HD LIVE VIDEO MIXER

Ideal in live events or installations requiring a high channel count and the ability to accept a variety of video input formats out of the box. All-in-one 14 channel (16 input) seamless switcher/mixer. Connect HS/SD-SDI x8, DVI-D x2, RGB x2, component x2, S-Video, and composite inputs. Also input still from a USB thumb drive. Output options include HD/SD-SDI, DVI-D, RGB, component, S-Video and composite. Contains built-in high-res preview monitor, frame synchronizer and up/down scalars. Effects include a downstream keyer, composite keyer, picture-in-picture and 9 wipe patterns. Multi-screen output options including the ability to SPAN the mixer output to two projectors with the ability to edge-blend the center. Supports video resolutions from 480i/29.97 to 1080p/60, computer resolutions from 640x480 to 1920x1080.



ITEM	DESCRIPTION	PRICE
V-1600HD	16 input, 9 output, live video mixer	CALL

TVOne

TV ONE S2 SWITCHER/INPUT EXPANSION MODULES

Any of the S2 Series can be used as standalone video and audio switcher or as expansion module for the C2 Scaler/Switcher Series. Only one S2 unit can be attached to a C2 product, but several S2 units can be daisy chained to each other.



ITEM	DESCRIPTION	PRICE
S2-101AA	1x2 audio power amplifier	335.75
S2-105CV	5x2 composite video switcher	250.75
S2-105CVA	5x2 composite video/audio switcher	335.75
S2-105DVA	5x1 DVI-D and stereo audio switcher	845.75
S2-105PC	5x1 RGB/YpPr switcher	505.75
S2-105PCA	5x1 RGB/YpPr switcher and stereo audio switcher	675.75
S2-105YC	5x2 YC (S-Video) switcher	250.75
S2-105YCA	5x2 YC (S-Video) and stereo audio switcher	335.75
S2-106AD	6x2 stereo audio switcher with full processing	845.75
S2-108HD	8x2 HD/SD-SDI routing switcher	1440.75
S2-109PC	9x1 RGB/YpPr switcher	675.75
S2-110CV	10x2 composite video switcher	505.75
S2-110YC	10x2 YC (S-Video) switcher	420.75

VMC VMC DIGITAL SIGNAGE SYSTEM

Create, store, schedule and play up to 250 separate crawl or full-screen messages over any TV signal.



Text options include 5 fonts in 4 sizes with 8 colors and 8 shades of each color for maximum impact. Communicate with customers using text, digital images and video clips. Up to 32 VM-3s can be daisy chained together to display the same or a distinctive set of messages. Control the VM-3 remotely via a LAN or the internet using the IP/Serial Port Converter. The optional VMConsole software for Windows® PCs allows for the creation, storage and transmission of messages. The VM-3 is commercial quality and features metal construction, an internal power supply (110V & 220V), BNC connectors and a standard keyboard. The DV4-HD 1080p Media Player performs automatic playback of Hi-Res MPEG and JPEG images and video, with audio, in a rotational play list. It also features a crawl line that can be displayed with more than a dozen screen templates. Use as a stand-alone unit, or in conjunction with the VM-3, when character generation or scheduling is desired. Content and control are managed through VMC's Network Upload Service, simply add media, create a playlist and export to the DV4-HD. Supports MPEG-1, MPEG-2, MPEG-4, MPEG Still, MP3 audio, JPEG still images, and VGA (640x480).

ITEM	DESCRIPTION	PRICE
VM-3	Master unit (1 video source)	750.00
VM-3NET	Slave unit (additional video sources) network kit	730.00
VMCONSOLE	PC software	80.00
DV-4HD	HD DV media player for VM-3	1121.25
IP/SERIAL-PORT-LAN	IP/Serial port converter for LAN (requires VMConsole software)	240.00
IP/SERIAL-PORT-INT.	IP/Serial port converter for Internet (requires VMConsole software)	294.25
TRAINONE	One day of on-site training	350.00

AUDIO



COMPUTER AV



VIDEO



LIGHTS



MUSIC



ACCESSORIES

