













































GENTNER ASSISTIVE LISTENING SYSTEMS

Operating in the 72-76MHz FM band, Gentner Assistive Listening Systems tune to all 37 ALS channels and work indoors as well as outdoors with "no line-



of-sight" requirements. These systems connect easily to existing public address systems. The TX-37A can transmit over 300ft. Its universal input accepts mic level, line levels, and speaker level signals. Features include adjustable signal strength, built-in test tone for tuning, and remote mount antenna with 50' of cable. The Digital-1 is designed to be field-preset to a single ALS channel for very easy operation. The user just turns it on and adjusts the volume. Digital tuning eliminates any problems that can occur from frequency drift or changes in the environment. The Digital-6 Plus is a 6-preset version of the Digital-1, used primarily for multi-language or multi-room applications. The RX-1A is a low-cost ALS receiver that uses manual tuning. Gentner's FM design and high level of sensitivity allows flexibility not found in infrared (IR) systems. Accessories include a variety of headphones and earpieces, as well as battery chargers and more.

chargers and more.		
ITEM	DESCRIPTION	PRICE
Systems		
PACKAGE-DIGITAL-10	TX37A + (10) Digital-1 receivers, plaque, sticker,	
	rack kit, (5) packs of 4 Ni-Cad batteries	1762.35
PACKAGE-DIGITAL-10C.	TX37A + (10) Digital-1 receivers, BC10B charger, plag	ue,
	sticker, rack kit, (5) packs of 4 Ni-Cad batteries	2124.30
Components/Accesso	ries	
TX37Å	AC-powered transmitter only	564.95
RX1A	Economy single-channel receiver w/single earbud	67.95
910-402-003	Single-channel portable digital rcvr w/single earbud	112.95
DIGITAL-6-PLUS	6-channel portable digital receiver w/single earbud	135.95
BC10B	Optional battery charger for up to 10 rcvrs	361.95
910-200-016	4-pack of Eveready Ni-Cad AA cells	3.53
910-402-101	Single-earbud	4.95
910-402-102	Dual-earbud	8.95
910-402-102C	Replacement ear cushion	0.19
	Mono-headphone	



VENTURE-BASE



GENTNER VENTURE TOUR GUIDE/LANGUAGE INTERPRETATION SYSTEM

The Venture products are perfect for both tour group and language translation applications. The Venture-Base transmitter broadcasts on its own auditory assistance band, so it won't interfere with other FM devices. It features field-selectable channels (19 in the 216MHz frequency band) with digital selection, adjustable RF level to allow control of RF coverage and Aphex® processing for increased intelligibility. It transmits to an area of more than 700,000 square feet and multiple receivers can be used in one location. You can also connect any existing audio system via a tape or mixer auxiliary output. The universal input stage accepts audio from a mic, line, or speaker, producing exceptional audio quality at all levels. The Venture-Express is a portable transmitter version that is ideal for applications where one person needs to transmit audio to multiple participants. Both receiver options operate on two AA cells, and are digitally tuned to lock onto the desired frequency.

ITEM	DESCRIPTION	PRICE
VENTURE-BASE	FM transmitter w/flex antenna, remote-mount, RG174 cable	. 531.95
VENTURE-EXPRESS.	Portable FM transmitter w/lav microphone, uses AA cells	320.00
VENTURE-1	Digital receiver, single-channel, includes single earbud	107.95
VENTURE-6	Digital receiver, 6-channel, includes single earbud	129.95
930-TOU-RGU-R	Tour guide system: 1 Venture-Express, 10 Venture-1 receivers,	
	1 BC10B battery charger, & 5 packs of Ni-Cad batteries	1761.45
TRANSLATOR-SYS	Translator system: 2 Venture-Base, 10 Venture-1 receivers,	
	1 BC10B battery charger, & 5 packs of Ni-Cad batteries	2143.40

3010620. Assistive listening system, 72.1MHz... 3010640...... Receiver, 72.1MHz Transmitter, 72.1MHz.....

ings to mid-sized house-of-worship venues. The system consists of one wireless

transmitter, four pre-tuned portable wireless receivers, and four earbuds. Unlike

infrared systems, this system can be used outside or inside in bright light. System

packages consist of one transmitter, four receivers, and four standard ear buds. Any

ASSISTIVE LISTENING SYSTEM This RF system operates in the 72-76MHz band and is ideal for applications ranging from small meet-

number of additional receivers can be added.

DESCRIPTION

ITEM



LISTEN LISTENPOINT™ AUDIO SYSTEM An easy way to incorporate audio structure into a classroom, training facility, courtroom, meeting room, multi-purpose rooms and more. It can be used as a simple sound system or can be interfaced with a Listen FM or IR assistive listening system, telephone conferencing equipment, computer for VOIP/Skype™ conference calls, external paging, third party control, or a DVD player. The LPT-C2 Control Unit features 2 stereo inputs and RS232. The LPT-C6 control adds 2 more stereo inputs, stereo aux output, balanced audio I/O, and direct T-Con I/O. Both control units integrate with the room modules via Cat-5e cable. Room modules feature a paging input,

6-12VDC input, i	relay output, 2 remote sensor inputs, and speaker outp	uts.
ITEM	DESCRIPTION	PRICE
LPT-S1-01	Basic System (M1 mic kit, C2 control unit, R12 room module).	1031.00
LPT-S2-01		
	four 6" ceiling mounted speakers, and R12 room module)	1453.91
LPT-S3-01	Performance System (2 M1 mic kits, C6 control unit,	
	four 6" ceiling mounted speakers, and R14 room module)	1859.90
LPT-S5-01	Advanced System (M1 mic kits, C6 control unit,	
	four 6" ceiling mounted speakers, and R24 room module)	1329.95
LPT-M1	M1 microphone kit (microphone, Li-ion rechargeable battery,	
	charging station and clips)	299.00
LPT-C2-01	Control unit, standard	249.00
LPT-C6-01	Control unit, advanced	399.00
LPT-R2	Room module (2 mic max/no power amp), 1 speaker out	399.00
LPT-R4	Room module (4 mic max/no power amp), 1 speaker out	499.00
LPT-R12	Powered room module (2 mic max/60W), 4 speaker out	449.00
LPT-R14	Powered room module (4 mic max/60W), 4 speaker out	549.00
LPT-R22-01	High powered room module (2 mic max/120W), 4 speaker out .	549.00
LPT-R24-01	High powered room module (4 mic max/120W), 4 speaker out .	649.00
LPT-A104	6" ceiling speaker	49.99
LPT-A104-P	6" plenum-rated ceiling speaker	109.00
LPT-A105	8" ceiling speaker	69.99
LPT-A106	5" wallmount speaker	59.99

AUDIO















































LISTEN VALUE PACKAGE This package offers a low-priced 72MHz solution for your assisted listening needs. It includes (4) 3-channel wireless receivers, (4) earphones, a 3-channel wireless transmitter and assisted listening plaque. It's easy-to-use and ideal for houses of worship, classrooms, theatres, employee training applications, and business meetings. The LR-200-072 receivers offer 3 preset frequencies and can be used with any of Listen's current line of earphones.

ITEM		PRICE
VALUE-PACK	3-channel Value Package including (1) 72MHz transmitter,	
	(4) LR-200-072 receivers, (4) LA162 earbuds, ADA signage	
LR200-072	Standard 3-channel FM receiver only (72MHz)	76.00
LA162	Stereo earbuds	11.00
LA165	Stereo headphones	18.00
LA166	Neck loop	55.00
	Ear speaker	

LISTEN LSD-ADA-072 BASIC FM ASSISTIVE LISTENING SYSTEM

The LS-ADA-072 system meets the minimum requirements of the 2010 Americans with Disabilities Act standards for accessible design. In



addition to ensuring that public facilities are compliant, the system helps solve frustrating but common sound problems caused by distance, background noise, or poor room acoustics. This installed sound system includes a LT-803 stationary transmitter, (2) LR-200 receivers with LA-161 single-piece earphone, LA-123 90° helical antenna, (2) LA-166 neckloops, alkaline batteries and ADA signage kit. Available only on the 72MHz frequency band, and can be customized if you need additional components.

ITEM	DESCRIPTION	PRICE
LS-ADA-072-01	ADA basic FM assistive listening system	798.96



LISTEN LS-17-072 ADA VALUE STATIONARY FM ASSISITIVE LISTENING

SYSTEM An affordable solution to meet the 2010 Americans with Disabilities Act standards for accessible design. In addition to ensuring that public facilities are compliant, the system helps solve frustrating but common sound problems caused by distance, background noise, or poor room acoustics. This installed system includes a Stationary Transmitter, rackmount kit, a kit to front-mount the helical antenna, (4) LR-200 receivers with ear speakers, (2) neck loops, alkaline batteries, and ADA signage kit. Available only on 72 MHz frequency band, and can be customized if you need additional components.

ITEM	DESCRIPTION	PRICE
LS17-072	Value assistive listening system	. 1078.96



LISTEN LS-86 ADA STANDARD STATIONARY IR SYSTEM This IR system is designed for applications that are looking for an IR solution to meet the needs of the new 2012 Americans with Disabilities Act (ADA) regulations. Ideal for applications where security or the number of transmissions are a priority. It can accommodate up to 4 listeners and has an impressive range of 10,000 sq ft per radiator. This system includes 2 stethoscope receivers, 2 lanyard receivers, 2 stationary IR radiators, 2 neckloops, 2 earphones, 1 transmitter, 1 rackmount kit and 1 ADA signage kit. The system can be customized if necessary. The system contains everything you need to fully integrate with your existing sound system.

	-		-			
ITEM		DESCRIPTION				PRICE
LS-86-01	-WH	ADA standard	stationary	IR s	ystem	 3243.96



LISTEN LS-16 ADA STANDARD STATIONARY FM SYSTEM The LS-16 is specifically designed to meet the 2010 Americans with Disabilities Act (ADA) standards for accessible design. In addition to ensuring that public facilities are compliant; the system helps solve frustrating but common sound problems caused by distance, background noise, or poor room acoustics. The system includes a Stationary FM Transmitter and Universal Antenna Kit, rackmount kit, (4) LR-400 Receivers with ear speakers, (2) neck loops, alkaline batteries and ADA signage kit. The system is available on either the 72 or 216 MHz frequency band, and can be customized if you need additional components.

ITEM	DESCRIPTION	PRICE
LS16-072	ADA Standard stationary FM system	1658.96



LISTEN FM SERIES Use these wireless audio solutions for assistive listening, tour groups, language interpretation, soundfield, and audio distribution. Has 57 channels and is compatible with other manufacturers. Installed systems reach 3,000' and portable systems reach 150'. Choice of earphone and microphone styles. Ready-to-use systems feature 80dB S/N ratio. Custom systems and 30-day risk-free demos available. Call for other systems & accessories.

ITEM FM Systems	DESCRIPTION	PRICE
	Try Listen system (72MHz) w/transmitter, antenna,	
	3 portable digital receivers, 3 single ear buds	1034.97
LS02-072	Basic system (72MHz) w/transmitter, antenna,	100
	4 portable digital receivers, 4 ear buds	1138.96
LS03-216	Performance system (216MHz) w/transmitter, antenna &	
	rackmount kits, 4 portable display receivers, 4 ear speakers,	
	4 batteries. System also available in 72MHz	1548.96
LS04-216	Advanced installed system (216MHz) w/transmitter,	
	antenna & rackmount kits, 4 portable programmable receivers,	
	4 ear speakers, charging/carrying case, rechargeable batteries.	
	Also available in 72MHz	2017.96
LS05-216	Personal portable system (216MHz) w/portable transmitter,	
	lavalier mic, portable display receiver, soft case, batteries.	
	System also available in 72MHz	705.98
LS06-216	7-person portable system (216MHz) w/transmitter, behind	
	the head mic, 7 portable display receivers, 7 ear speakers,	
	carrying case, 8 batteries. System also available in 72MHz	1905.92
LS07-216	15-person portable system (216MHz) w/transmitter, behind	
	the head mic, 15 portable display receivers, 15 ear speakers,	
	carrying case, 15 batteries. System also available in 72MHz	. 3328.84
LS08-216	15-person advanced system (216MHz) w/transmitter, behind	
	the head mic, 15 programmable display receivers,	
	15 ear speakers, charging/carrying case, 16 rechargeable	
	batteries. Also available in 72MHz	4639.84
LS13-216	30-person tour group system (216MHz) w/transmitter,	
	behind the head mic, 30 display receivers, 30 ear speakers,	
	charging/carrying cases, 31 rechargeable batteries.	0411
	System also available in 72MHz.	CALL





Connecting People to Positive Experiences





· Proven, versatile, and ADA-compliant assistive listening solutions bring enhanced, high-quality audio experiences to people in churches, theaters, concert halls, and other gathering places.

 Convenient, easy-to-use wireless tour group and language interpretation solutions make it easy for a speaker, guide or language interpreter to be heard clearly and precisely by any size group - even in the noisiest and most chaotic indoor and outdoor settings.

 Friendly, affordable ListenPoint audio integration and amplification solutions for classrooms, training rooms, and meeting rooms will boost retention and make it easy to integrate sounds from many different sources into one clear, consistent audio experience.

30 day no obligation demonstrations available







































ACCESSORIES













TELEX SOUNDMATE™ SM2 SYSTEM This Soundmate personal listening system helps overcome background noise and poor acoustics that hamper listening for the hearing impaired. This system consists of (1) ST300 transmitter, (4) SR50 singlechannel receivers, and (4) SEB1 single earbuds. The ST300 transmitter features 17-user selectable frequencies (72.1-76MHz)



controlled by front-mounted buttons, headphone jack, and level control. On the back of the unit is balanced XLR-F jack with selectable mic/line, and 70V input options as well as an unbalanced 1/4" input. Other optional receivers exist as well. The SR400 is a digital 17-channel portable receiver that features an enhanced dynamics range (EDR) that provides clearer, more dynamic audio. Carrying case for system is optional.

ITEM	DESCRIPTION	PRICE
SM2-71917	. Hearing assistance system with (1) ST300, (4) SR50s, (4) SEB1s .	. 1029.00
SR50	. Single-channel receiver (included in SM2)	100.00
ST300	. 17-channel base transmitter (included in SM2)	709.00
SR400-71913-000	. Optional 17-channel receiver	311.00
SM-C-71077001	. Optional carry case for SM2	101.00





WILLIAMS SOUND PLA-215 ROOM LOOP AMPLIFIER Ideal for use at home or

in small conference rooms up to 540 square ft. System includes 120ft. of induction loop wire - simply fed from the amplifier and back to it again, forming a loop. In addition to settings for basic volume and tone, the digitally controlled induction loop amplifier uses automatic gain control to stabilize the volume for fluctuating input levels. The device can accommodate the connection of two audio sources; choose your source with the quick touch of a button (mic or line in). I/O consists of (2) 1/8" mic inputs, 2 RCA left/right line inputs, push grip connectors for loop cable/pad out and an 1/8" headphone out. Includes PLA-215 with power cord, 1 mic with 14 ft. (4 m) of cable, 122 ft. (37 m) of 18ga standard wire (0.75 mm²) and cable clips, and audio input cables.



VERTICAL

ITEM	DESCRIPTION	PRICE
PLA-215	. Room loop amplifier	. 199.00

WILLIAMS SOUND PI A-90 PORTABLE INDUCTION LOOP

SYSTEM Compact and easy to install, this portable induction loop system readily accommodates individuals with hearing difficulties at a bank teller window, information desk, store counter or anywhere customers/visitors need to hear what is being said. Hearing



HotSpot picks up external voices with an integrated mic or with an optional external mic. The system transmits spoken word clearly and directly to a listener's hearing aid equipped with a T-coil. Designed to meet ADA accessibility requirements. Operation range is approx. 3-4ft. I/O consists of 1/8" mono jack in for external mic and 1/8" stereo headphone out. Built in 12VDC rechargeable battery will last approx. 6 hours. Includes (1) Hearing HotSpot™ counter loop, (1) rechargeable 10x AA NiMH battery pack, and (1) TFP 046 International Power Supply.

ITEM	DESCRIPTION	PRICE
PLA-90	. Portable induction loop system	249.00



SOUND **PORTABLE** INFRARED ADA KIT "All-in-one" ADA compliance kit for hearing accessibility and/or language interpretation in a smallgroup setting. Ideal for secure applications such as parent/teacher conferences or small meeting rooms, it operates at 2.3MHz/2.8MHz, at a range of up to 30ft. The kit includes WIR 250 small area IR system,



BAT KT6 AA rechargeable battery system, (2) WIR RX22-4 infrared receivers, (2) HED 026 headphones, NKL 001 neckloop, MIC 049 omnidirectional conference mic, WCA 007 WC mic extension cable, CCS 030 carry case, & IDP 008 ADA wall plaque.

ITEM	DESCRIPTION	PRICE
IR-ADA-KIT	. Portable, infrared, all-in-one kit, up to 30ft	884.00

WILLIAMS SOUND PERSONAL PA® 377 FM LISTENING

SYSTEMS The Personal PA® 377 large-area listening system broadcasts voice or audio wirelessly at a range of up to 1000 feet. System includes 1 PPA-T35 transmitter and 4 PPA SELECTTM R37 receivers. T35 transmitter features a sleek digital display, powerful microprocessor, easy-to-use push button controls, and



auto configuration for easy set-up. System is completely field-tunable and features 17 wide-band and 77 narrow-band channels in the 72-76MHz range. R37 receivers feature seek-button channel selection and boast 50 hours of operating time on 2 AA alkaline batteries (included). These systems are ideal for use in churches, universities, classrooms, auditoriums, theaters and conferences, and they carry a 5-year warranty on parts/labor and a 90-day warranty on accessories.

warranty on parts/labor and a 50-day warranty on accessories.			
ITEM	DESCRIPTION	PRICE	
PPA-377	Wide-band system with (1) PPA-T35, (4) PPA-R37s,		
	(4) EAR-013 earphones, (1) IDP-008 ADA wall plate,		
	(1) WCA013 audio cable, (1) ANT-025 whip antenna,		
	(1) TFP016 power supply	1030.00	
PPA-377-00	Same as PPA-377 but without EARO13 earphones	935.00	
PPA-377-PRO	Wide-band system with (1) PPA-T35, (4) PPA-R37s,		
	(4) EAR-013 earphones, (1) IDP-008 ADA wall plate,		
	(1) WCA013 audio cable, (1) ANT-005 coaxial antenna,		
	(1) TFP016 power supply, (1) RPK-005 rack panel kit	1164.00	
PPA-R37	Single-channel receiver w/belt clip, batteries & EAR-013 earphone	103.00	
CHG3512-PRO	12-unit charger for PPA-R37 receivers	522.23	

WILLIAMS SOUND DIGI-WAVE DSS WIRELESS LISTENING SYSTEM

A 2-way digital listening system in the 2.4GHz band. With the push of a button, users can access 2-way communication for easy audience/group member participation. Capable of transmitting and receiving up to 100' outdoors and up to 200' indoors. Operating on the 2.4GHz band with patented frequency-hopping software, it has a high resistance to RF interference. Operates on 4 channels simultaneously in 2-way mode and up to 15 channels simultaneously in 1-way mode. All controls are located on the



front panel. The DLR-50 receiver display shows channel of operation, volume setting, and low battery status. The DLT-100 transceiver display shows current set-up, battery life, time, and RF strength. It also features a built-in microphone and speaker, and includes a charger with 14 hours of use per charge.

ITEM	DESCRIPTION	PRICE
DLR-50	Wireless digital receiver	178.00
	Wireless digital transceiver	
CCS-044	Silicone skin/wrist strap for the DLT-100	11.56
RCS-008	Wrist strap for the DLR-50	3.75
	2-bay charger (for DLT-100)	







SHOW

TELL

INTERACT

GMFR

IMPRESS

DIGI: WAVE

2-WAY

REAL-TIME COMMUNICATION

- BECAUSE YOUR STORY IS IMPORTANT

W/ WILLIAMS SOUND®

WIRELESS TOUR GILIDE SYSTEMS

FULL COMPASS
PRO AUDIO I VIDEO I AV I LIGHTING
MUSICAL INSTRUMENTS
800-356-5844
FULLCOMPASS.COM