ii ii ii ii

COMPUTER AV

ACCESSORIES









### LINE 6 STAGESOURCE SERIES LOUDSPEAKER SYSTEM

These 3-way, tri-amped loudspeaker systems are optimized for a variety of performance scenarios. A combination of on-board accelerometers and pole-mount sensors automatically detect speaker orientation and set the DSP-based Smart Speaker modes accordingly. Other features include integrated 12-band feedback suppression, multifunction design, and (4) M10 fly points. L6 LINK™ digital networking support allows for automatic self-configuration, Smart Speaker mode adjustment, and system-wide optimization. For use as a stand-alone PA, L3t adds an integrated 2ch mixer with EO, effects, and acoustic guitar modeling. The L3M/L3T models each have (1) XLR-1/4" balanced line in, (1) stereo RCA in and (1) L6 LINK<sup>TM</sup> XLR. The L3S sub has (1) XLR-1/4" balanced line in and the L6 LINK<sup>TM</sup> XLR.

ITEM	DESCRIPTION	PRICE
STAGESOURCE-L3M	Dual 10", 3-way, 1400W, active speaker	899.99
STAGESOURCE-L3T	As above, with DSP and 2-channel mixer	999.99
STAGESOURCE-L3S	Dual 12", 2-way, 1200W, active subwoofer	1199.99



**SEE PAGE 206** 

JOLLY5BA

JOLLY12BA

## GAMADDIO

### GALAXY AUDIO HOTSPOT MINI SPEAKERS The

PA6S is a compact PA 2-way system featuring a 6.5" LF neodymium woofer and a 1.5" HF neodymium tweeter. It has a built-in compressor/limiter and an XLR pass thru on channels 1 and 2. The HOT-SPOT-VC-7 (HS7) is engineered for near-field vocal monitoring and has two Neolite 5" drivers and an 18dB stepped attenuator volume control. Both models include an integrated handle and mounting point for a mic boor



nanuic and mo	inting point for a fine boom.		.07
ITEM	DESCRIPTION	F	PRICE
PA6S	2-way powered PA, 170	)W @ 4Ω, 80Hz-18kHz2	99.99
HOT-SPOT-VC-7	Vocal monitor, passive	. 200W. 150Hz-18kHz 1	39.99

### GALAXY AUDIO NANO SPOT POWERED MONITOR

The NSPA has a 3" driver, 25W amplifier, 2-band EQ, built-in compressor and can provide 24V phantom power. Inputs consist of (1) XLR, (1) 1/4" TRS and (1) 1/8" TRS jack. It is stand/bracket-mountable and ships with a bracket. Power supply is included.








## **FBT JOLLY SERIES COMPACT**

SPEAKERS These are lightweight and compact 2-way speakers in black polypropylene enclosures and come in passive and active models, some of which are biamped. They feature 5"-15" woofers and dome tweeters. Models listed with Neutrik Combi (XLR and 1/4") input jacks also have

mic/line inputs. The Red Series offers slightly less powerful, less



JOLLY5RA. .5" active speaker, 60W, Neutrik combi-jack input.......229.00 JOLLY8RA .8" active biamped speaker, 80/20W, Neutrik combi-jack input 70V/100V Model...


JBL CONTROL®1 PRO/CONTROL® 5 **SPEAKERS** Combining high performance, compact design and rugged construction, the Control Series offers unprecedented versatility. The Control® 1 Pro

has a 5.25" woofer and a 0.75" polycarbonate dome tweeter. An updated crossover network design provides steeper crossover slopes for improved sonic performance and consistency throughout the listening area. A wall-mount bracket is included. The Control® 5

features a 6 1/2" woofer and 1" titanium tweeter. Both models feature magnetically shielded transducers, making them well-suited for use near video monitors. Inputs on each model are spring-loaded terminals. Mounting brackets are included with both models. Priced as each, but sold in pairs.

ITEM	DESCRIPTION	PRICE
CONTROL-1-PRO	5.25" 2-way speaker, 80Hz-20kHz, 150W, 4Ω	82.00
CONTROL-1-PRO-WH.	. As above, in white	82.00
CONTROL-5	6.5" monitor loudspeaker, 75Hz-20kHz, 175W, $4\Omega$ , black	169.00
CONTROL-5-WHITE	. As above, in white	169.00
5-0100	Ultra-duty mount bracket for Control-1-Pro	64.00

JBL CONTROL 29AV-1 An upgraded version of the Control 29AV loudspeaker, featuring re-voicing advancements in the crossover network. Developed in conjunction with Walt Disney Imagineering, the re-voicing provides a flatter frequency response with more natural midrange sound character, while



C29AV-1 ...8" 2-way speaker, 300W program. JBL CONTROL 30 A 10" 3-way speaker featuring

The state of the s
a 5-1/4" mid-range and compression driver HF
and 120x110 deg coverage. Has an integral 70V
transformer, a weather-resistant finish, and Sonic
Guard overpower protection.

		-
ITEM	DESCRIPTION	PRICE
CONTROL-30	.10" 3-way speaker, black	681.00
CONTROL-30-WHITE	.10" 3-way speaker, white	681.00





















































JBL PRX400 SERIES PASSIVE PORTABLE SPEAKERS Provides sensitivity, frequency response, and power handling of well-designed speakers, tailored for demanding audio environments. All models feature tough DuraFlex<sup>TM</sup> surfaces, 16ga. screen-backed steel grille, suspension points, and professional connectors. All except PRX418S use a 90° x 50° nominal coverage pattern.

ITEM	DESCRIPTION	PRICE
PRX412M	. 12" 2-way, 300W, 65Hz-16kHz, 8Ω,	
	stage monitor and loudspeaker	499.00
PRX415M	. 15" 2-way, 300W, 75Hz-16kHz, 8Ω,	
	stage monitor and loudspeaker	
PRX425	. 15" dual 2-way, 600W, 75Hz-16kHz, 4Ω, loudspeaker	749.00
PRX418S	. 18" 2-way, 800W, 52Hz-120Hz, $8\Omega$ , subwoofer	749.00



JBL PRX600 SERIES ACTIVE PORTABLE SPEAKERS This series employs technology that allows you to create versatile and portable systems. Each model is designed for specific applications but integrate seamlessly with one another to offer many choices when building a system. Features Neodymium compression drivers, strong, lightweight poplar plywood and are protected by JBL's DuraFlex™ finish. The amplifier input panel of all models has XLR or 1/4" mic/instrument inputs with XLR loop through.

ITEM	DESCRIPTION PRICE	CE
PRX612M	.12" 2-way active speaker, 1000W (2 x 500), Crown Class 'D' amp.	
	50Hz-19.5kHz, 90° x 50° nominal coverage, pole mount socket 799.0	00
PRX615M	.15" 2-way active speaker, 1000W (2 x 500), Crown Class 'D' amp,	
	45Hz-19kHz, 90° x 50° nominal coverage, (8) M10 suspension	
	and (1) pullback point	)0
PRX625	.15" dual 2-way active speaker, 1500W (3 x 500),	
	Crown Class 'D' amp, 40Hz-19.5kHz, 90° x 50° nominal coverage,	
	(8) M10 suspension and (1) pullback point	00
PRX635	.15" 3-way active speaker, 1500W (3 x 500), Crown Class 'D' amp,	
	41Hz-19kHz, 90° x 50° nominal coverage, suspension points	
	and pole mount socket	00
PRX618S	.18" active subwoofer, 600W, Class 'D', 41Hz-130Hz,	
	top pole mount	00
PRX618S-XLF	.18" active subwoofer, 1000W (2 x 500), Class 'D', 30Hz-105Hz,	
	top pole mount	00
GPA-712SM	Rolling speaker bag for PRX12M	
	- 0	

JBL JRX SERIES Delivers the performance and prestige JBL is known for at an affordable price point. Features include 900x400 Progressive Transition Waveguide for best horn performance, beefy all steel handles and 18 gauge steel grill, SonicGuard protection, 3/4" MDF wood construction and dual-angle pole socket for better coverage. Connections are both Neutrik Speakon and 1/4" phone sockets. Install versions have no handles, feet or pole sockets but have M10 eyebolts.

Follow us!



ITEM	DESCRIPTION	PRICE
JRX112M	. 12" 2-way floor monitor 60Hz-16kHz : Q 250/1000W 43 lbs	. 289.00
JRX112MI	. Install version	. 379.00
JRX115	. 15" 2-way, 38Hz-16kHz 8Ω 250/1000W 60.5 lbs	. 299.00
JRX115I	. Install version	. 399.00
JRX118S	. 18" subwoofer, 38Hz-300Hz 4Ω, 350/1400W 71 lbs	. 499.00
JRX118SP	. 18" powered subwoofer, 300/500W amplifier,	
	stereo crossover, XLR inputs	. 899.00
JRX125	. Dual 15" 2-way, 35Hz-16kHz 4Ω 500/2000W 94 lbs	. 449.00



### JBL VP7212/95DP POWERED SPEAKER

A biamplified 12" 2-way integrated loudspeaker system with 1100W of power and JBL DrivePack® technology. It has a12" Differential Drive® low-frequency driver and a 4" titanium-damped diaphragm high-frequency driver. The enclosure is 5/8" multi-ply exterior grade Baltic birch with internal bracing and black DuraFlex® finish. Other features include a 90°x 50° rotatable waveguide, RJ45 network connector, XLR input and loop through connectors, Neutrik Powercon connectors, M10 & flytrack suspension points and a powder-coated perforated steel grille.

ITEM	DESCRIPTION	PRICE
VP7212/95DP	12" 2-way powered speaker, 63Hz-18kHz	CALL

### **JBL EON 300 & 500 SERIES**

POWERED SPEAKERS The EON-305 is a 15" 2-way passive loudspeaker that features 2 parallel-linked Speakon/1/4" combo jacks. The EON-315's input is a balanced XLR/1/4" combo that is mic-line switchable and features one XLR output for signal loop-through. The EON 500 Series features one XLR out (selectable), one XLR/1/4" input, additional 1/4" ins, and Differential Drive® woofers. The EON-510 has a 10" woofer, the EON-515XT has a 15" woofer and the EON- 518S has an 18" woofer. The EON-515XT also features Crown® Class 'D' technology. The EON-518S features level control, dual inputs, a stereo crossover network, a pole-mount cup for sub/satellite applications, a



polarity reverse switch, peak limiter and a speaker level input.	
ITEM DESCRIPTION	PRICE
EON-30515" 2-way, passive, 250W, 100°x60°, 50Hz-18kHz, 33 lbs	379.00
EON-31515" 2-way, active, 220W/LF, 60W/HF, 100°x60°, 50Hz-18kHz, 35 lbs	399.00
EON-51010" 2-way, active, 220W/LF, 60W/HF, 100°x60°, 70Hz-17kHz, 17 lbs	399.00
EON-515XT15" 2-way, active, 525W/LF, 100W/HF, 100°x60°, 42Hz-18kHz, 32.5 lbs.	699.00
<b>EON-518S</b> 18" subwoofer, active, 500W, 42Hz-100Hz, 65 lbs	699.00
GPA-712LGRolling speaker bag for EON 515XT	139.99



JBL STX800 SERIES These speakers offer high performance in a portable, truckfriendly package. Full-range boxes in this series feature JBL's PTTM Waveguide that create a smoother frequency response and eliminate harmonic distortion. The LF drivers all have Vented Gap Cooling<sup>TM</sup> which helps reduce heat and provides the full output capacity of the speaker even after long hours of use. Series subwoofers have even more significant reductions in heat and compressions thanks to Super Vented Gap<sup>™</sup> technology. All STX800 speakers are covered in rugged Duraflex<sup>™</sup> and have 14-guage steel grills. Connections are all NLA.

ITEM	DESCRIPTION	PRICE
STX812M	12" 2-way, 800W, 8Ω, 50Hz-20kHz	1199.00
STX815M	15" 2-way, 800W, 8Ω, 41Hz-20kHz	1499.00
STX825	Dual-15" 2-way, 1600W, 8Ω, 34Hz-20kHz	1999.00
STX835	Dual-15" 3-way, 1600W, 8Ω, 32Hz-20kHz	2599.00
STX818S	18" subwoofer, 1000W, 8Ω, 35Hz-25kHz	1199.00
STX828S	Dual-18" subwoofer, 2000W, 8Ω, 32Hz-25kHz	1999.00





# PRX600

# PERFORMANCE YOU CAN TRUST



Picturer

PR X615M MAX SPL: 135 dB 43.5 lbs.

# FULL COMPASS

PRO AUDIO | VIDEO | AV | LIGHTING MUSICAL INSTRUMENTS

800-356-5844

FULLCOMPASS.COM

Your audience deserves to hear every note, every word, and every beat, PRX600 Series speakers were designed from the ground up to perform in the real world where difficult acoustical environments, high ambient noise levels or loud volumes are the norm. With four new full-range models and two new subwoofers you can tailor a system to fit your unique needs. And our 60 years of building speakers is engineered into every PRX600. Knowing that you can rely on your system to deliver gives you the freedom to deliver your very best.

That's performance you can trust.





Hear the truth.

















































# MACKIE.



#### **MACKIE DLM SERIES POWERED SPEAKERS**

Ridiculously lightweight and loud, these ultra-compact powered loudspeakers meld efficient Class 'D' power amps with proprietary TruSource® DSP to deliver 2000W of clear, full fidelity audio in a system that fits inside nearly any car. The DLM8 and DLM12 feature the integrated DL2 digital mixer — a powerful one-touch mixer offering 2 versatile channels with discrete EQ/FX controls, 16 channel FX, XLR/TRS combo and RCA dual connectors. They also offer an integrated kickstand (for use as a personal monitor), multi-band feedback destroyer, 6 speaker voicing modes, and can be pole mounted on a tripod or atop a DLM12S using the SPM300 speaker pole, flown via standard M10 rigging hardware, or wallmounted via the SWM300 articulated arm. All models offer alignment delay up to 300ms, 3 memory locations for instant recall, rugged metal grille and Smart Protect DSP amp/driver protection. The DLM12S is a 12" powered subwoofer featuring DLP digital processing, a digital crossover with presets for use with DLM and SRM series speakers, and 6 XLR connections to meet all your I/O needs (2 line level, 2 full-range, 2 hi-pass).

ITEM Speakers	DESCRIPTION	PRICE
	Active, 8" woofer, 1-3/4" tweeter	699.99
DLM12	Active, 12" woofer, 1-3/4" tweeter	849.99
DLM12S	Active 12" subwoofer	999.99
Speaker Cover	rs	
DLM8-BAG	Bag for DLM8	64.99
DLM12-BAG	Bag for DLM12	79.99
DLM12S-COVER. Accessories	Cover for DLM12S	79.99
SPM300	Pole mount for DLM8 and DLM12	44.99
SWM300	Wall mount for DLM8 and DLM12	99.99



MACKIE S500 SERIES PASSIVE LOUDSPEAKERS These wood-cabinet speakers offer extended low frequencies without rattles or vibrations. Full-range boxes have a 1" HF driver with a wide-dispersion 90°x50° horn. The cabinets are covered in a PVC vinyl to protect against dings and moisture. They have built-in HF circuit protection, NL4 and 1/4" inputs, and thru connections for connecting multiple units to one amplifier. The S518S subwoofer has a built-in lo-pass filter allowing it to focus only on the low frequencies without the use of an external crossover.

ITEM	DESCRIPTION	PRICE
S512	12" 2-way, 500W, 8Ω, 49Hz-18kHz	289.99
S515		299.99
	Dual-15" 2-way, 1200W, 8Ω, 51Hz-18kHz	
\$518\$	18" subwoofer 900W 8Q 37Hz-220Hz	199 99

# MACKIE THUMP SERIES POWERED LOUDSPEAKERS

These lightweight & portable speakers feature Class 'D' Fast Recovery<sup>TM</sup> amplification, integrated precision crossovers, and transducer time alignment.



The TH-12A and TH-15Ā have a 12" and a 15" woofer respectively, 1" compression drivers, mic/line inputs, and 3-band EQ with a sweepable mid. Each works well as a monitor wedge, in addition to its normal pole-mounted orientation. The SRM1801 has an 18" woofer with 125Hz precision crossover, dual XLR inputs, stereo hi-pass and full-range outputs.

ITEM	DESCRIPTION	PRICE
TH-12A	12" powered pole-mountable loudspeaker, 400W, 25.5 lbs	299.99
TH-15A	15" powered pole-mountable loudspeaker, 400W, 36 lbs	349.99
SRM1801	18" powered subwoofer, 1000W, 73 lbs	699.99
GPA-715	Rolling speaker bag for 15" speakers	139.99
GPA-712SM	Rolling speaker hag for 12" speakers	119 99

### MACKIE SRM SERIES SPEAKERS

Both models feature XLR mic/line input, 24dB/ octave Linkwitz-Riley electronic crossover, electronic time correction, phase alignment and EQ for studio-quality sound. They are flyable, pole-mountable and also work as a floor wedge. The SRM450v2 additionally features a unique 3-piece wide-dispersion horn. The C200 and C300Z are passive versions of these mod-



els. The SRM1801 has an 18" woofer with 125Hz precision crossover, dual XLR inputs, stereo hi-pass and full-range outputs.

ITEM DESCRIPTION

DESCRIPTION

ITEM	DESCRIPTION	PRICE
SRM350-V2	. 2-way 10" biamped, 165W LF/30W HF, 26 lbs	499.99
C200	. As above, passive version	199.99
SRM450-V2-BLACK .	. 2-way 12" biamped, 300W LF/100W HF, 40 lbs	599.99
C300Z	. As above, passive version	349.99
SRM1801	. 18" powered subwoofer, 1000W, 73 lbs	699.99
SPM200	. Locking speaker pole	39.99
GPA-712LG	. Rolling speaker bag for SRM450	139.99



# MACKIE HD SERIES POWERED LOUDSPEAKERS The HD1221, HD1521, HD1531 feature Class 'D' Fast Recovery<sup>TM</sup> amplification, precision crossovers, time cor-

feature Class 'D' Fast Recovery™ amplification, precision crossovers, time correction and patented acoustic correction in order to provide high-definition clarity and superior performance. All 3 speakers feature custom EAW transducers and the HD1521 and HD1531 have an integrated user-adjustable 3-band EQ with sweepable mid. All 3 are flyable as well as pole-mountable and have a compact but rugged birch plywood cabinet. The HD1501 and HD1801 subwoofers also have Class 'D' amplification and feature internal crossovers, tuning filters, phase alignment with loudspeakers, a hi-pass output, and protection circuitry.

ITEM	DESCRIPTION	PRICE
HD1221	12" 2-way active speaker, 500W/LF, 100W/HF,	
	55Hz-20kHz, 90°H x 50V°, 133dB Max SPL, XLRF in,	
	XLRM loop out, 50 lbs	799.99
HD1521	15" 2-way active speaker, 700W/LF, 100W/HF,	
	50Hz-18kHz, 80°H x 50V°, 135dB Max SPL, XLRF in,	
	XLRM loop out, 80 lbs	999.99
HD1531	15" 3-way active speaker, 700W/LF, 100W/MF, 100W/HF,	
	50Hz-18kHz, 90°H x 40V°, 135dB Max SPL, XLRF in,	
	XLRM loop out, 96 lbs	1249.99
HD1501	15" powered subwoofer, 600W RMS, 1200W peak, 36Hz-145Hz,	
	126dB Max SPL, XLRF ins, balanced XLRM outs, 80 lbs	899.99
HD1801	18" powered subwoofer, 800W RMS, 1600W peak, 35Hz-145Hz,	
	133dB Max SPL, XLRF ins, balanced XLRM outs, 106 lbs	999.99
FB221	Flybar for HDA & HD1801	1483.00
PA-A2	Eyebolt kit for HD Series speakers	47.99





COMPUTER AV

ACCESSORIES



PEAVEY PVX SERIES SPEAKERS Constructed with a lightweight molded polypropylene exterior, these speakers are ideal for live music or speech applications. All models feature woofers with 2-3/8" voice coils and a 1.4" titanium compression driver coupled to a constant directivity horn. Multiple cabinet fly points, angled sides for use as a floor monitor, and an integrated pole mount allow for flexible speaker placement. Active models feature DDT compression, module bay for use of expansion modules, balanced XLR / 1/4" TRS combo input, and XLR /1/4" through outputs. Passive versions can handle 400W program and 800W peak, and utilize parallel 1/4" and 4-pin twist-lock inputs.

ITEM	DESCRIPTION	PRICE
PVXP12	. 12" 2-way, active loudspeaker	349.99
PVX12	. As above, passive version	199.99
PVXP15	. 15" 2-way, active loudspeaker	399.99
PVX15	. As above, passive version	249.00









**PEAVEY PV® SERIES** 

**POWERED LOUDSPEAKERS** Both portable powered enclosures are rated at 400W program and feature DDT<sup>TM</sup> compression, RX<sup>TM</sup> 14 titanium compression drivers, 15" woofers with 2.375" voice coils, and LED signal present and DDTTM activation indicators. Also has combination 1/4"/XLR inputs, as well as XLR and 1/4"

through outputs. Carpet covered with integrated pole mounts.

ITEM	DESCRIPTION	PRICE
PV115D	Powered loudspeaker with (1) 15" woofer	299.99
PV215D	Powered loudspeaker with (2) 15" woofers	499.99







PEAVEY PR SERIES SPEAKERS Constructed with a lightweight molded polypropylene exterior, these speakers are ideal for live music or speech applications. All models feature woofers with 2.375" voice coils, 1.4" titanium compression driver, a 90°x40° constant directivity horn, top and bottom flying point inserts, and a molded-in pole mount. The non-powered versions can handle 400W program and 800W peak. Powered models feature DDT compression, are capable of up to 120dB SPL, balanced XLR-F / 1/4" TRS mic/line combo jack, provides 150W RMS to the woofer, and 50W RMS to the tweeter. The PRSUB's woofer sports a 2.5" voice coil and has the same power rating as the unpowered speaker models.

ITEM	DESCRIPTION	PRICE
PR10	. 10" 2-way, passive, 400W, 54Hz-21kHz	159.99
PR12	. 12" 2-way, passive, 400W, 54Hz-21kHz	189.99
PR12D	. 12" 2-way, active, bi-amped, 200W, 54Hz-21kHz	339.99
PR15	. 15" 2-way, passive, 400W, 49Hz-21kHz	229.99
PR15D	. 15" 2-way, active, bi-amped, 200W, 49Hz-21kHz	399.00
PRSUB	. 15" passive subwoofer, 400W, 45Hz-3kHz (-10 dB, half spac	e) 239.99



PEAVEY ELEMENTS™ WEATHER-RESISTANT SPEAKERS The C Series features composite fiberboard enclosures which remain stable in wet conditions, yet have the resonant properties of wood. The M Series have rugged molded cabinets and feature stainless multi-fly-point hardware. All models are IP45 rated, have weatherproof Black Widow ® woofers and RXTM22 2" titanium diaphragm compression driver tweeters (expect the 108C). Can be ordered in 60°x40° or 105°x60° coverage patterns.

ITEM	DESCRIPTION	PRICE
Elements C Series		
108C	. 8" 2-way speaker, 75°x75° horn	599.99
112C	. 12" 2-way speaker, Quadratic-Throat Waveguide® rotatable horn	899.99
115C	. 15" 2-way speaker, Quadratic-Throat Waveguide® rotatable horn	999.99
Elements M Series		
108M	. 8" 2-way speaker, Quadratic-Throat Waveguide® rotatable horn	499.99
110M	. 10" 2-way speaker, Quadratic-Throat Waveguide® rotatable horn	699.99
112M	. 12" 2-way speaker, Quadratic-Throat Waveguide® rotatable horn	799.99
212-SUB	. 2x12" subwoofer	999.99



