















MUSIC



COMPUTER AV







VIDEO









ACCESSORIES



















Blackmagicdesign

TVIEW



BLACKMAGIC DESIGN SMARTVIEW LCD MONITORS Smartview Monitors include 3-color integrated tally borders,

international power supply, Ethernet connection, USB 2.0 update port, SDI inputs with loop out, switchable between SD-, HD- and 3G-SDI. Duo features (2) 8" LCD screens in a compact 3RU design while HD features (1) 17" 1080p LCD screen in a sleek 6RU design. Both are only 1" thick and perfect for any rackmount setup.

		г.
ITEM	DESCRIPTION	PRICE
SMARTVIEW-DUO	Dual 8" LCD 3RU rackmount monitor	660.25
SMARTVIEW-HD	. 17" HD LCD 6RU rackmount monitor	850.25

datavideo



DATAVIDEO TLM-702 DUAL 7" TFT LCD MONITORS The TLM-702 includes two 7" TFT LCD monitors (1440x234) in a standard 19" rackmount, 3RU high. It can tilt up to +/- 30° and lock in any position. Controls include flip, 4:3 aspect, 16:9 aspect, mirror image, source select, contrast, brightness, color, and tint.

•		
ITEM	DESCRIPTION	PRICE
TLM702	. (2) 7" TFT LCD monitor, 3RU	816.00
TLM702MH	. TLM-702 monitor with holder to attach to SE-500 switcher	. 1008.00



DATAVIDEO TLM433 THREE 4.5" LCD MONITOR UNIT This rackmountable unit has adjustments for contrast, brightness, color & tint and an LED tally light indicator above each screen. Includes 3 composite video BNC outs for loop-through.

ITEM	DESCRIPTION	PRICE
TLM433	Rackmount (3) 4.5" LCD broadcast monitors, 2RU	. 960.00

DATAVIDEO TLM-170H LCD MONITOR

The TLM-170H is a 17.3", HD-SDI desktop monitor. It features a 1600x900 resolution and a backlit LED screen (desktop only). It also has built in stereo speakers and an audio level indicator. Connections include two CV inputs, one S-Video, HD-YUV, HD-SDI and HDMI.

op nd	
so	
el	1 4000
ts,	*********
	PRICE

ITEM	DESCRIPTION	PRICE
TLM-170H	Desktop monitor with backlit LED	
TLM-170HM	1RU rack-mounted LCD monitor	2112.00
TLM-170HR	7RU rack-mounted LCD monitor	1728.00

DATAVIDEO TLM-700HDPD 7" HD/SD-SDI FIELD MONITOR Suited

for use in the field or studio, this unit can be powered with 12V DC or AC and automatically switches between PAL and NTSC. It features a standard V-mount that allows you to use universal batteries. A sunshade is included for in-the-field applications. It can be calibrated with an internal color bar,



color temperature, color select and the "blue-only" mode. Inputs include HD/SD-SDI, HDMI, YUV component and composite and a 15-pin D-sub connector for tally control. Includes 12V DC power supply, battery not included.

ITEM	DESCRIPTION	PRICE
TLM-700HDPD	. 7" TFT LCD field monitor with HD/SD-SDI input	768.00
MO-TLM700	. Case for TLM700HD (by Porta-Brace)	181.41
E7S	. IDX Li-lon V-Mount battery 71Wh/4.8Ah, 14.8V	259.00

IKAN D-SERIES LCD MONITORS These small and lightweight camera field monitors have a HD resolution of 1280x800 pixels and are equipped with 3G-SDI (input/output) and a HDMI input. Features false color, peaking, DSLR scaling and



customizable function buttons on the back. Units come in 5" or 7" IPS and are available as waveform monitors with waveform, vectorscope, and RGB parade options.

ITEM D5	DESCRIPTION 5.6" 3G-SDI LCD monitor with hi-def panel	PRICE 99.00
	As above, with waveform	
	7" 3G-SDI LCD monitor with hi-def IPS panel	
	As above, with waveform	

IKAN VL5 5" HDMI FIELD MONITOR With a resolution of 800 x 480 and the additional functionality of DSLR Scaling, the lightweight VL5 5" HDMI monitor is complemented by pro features such as peaking, under scan, switchable aspect ratio & aspect ratio guides, blue gun and adjustable RGB. It accepts 480i/p, 576i/p, 720p, and 1080i/p inputs via



ITEM

HDMI. Included with the VL5 are an AC adapter, your choice of Sony, Panasonic or Canon DV battery adapter plates and an anti-glare visor for bright conditions. Deluxe Kit is also available which includes choice of battery and charger, battery plate, AC adapter, shoe mount, mini & standard HDMI cables, sun visor and a soft case.

ITEM	DESCRIPTION	PRICE
VL5-C	5" HDMI field monitor with Canon battery adapter plate	224.00
VL5-P	As above, with Panasonic battery adapter plate	224.00
VL5-S	As above, with Sony battery adapter plate	224.00
VL5-C-DK	5" HDMI field monitor deluxe kit with Canon accessories	359.00
VL5-P-DK	As above, with Panasonic accessories	359.00
VL5-S-DK	As above, with Sony accessories	359.00

IKAN VK5 & VK7I HDMI MONITORS The ikan 5" VK5 and 7" VK7I are perfect solutions for DLSR monitoring with their light weight, low profile designs. Both monitors feature HDMI inputs, and many pro features such as red peaking, DSLR scaling, false color and clip guides. The VK7I has additional features including a HD IPS display panel, looping HDMI, composite, and component inputs, as well as an RJ45 tally connection



and a pro XLR power connector. Powering these monitors in the field is easy with snap-on/screw-on battery plates that are compatible with a variety of Pro, DV style, and LP-E6 style batteries. Deluxe kits are also available which include the battery, battery charger and soft case in addition to the standard accessories.

ITEM	DESCRIPTION	PRICE
VK5-C	5" HDMI field monitor with Canon battery adapter plate	359.00
VK5-P	As above, with Panasonic battery adapter plate	359.00
VK5-S	As above, with Sony 'L' Series battery adapter plate	359.00
VK7I-C	7" HDMI IPS field monitor with Canon battery adapter plate	449.00
VK7I-P	As above, with Panasonic battery adapter plate	449.00
VK71-S	As above, with Sony 'L' Series battery adapter plate	449.00
VK71-SU	As above, with Sony BPU Series battery adapter plate	449.00
VXPBK-A	'Gold' mount pro battery adapter plate	135.00
VXPBK-S	'V' mount pro battery adapter plate	135.00





composite video as well as RCA audio-in. DT-E models feature a TN Panel with LED backlighting that provides improved contrast and black level, as well as 20-30% less power consumption. DT-V models have a superior IPS display, built-in waveform/ vectorscope and a 3G/dual-link HD-SDI input that enables monitoring of 1080/60p signals. The DT-3D24G1U uses passive 3D technology to display flicker-free images and is compatible with side-by-side and line-by-line 3D formats.

ITEM	DESCRIPTION	PRICE
DTE17L4GU	17" HD LED LCD monitor with HD/SD-SDI	2415.00
DTE21L4U	21" HD LED LCD monitor with HD/SD-SDI	2650.00
DTV17G1Z	17" HD IPS LCD monitor with 3G/dual-link HD-SDI	2695.00
DTV24G11Z	24" HD IPS LCD monitor with 3G/dual-link HD-SDI	3795.00
DT3D24G1U	24" HD 3D LCD monitor with (2) 3G/dual-link HD-SDI	CALL
RAK17LCDGS	Rackmount kit for DTV17G1Z	140.00
RAK2024LCD	Rackmount kit for DTV 20" to 24" LCDs	174.81

Marshall Electronics

DECUDIDATION



MARSHALL ELECTRONICS MD SERIES LCD RACK DISPLAYS MODULAR INPUTS The MD series of rack monitors feature interchangeable input modules. V-MD434 and V-MD503 units feature advanced front panel menu and feature control. V-MD702, V-MD171X, and V-MD201 feature composite and component inputs. All models feature false color filter, markers, freeze function, status display, color temp presets, RGB gain/bias adjust, blue gun, pixel-to-pixel and hard tally. V-MD171X and V-MD201 monitors can be used on desktops with purchase of optional stand. Monitors can be purchased with 3GSDI input modules already

HEIN	DESCRIPTION	PKILE
V-MD4	34 2RU (4) 4.3" 800x480 widescreen rack monitor unit, with	
	front-panel menu/feature control, without input modules	2597.85
V-MD5	032RU (3) 5" 800x480 rack monitor unit, with front-panel	
	menu/feature control, without input modules	2011.35
V-MD5	633RU (3) 5.6" LED-backlit 1280x800 rack monitor unit	
	with composite/component inputs	2988.85
V-MD7	23RU (2) 7" LED-backlit 800x480 rack monitor unit,	
	without input modules	1723.85
V-MD7	02As V-MD72, with composite/component inputs	1907.85
V-MD1	71X	uts 1896.35
V-MD2	017RU 20" 1600x900 rack monitor with composite/component in	outs 1493.85
Input	Modules for V-MD434, V-MD503	
MD-3G	SDI-B3G/HD/SDI input module with loop-through	320.85
	SDIX2-B2-channel HDSDI input module with switched output	
	IX2-B2-channel HDMI input module	
	II-BDVI-I input module	
	Modules for All Other Models	
	SDI-A3G/HD/SDI input module with loop-through	320.85
	SDIX2-A2-channel HDSDI input module with switched output	
	IX2-A2-channel HDMI input module	
	II-ADVI-I input module	
	on Stands	100.70
		24.44
	Desktop stand for V-MD171X rack monitor	
V-5120	Desktop stand for V-MD201 rack monitor	45.94
	N P	

V-R231-IMD-HDSDI



ELECTRONICS IN-MONITOR DISPLAY-CAPABLE LCD MONITORS Allows UMD (Under-Monitor Display) information and tallies to be displayed directly within the monitor. Available features include on-screen video time code, 3-color "Soft" Tallies, audio presence indicator and easy menu navigation. Integrates easily with existing Tally systems and controllers, while supporting Image Video, NVISION, TSL, and MEI protocols. All except the Quad Viewer monitors include HDSDI/SDI inputs and can be used as standalone displays with HDSDI loop-through. Quad Viewer models offer full-screen mode for video and DVI and quad-split mode (via built-in HD quad splitter) which is scaled to fit onscreen in the highest resolution. The Quad Viewer models have (4) independent HDSDI inputs, (1) DVI input, field-upgradeable firmware, and an RS422/485 port with pass-through. Dual Link/Waveform models feature 10-bit video path with 3G capable monitors and can display live video, audio bars, waveform and vectorscope in quad-view mode. They also have (2) 3G/HD/SDI inputs, Dual Link, a DVI input, RS485 firmware updating, and closed captioning (CEA-608-B, CEA-708-B). The NCB-1005 allows connected IMD monitors to be controlled by PC via Ethernet.

ITEM DESCRIPTION PRIC	Ε
V-R653P-IMD-TE (3) 6.5" HD/SD monitors in 2RU rack unit, 1024xRGBx768 4483.8	5
V-R653SB-IMD As above, outdoor version	5
V-R1041-IMD-TE4U 10.4" HD/SD rackmount monitor, 4RU, 1024xRGBx768 2068.8	5
V-R1042-IMD-TE4U (2) 10.4" HD/SD monitors in 4RU rack unit, 1024xRGBx768 3444.2	5
V-R171X-IMD-HDSDI 17" HD/SD rackmount monitor, 6RU	5
V-R201-IMD-TE 20" HD/SD rackmount monitor, 6RU, 1680xRGBx1050 1930.8	5
VP-LCD171H-ST-01 VESA mount stand w/pivot and tilt for 20", 23" monitors 182.8	5
NCB-2010 Network control box for -IMD monitors	5
V-R171X-IMD-HDSDI 17" rackmount monitor, 6RU, 1920xRGBx1200	5
QV171X-HDSDI 17" HD rackmount Quad Viewer monitor, 6RU, 1920x1200 3448.8	5
V-ST15 Desktop stand for Quad Viewer monitors	
V-R171X-DLW	5
V-R261-DLW	5



























































































ACCESSORIES













Marshall Electronics

V-R44P



MARSHALL ELECTRONICS PROFESSIONAL LCD RACK MOUNT MONITORS

These come in a wide variety of size and mounting arrangements. Displays are lightweight, have a shallow depth, run cool and tilt for optimum viewing. Many models feature TFT MegaPixel™ displays for better images and pixel density compared to other monitors. Configurations are available with HDSDI, SDI, DVI, Component HD/SD, and composite video inputs.

ITEM	DESCRIPTION	PRICE
V-R43P	Triple 4" in 2RU, composite ins on each	. 1006.25
V-R44P	Four 4" in 2RU, composite ins on each	. 1263.85
V-R573P	Triple 5.7" in 3RU, 2 composite ins on each	. 1378.85
V-R653P-HDSDI.	Triple 6.5" HD in 3RU, SDI/HDSDI inputs, composite & component ins	. 3103.85
V-R70P-HDSDI	Standalone 7" HD widescreen 1.2 TFT-Megapixel, video	
	assist monitor, HDSDI/SDI ins	. 1608.85
V-R70-1M	Rackmount adapter for V-R70P units	59.80
V-R72DP-2C	Dual 7" widescreen in 3RU, 2 composite ins on each	. 1608.85
V-R72P-2HD	Dual 7" multiformat widescreen 1.2 Megapixel in 3RU, with composite,	
	S-video, component HD/SD(YPbPr) & HD/SDI ins on each	. 3161.35
V-R82SB-AFHD	Dual 8.4" backlit/for outdoor use in 4RU, 800x600, with	
	HDSDI/SDI, component, composite, S-video, DVI, SXGA ins on each	. 4081.35

V-LCD15SB-AFHD-DT V-I CD651STX-HDA

MARSHALL ELECTRONICS PORTABLE FIELD MONITORS These models are designed for outdoor and high ambient light situations. The LCD70XP and LCD651STX models have expanded hi-definition input options (HDMI/3GSDI), false color exposure assist, and peaking filter focus assist. The LCD651STX and LCD70XP models are also available with Canon, JVC, Panasonic and Sony battery mounts.

ITEM	DESCRIPTION	PRICE
Sunbright Models		
V-LCD65SB-HDA	6.5" Hi-res Sunbright monitor, RGB, 640x480	1493.85
V-LCD84SB-AFHD	8.4" Hi-def Sunbright monitor, RGB, 800x600,	
	also has SDI/HDSDI, VGA, DVI and S-Video inputs	1608.85
V-LCD15SB-AFHD-DT.	15" Hi-def Sunbright monitor, 1024x768, SDI/HDSDI,	
	VGA, DVI and S-Video inputs, includes desktop stand	2528.85
5" Model		
V-LCD50-HDMI	5" HDMI camera-top monitor, 800x480, uses AA batteries	516.35
6.5" Models		
V-LCD651STX-HDA	6.5" Hi-res camera-top monitor, 1024x768	1528.35
V-LCD651STX-HDA-AB.	As above, with Anton Bauer battery adapter	1631.85
V-LCD651STX-HDA-VM	As above, with V-Mount battery adapters	1631.85
V-LCD651STX-HDMI	6.5" Hi-res camera-top monitor with HDMI in, 1024x768	1608.85
V-LCD651STX-HDMI-AB.	As above, with Anton Bauer battery adapter	1723.85
V-LCD651STX-HDMI-VM	As above, with V-Mount battery adapters	1723.85
V-LCD651STX-3GSDI	6.5" Hi-res camera-top monitor w/3G/HD/SD in, 1024x768	1769.85
V-LCD651STX-3GSDI-AB	As above, with Anton Bauer battery adapter	1884.85
V-LCD651STX-3GSDI-VM	As above, with V-Mount battery adapter	1884.85
7" Models		
V-LCD70XP-HDMIPT	7" Hi-res camera-top monitor with HDMI in, 800x480	895.85
V-LCD70XP-HDMIPT-AB.	As above, with Anton Bauer battery adapter	1010.85
V-LCD70XP-HDMIPT-VM	As above, with V-Mount battery adapter	1010.85
V-LCD70XP-3GSDI-AB	As above, with Anton Bauer battery adapter	1102.85
V-LCD70XP-3GSDI-VM.	As above, with V-Mount battery adapter	1102.85

Marshall Electronics

MARSHALL ELECTRONICS LYNX™ SERIES LCD MONITORS Displays are lightweight, shallow in depth, run cool and tilt for viewing. Many models feature TFT MegaPixel™ displays offering the highest pixel density for improved images compared to similar CRT and standard LCD products. Available in 10" to 19" displays. Significant improvements have been



made to brightness, contrast ratio, and viewing angles. Various input configurations available. MegaPixel models feature screens calibrated to SMPTE/IBU standards for color gamut and color temperature.

color gainer and co	color gamat and color temperature.			
ITEM	DESCRIPTION	PRICE		
M-LYNX-10	10" 4:3 LCD monitor, 800x600 with composite,			
	S-video, VGA and stereo inputs	306.03		
M-LYNX-10W	10" TFT 16:9 LCD monitor with rear speakers, remote control,			
	1024x600, composite, S-video, DVI, VGA & stereo audio inputs	368.81		
M-LYNX-15	. 15" 4:3 LCD monitor with speakers, 1024x768, (2) composite,			
	component, S-video, VGA, DVI and (2) audio inputs	413.65		
M-LYNX-17	. 17" 5:4 LCD monitor with speakers,1280x1024, (2) composite,			
	component, S-video, VGA, DVI and (2) audio inputs	447.28		
M-LYNX-17SDI	17" 4:3 LCD monitor with SD-SDI BNC loop-thru	265.61		
M-LYNX-19	19" 5:4 LCD monitor with speakers, 1280x1024, (2) composite,			
	component, S-video, VGA, DVI inputs and (2) audio inputs	548.17		
M-LYNX-19SDI	. 19" 5:4 LCD monitor with SD-SDI BNC loop-thru	344.08		



MARSHALL ELECTRONICS ORCHID® SERIES RACKMOUNT BROADCAST LCD MONITORS This series of rackmount monitors not only integrates interchangeable components or DVI input modules, but is also packed with additional features such as re-clocked outputs, auto-sensing HDSDI inputs, real-time waveform monitors and color vectorscopes, tri-color tally indicators, adjustable color temperature, timecode, precision gamma settings, adjustable clipping indicators, and more. All models are capable of de-embedding and displaying up to 16 channels of audio, any 2 channels of which can be monitored at one time. Each unit comes with at least one HDSDI input, one HDSDI output, and one input slot per screen, and stereo audio 3.5mm outputs

ITEM	DESCRIPTION	PRICE
OR-434	. Four 4.3" monitors, 2RU, 5 assignable function keys and	
	1 joystick menu system, 800x480	4426.35
OR-503	. Three 5" monitors, 3RU, 6 assignable buttons/screen,	
	4 assignable rotary encoders, 5-button menu system, 800x480	3908.85
OR-701A	. Single 7" monitor, 3RU, dual HD/SD-SDI inputs, stereo speakers,	
	11 assignable function keys, 4 assignable rotary encoders,	
		2413.85
OR-702	. Two 7" monitors, 3RU, 11 assignable function keys,	
	4 rotary encoders, 5-button menu system, 800x480	3310.85
OR-841-HDSDI	. Single 8.4" portable field monitor, 4RU, 1024x768,	
	9 assignable buttons	2758.85
OR-901-XDI	. 9" monitor, rack/camera mountable, 4RU, HD-SDI/HDMI, 3D ready	3276.35
OR-YPR	. Optional component input module	228.85
OR-DVI	. Optional DVI-I input module	182.85

BTLH1760

PANASONIC BROADCAST LCD MONITORS

Designed for critical broadcast and production applications as reference grade HD and SD monitors.

applications as re	reference grade 11D and 0D monitors.	
ITEM	DESCRIPTION	PRICE
BTLH910GJ	. 9" HD/SD LCD 15:9 EVF monitor, 1280x768, HD/SD-SDI,	
	HDMI, BNC, and D-Sub inputs, 3.7 lbs	2995.00
BTLH1760PJ	. 17" LCD monitor (16:9), 1280x768, Vectorscope/WFM,	
	DVI-D and (2) HD-SDI/SDI inputs, embedded audio,	
	time code/CC capable, with desk stand, 13.7 lbs	4220.00
BTLH2550PJ	. 25.5" HD widescreen monitor, 1920x1200, DVI-D and	
	(2) HD-SDI inputs, composite, component, vectorscope, 18.1 lbs	3509.00
Accessories		
BT-MOUNT	. Camera monitor mount for BTLH910GJ	151.20
BTMA1710G	. Rackmount adapter for BTLH1760, 2RU	246.00
	. Thermodyne case for BTLH1760	
	. Travel case for BTLH2550	
MO-LH910B	. Flat screen monitor case for the BTLH910G, black (by Porta-Brace	181.41
Call for more acc	cessories.	







Marshall Electronics

7" Professional Camera-Top LCD Monitor

V-LCD70MD

- The perfect solution for DSLR and Professional Video Cameras
- High Resolution 1024 x 600 LED Backlit IPS panel
- Professional features includes False Color and Peaking Filters,
- · Pixel-to-Pixel, Image Flip, Freeze Frame, Safe Markers, and more
- HDMI Pass-Through (HDCP Compliant)
- HDMI Auto Color Space and Ratio detect
- New Peaking Filter (Choice of four color highlights and variable sensitivity)
- Easily mounts on most cameras (hot shoe adapter included)
- Variety of Optional User-Replaceable Battery Adapters available
- · Designed, engineered, and assembled in USA



For photographers, videographers, producers, and directors alike...



WE DO IT ALL.



































ACCESSORIES











PANASONIC PROFESSIONAL PLASMA DISPLAYS & HOSPITALITY PLASMA DISPLAYS

	TH42PF50U	TH50PF50U	TH60PF50U	TH85PF12U	TH42PH30U	TH50PH30U
DISPLAY		1080p			HD Model	
CREEN SIZE(DIAG.)	41.6"	49.9"	60.1"	85.3"	41.6" 49.9"	
3D READY		Yes		No		
FFECTIVE DISPLAY AREA (W x H)	56.5"x32.8"	52.3"x29.4"	43.5"x24.5"	36.3"x20.4"	43.6"x24.5"	36.3"x20.4"
ESOLUTION (H x V)		1920 x 10	80 pixels		1024 x 70	68 pixels
CONTRAST RATIO (BRIGHT AREA)		Max 5,000,000:1		Max 40,000:1	Max 2,0	00,000:1
PC SIGNAL COMPATIBILITY	VGA, SVGA, XGA, WXGA, SXGA, SXGA+, UXGA (compressed), WUXGA		VGA, SVGA, XGA, WXGA, SXGA (compressed), UXGA VGA, WVGA, SVGA, XGA, WXGA, SXGA, UXGA, WUXGA, WXGA, SVGA, WXGA, SXGA, WXGA, WXG		XGA, SXGA, UXGA, WUXO	
VIDEO SIGNAL COMPATIBILITY	525(480)/60i, 60p; 625(375)/50i, 50p; 625(376)/50p; 750(720)/60p, 50p; 1125(1080)/60i, 50i, 24p, 24sF, 25p, 30p, 60p, 50p; 1250(1080)/50i; 2048x1080/24p, 24sF		525(480)/60i, 60p; 625(575)/50i, 50p; 625(576)/50p; 750(720)/60p, 50p; 1125(1080)/60i, 50i, 24p, 24sF, 25p, 30p, 60p, 50p; 1250(1080)/50i			
WIRELESS I/F	Yes		No			
INPUT/OUTPUT						
PC/IN AUDIO	Mini D-sub 15pin x 1, DVI-D x 1, Plug & Play (VESA DDC 2B), M3 jack x 1		Mini D-sub 15pin x 1, Plug & Play (VESA DDC 2B), M3 jack x 1	Mini D-sub 15pi Plug & Play (VESA I	n x 1, DVI-D x 1, DDC 2B), M3 jack x 1	
SERIAL	D-sub 9-pin x1, external control, RS232C compatible					
ERCHANGEABLE TERMINALS						
SLOT 1			Va	cant		
SLOT 2	Vacant		HDMI In TYPE A connector x 2	Vac	ant	
SLOT 3	Component In N/A BNC x 3 Y/G w/stereo audio N/A		/A			
UILT-IN TERMINAL	Component/RGE	Composite In w/ stereo audio, B In (BNC x 3) w/ stereo audio, HDM	I, DVI-D w/ audio	VGA w/audio, 9-Pin RS232C, L/R audio out	Composite In Component/RGB In (BNCx3) w/s	w/stereo audio, tereo audio, HDMI, DVI-D w/s
SOUND/AUDIO OUT		16W (8W + 8W)		Unlisted	16W (8V	V + 8W)

















PANASONIC PROFESSIONAL PLASMA MODELS UP TO 100,000-HOUR PANEL LIFE (SEE CHART ABOVE)
ITEM DESCRIPTION

IIEM	DESCRIPTION	PRICE
Professional Plasm	na Models – up to 100,000 hour panel life	
TH85PF12U	85" HD plasma display, 1080p, black	CALL
TH60PF50U	60" HD plasma display, 1080p, black	2166.00
TH50PF50U	50" HD plasma display, 1080p, black	1488.00
TH42PF50U	42" HD plasma display, 1080p, black	1170.00
TH50PH30U	50" HD plasma display, black	912.00
TH42PH30U	42" HD plasma display, black	666.00
Partial List of Acce	essories/Terminal Boards for Pro Series	
TYFB10HMD	Dual HDMI terminal board (slot 1 or 2)	162.00
TY42TM6G	RGB active through terminal board (slot 1 or 2)	150.00
TYFB11DD	DVI-D terminal board (slot 1 or 2)	150.00
TYFB9RT	IR through terminal board (any slot)	132.00
TY42TM6P	PC input terminal board (any slot)	102.00

ITEM	DESCRIPTION	PRICE
Partial List of Ac	cessories/Terminal Boards for Pro Series (continued)	
TYFB9BD	BNC dual video terminal board (slot 1 or 2)	156.00
TY42TM6B	BNC composite video terminal board (slot 1 or 2)	138.00
TY42TM6Y	Composite/component video terminal board	
	(slots 1 and 2, or slots 2 and 3)	240.00
TY42TM6Z	RCA component video terminal board (any slot)	102.00
TY42TM6V	RCA composite video terminal board (slot 1 or 2)	138.00
TYFB11DHD	Dual Link HD-SDI board (slot 1 or 2)	2520.00
TYFB10HD	HD-SDI terminal board with audio (slot 1 or 2)	1560.00
TYFB9HD	HD-SDI terminal board (slot 1 or 2)	1260.00
TYFB10WPU	Wireless presentation board (slots 1 and 2, or slots 2 and	3).
	(IEEE802.11b/11g)	324.00
TYTP42P10S	Touch Panel for TH42PH30U	2640.00
TYWK65PR20	Wall hanging bracket, angled	360.00





Follow us!

SONY

BRAVIA® LED INTERNET TELEVISIONS These slim LED TV's feature Full HD 1080p for picture detail and Edge LED backlighting for better contrast. Enjoy wireless access to Sony Entertainment Network, YouTube and more with the included Wi-Fi adaptor.



Digital Noise Reduction enhances detail while MotionFlow™ XR 240 technology will smooth out fast camera motion. Audio power output is 8W+8W (10W+10W on KDL55EX640). This series includes analog audio (2 in/1 out), (1) component and (2) composite inputs, digital audio out, (4) HDMI, PC in, USB and Ethernet.

ITEM	DESCRIPTION	PRICE
KDL40EX640	.40" 1080p LED HDTV with MotionFlow	899.99
KDL50EX645	46" 1080p LED HDTV with MotionFlow	. 1291.57
KDL60EX645	.55" 1080p LED HDTV with MotionFlow	. 1987.04

SONY PROFESSIONAL **LCD COLOR MONITORS**

An extensive line-up of SD and SD/HD professional LCD monitors from 15" to 42" featuring fast video response, extremely high brightness, contrast, color



depth and wide viewing angle. A one-piece construction that includes integrated stand. The LMD4251TD add 3D capability, 3D glasses required. All models are ideal for HDV production applications with some models supporting HDMI or DVI.

ITEM	DESCRIPTION	PRICE
LMD1510W	15.6", 1366x768, HDMI, Composite, Component, Y/C, SDI	752.75
LMD1530W	15", 1280x768, HDMI, SDI, Composite, Y/C and RGB	1078.77
LMD1541W	15", 1280x768, HDMI, SDI, Composite	2123.43
LMD1751W	. 17", 1280x768, DVI-D, SDI	2259.96
LMD2110W	21.5",1920x1080, HDMI, SDI, Composite, Y/C and RGB	951.06
LMD2451W	24", 1920x1200, DVI inputs, Composite, Y/C and RGB	3502.93
LMD2451WHD	LMD2451W packaged with BKM243HS HD/SD SDI adapter	3563.63
LMD4251TD	42", 1920x1200, 3D, DVI inputs, Composite BNC	CALL
Accessories		
MB533	Rackmount kit for LMD1530W	225.50
MB534	Rackmount kit for LMD1541W	188.51
BKM243HS	HDSDI/4:2:2 SDI input adapter, for LMD2051W, LMD2451W.	1030.38
TDGBR250/B	. 3D glasses	48.00

SONY PVM SERIES OLED PROFESSIONAL

VIDEO MONITOR The PVM series uses a 960x540 OLED (Organic Light Emitting Diode) panel, which creates true blacks and higher contrast than LCDs. Picture quality is excellent both indoors and outdoors, Supports broadcast standards SMPTE-C, EBU, and ITU-R BT.709, with resolutions from NTSC/PAL to 1080p60. The PVM740 comes standard with one



composite, one auto detecting SDI/HDSDI/3G input, one HDMI input, internal waveform monitor, 1/4" and 3/8" holes for camera mounting, and AC power adapter.

ITEM	DESCRIPTION	PRICE
PVM740	7 1/4" OLED professional monitor	2243.21
PVM1741	17" OLED monitor, (2) 3G/HD/HD-SDI, HDMI and composite in	puts 3690.00
PVM2541	25" OLED monitor, (2) 3G/HD/HD-SDI, HDMI and composite in	putsCALL
VF510	ENG field kit for PVM740L	385.14
MB531	Rackmount kit	288.86

SONY FWD SERIES HD LED DISPLAYS These public display HD LED LCD's have slim bezels for a more refined and stylish look. Incorporating high-quality, professional 46" and 42" (diagonal) LCD panels, they offer full HD (1920x1080) resolution and high brightness for use in bright light conditions. They support audio in/out (pinjack), HDMI in, HD15 in/out with audio in, composite in/out (BNC x 2) with audio in, component video in



with audio in (pin jack x 3) and L/R speaker out. Also equipped with a network port for remote control/monitoring. An option slot accepts a range of adapters for versatility. Well-suited for retail shops, shopping malls, hospitals or schools. The FWDS42B2 is a low power consumption (120W) model and has DVI-D and HDMI inputs.

ITEM	DESCRIPTION	PRICE
FWDS42H2	. 42", slim HD LED display	1811.04
FWDS46H2	. 46", slim HD LED display	2028.37
FWD42B2	. 42" slim HD LED display, low power consumption	1303.95
BKMFW16	. HDSDI/SDI input adapter	879.89



VISION LCD MONITORS DESCRIPTION


ITEM 4" to 5.6" Monitors

All include LED b	acklight for better color saturation and longer life.
.CD400X4	. Four 4" LCD units in 19" rackmount kit, tilts 90°, NTSC/PAL, 2RU 1010.00
.CD410	. 4" field monitor with audio, battery pack, NTSC
.CD411	. As LCD410, adds BNC in/out
.CD501	. 5" field monitor with stereo audio headphone jack, NTSC/PAL 258.00
.CD560X3	. Three 5.6" LCD units in rackmount kit, tilts 90°, NTSC/PAL, 3RU 942.00
.CD562	. 5.6" field monitor with audio, battery pack, NTSC/PAL
.CD565	. As LCD562, adds BNC
7" - 8" Monitor	\$
.CD703HD	. HD 7", 16:9, DVI, component in/out, S-Video in/out, BNCin/out, 1080p 629.00
.CD703HD-KIT	. LCD-703HD with rechargeable battery pack, tote bag, and AC807.00
.CD703HD1	1 LCD-703HD in rackmount kit. 3RU

LCD562 5.6" field monitor with audio, battery pack, NTSC/PAL 317	.00
LCD565 As LCD562, adds BNC	.00
7" - 8" Monitors	
LCD703HD HD 7", 16:9, DVI, component in/out, S-Video in/out, BNCin/out, 1080p 629	.00
LCD703HD-KIT LCD-703HD with rechargeable battery pack, tote bag, and AC	.00
LCD703HD1 1 LCD-703HD in rackmount kit, 3RU	00.0
LCD703HD2 2 LCD-703HD in rackmount kit, 3RU	.00
LCD703HDA LCD-703HD with Anton Bauer QRC-Gold mount	.00
LCD703HDV LCD-703HD with "V" lock mount for IDX batteries	.00
LCD842HD HD 8.4", 4:3 with 16:10 capability, composirt, component, S-Video, VGA, HDMI 785	.00
LCD842HD2 Two 8" LCD in rackmount kit, no audio, 4RU	00.0
10.4" MONITORS	
LED1002HD 9.7", 2x composite in/out, 2x speakers, 1024x768	.00
15.4" MONITORS	

15.4" MUNITURS	
LCD1560HD 15.4", 16:9, audio, composite, component, S-Video analog RGB, HDMI,	
RS232, supports 1080p/i, 720p & 480p/i6	62.00
LCD1560HDR LCD-1560HD in rackmount kit. 6RU	62.00

TV ONE PROFESSIONAL RACK MOUNT LCD MONITORS These LCD monitors are available in a variety of screen sizes and input configurations to satisfy most applications.



ITEM	DESCRIPTION	PRICE
LM404R	Quad 4", composite and S-video inputs, tilt rackmount	1440.75
LM563R	Triple 5.6", composite and S-video inputs, tilt rackmount	1695.75
LM701M	Single 7" with dual composite inputs, metal case, Vesa	505.75
LM1511R	Single 15" composite, S-video, PC, stereo, XGA tilt	
	rackmount, VESA mount	1270.75
LM1911R	Single 19" composite, S-video, PC, stereo, SXGA tilt	
	rackmount, VESA mount	1610.75
LM1920R	Single 19", composite, S-video, PC, stereo, VESA mount	930.75

vaddio REDEFINING CAMERA CONTROL



Excellent rackmount monitors for a variety of applications that require high resolution monitoring of SD cameras. Each includes 2 or more monitors in a 3RU enclosure with tilt mechanism (PREVIEW-QUAD-4 is 2RU). Color, contrast, brightness, and On/Off controls per LCD (except PREVIEW-QUAD-4). The SD monitors offer active matrix LCD screens and inputs with active looping outputs on BNC connectors.

ITEM	DESCRIPTION	PRICE
PREVIEW-DUAL-6.4	Dual 6.4" LCD rack mount monitor, 3RU	1148.40
PREVIEW-TRIPLE-5.6	Triple 5.6" LCD rack mount monitor, 3RU	1071.60
PREVIEW-QUAD-4	Quad 4" LCD rack mount monitor, 2RU	994.80

VariZoom

VARIZOOM VZ-TFT7 16:9 7" ON-CAMERA MONITOR An external video display allowing

more free movement away from camera with a generous 30°/60° viewing angle. Can use for most aspect ratios and has RCA video and 2.1mm 12V DC input. 10W max power consumption. Includes AC adapter and 4' RCA cable.



ITEM	DESCRIPTION	PRICE
VZ-TFT-7	7" 16:9 on-camera monitor w/video cable and universal power supply	264.62
VZ-TFT-7U	7" 16:9 on-camera monitor w/case, 702M battery kit, shoe and sunhood	386.10























































