




















AUDIO – MICROPHONE CABLE, 2-CONDUCTOR SHIELDED

ITEM		GAUGE	STRANDING	O.D.	PF/FT	SHIELD	JACKET
Belden	8412		20	26x34	.262"	30	85% Braid EDPM Rubber
Gepco	MP1022		24	41x40	.195"		95% Braid Synth Rubber
Liberty	22-1P-EZ-BLK		22	7x30	.155"		100% Alum/Poly Foil PVC
Mogami	W2549		22	30x37	.236"	23	Super Flexible PVC
Whirlwind	WMKPV		22	26x36		35	78% BC Braid Flexible PVC, black

AUDIO – ANALOG MIC CABLE: 4-CONDUCTOR STAR-QUAD, LOW NOISE, FOR PORTABLE USE



ITEM		GAUGE	STRANDING	O.D.	PF/FT	SHIELD	JACKET
Canare	L4E6S		24	40	.237"	46	95% Braid PVC
Liberty	24-2P-STAR-BLK		24	41x40	.24"		96% PVC
Mogami	W2534		24	20x37		20	Spiral Super Flexible PVC

AUDIO – ANALOG MIC/LINE PERMANENT INSTALL, 2-CONDUCTOR, FOIL SHIELD WITH DRAIN WIRE



ITEM		GAUGE	STRANDING	O.D.	PF/FT	SHIELD	JACKET	NEC
Belden	1503A		22	7x30	.142"	53	100% Foil PVC	CM
Belden	8450		22	Solid	.118"	40	100% Foil PVC	CM
Belden	9451		22	7x30	.135"	34	100% Foil PVC *	CMR
Canare	L4E6AT		20		.244"	46	100% Alum. Tape PVC	
Gepco	61801EZ		22	7x30	.140"	34	100% Foil PVC	CMR
Liberty	22-1P-CMP-EZ-BLK		22	7x30	.13"		100% Alum/Poly Foil PVC	CMP
West Penn	291		22	7x30	.165"		100% Foil PVC	CL2
West Penn	292		20	7x28	.184"		100% Foil PVC	CL2
West Penn	293		18	7x26	.208"		100% Foil PVC	CL2
West Penn	25291B		22	7x30	.165"		100% Foil PVC	CMP
West Penn	25292B		20	7x28	.143"		100% Foil PVC	CMP

* Features self-stripping foil and BananaPeel- no jacket, just pull and peel.

AUDIO – DIGITAL MIC CABLE: AES/EBU 2-CONDUCTOR SHIELDED, 110 OHMS, LOW CAPACITANCE

ITEM		GAUGE	STRANDING	O.D.	PF/FT	SHIELD	JACKET
Cable Up	AES7-500		24	7x30	.198"	14.5	95% Braid Non-plen PVC
Canare	DA206		20		.287"	14.6	95% Braid Non-plen PVC, blue

AUDIO – ANALOG MIC/LINE MULTIPAIR (SNAKE), FOIL SHIELD, COMMON JACKET

ITEM		GAUGE	PAIRS	O.D.	PF/FT	SHIELD	JACKET	NEC
Gepco	6604HS		22	4	.285"	52	100% Foil/mylar side out Plenum PVC	CMP
Gepco	6608HS		22	8	.385"	52	100% Foil/mylar side out Plenum PVC	CMP

Bulk wire is available in standard spool lengths, and some can be cut to your requirements. Please call for specifics.

Visit fullcompass.com today!

For expert advice - call: 800-356-5844

M-F: 9:00-5:30 Central



AUDIO



MUSIC



COMPUTER AV



VIDEO











LIGHTS












ACCESSORIES



AUDIO – ANALOG MIC/LINE MULTIPAIR (SNAKE) WITH INDIVIDUAL JACKETS PER PAIR

ITEM			GAUGE	PAIRS	O.D.	PF/FT	SHIELD	JACKET	NEC
Geppo - Call for Length information, some available by the foot (varies).									
Geppo	GA61804GFC		22	4	.40"	60		PVC	CMR
Geppo	GA61806GFC		22	6	.475"	60		PVC	CMR
Geppo	GA61812GFC		22	12	.635"	60		PVC	CMR
Geppo	GA61820GFC		22	20	.800"	60		PVC	CMR
Geppo	GA61832GFC		22	32	.935"	60		PVC	CMR
Geppo - Direct Burial series - for permanent underground installs, incl. water blocking tape that is wrapped around cable core, difficult to puncture.									
Geppo	GA61806PEF		22	6	.475"	48	100% Foil	PVC/Base10	
Geppo	GA61812PFF		22	12	.635"	48	100% Foil	PVC/Base10	
Mogami - Super flexible down to -2° C, channel #s printed & underlined on jacket to ensure correct ID. Ideal for soldering or crimping to connectors.									
Mogami	W2932		25	8	.453"	40		PVC	
Mogami	W2934		25	16	.622"	40		PVC	
Mogami	W2936		25	24	.787"	40		PVC	
Mogami	W2938		25	32	.854"	40		PVC	
Pro Co	AC4		24	4	.425"	21		PVC	
Pro Co	AC8		24	8	.550"	21		PVC	

AUDIO – SPEAKER CABLE, PORTABLE HIGH FLEXIBILITY, HEAVY DUTY JACKET

ITEM			GAUGE	COND.	O.D.	JACKET	NEC	DESCRIPTION
Belden - 2 Conductor, ultra flexible, ideal for home theater installs, jackets marked at 2' intervals. Black, white, gray blue or green jackets.								
Belden	5000UP		12	2	.302"	PVC	CL3	
Belden	5200UP		16	2	.208"	PVC	CM	
Canare	4S8		16	4	.327"	PVC		General purpose, biamp rigs
Canare	4S11		11	4	.421"	PVC		Long runs, subwoofers, gray only
Geppo - All-weather TPE outer jacket, round construction, ideal for Speakon.								
Geppo	GSC132		13	2	.350"	TPE, black		
Geppo	GSC134		13	4	.420"	TPE, black		
Geppo	GSC138		13	8	.580"	TPE, black		
Pro Co	11-4		11	4		PVC		
Pro Co	13-8		13	8		PVC		
Pro Co	14-2		14	2		PVC		




Bulk wire is available in standard spool lengths, and some can be cut to your requirements. Please call for specifics.

BULK WIRE NEC RATINGS










CMP – Rated for all in-wall, plenum and riser applications. • **CMR, CL3R, CL2R** – Rated for all in-wall and riser applications, not permitted in plenums.
CM, CMG, CL2 – In-wall rated; permitted in 1-2 family residential riser applications, or in riser with raceway/fireproof shaft; not permitted in plenums.



AUDIO – GUITAR / KEYBOARD / INSTRUMENT CABLE

ITEM			GAUGE	COND.	O.D.	PF/FT	SHIELD	JACKET
Cable Up - Guitar cable, low noise, low capacitance.								
Cable Up	M54C-500		20	1	.236"	37.2	PVC	Conductive PVC Layer
Canare - For electronic instruments, test probes, audio patch, and amp to cabinet leads.								
Canare	GS6		18	1	.228"	49	OFC >92% Braid	Carbon Sleeve
Gepco - Data-grade, foam dielectric (drastically reduces capacitance), abrasion resistant PVC.								
Gepco	XB20UB		20	1	.228"	22.3	Double 95% TC Braid	PVC





AUDIO – UNSHIELDED CABLE: FOR SPEAKER AND CONTROL APPLICATIONS

ITEM			GAUGE	COND.	O.D.	STRANDING	JACKET	NEC
Belden	8471		16	2	.274"	19 x 29	PVC	CMG
Belden	8477		22	2	.386"	65 x 30	PVC	CL3R
Coleman	23288		12	2	.41"	65 x 30	T*Prene	
Gepco	GSC134		13	4		52 x 30	PVC	
Liberty	22-2P-SHEX-YEL		22	2	.186"	16 x 34	PVC	CL3
Pro Co	14-2		14	2	.325"	41 x 30	PVC	
Pro Co	12-2		12	2	.365"	65 x 30	PVC	
West Penn	224		18	2	.186"	7 x 26	PVC	CL2, CMR
West Penn	226		14	2	.24"	19 x 27	PVC	CL2, CMR
West Penn	227		12	2	.278"	19 x 25	PVC	CL2, CMR
West Penn	25224B		18	2	.138"	7 x 26	Plenum	CMP

AUDIO – S/PDIF DIGITAL AUDIO CABLE – 75 OHM

ITEM			GAUGE	STRANDING	O.D.	PF/FT	JACKET	NEC
Belden	1505F		22	7x29	.242"	17	PVC Black	CM
Gepco	VDM230		Mini23	Solid	.164"	16.5	PVC, Multiple Colors	CMR
Gepco	VHD1100		RG11/14	Solid	.405"	16.2	PVC, Multiple Colors	CMR
Gepco	VHD2000M		21	19x34	.242"	17	Flexible PVC	
Gepco	VSD2001		RG6/18	Solid	.272"	16.3	PVC, Multiple Colors	CMR
Gepco	VPM2000		RG59/20	Solid	.272"	16.3	PVC, Multiple Colors	CMR

AC – POWER CABLE FOR PORTABLE USE

ITEM			GAUGE	COND.	JACKET
Coleman	22327		14	3	TPE Seoprene
Coleman	22328		12	3	TPE Seoprene
Coleman	22329		10	3	TPE Seoprene
Coleman	23388		12	3	T*Prene SJEW

Bulk wire is available in standard spool lengths, and some can be cut to your requirements. Please call for specifics.

Visit fullcompass.com today!

For expert advice - call: 800-356-5844

M-F: 9:00-5:30 Central



AUDIO



MUSIC



COMPUTER AV



VIDEO







LIGHTS










ACCESSORIES







LIGHTING – DMX CABLE – BULK

ITEM	GAUGE	COND.	STRANDING	O.D.	SHIELD	JACKET	NEC
Belden 9729 	24	4	7x32	.024"	100% Foil	PVC	CM
Belden 9841 	24	4	7x32	.232"	100% Foil + 90% TC Braid	PVC	CM
Belden 9842 	24	4	7x32	.34"	100% Foil + 90% TC Braid	PVC	CM
Geeco DLG224 	24	4	7x32	.27"	100% Foil + 90% TC Braid	PVC	






DATA – CAT5E AND CAT6 BULK CABLE

ITEM	TYPE	GAUGE	COND.	PAIRS	O.D.	PF/FT	STRANDING	JACKET	NEC
Belden 1583A-1000 	CAT5e	24	8	4	.214"	15	Solid	PVC	CMR
Belden 1585A-1000 	CAT5e	24	8	4	.2"	15	Solid	Plenum	CMP
Belden 106X12 	CAT6	23	8	4	.295"	17	Solid	PO	CMR
Belden 106X13 	CAT6	23	8	4	.295"	17	Solid	Plenum	CMP
Geeco CT504HD 	CAT5e	24		4	.26"	17	41 x 40	TPE, black	
Liberty 24-4P-L5SH-EN-BLU 	Shielded CAT5	24	8	4	.237"	17.0	Solid	FR-PVC	CMR
Liberty 24-4P-L6SH-BLK 	Shielded CAT6	24	8	4	.270"	17.0	Solid	FR-PVC	CMR



DIGITAL/ANALOG VIDEO – 75 OHM SDI/HDSI COAXIAL CABLE – RG6

ITEM	GAUGE	STRAND	O.D.	PF/FT	VEL-PROP	SHIELD	JACKET	NEC
Belden WV-1694D 	2 x 18	Solid	.334"x.618"	16.2	82%	100% Duofoil + 95% TC Braid	Non-plenum	CMR
Belden 1694A 	RG6/18	Solid	.275"	16.2	82%	100% DuoFoil + 95% TC Braid	Non-plen PVC	CMR
Belden 1695A 	RG6/18	Solid	.234"	16.2	82%	100% DuoFoil + 95% TC Braid	Plenum	CMP
Liberty 18-CMR-SD-BLK 	18	Solid	.27"	16.2	82%	100% Alum/Poly + 95% TC Braid	PVC	CMP

DIGITAL/ANALOG VIDEO – 75 OHM SDI/HDSI COAXIAL CABLE – RG59

ITEM	GAUGE	STRAND	O.D.	PF/FT	VEL-PROP	SHIELD	JACKET	NEC
Belden 1505A 	RG59/20	Solid	.233"	16.3	83%	100% DuoFoil + 95% TC Braid	Non-plen PVC	CMR
Cable Up RG59ST-500 	RG59/22	7x29	.242"	17	80%	Double TC Braid 95%	Non-plen PVC	CM
Geeco VPM2000 	RG59/20	Solid	.242"	16.3	83%	100% Foil/95% TC Braid	Non-plen PVC	CMR
Geeco VPM2000TS 	RG59/20	Solid	.2"	16	84%	100% Foil/95% TC Braid	Plen PVC	CMP
Liberty 20-CMR-VIDEO-BLK 	20	Solid	.24"			100% Alum/Poly + 95% TC Braid	PVC	CMR

VIDEO – RG-59/8281F TYPE (STANDARD & PLENUM) SINGLE CHANNEL

ITEM	GAUGE	STRANDING	O.D.	PF/FT	VEL-PROP	SHIELD	JACKET	NEC
Belden 8241 	RG59/23	Solid	.242"	21	66%	95% Braid	PVC	CM
Canare - Highly flexible, copper braid shield polyethylene dielectric								
Canare LV61S 	RG59/24	7/7.88	.24"	21	66%	95% Braid	Poly	

Bulk wire is available in standard spool lengths, and some can be cut to your requirements. Please call for specifics.

BULK WIRE NEC RATINGS

CMR – Rated for all in-wall, plenum and riser applications. • CMR, CL3R, CL2R – Rated for all in-wall and riser applications, not permitted in plenums.
CM, CMG, CL2 – In-wall rated; permitted in 1-2 family residential riser applications, or in riser with raceway/fireproof shaft; not permitted in plenums.