

















































ALESIS MULTIMIX 8-LINE This mixer puts an 8-channel line mixer in one rack space. Channel 1 will also accept a mic input. Features include a stereo effects bus, individual pan and effects send on each channel, signal clip and overload LED's on each input, 5-stage LED for output level monitoring, stereo monitor output, and is expandable to 16 channels by lining a second unit. When a mono signal is present on any input or stereo send, the left signal is automatically summed to mono for mono or stereo compatibility. All connections are TRS except for the XLR microphone input on channel one.

ITEM DESCRIPTION MULTIMIX-8L.. . 8-channel line mixer ...

5 5	2 2 3	0 AL	ESISMONT	
2 1 5 1	5 1 5 1 5 1	# 1 8 1 12 to	1 7 2	
	0 0		<u> </u>	•

MULTIMIX10-WIRELESS **ALESIS MULTIMIX MIXERS/AUDIO INTERFACES** 

These affordable mixers offer 100 28-bit effects, 3-band EQ per channel, +48V phantom power and LED metering. The 4- and 8-channel models have rotary faders and the 10-, 12- and 16-channel versions have 60mm faders. The USB models double as powerful PC and Mac computer audio interfaces, no drivers required, and come with Cubase LE (except the MultiMix 10 Wireless, which has a 2-band EQ on mic inputs, hi-pass filtering, a high-impedance guitar input but no effects.) Wireless model accepts stereo audio from any Bluetooth-enabled device on Channels 9/10.

•	•	
ITEM	DESCRIPTION	PRICE
MULTIMIX-12R	Rackmount mixer, 12-channe	el299.99
MULTIMIX10-WIRELESS	Rackmount mixer, 10-channe	el, with Bluetooth input 299.99



ASHLY MX-406 6-INPUT STEREO RACKMOUNTABLE MIXER This 6-input mixer has a 3-position switch for input gain (-20, -40 and -60dB) and +48VDC phantom power. Each channel has high and low shelving filters, aux input control, and balanced XLR mic as well as 1/4" TRS line inputs. Includes 1/4" left and right stereo outs, balanced XLR mono out and stereo headphone out.

ITEM	DESCRIPTION	PRICE
MX406	6-input stereo rackmount mixer	. 900.00



ASHLY MX-508 8-INPUT STEREO RACKMOUNTABLE MIXER An 8-input rackmountable mixer with 84dB of mic gain, and +48VDC phantom power. Each channel has a 3-band EQ with sweepable mid, -20dB pad, 2 aux sends (one pre-, one post-EO), and both balanced XLR mic and 1/4" TRS line inputs. Includes transformerbalanced left and right XLR and 1/4" outputs, mono out and headphone out.


	0		•	
ITEM	DESCRIPTION			PRICE
MX508	8-input stereo rac	kmount mixer		1440.00



ASHLY LX308B A line level, 8-channel stereo (or 16 channel mono) mixer in a single rack space. Each input has a pair of 1/4" jacks with level and pan controls on the front panel. Channels 1 and 2 will accommodate line or mic levels. Left and right clip indicators monitor all internal amps. L/R level control, variable panning, stereo mute switch and mono sum output controls. 1/4" output jacks operate balanced or unbalanced. Additional pre-master sub inputs and outputs allow linking to other mixers.

		•			
ITEM	DESCRIPTION				PRICE
LX308B	. 8-channel stered	o/16-channel	mono line	mixer	575.00

Follow Us!



ART MIC/LINE MIXERS Both mixers provide basic mic/line mixing in a convenient, easy-to-use 1RU rack format. The MX622 features (3) XLR balanced mic/line inputs, (3) sets of RCA stereo inputs with separate volume controls, 2-band master EQ, 1/4" effects send with stereo returns, 1/4" balanced outputs. The MX821 combines 8 input channels into 1 mono line level mixed output. It features XLR mic and 1/4" line inputs on each channel as well as level and tone controls on each channel. An RCA aux bus input along with an RCA pre-fade output allows multiple MX821s to be linked together when more channels are needed. Both models have selectable phantom power for each mic channel.

ITEM	DESCRIPTION	PRICE
MX622	6-channel mixer with EQ and FX loop	149.00
MX821	8-channel mixer with tone controls, linkable	185.00



ART MX821S RACKMOUNT MIXER Aversatile rackmount mixer combining eight independent input channels into a stereo line-level output. Each input accepts balanced XLR microphone input or 1/4" TS line-level signal and provides independent level and pan controls. +48V phantom power may be individually selected for each input. A master level control adjusts the signal output to the (2) 1/4" main outputs. Prefade output and Aux Bus input RCA jacks allow patching of multiple units for expanded channel count. It is housed in a rugged 1RU chassis with an internal power supply.

ITEM	DESCRIPTION	PRICE
MX821S	. Rackmount mixer	185.00



ART MX225 5-ZONE STEREO DISTRIBUTION MIXER Designed for remote volume control of multiple amplifiers or powered speakers in a distributed audio system. The 2 input sources are routed to 5 output zones and each source input pair has separate left and right balanced line level signals. Each output zone features independent level control from inputs 1 and 2, stereo/mono selector with mono indicator, LED level metering, and left and right balanced line level zone outputs. Features a built-in power supply.

ITEM	DESCRIPTION	PRICE
MX225	.5-zone mixer, (4) XLR female inputs, (10) XLR male outputs,	1RU 149.00

## ARTcessories<sup>\*\*</sup>

ARTCESSORIES MACROMIX 4-CHANNEL PERSONAL MONO MIXER Connect MacroMix

DECEDITION

between up to 4 line-level sources and output to a dual RCA output. 4 level controls. Inputs 1 and 2 are dual RCA, input 3 is either 1 1/4" input or dual RCA inputs, and input 4 is a 1/4" input. 1/4" headphone/line output provided, and up to 32dB of input gain is possible. 12VDC.



ARTCESSORIES POWERMIX SERIES LINE LEVEL MIXERS Small, easy to use and flexible. All input channels have their own volume control.

DDIAL

IIEIVI	DESCRIPTION	LKIPE
SPLITMIX-4	Passive 4-channel mono with 1/4" inputs, mono output	. 50.00
PWRMIX-3	3-channel stereo mixer with individual panning, and 2 stereo	
	headphone outputs with volume control. Inputs and	
	outputs are stereo 1/4" unbalanced connectors	. 89.00









AKG DMM SERIES AUTOMATIC MICROPHONE MIXERS These automatic mixers have functions for level, treble, bass, low cut, limiting, compression, automixing (yes/no), priority (ducking), pan/balance, routing to REC, routing to out 1, and routing to out 2. The DMM6 includes 6 mic or line inputs, with DSP offering up to 60

channels of mixing by cascading up to 10 DMM6s and is designed for spoken word applications. The DMM12 offers 12 mic/line inputs, 120 channels via cascading and is more suited for large meetings and conferences. The DMM12 BC is similar to the DMM12, but adds one AES-EBU output, two additional stereo audio outputs and a 12-band graphic EQ on the 2 main outputs.

ITEM	DESCRIPTION	PRICE
DMM6	6 mic/line in automatic mixer	. 1666.00
DMM12	12 mic/line in automatic mixer	. 2249.00
DMM12BC	.12 mic/line in automatic mixer with AES-EBU out	2799.00



**AUDIO-TECHNICA SMARTMIXERS® AUTOMATIC MIXERS** These automatic mixers are ideal for meetings, seminars, teleconferencing, worship services, radio and TV broadcasting and AV applications. All switching is under microprocessor control with proprietary algorithms for instant, seamless operation. An individual priority pre-select switch for each balanced mic/line input channel allows choice of one-channel-at-a-time operation, all channels active, or any mix of moderator override. The last microphone on stays on so that ambient sound is never muted. Plus, SmartMixers can be linked to create a system for large multi-mic installations. The priority control system extends throughout the entire chain. The AT-MX381 is compatible with Crestron and AMX systems and includes a RS232 port for PC connection with included SmartMixer software.

ITEM	DESCRIPTION	PRICE
ATMX341B	4-channel auto mixer with 12V phantom	507.89
ATMX351A	4-channel, 1 aux input auto mixer with 48V phantom	691.43
ATMX381	8-channel auto mixer with 48V phantom	1392.34



AUDIO-TECHNICA AT-DMM828 SMARTMIXER® This digital automatic 8-channel matrix mixer is designed to provide automatic mixing functions for installed sound, house of worship, broadcast and conference applications. Engineered with an intuitive, easy-to-use software GUI, the AT-DMM828 automatically keeps the number of open microphones to a minimum, controlling background noise and feedback while providing increased clarity and audio quality. Its eight balanced inputs allow use with both mic- and line-level signals, whith each input providing +48V phantom power, individual gain and volume controls, adjustable gate and low-cut filter. It is equipped with eight balanced audio outputs to drive amplifications systems or other equipment. RS232 and USB data ports provide a connection point for a PC running the included SmartMixer software. Compatible with Crestron® and AMX® systems.

ITEM	DESCRIPTION	PRICE
AT-DMM828	Smartmixer, 8 channels	1799.00



behringer



BEHRINGER ULTRALINK PRO MX882 8-CH SPLITTER/MIXER 8-in/2- out line mixer / 2-in/8-out line splitter. Each channel can operate independently in mixer or splitter mode and is usable as 6-in/6-out level matching amplifier or direct inject box. It can act as a level converter (-10dBV and +4dBu) and has bandwidth of 5Hz-200kHz. I/O includes XLR balanced and 1/4" connections.

ITEM	DESCRIPTION	PRICE
MX882-ULTRALINK-PRO	.8-channel mixer/splitter	99.99



## BEHRINGER ULTRAZONE ZMX8210 8-CHANNEL 3-BUS MIC/LINE ZONE

MIXER Designed for fixed installations at restaurants, gyms, and offices the ZMX8210 distributes music and announcements up to three zones (8 inputs, max). Includes ducking capabilities and +48V phantom power. Features a master 4-band equalizer and high-quality mic preamps on all channels. Also features 6 low-noise mic/line inputs with gain control, -20dB pad, bus-assign switches, level/clip indicator, 2 selectable high-headroom stereo inputs (with mono/stereo switch), and more.

ITEM	DESCRIPTION	PRICE
ZMX8210-ULTRAZONE	.8-channel 3-zone mixer for music and paging	149.99



BEHRINGER RX1202FX MIC/LINE MIXER This versatile and multi-purpose 12-channel rackmount mixer has been designed as a submixer for your keyboard and drum setup, multi-track monitoring or as a line mixer in fixed audio/video installations. It features 8 IMP "Invisible" Mic Preamps with ultra-low noise and transparent audio quality. The mixer also features a 24-bit digital stereo FX processor with 100 presets, switchable +48V phantom power for condenser microphones and offers a 2-band EQ with clip LED for each channel. Other notable features are 4 high headroom line inputs, 2 aux sends per channel, 1 pre fader for monitor applications, and 1 post fader for internal FX or as an external send, and separate control room, phones, and stereo CD/tape outputs. Balanced main mix outputs are provided with XLR connectors.

ITEM	DESCRIPTION		PRICE
RX1202FX	12-channel mic/line mixer,	3RU	. 219.99



BEHRINGER RX1602 EURORACK This 16-input line mixer can be used as a flexible keyboard and multi-purpose submixer, multi-track monitoring mixer, level translator, FX return submixer, and more. Its ultra low-noise ULN design assures the highest possible headroom and ultra-transparent audio. It features dedicated balance and level controls plus +4/-10 level selection per channel, and monitor/FX send control on each section with global master send control for flexible monitoring, recording, or effects applications. Monitor/FX signals are assignable to phones output for added flexibility. An illuminated double-function "mute" button on each section with additional "clip" indication provides comfortable input source/level information. The unit's high-quality detented rotary controls and the rugged construction ensure long-term life and reliability under the most demanding conditions.

ITEM	DESCRIPTION	PRICE
RX1602-EURORACK	16-input line mixer	149.99



















































BY PEAVEY





















































### PEAVEY ARCHITECTURAL **AUTOMIX® CONTROL 8**

An automatic mixer with 8 transformer-balanced mic/ line inputs. Each channel provides a gain control, 48V phantom power, low-cut filter, activity/clipping LED, an aux send control and choice between manual or auto-

matic operation. Each channel also provides a defeatable insert point, 5 V TTL status output and can be muted individually or multiple channels can be muted simultaneously via an assignable mute bus. In addition, channels 1 and 2 provide an adjustable priority control. The master section provides a gain trim control, three 1/9-octave sweepable notch filters, a downward expander, transformer-balanced outputs (main and aux), and remote volume connections. Multiple units may be linked together to form a single mixer with many more inputs (16, 24, 32, etc).

· ·		•				-	
ITEM	DESCRIP	TION					PRICE
AUTOMIX-CONTROL8	8-channe	I autom	atic mi	c/line	mixe	er	802.10







Can control up to 5 rooms per controller. Dual processors supervise room combinations and levels in a highly flexible, yet compact controller. Mic and line inputs with level metering are provided for each room. Background music and paging inputs are provided. Other features include all electronic switching, solid-state level control and linkable controllers for larger systems or room configurations.

	DESCRIPTION	PRICE
RCX-5C	. System controller	1176.90
	. Volume control	
RCX-2	. Room control panel	249.35
RCX-J1	. XLR audio input panel	50.28
RCX-J3	. XLR/stereo RCA input panel	90.95
We handle all the	input and output modules for the RCX. Call for	complete details.

### **RADIO DESIGN LABS AUDIO MIXERS**

This series offers gold-plated RCA in/out jacks, plus headroom that accommodates high input level. Both models offer a dual-LED VU meter for each channel, 1 line input on MINI or RCA jacks, and unbalanced out on MINI (except for



EZ-MX4ML) or RCA jacks. EZ-MX4L offers 4 channels and 3 unbalanced line inputs on RCA jacks. EZ-MX4ML offers 2 mic and 2 line inputs. It also has 2 balanced mic ins on XLR and one unbalanced line in on RCA jacks. Mic inputs provide phantom voltage. The RUMX4T has 4 channels with expansion capability. It offers XLR mic ins, phono jack line ins, mic/line XLR out (switchable), unbalanced line out and direct in, switchable 24V phantom per mic input, and switchable compressor/limiter.

ITEM	DESCRIPTION	PRICE
EZ-MX4L	4-channel stereo line-level audio mixer	152.93
EZ-MX4ML	2-mic and 2-stereo line audio mixer	162.23
RUMX4T	4-channel mic/line mixer with phantom power, mic/line out	331.98

### **RADIO DESIGN LABS** ST-UMX3 3X1 UNIVERSAL **AUDIO MIXER**

This 3-channel unit combines mic- or line-level signals to a single mic/line output. Each input features a separate preamp circuit, isolating it from the other inputs. The output ampli-



fier includes a dual-LED VU meter. Flexible switching between mic and line signals allows installers to address a wide variety of mixing solutions with only one product. Power supply not included. Must use ST-MPA2 adapter if using phantom power.

ITEM	DESCRIPTION	PRICE
STUMX3	3x1 Universal Audio Mixer, requires PS24AS power supply	. 132.39
STMPA2	Phantom power adapter, requires PS24AS power supply	88.53
PS24AS	Power supply, 24Vdc, 500mA, 100-240 VAC	22.23

# **Solid State Logic**





SOLID STATE LOGIC SIGMA ANALOG SUMMING ENGINE Offering the ease of ITB mixing using the DAW of your choice, this 100% analog summing mixer provides 16 flexible channels, switchable between stereo and mono for up 32 channels at mixdown. MDAC control technology reads your DAW's automation to drive the SuperAnalogue mix engine feeding 2 stereo mix buses with individual stereo inserts for parallel compression or printing of post-processed stems. All channels offer direct outputs, and Mix Bus B can be injected into Mix Bus A; both Mix Bus inserts include an insert sum feature. Remote control can be accessed via standard MIDI hardware control surfaces, including MIDI learn for easy setup; dual-action front panel push/hold buttons or a footswitch can be assigned to switching functions as well. MIDI-over-Ethernet allows for control and connection to a cross-platform software interface, and the Sigma can also be remote controlled via an iOS device.

ITEM	DESCRIPTION	PRICE
SIGMA	. 16-channel DAW-automated analog summing mixer	4499.00





RANE CP66 COMMERCIAL PROCESSOR/MIXER This multiple-input processor with paging support is designed for use in multi-zone environments. With 6 Program inputs, 6 linkable Zone outputs, Page input, and support for the Rane PAGER2, DR1, and DR3 Digital Remotes, a multitude of system configurations are possible. It can be configured using its front panel controls, and easily set up by a technician in any location without a computer. Included Windows® software (connected through USB) provides the additional ability to save and load pre-configured settings for easy deployment, and also allows custom Zone and Group naming.

ITEM	DESCRIPTION	PRICE
CP66	Commercial processor	1099.00
	Level remote	
DR3	Source and level remote	319.00
PAGER2	Paging station	295.00



RANE SM26S LINE MIXER/SPLITTER A combo 6-in/2-out mixer and 2-in/6out splitter in one. Can be configured to perform mixing and splitting combos simultaneously. Features mix/pan and level controls with 12dB gain for each channel, and can also operate as a multi-effects mixer/splitter for a guitarist or as a distribution amp/line booster/zone level controller.

IIEM	DESCRIPTION	PRICE
SM26S	Line mixer/splitter	379.00
	•	

















RANE MLM SERIES MIC/LINE MIXERS The MLM42S and MLM82S are 1RU mixers ideal for mixing mics and stereo/mono line level inputs together. Inputs are split between mic/line switchable balanced XLR inputs and mono balanced XLR/ stereo 1/4" TRS inputs on each channel. Includes 15V phantom power, 3-band EQ per channel (MLM42S only), post-mix effects loop with wet/dry pan controls, and a choice of RCA unbalanced; XLR and TRS balanced parallel outputs, (balanced outputs are mic or line selectable). The MLM103 features 6 balanced mic ins with switchable +12V phantom power and 2 balanced stereo line level ins, both with 3-band EQ and mix level control. Mic preamps feature direct outs that can monitor the signal "pre" or "post" the mix level control via rear panel switches. A and B outputs can be used as a single-zone stereo pair or as 2 independent mono zones. Aux out is mono. Outputs are Euroblock connectors. Input overload indicators are found on all models. Both the MLM103 and MLM82S models feature internal universal power supplies (100-240 VAC).

ITEM	DESCRIPTION	PRICE
MLM42S	4x2 mic/line mixer, 1RU	399.00
MLM82S	8x2 mic/line mixer, 1 RU	439.00
MLM103	10x3 mic/line mixer, 3RU	839.00



RANE MLM65 MIC/LINE MIXER Features 6 mic/line XLR inputs with front panel pan and fader lever control, rear panel screw-driver gain trims, overload indicators, 12V phantom power, and mic/line switches. Also features selectable aux input with fader level control on the front panel, 5 RCA inputs on the rear panel with screw-driver gain trims. Aux 1 features a 1/8" TRS jack input as well as a USB charge port, aux 4 includes a phono/line switch and a phono ground lug for integrating turntables, and aux 6 is a USB audio port. 1/4" and 1/8" headphone jacks on front panel receive audio from the Cue button and feature rotary level control and dedicated meters with peak hold. The main front panel fader and peak hold meter only affects the main stereo XLR outputs. Digital audio outputs include S/PDIF, TOSLINK, and USB.

ITEM	DESCRIPTION	PRICE
MLM65	6-input mic/line mixer with USB, S/PDIF, TOSLINK outputs	999.00
THE RESERVE	The second secon	

RANE AM1 AND AM2 RACKMOUNT AUTOMIXERS Both models act as gain-sharing automatic mixers, a stand-alone mic mixer (AM2, or stand-alone mic/line mixer (AM1). The AM1 also can be used as a USB audio I/O device and a manual line mixer. The AM1's 4 XLR mic inputs and the AM2's 8 XLR mic inputs feature front panel level controls and a front panel mic mix level control, while the rear panel features 3-position switches for each input. Both also feature fixed 100Hz to 7kHz bandpass filters, 3 aux inputs (dual RCA, 1/8", USB), and signal and overload indicators on mic and aux inputs. Both units' XLR main output can be set to mic or line level to feed a mic snake or +20 dBu max balanced input. Using the RAD port, either unit can transport its main mix to a CobraNet network via a Rane Mongoose. Up to seven AM2 units can be cascaded into an AM1 unit, creating a total of 60 gain-shared mic inputs.

ITEM	DESCRIPTION	PRICE
AM1	. 4-channel automixer with USB audio I/O	. 899.00
AM2	. 8-channel automixer	. 999.00
MONGOOSE	. Remote audio CobraNet interface	1399.00
The same of the same	Security and Security	



RANE CP64S COMMERCIAL PROCESSOR/ZONE MIXER A single space rackmount mixer/processor with 4 line inputs and 4 level priority assignable to 2 zone outputs with 7-band EO 2 independently assignable mic/line page inputs with defeatable ducking. Has remote controls available for page assign (PR 2) and source/volume (ZR 1), RCA line inputs. I/O also includes euroblock page inputs, remote, and zone outputs.

ITEM	DESCRIPTION	PRICE
CP64S	Zone mixer	759.00
CP52S	Single-zone version	519.00





ROLLS RM69 MIX MATE 3 A 6-channel 1RU audio mixer. There are (2) microphone inputs with phantom power, (4) stereo RCA line-level inputs, and (1) 1/8 stereo line input shared with RCA input 4. Outputs include 2 XLR, stereo RCA, and 1/8" headphone jack.

DESCRIPTION

DESCRIPTION

RM69	Rackmount mixer, 6-channel	138.60
HORLS (0)	0.0.0000000	
ROUS C	E AA 00,0000	

ROLLS RM67 MIXMAX-7 Used in restaurants, schools, and industrial applications. Features 3 XLR mic inputs with phantom power and 3 stereo RCA line inputs. The outputs are RCA and 1/4".

RM67	Mic/line mixer	211.68
ROUS .	0 0 0 0 0	999999.E
The same of the last	Rus	

ROLLS RM68 3-MIC/3-LINE ZONE WOLF RACK MOUNT MIXER Can mix up to three mics with three stereo sources and send them in any combination to 2 separate zones. Works great as a HiFi preamp. Features 3 XLR phantom powered inputs, 6 RCA, bass and treble controls, 1/4" TRS outputs, and has 106dB S/N ratio with +17dB output gain.

ITEM	DESCRIPTION	PRICE
RM68	. Mic/line mixer	291.06



ROLLS RM219 STEREO LINE MIXER Aline-level mixer with 9 channels of stereo 1/4" inputs, a single XLR mic input, a tape input and output provided via stereo RCA jacks and a mono auxiliary send and stereo returns. Each channel has a signal level control, a right/left balance control, an auxiliary level control and a clip LED indicator. The master section has a tape input level control, an auxiliary return level control, and a master output volume control. Also has a headphone output with level control provided by the master level controls.

ITEM RM219	DESCRIPTION Stereo line mixer	PRICE 245.70
pours 10 1 40		act ar



ROLLS RM82 8-MIC MONO MIXMAX RACKMOUNT MIXER The RM82 mixes 8 XLR mic (with 12V phantom power) or 1/4" unbalanced inputs to a single, balanced 1/4" TRS output. There is also a passive tone control for each channel. Perfect for board rooms, small clubs, schools or churches, the unit is compact yet easy to operate. Each 1/4" input may be internally jumpered—converting it into a Direct Output.

ITEM	DESCRIPTION	PRICE
RM82	Mic/line mixer	226.80

# **Certified Repair by Experienced Technicians**

Full Compass is a factory-authorized repair center for many of the major brands we carry.











PRICE





































































































SCM262

MAN DEL	STEREO	MIX STEREO RIFUTS	MICHPUTS
- 65	est y their	0.0.0	
600	00	0.0.0	000
COS. 120 No. SANSON MINA		······ 🔞 💳 🔞	·

SCM268



SHURE SCM262/SCM268 MIXERS The SCM262 has 2 XLR mic inputs, 3 stereo unbalanced aux inputs (RCA), defeatable ducking, jukebox mute and 12V phantom power. Other key features include bass and treble controls on the master output, 1 unbalanced stereo aux level output (RCA) and 1 balanced stereo mic/ line output (1/4" TRS). loops. The SCM268 has 4 transformer-balanced XLR mic level inputs, 1 transformer-balanced XLR mic/line output and 1 internal toroidal power transformer making this mixer perfect for many types of applications. Other key features include 5 unbalanced aux level inputs (RCA), an LED peak output meter, 12V phantom power, built-in low-cut filters on mic inputs and 1 unbalanced aux level output.

ITEM	DESCRIPTION	PRICE
SCM262	Stereo mixer	247.54
SCM268	Mixer	262.08

Little principles extension principles and a second second	7111000

SHURE SCM410, SCM800 AND SCM820 MIXERS The SCM410 is a 4-channel auto-mixer in a half-rack chassis with 4 mic level XLR ins. 1 balanced XLR mic/line out and 1 balanced RCA aux out. The SCM800 is an 8-channel manual mixer with 8 mic ins on terminal block connections, send/receive 1/4" per channel, 48V phantom power per channel, terminal block line out, 2 aux ins that feed one channel, headphone out, and more. The SCM820 is an 8-channel digital auto mixer with enhanced I/O connectivity options. It features per-channel direct outs, mix A and B outs, individual channel control, and more. The standard version SCM820 has phoenix type connectors for inputs and outputs and RJ45 for networking. Please call for a full listing of connection options.

ITEM	DESCRIPTION	PRICE
SCM410	. 4-channel auto mixer	728.83
SCM800	. 8-channel manual mixer	655.20
SCM820	. 8-channel IntelliMix® digital automatic mixer	1999.00
RKC800	. Rackmount XLR connector panel for the SCM800	218.03



WHIRLWIND MIX-5S 4-INPUT STEREO MIXER This all-purpose rackmount mixer for sound contracting offers 4 input channels, each with XLR and 1/4" TRS balanced connectors, suitable for mic or line level use. The LED readout provides a visual indication of levels, and phantom power is provided for operating condenser microphones. XLR and 1/4" TRS outputs are provided, with switchable mic or line level XLR output. The outputs have their own drive-circuit for isolation. An aux channel is provided with RCA input jacks for connecting a tuner, CD player, tape player, etc.

ITEM	DESCRIPTION	PRICE
MIX-5S	4-input rackmount stereo mixer	353.79

Follow Us!





LECTROSONICS DM SERIES DIGITAL MATRIX PROCESSORS The DM Series provides digital audio processing, mixing and routing for sound reinforcement and conferencing with multiple microphones and loudspeaker configurations. They have auto mic mixing with proportional gain and AutoSkew<sup>™</sup> at the matrix crosspoints. They feature 6 filter stages plus compressor, ADFE and delay on each input, 9 filter stages plus compressor, limiter and delay on each output, 128 global macros available with up to 64 commands per macro. The USB and RS232 interface is for setup and control, and uses LecNet2 or AMX<sup>©</sup> and CRESTRON<sup>™</sup> control systems. The 3 available models are the same except for the number of inputs and outputs. They can be stacked in a master/ slave configuration to expand the number of inputs for any size system.

ITEM	DESCRIPTION	PRICE
DM812	Digital matrix audio processors, 8-in/12-out	CALL
DM1612F	Digital matrix audio processors, 16-in/12-out	CALL
DM1624F	Digital matrix audio processors, 16-in/24-out	CALL





## STUDIO TECHNOLOGIES 742 AUDIO MIXER

TECHNOLOGIES Expressly designed for use in electronic-newsgathering (ENG) vehicles and small production

truck applications. Offers a flexible monitor section, setup oscillator with dedicated output, all operator controls on the front panel, single rack-space mounting and internal power supply. It also provides 4 mic/line and 4 line-only inputs, 2 compressors and two 10-segment LED meters.

ITEM	DESCRIPTION	PRICE
MODEL-742A	4 mic/line. 4 line-only ins	1088.87

## Symetrix



SYMETRIX ZONE MIX 761 ZONE PAGING MIXER A complete zone mixing, paging, and music management solution designed to save integrators time and money. Perfect for restaurants, hospitality establishments, nightclubs and more. A Graphic User Interface provides a familiar hardware-like layout allowing for a low learning curve and quick use. From elegant remote controls to a simple 3rd party control protocol, the Zone Mix 761 is all about integration. Includes (8) mono-summed stereo inputs on RCA, (4) balanced mic/line ins on terminal blocks, and (6) outs on terminal blocks.

ITEM	DESCRIPTION	PRICE
761	12-in/6-out zone mixer.	1349.00



Ask us about our 2- and 3-year extended warranties!





