

- AUDIO
- VIDEO
- COMPUTER AV
- MUSIC
- ACCESSORIES
- LIGHTS



**ATLAS SOUND AP-15 OMNI-PURPOSE PAGING HORN**

The 8Ω Model AP-15 and transformer-equipped Model AP-15T are double re-entrant loudspeakers which deliver 15W of continuous power handling, superior intelligibility and unparalleled efficiency. The speakers operate within a nominal frequency response range of 400Hz-14kHz and offer a sensitivity of 120dB at rated power to provide clear voice and signal communication. The transformer-equipped version includes a versatile, 3-way, 25V/70.7V/100V line transformer to meet a variety of distributed system needs. The transformer is easily adjustable using the exclusive Vari-Tap® Connect Center which features a 7-position, watts/impedance selection switch.



ITEM	DESCRIPTION	PRICE
AP-15	Paging horn, 8Ω, 15W, 70° dispersion, grey.....	80.50
AP-15T	As AP15, with 25V/70.7V/100V transformer, with 5 tap settings, grey.....	97.50
AP-15TC	As AP15T, beige.....	100.50

**ATLAS SOUND APX CD HORNS** The APX constant-directivity speaker brings “pro-audio” control technology to the indoor/outdoor commercial sound market. Now you can point and direct sound where you want it with excellent clarity in the target zone. APX models achieve consistent beamwidth control in both horizontal and vertical directions over a wide frequency range. Available in a 40W version, this model is equipped with 25V/70.7V/100V internal transformers. Mounts to 1-gang, 2-gang, or 4-inch sq. E.O. box.



ITEM	DESCRIPTION	PRICE
APX40TN	40W CD horn.....	103.50

**ATLAS SOUND AP-30 SERIES HORN LOUDSPEAKERS** The 8ohm Model AP-30 and transformer-equipped Model AP-30T are double re-entrant loudspeakers which deliver 30W of continuous power handling, superior intelligibility and unparalleled audio conversion-efficiency. The AP-30 Series operates within a nominal frequency range of 300Hz-12kHz and offers a sensitivity of 126dB at rated power to provide clear voice and signal communication. The AP-30T features an integral transformer to meet a variety of distributed system needs. It is equipped with a versatile, 3-way, 25V/70.7V/100V line transformer. Transformers are adjustable using Atlas Sound’s exclusive Vari-Tap® Connect Center which features a 7-position, watts/impedance selection switch. The labor saving Vari-Tap terminal is screwdriver adjustable and includes a protective cover with built-in strain relief.



ITEM	DESCRIPTION	PRICE
AP-30	8Ω, 30W horn loudspeaker.....	111.50
AP-30T	As above, with 25V/70.7V/100V line transformer.....	127.50



**EV COBRA-IIB**

The Cobraflex IIB has a slightly smaller size and coverage pattern than the Cobraflex III. Driver must be ordered separately. Recommended drivers: ID30C-8, ID30C-16, ID30CT, ID60C-8, and ID60CT. 80° x 60° beamwidth. 9.3" x 18.5" x 10.3" (HWD).



ITEM	PRICE
COBRA-IIB	156.00

**EV COMPRESSION DRIVERS**

Ideal for Cobraflex and other EV/University horns, available in 8Ω or with built-in 70V transformer.



ITEM	DESCRIPTION	PRICE
ID30C8	30W 8Ω.....	144.00
ID30CT	30W 25V/70V.....	168.00
ID30C16	30W 16Ω.....	144.00
ID60DT	60W 25V/70V.....	306.00

**EV PA430 CONSTANT DIRECTIVITY PAGING HORN** The world’s only constant directivity paging projector the PA430 provides predictable performance and offers a unique patented omnidirectional swivel-mount system. The PA430 solves many of the problems encountered by designers of distributed paging systems. The PA430T version has an input transformer to match 25V, 70.7V, or 100V lines.



ITEM	DESCRIPTION	PRICE
PA430	Paging horn.....	131.00
PA430T	70V paging horn.....	161.00



**JBL CSS PAGING HORNS**

Excellent vocal clarity for public address systems, announcement/paging, intercom, security, alarm and industrial applications. Sturdy ABS construction with corrosion-resistant stainless steel hardware. Both models include an onboard UL-registered multi-tap transformer for use with 70V and 100V distributed speaker lines. A bypass position allows for 8Ω ohm operation.



ITEM	DESCRIPTION	PRICE
CSS-H15	15W paging horn.....	76.00
CSS-H30	30W paging horn.....	104.00



**TOA CS SERIES WIDE-RANGE PAGING HORNS**

Ideal for indoor and outdoor commercial sound system applications, voice paging, background music and tone signaling distribution. Compared to traditional metal paging horns, CS Series speakers offer a wider frequency range and superior sound quality. Each includes a built-in 70.7V/100 V transformer with screwdriver-adjustable power taps. All CS models are fully weather-resistant to withstand demanding environments with a sealed enclosure, full-range moisture-resistant cone speaker, stainless steel mounting hardware and a protective mesh grille. The enclosure is also coated with polyurethane resin paint to resist the fading effects of prolonged exposure to ultraviolet light. Speakers have a 5-year warranty.



ITEM	DESCRIPTION	PRICE
CS64	6W horn, 130Hz-13kHz, 96dB max SPL.....	CALL
CS64/U	UL listed version of CS64.....	CALL
CS154	15W horn, 150Hz-15kHz, 97dB max SPL.....	CALL
CS154/U	UL listed version of CS154.....	CALL
CS304	30W horn, 120Hz-15kHz, 98dB max SPL.....	CALL
CS304U	UL listed version of CS304.....	CALL



**TOA SC SERIES PAGING HORN SPEAKERS**

These provide intelligible voice paging and tone signaling for indoor and outdoor sound system applications. SC Series models are available with a choice of power ratings from 10W to 50W, are easy to install in wall, pole or ceiling-mount applications and include corrosion-resistant stainless-steel mounting hardware. They are designed for intercom talkback applications requiring dual operation as both a microphone and speaker. Each model is a double re-entrant horn with compression driver for high sensitivity and a lightweight aluminum enclosure. They are fully weather-resistant for reliable operation in demanding environments and the loudspeaker diaphragm is heat and moisture-resistant. The SC Series are also IP-65 standards compliant for dust and moisture-resistance with a wide operating temperature range from -4°F to 130°F. Includes a 5-year warranty.

ITEM	DESCRIPTION	PRICE
SC610	10W horn, 315Hz-12.5kHz, 110dB max SPL.....	CALL
SC610T	SC610 with 25V/70.7V transformer.....	CALL
SC615	15W horn, 280Hz-12.5kHz, 112dB max SPL.....	CALL
SC615T	SC615 with 25V/70.7V transformer.....	CALL
SC630	30W horn, 250Hz-10kHz, 113 dB max SPL.....	CALL
SC630T	SC630 with 25V/70.7V transformer.....	CALL
SC651	50W horn, 250Hz-6kHz, 108dB max SPL.....	CALL



Follow Us!

We service many of the major brands that we carry. Call our Authorized Repair Department at 800-356-5844 x1354.