



Tripp Lite
1111 West 35th Street
Chicago, IL 60609 USA
Telephone: +(773) 869 1234
E-mail: saleshelp@tripplite.com

Model #: SU6000RT3UHV

SmartOnline Expandable Rack / Tower UPS System - Online, double-conversion protection for mission critical applications

Highlights



- 6000VA online 6U rack / tower UPS (3U Power Module + 3U Battery Pack)
- Enhanced serial communications ports, SNMP/Web card slot and EPO jack
- Maintains 200, 208, 220, 230 or 240V output +/-2% during brownouts to 156 and overvoltages to 276V
- Fault tolerant manual and auto bypass modes
- Expandable runtime with optional BP240V10RT3U battery packs
- \$250,000 [Ultimate Lifetime Insurance](#) (USA, Puerto Rico & Canada only)

Description

Tripp Lite 6kVA Smart Online RM UPS - 6000VA. The Smart Online SU6000RT3UHV double-conversion UPS protects server, networking or telecommunications equipment from blackouts, voltage fluctuations and surges in a compact tower/rackmount housing. In a rack configuration, the power module and battery pack occupy only 3 rack spaces each (6U total). Upright tower placement of entire system supported with included tower stands. Large capacity 6000VA/4200 watt power module double-conversion technology converts raw input AC to DC, then resynthesizes it back to perfect sine wave AC output within 2% of user-selectable 200/208/220/230/240V AC output voltages. Frequency regulation locks output power to 50/60Hz (+/-0.2 Hz), removing harmonic distortion, fast electrical impulses and other hard-to-solve power problems not addressed by other UPS types. Perfectly regulated, continuous sine wave output with zero transfer time offers guaranteed uptime and compatibility with all equipment types. Hardwire input and output connections support a variety of permanent or PDU style power connections. Battery support can be extended through the addition of external battery packs (part# BP240V10RT3U). Includes slot for internal SNMP/WEB card, plus DB9 contact-closure, and DB9 enhanced serial monitoring ports for unattended shutdown, remote control and monitoring of UPS system and power data.

Applications

Ideal for protection of critical 200/208/220/230/240v equipment in server rooms, internetworking closets and telecommunications systems in rackmount or tower applications. Common applications include corporate or departmental servers, workstations, hubs, routers, bridges, CAD/CAM workstations, concentrators, IP telephony and traditional PBX switching systems.

Package Includes

- SU6000RT3UHV system includes 1 3U power module and 1 3U battery pack
- PowerAlert UPS management software and complete cabling
- Mounting hardware to support each 3U module in 4 post rack enclosures/tower stands
- Warranty information
- Instruction manual

Features

- True on-line, double conversion UPS provides pure, sine wave AC output at all times
- World-wide compatibility with Euro 50Hz and High Voltage North American 60Hz power
- Maintains continuous operation through blackouts, voltage fluctuations and surges with zero transfer time

Removes harmonic distortion, electrical impulses, frequency variations and other hard to solve power problems
 6000VA/4200 watt power capacity with hardwire input/output connections
 Accepts input voltages between 156 and 276, regulating output within 2% of selectable 200/208/220/230/240v AC output
 Standard included 3U battery pack provides 20 minutes runtime at half load (3000VA) and 8 minutes at full load (6000VA)
 Expandable runtime with multiple external battery packs (part# BP240V10RT3U)
 Innovative design makes unit adaptable for rackmount, tower, or stacking applications
 Power module and battery pack require only 3 rack spaces each (6U total rack space usage)
 DB9 serial port for network interface; SNMP compatible
 Slot for optional SNMP/web card (part# SNMPWEBCARD)
 PowerAlert unattended shutdown software and 6 ft. network cable included
 Fault tolerant auto-bypass maintains continuous utility output to connected equipment, even in cases where the UPS is overloaded or suffers an internal failure that requires service
 Diagnostic LEDs
 Mounting hardware included with each 3U module for 4 post rackmount installation, 2 post telecom rack compatible with separate purchase
 2POSTRMKITWM (2 required)
 Includes RJ11 EPO (emergency power off) port and interconnection cable
 \$250,000 Ultimate Lifetime [connected equipment insurance](#) (USA , Puerto Rico, & Canada Only)
 2 year manufacturers product warranty

Specifications

SYSTEM OVERVIEW	
Voltage compatibility	208V AC (200/208/220/230/240V)
Frequency compatibility	50/60Hz
OUTPUT	
Output VA	6000
Output watts	4200
Output nominal voltage	208V AC (200/208/220/230/240V)
Output voltage regulation	Maintains pure sine wave output at all times, regulated within 2% of selected nominal output voltage, less than 5% total harmonic distortion
Output frequency regulation	Regulates line frequency to 50/60Hz +/- 0.05Hz
Outlet quantity / type	Hardwire
Overload protection	Resettable 40A circuit breaker
INPUT	
Maximum input amps	30A / 4700 watts max.
Input connection type	Hardwire
Recommended electrical service	30A 208V
BATTERY	
Full load runtime	Included batteries = 8 min (6000VA)
Half load runtime	Included batteries = 20 min (3000VA)
Expandable battery runtime	Supports extended runtime with optional external battery pack BP240V10RT3U (multi-pack compatible)
DC system voltage	240 VDC
Typical battery lifespan	3-6 years, depending on usage

Battery recharge rate	Less than 8 hours to 90% (included battery set only)
VOLTAGE REGULATION	
Voltage regulation description	On-line, double-conversion process give this UPS the ability to maintain output voltage within +/-2% of selected nominal voltage at all times
Overvoltage correction	Maintains continuous operation without using battery power during overvoltages to 276VAC, regulating output within 2% of selected nominal
Brownout correction	Maintains continuous operation without using battery power during brownout / undervoltage conditions to 156VAC, regulating output within 2% of selected nominal
LEDS ALARMS & SWITCHES	
Front panel LEDs	6 LED DISPLAY: line power, bypass, inverter, charger, output AC and battery operation. SELECTABLE LCD DISPLAY: input/output voltage, Hz, battery voltage and charge level and detailed warnings regarding all major UPS functions. LED/LCD display panel easily rotates for viewing in rackmount or tower configurations.
Alarms	Multi-function audible alarm offers notification of UPS start, backup operation, low battery, overload, UPS fault, inverter fault, DC bus fault, overtemperature, remote shutdown, shutdown imminent and shutdown complete
Switches	Includes main power off/on switch, plus 2 switches to set and execute scrollable LCD functions
SURGE / NOISE SUPPRESSION	
AC suppression response time	Instantaneous
EMI / RFI AC noise suppression	Yes
PHYSICAL	
Shipping weight (lbs)	323
Shipping weight (kg)	145.4
Unit weight (lbs)	Power Module 43.8 lbs., Battery Pack: 139 lbs.
Unit weight (kg)	Power Module: 19.7 kg, Battery Pack: 61kg
Unit Dimensions (HWD/in)	Power Module 5.25 x 17.5 x 26, Battery Pack 5.25 x 17.5 x 25
Unit Dimensions (HWD/cm)	Power Module 13.3 x 44.5 x 66, Battery Pack 13.3 x 44.5 x 63.5
Material of construction	Steel
Form factors supported	Rack (6U)
Cooling method	Built-in cooling fan
Battery Access	User replaceable, hot swappable external battery pack
ENVIRONMENTAL	
Operating Temperature	+32 to +104 degrees Fahrenheit / 0 to +40 degrees Celsius
Storage Temperature	+5 to +122 degrees Fahrenheit / -15 to +50 degrees Celsius
Relative Humidity	0 to 95%, non-condensing
Line mode BTU/hr. (Max.)	1418
COMMUNICATIONS	
Network monitoring port	Includes 2 built-in DB9 monitoring ports (1-RS232 / 1-contact closure)
Software and cabling included	Includes PowerAlert UPS monitoring software for all common network and standalone operating systems. Cabling included.
SNMP compatibility	Built-in accessory slot accommodates internal SNMP / Web card and other network accessories

LINE / BATTERY TRANSFER	
Transfer time from line power to battery mode	ZERO - online UPS continuously converts incoming AC to DC, then back to AC. When line power is interrupted, UPS maintains continuous output from battery reserves with absolutely no disruption in output AC power.
Low voltage transfer to battery power	Maintains continuous operation during undervoltages as low as 156VAC. Below this point, output is maintained utilizing battery reserves.
High voltage transfer to battery power	Maintains continuous operation during overvoltages to 276VAC. Above this point, output is maintained utilizing battery reserves.
CERTIFICATIONS	
Certifications	Tested to UL1778 (USA), cUL (Canada), CE (Europe), Class A (emissions), NOM (Mexico), GOST, IRAM, SASO
WARRANTY	
Product warranty	2 year product warranty
Connected equipment insurance (USA and Canada Only)	\$250,000 connected equipment insurance (USA , Puerto Rico, and Canada only)
Optional coverage	3 year, 5 year, next day and on-site warranty coverage available for select opportunities - contact Tripp Lite
SPECIAL FEATURES	
EPO port	Includes dedicated EPO (emergency power off) interface and cabling
Cold Start	Yes, inverter can be "cold started" to enable temporary AC output during a power failure
Appearance	Attractive black steel rackmount housing
BATTERY PACK ACCESSORY (optional)	
Battery Pack Accessory (optional)	BP240V10RT3U (optional)

More information, including related products, owner's manuals, and additional technical specifications, can be found online at www.tripplite.com/products/model.cfm?txtModelID=1972.