

speco technologies®

## Intensifier™ Series Dome Cameras



**HTINTD8** (2.8-12mm lens)  
**HTINTD9** (5-50mm lens)  
**HTINTD10** (9-22mm lens)

### Features

#### *See In The Dark Without IR LEDs*

- Weatherproof operation, IP-67
- Tamper resistant
- Amplify existing light with no distance limitations
- No problems caused by objects that reflect or absorb IR light sources
- 560 lines of resolution
- Min. illumination 0.002 lux (Intensifier™ @ 256x)
- Dual voltage 12V DC & 24V AC operation
- Full OSD operation
- External controls for zoom and focus
- SLC - Speco Light Compensation
- S/N Ratio more than 50dB (weight on)
- EZ mount system simplifies installation
- Wall & ceiling mountable

### Specifications

Image Pick-Up Device	1/3" Sony Super-HAD™ CCD - 410K
Resolution	560 TV lines
Minimum Illumination	.0002 lux - (Intensifier™ @ 256x)
S/N Ratio	More than 50dB (weight on)
White Balance	ATW/AWC/MANUAL (1800K - 10,500K)
Video Output	Composite video 1.0 Vp-p into 75 Ohm + test connection
Electronic Shutter	Auto/Manual (1/60 - 1/120,000 seconds)
OSD	Built-in - controlled by internal buttons
SLC (Speco Light Compensation)	Low, middle, High, Off, Selectable
Auto Gain	Low, middle, High, Off, Selectable
Reduce Noise	Low, middle, High, Off, Selectable
Day & Night (Color)	On / Auto Selectable
Sharpness	On / Off (Level Adjustable)
Privacy	On / Off (4 Programmable Zones)
Power Supply	24 Volts AC, 12 Volts DC - Dual Voltage
Power Consumption	350mA
Lens	DC Auto Iris Varifocal Lens (2.8-12mm, 5-50mm or 9-22mm)
Total Pixels	811(H) x 508(V)
Effective Pixels	768(H) x 494(V)
Scanning Frequency	15.734kHz(H) / 59.94Hz(V)
Scanning System	2:1 Interlace
Synchronization	Internal / Line lock in 24V AC
Operating Temperature	-14°F to 122°F - RH 95% Max.
Storage Temperature	-40°F to 140°F - RH 95% Max.
TV System	NTSC
Dimensions	5.5" W x 4.4" H x 5.5" D
Weight	3 lbs.

Specifications subject to change

For more information contact us at:

Speco Technologies 200 New Highway, Amityville, NY 11701 Web: [www.specotech.com](http://www.specotech.com)  
 Toll Free: 1-800-645-5516 In Metro NY: 631-957-8700 Fax: 631-957-9142 or 631-957-3880