

Speco Technologies' high-end, **Ciela Surround™ Sound Series** offers harmonized engineering where each speaker in the system was developed to provide the ultimate listening experience.

Our in-ceiling (SP-6CLC/SP-8CLC) and in-wall (SP-6CLW/SP-8CLW) speakers feature pivoting titanium dome tweeters that focus the high frequencies to your customized listening area. The injection-designed woofers with rubber surround deliver powerful, rich low frequency responses with minimal distortion.

The **Ciela Surround™ Sound Series'** dual voice coil, in-wall subwoofer (SP-8CLSW) offers a deep, rich bass experience without sacrificing floor space in your home theater environment. The in-wall center channel speaker (SP-5CLCC) offers an ultra-wide, horizontal sound dispersion that brings pre-recorded dialog to the forefront.

The **Ciela Surround™ Sound Series** with its sonic performance and flat frequency response curves will offer crystal clear sound and reliable home theater enjoyment for years to come.



Injection-cone woofers with rubber surround - Provides the exact combination of durability and flexibility to create precision sound waves.



Titanium dome pivoting tweeters - Premium high frequency component tweeters that can be focused to desired listening area.



18 dB sophisticated crossover networks - Efficiently and accurately separates frequencies for true fidelity sound.



Individual decibel settings for woofer and tweeter on satellite speakers - Allows listener to cater the speakers to their listening preferences for maximum enjoyment.



Beautiful silver and black design with decorative outer rims - Adds beauty and aesthetics to your home theater environment.

## Features

Crystal clear and powerful sound reproduction

Ample RMS power ratings

Wide frequency responses

High-power, dual-woofer, shielded center channel speaker

High-power, passive, dual voice coil subwoofer

Recessed in-wall mounting

Easy Mount Tabs

## Benefits

Definition and clarity to enhance the listener's entertainment enjoyment.

Handles high-wattage home theater channel requirements.

Provides clear, uncompromised high and low ends of the sound spectrum.

Provides an ultra-wide horizontal sound dispersion that brings pre-recorded dialog to the forefront. Provides protection for magnetic television screens.

Offers deep and rich low frequencies to feel the bass experience.

Small footprint and stealth appearance without sacrificing floor space.

For ease of installation.



Feature: Matched, flat frequency response curves.

Benefit: Harmonized engineering resulting in true fidelity speakers that work in unison without distortion.

speco technologies  
simply unique.

**CIELA**<sup>™</sup>  
S U R R O U N D



Sold in pairs  
SP-6CLW



Sold in pairs  
SP-8CLW



Sold  
individually  
SP-8CLSW

#### 6.5" IN-WALL SPEAKER SYSTEM

- 6.5" Injection-Cone with Rubber Surround
- Titanium Dome Pivoting Tweeter
- 60 Watts RMS/ 100 Watts Max
- Frequency Response: 60Hz-20kHz
- 12 oz. Magnet
- 8 Ohms
- 8 3/4" W x 12 1/4" H x 3 1/2" D
- Mounting Dimensions: 7 1/2" L x 11" H
- 3dB Switches for Woofer & Tweeter
- EZ mount tabs for ease of installation
- Mounting Bracket BRW-6

#### 8" IN-WALL SPEAKER SYSTEM

- 8" Injection-Cone with Rubber Surround
- Titanium Dome Pivoting Tweeter
- 80 Watts RMS/ 120 Watts Max
- Frequency Response: 50Hz-20kHz
- 12 oz. Magnet
- 8 Ohms
- 10 1/4" W x 14 1/4" H x 4" D
- Mounting Dimensions: 9" L x 13" H
- 3dB Switches for Woofer & Tweeter
- EZ mount tabs for ease of installation
- Mounting Bracket BRW-8L

#### 8" IN-WALL SUBWOOFER

- 8" Polypropylene Woofer with Rubber Surround
- 100 Watts RMS/ 160 Watts Max
- Frequency Response: 40Hz-140Hz
- 20 oz. Magnet
- 10 1/8" W x 10 1/8" H x 4 1/4" D
- Mounting Dimensions: 8 3/4" L x 8 3/4" H
- 8 Ohms
- Dual Voice Coil
- EZ mount tabs for ease of installation
- Mounting Bracket BRW-8SW



Sound Without Limits.



Sold in pairs  
SP-6CLC



Sold in pairs  
SP-8CLC



Sold individually  
SP-5CLCC

#### 6.5" IN-CEILING SPEAKER SYSTEM

- 6.5" Injection-Cone with Rubber Surround
- Titanium Dome Pivoting Tweeter
- 60 Watts RMS/ 100 Watts Max
- Frequency Response: 60Hz-20kHz
- 12 oz. Magnet
- 8 Ohms
- 9" Diameter x 4" D
- Mounting Dimension: 8 3/8" Diameter
- EZ mount tabs for ease of installation
- Mounting Bracket BRC-6F

#### 8" IN-CEILING SPEAKER SYSTEM

- 8" Injection-Cone with Rubber Surround
- Titanium Dome Pivoting Tweeter
- 80 Watts RMS/ 120 Watts Max
- Frequency Response: 50Hz-20kHz
- 12 oz. Magnet
- 8 Ohms
- 11" Diameter x 5 3/4" D
- Mounting Dimension: 10" Diameter
- EZ mount tabs for ease of installation
- Mounting Bracket BRC-8L

#### CENTER CHANNEL SPEAKER

- 5.25" Injection-Cones with Rubber Surrounds
- Titanium Dome Tweeter
- 80 Watts RMS/ 140 Watts Max
- Frequency Response: 65Hz-20kHz
- 8 oz. Shielded Magnets
- 8 Ohms
- 17 1/2" W x 8 3/4" H x 3 3/4" D
- Mounting Dimensions: 16 1/2" L x 7 1/2" H



Sound Without Limits.

For more information contact us at: Toll Free: 1-800-645-5516

In Metro NY: 631-957-8700 Fax: 631-957-9142 or 631-957-3880 [www.specotech.com](http://www.specotech.com)

