

speco technologies®

Color Video Security Intercom System



VDP-M6S (Monitor)



VDP-C6F (Camera)



VDP-C6S
(Surface Mount Camera
also available)

VDP-6000

Our two-way color video security intercom system has a flat 4" color screen. It offers a two way manual switcher, a 165 foot maximum wiring distance and can be used with an optional door release. The manual switcher allows the system to be expandable up to 2 monitors and 2 cameras. The system comes with an indoor/outdoor flush mount camera.

Specifications

	VDP-M6S (Monitor)	VDP-C6F (Camera) VDP-C6S (Surface Mount Camera)
Angle of Picture	N/A	Horizontal: 110° - Vertical 92°
Call Signal Device	Door chime	N/A
Communication System	Duplex handset	Duplex hands free conversation
Connection	Screw terminals	Screw terminals
Dimensions	8-1/4"(H) x 7-1/2"(W) x 2-1/3"(D)	7-1/4"(H) x 4-3/4"(W) x 3/4"(D) VDP-C6S: 4.25"(H) x 3.5"(W) x 1.6"(D)
Housing	White plastic	Pewter gray metal
Illumination	N/A	Infrared LED's
Lens	N/A	2.9mm
Max Wiring Distance	165' (22AWG wire)	165' (22AWG wire)
Minimum Illumination	N/A	0.1 lux on object up to 19 feet
Monitor	4" Flat color CRT	N/A
Operating Temp	14°F to 104°F	-4°F to 122°F
Output Impedance	N/A	Video 300 ohm - Audio 600 ohm
Power Consumption	Max 24VA standby 2VA	Max 3 watts
Power Source	12V regulated DC, (power supply included)	Power supplied from monitor
Scanning Frequency	Horizontal: 15.75 KHz, Vertical: 60Hz	Horizontal: 15.75 KHz, Vertical: 60Hz
Weight	2.86 lbs.	1.1 lbs.
Wiring	4 Wires, 22 gauge minimum	4 Wires, 22 gauge minimum

Note: VDP-6000 is not compatible with VDP-5000 (B/W) or components

Options:

VDP-M6F Extra Surface Mount Monitor
VDP-C6F Extra Flush Mount Camera

Extra VDP-C6S Extra Surface Mount Camera

Specifications subject to change

For more information contact us at:

Speco Technologies 200 New Highway, Amityville, NY 11701 Web: www.specotech.com
Toll Free: 1-800-645-5516 In Metro NY: 631-957-8700 Fax: 631-957-9142 or 631-957-3880

VDP-6000