

speco technologies®

Wide Dynamic Range Color Vandalproof, Weatherproof Dome Camera with IR LEDs



WDR650S (silver housing)

WDR650W (white housing)

Features

- Wide Dynamic Range For Tough Back-Lit Situations
- 540 Lines Resolution
- Full OSD Control for Easy Set-Up
- 65' range in total darkness with 22pcs of IR LEDs
- Minimum Illumination to 0.005 in DSS Mode
- Tamperproof Construction
- IP67 rated for extreme weather applications
- Side Control Board for Easy Function Adjustments
- Automatic Gain Control
- Back Light Compensation
- Dual Voltage Operation
- Video Test Output Cable Included
- Available in White & Silver Housings
- Available Accessories:
 - 650WMT - Wall Mount
 - 650CMT - Ceiling Mount
 - 650JBMT - Junction Box
 - 650CP - Corner/Pole Mount Adapter

Specifications

| | |
|-----------------------|---|
| Resolution | 540 lines |
| Image Sensor | 1/3" Sony Double Density CCD |
| Lens | 4-9mm Varifocal Auto Iris |
| Effective Pixels | 768(H) x 494(V) (NTSC) |
| Minimum Illumination | 0 Lux with LED on, 0.0005 Lux with DSS Active |
| Electronic Shutter | 1/60 Sec. to 1/100,000 Sec. |
| Video Output | 1.0 Vp-p (sync. negative) |
| TV Type | NTSC |
| Scanning System | 2.1 interlace |
| Synchronization | Internal / External (24 AC) |
| S/N Ratio | 45dB or more (AGC OFF) |
| Dynamic Range | 120dB (max) |
| OSD Menu Control | Semi OSD Button Control |
| WDR | WDR / BLC / OFF |
| Gamma Characteristic | 0.45 typ. |
| Power Supply | Dual voltage - 24 Volts AC, 12 Volts DC |
| Consumption Current | Max. 800mA / 9.6W |
| Operating Temperature | -20°F to 120°F |

Specifications subject to change

For more information contact us at:

Speco Technologies 200 New Highway, Amityville, NY 11701 Web: www.specotech.com
Toll Free: 1-800-645-5516 In Metro NY: 631-957-8700 Fax: 631-957-9142 or 631-957-3880