


Coaxial Connectors


3 Piece and 2 Piece BNC

DESCRIPTION

- Cambridge 3-piece connectors can be double crimped or crimped and soldered
- 2-piece connectors twist easily onto the cable
- Both connectors are UL listed



"BNC" 2-piece Connector



"BNC" 3-piece Connector

3-PIECE CONNECTORS - Part Number and Cable Data

West Penn Wire/CDT Part No.	Cable	Contact I.D.	Body I.D.	Ferrule I.D.	Crimp Ferrule Hex Size	Crimp Tool
CN-BM53-1	RG-58, 141	.044	.126	.206	.213	TL-103
CN-BM53-2	RG-59, 62	.034	.173	.261	.255	TL-104
CN-BM53-3	P806	.034	.208	.344	.310	TL-107
CN-BM53-4	RG-MATV-59	.044	.173	.261	.255	TL-104
CN-BM53-5	RG-6	.044	.280	.280	.280	TL-110
CN-BM53-7	RG-7	.055	.252	.374	.385	TL-150
CN-BM53-10	RG-TFE-59	.0325	.141	.206	.213	TL-103
CN-BM53-11	RG-TFE-58	.044	.126	.192	.213	TL-103
CN-BM53-13	RG-58	.044	.126	.220	.213	TL-103
CN-BM53-18	RG-179	.0245	.107	.175	.184	TL-105
CN-BM53-19L/S	Plenum RGB	.0245	.167	.118	.184	TL-105
CN-BM53-25	RG-58 Thinnet	.044	.107	.175	.184	TL-105
CN-BM53-26	RG-11	.062	.290	.410	.445	TL-113
CN-BM53-30	RG-59 Plenum	.0325	.141	.220	.213	TL-103
CN-NM53-110	RG-8, 213	.110	.400 - .410	---	.404	TL-106
CN-ETN-23	Ethernet	.085	.400 - .410	---	.404	TL-106

BNC 3 PIECE CONNECTOR

FEATURES

- All pins can be crimped or soldered
- Gold captivated contacts
- Knurled tail on body
- UL listed

SPECIAL NOTES:

- For coaxial cable/connector cross reference, please refer to Technical Reference Section

2-PIECE CONNECTORS - Part Number and Cable Data

West Penn Wire/CDT Part No.	Cable	Wire Gauge	Jacket O.D.	Crimp Braid XPL	Crimp Stress Relief	Crimp Tool
CN-BM52-2	RG-59, 62	22	.220 - .250	.320	.250	TL-101
CN-BM52-3	P806	20	.272 - .307	.350	.288	TL-102
CN-BM52-4	RG-MATV-59	20	.242 - .251	.320	.250	TL-101
CN-BM52-5	RG-6	18	.265 - .280	.385	.320	TL-109
CN-BM52-10	RG-TFE-59, 62	22	.195 - .210	.320	.211	TL-100
CN-BM52-11	RG-TFE-58	22	.180 - .192	.320	.200	TL-108
CN-SWBM52-2	RG-59, 62	18	.220 - .250	.320	.250	TL-101
CN-BF52-2	Female RG-59	22	.220 - .250	.320	.250	TL-101
CN-BF52-3	Female P806	20	.272 - .307	.350	.288	TL-102
CN-BF52-5	Female RG-6	18	.265 - .280	.385	.320	TL-109
CN-PL259-1	RG-58	20	.185 - .205	.255	---	24-307

BNC 2 PIECE CONNECTOR

Features

- One-step termination with strain relief
- Crimpless/solderless center contact (patented)
- Self-terminating contact (patented)
- Hand tool available
- UL listed