

SLA Series -

SLA-4.1

formerly LA-1400

DESCRIPTION

The **SLA-4.1** is a high output Frequency Shaded Line Array loudspeaker employing a ribbon HF driver and four 4" LF drivers within a very low profile enclosure. It is designed to work in highly reverberant environments where very broad uniform horizontal coverage and a focused vertical pattern are beneficial.

A sophisticated filter circuit sequentially integrates drivers in the array to maintain pattern control to 900 Hz, and ensures a smooth transition from line-source to point-source behavior at lower frequencies. The result is very flat response and uniform pattern control, yielding superior speech clarity and musical detail.

KEY FEATURES:

- maintains 25° vertical pattern control to 900 Hz
- low profile: depth only 3.4"
- Frequency Shading optimizes pattern uniformity
- effective projection beyond 50 feet

APPLICATIONS:

- churches
- classrooms
- lecture halls
- presentation spaces





compact frequency-shaded line array

DESCRIPTIVE DATA

NOMINAL DATA

Components & Loading (4) 4" LF; (1) ribbon HF $120 - 20,000 \text{ Hz}, \pm 3 \text{ dB}$ Frequency Response Recommended High-Pass Filter 4th order Butterworth @ 100 Hz Sensitivity 95 dB @ 2.83V / 1M **Enclosure Type** Sealed enclosure, low profile column Impedance 4Ω (70-volt available) **Enclosure Material** Steel, composite endcaps Power Handling 175 W long-term (AES-2)

andling 175 W long-term (AES-2) Finish Black or White standard
Output 116 dB long-term, 122 dB peak (custom colors available)

Maximum Output 116 dB long-term, 122 dB peak (custom colors available)

Nominal Coverage Angles 120° H x 25° V Connectors NL4 and dual binding head screws

Dimensions height: 25.62 " / 651 mm Suspension Hardware (10) 1/4-20 threaded points on back and

width: 5.62 " / 143 mm endcaps – OmniMount 30.0 series compatible (two slotted L-brackets included)

System Configuration

Net Weight 12.0 lbs / 5.5 kg

Shipping Weight 15.0 lbs / 6.8 kg

Grille Integral, fabric wrapped

West Coast Office

1155-C Arnold Drive, #231 Martinez CA 94553 ph: **925 372-8156** email: orders@innovoxaudio.com

Central Office

296 North Pascal Street Saint Paul MN 55104 ph: **612 379-0100**

email: sales@innovoxaudio.com

innovoxaudio.com