



## Vinten Protouch

### Lightweight Camera Support System

The **New Pro-5<sup>Plus</sup>**, **Pro-6<sup>HDV</sup>** and **Pro-10** are designed to support the growing range of professional camcorders that weigh up to 10 kg, helping videographers to maintain a professional look and feel whilst managing a tight budget.

The **Protouch** range offers a **truly professional alternative**, backed by the **Vinten** brand.



[www.vinten.com](http://www.vinten.com)

**Vinten**

*simply perfection*

# Pro-5<sup>Plus</sup>

for smaller camcorders up to 4.5 kg

This **New** system features a **Pro-5<sup>Plus</sup>** head with sideload for rapid camera attachment, adjustment and removal, as well as a **Vinten Pozi-Loc** tripod and spreader for class-leading rigidity and stability. Supplied with a quality **Petrol<sup>TM</sup>** case the **Pro-5<sup>Plus</sup>** system provides professional camera support suitable for even the lightest camcorder.

**NEW**

- Sideload system
- Continuously variable pan and tilt drag
- Class-leading rigidity and stability
- Switchable counterbalance



# Pro-6<sup>HDV</sup>

for camcorders up to 6 kg

The **Pro-6<sup>HDV</sup>** features continuously variable fluid drag and stepped counterbalance for smooth camera control, as well as a sideload system for rapid camera attachment, adjustment and removal. It is available as a head only or incorporated into two highly specified systems with a **Vinten Pozi-Loc** tripod and either a floor or a mid-level spreader.

- Continuously variable fluid drag
- 3 levels of counterbalance plus zero position
- Illuminated levelling bubble
- Sideload system



Sideload system allows for rapid camera attachment, adjustment and removal.



3 levels of counterbalance plus zero position for extremely lightweight camcorders and easy to adjust pan and tilt drag.



Illuminated levelling bubble for quick and convenient set up in low light situations.

# Pro-10

for cameras up to 10 kg

The **Pro-10** includes continuously variable fluid drag for smooth control and movement, as well as an illuminated levelling bubble for quick and convenient set-up in low-light situations. Available as a head or system the **Pro-10** offers exceptionally good value support for the latest professional digital and ENG cameras.

- Continuously variable fluid drag
- Illuminated levelling bubble




## Pro-5<sup>Plus</sup> System Technical Specification

<b>Part No.</b>	Pro-5AP1F
<b>System Weight</b>	5.5 kg / 12 lbs
<b>Consisting:</b>	Pro-5 <sup>Plus</sup> head, single-stage tripod, floor spreader, soft case and multi-lingual operator guide
<b>Capacity</b>	4.5 kg / 9.9 lbs @ 55 mm CofG
<b>Counterbalance</b>	Selectable 1 step plus zero
<b>Pan Range</b>	360°
<b>Tilt Range</b>	+90°, -60°
<b>Ball Base</b>	75mm
<b>Camera Fixing</b>	Quick attachment and release Sideload system, utilising a standard slide plate complete with 3/8" and 1/4" camera screw
<b>Pan and Tilt Drag</b>	Infinitely adjustable
<b>Pan bar</b>	Single fixed length



## Balance Chart



## Pro-6<sup>HDV</sup> System Technical Specification

### Pro-6<sup>HDV</sup> pan and tilt head

<b>Part No.</b>	V4018-0001
<b>Weight</b>	2.2 kg / 4.8 lbs
<b>Capacity</b>	Maximum 6 kg / 13.2 lbs @ 55mm CofG
<b>Counterbalance</b>	Selectable 3 steps plus zero
<b>Pan and Tilt Drag</b>	Infinitely adjustable
<b>Pan Range</b>	360°
<b>Tilt Range</b>	+90°, -60°
<b>Ball Base</b>	75mm
<b>Camera Fixing</b>	Quick attachment and release Sideload system, utilising a standard slide plate complete with 3/8" and 1/4" camera screw
<b>Levelling Bubble</b>	Illuminated with low battery indicator
<b>Pan bar</b>	Single fixed length

### Pro-6<sup>HDM</sup> system


<b>Part No.</b>	Pro-6 <sup>HDM</sup>
<b>System Weight</b>	7.25 kg / 16 lbs
<b>Consisting</b>	Pro-6 <sup>HDV</sup> head, two-stage tripod, mid-level spreader, soft case and multi-lingual operator guide

### Pro-6<sup>HDF</sup> system

<b>Part No.</b>	Pro-6 <sup>HDF</sup>
<b>Weight</b>	7.35 kg / 16.2 lbs
<b>Consisting</b>	Pro-6 <sup>HDV</sup> head, two-stage tripod, floor spreader, soft case and multi-lingual operator guide



## Balance Chart



## Pro-10 System Technical Specification

### Pro-10 pan and tilt head


<b>Part No.</b>	3809-3
<b>Weight</b>	2.4 kg / 5.2 lbs
<b>Capacity</b>	10 kg / 22 lbs
<b>Counterbalance</b>	Fixed for a 7.5 kg / 16.5 lbs camera weight
<b>Pan Range</b>	360°
<b>Tilt Range</b>	+90°, -60°
<b>Ball Base</b>	75mm
<b>Camera Fixing</b>	Sliding quick release plate with 3/8" and 1/4" screws with locating pin
<b>Levelling Bubble</b>	Illuminated
<b>Pan bar</b>	Single fixed length

### Pro-10DC System

<b>Part No.</b>	Pro-10DC
<b>System Weight</b>	8.2 kg / 18.1 lbs
<b>Consisting</b>	Pro-10DC head, two-stage tripod, floor spreader, soft case and multi-lingual operator guide



## Balance Chart



# PD114 Dolly



The **Protouch PD114** multi-purpose dolly is an ideal optional accessory for any Protouch system. The lightweight and compact folding dolly is supplied with individual wheel locks and removable cable guards, making it ideal for studio and outside applications.

## Technical Specification

### PD114 Dolly

Type No:	U005-103
Capacity:	40 kg / 88.2 lbs
Weight:	5.2 kg / 11.5 lbs
Base Diameter:	112 cm / 44.1"
Wheel Diameter:	12.5 cm / 5"

## Spares and Accessories

V4032-0001 3818-3 3219-104	Protouch mid-level spreader Floor spreader Second Pan Bar for Pro-6 <sup>HDV</sup> and Pro-10
U005-620 3425-3P 3808-900SP	Second Pan Bar for Pro-5 <sup>Plus</sup> Tripod carrying strap Camera plate for Pro-5 <sup>Plus</sup> and Pro-6 <sup>HDV</sup> incl. 3/8" and 1/4" screws and locating pin
3809-900SP	Camera plate for Pro-10 incl. 3/8" and 1/4" screws and locating pin
U005-190	Soft Case for Pro-6 <sup>HDV</sup> and Pro-10 Systems
U005-621	Soft Case for Pro-5 <sup>Plus</sup> System

# Mid-Level Spreader



The Protouch floor spreader offers the most stability and a generous amount of flexibility, but a mid-level spreader will ensure stability and camera control in any terrain or situation. The **Protouch mid-level spreader**, suitable for all Protouch systems, allows individual telescopic adjustment of each leg and provides a wide range of stable footprints. The overall footprint is determined by a two position central selector allowing for an extremely small footprint for tight areas and a large footprint where conditions allow.

## Technical Specification

V4032-0001 Mid-level spreader (with 3 rubber feet)

## Vinten Service & Support

When you buy Vinten a global team of customer service professionals ensures that technical advice, training and service backup is always available. You can also register your product online to extend your warranty to from 1 to 2 years for **FREE**.

For more information visit  
[www.vinten.com](http://www.vinten.com)

### Changes in Product Specification

Vinten reserve the right to alter specifications or change materials where absolutely necessary. All sizes shown throughout this brochure are approximate and colours shown are as accurate as modern reproduction methods will allow. No liability can be accepted for any variation.

© 2009 The Vitec Group plc  
© VINTEN, VISION, VECTOR, QUICKFIX & QUICKFIT are registered trademarks of The Vitec Group plc.

QUALITY SYSTEMS APPROVED TO ISO 9001:2000  
Certificate No: Q09508  
V1/01/09

**Vinten**

*simply perfection*

Protouch Systems | Protouch Lightweight Camera Support