

SP-525W, SP-625W & SP-825W

The Series 25 Audio In-Wall Speaker line



Model Shown
SP-625W
(sold in pairs)

Speco Technologies' has leveraged over 40 years of residential sound expertise in developing our core in-ceiling and in-wall audio line, the **Series 25 Audio Speaker Line**.

Manufactured from durable and quality components, Speco Technologies' **Series 25 Audio Speaker Line** provides strong value. Enjoy the premium performance of full-range sound in your listening environment for countless years to come.

Specifications

SP-525W 5.25" IN-WALL SPEAKER

- 5.25" Polypropylene Woofer with Rubber Surround
- 1" Pivoting Silk Dome Tweeter
- +/- 3dB Treble Switch
- 30 Watts RMS
- 60 Watts Max
- Frequency: 70Hz-20kHz
- Sensitivity: 87 dB 1w/1m
- Impedance: 8 Ohms
- Dimensions:
7 5/8" W x 11" H x 3" D
- Mounting Dimensions:
6 1/8" W x 9 3/8" H
- 2.7 lbs. Each

SP-625W 6.5" IN-WALL SPEAKER

- 6.5" Polypropylene Woofer with Rubber Surround
- 1" Pivoting Silk Dome Tweeter
- +/- 3dB Treble Switch
- 40 Watts RMS
- 80 Watts Max
- Frequency: 68Hz-20kHz
- Sensitivity: 88 dB 1w/1m
- Impedance: 8 Ohms
- Dimensions:
8 3/4" W x 12 1/4" H x 3 1/2" D
- Mounting Dimensions:
7 1/2" W x 11" H
- 3.4 lbs. Each

SP-825W 8" IN-WALL SPEAKER

- 8" Polypropylene Woofer with Rubber Surround
- 1" Pivoting Silk Dome Tweeter
- +/- 3dB Treble Switch
- 50 Watts RMS
- 100 Watts Max
- Frequency: 51Hz-20kHz
- Sensitivity: 88 dB 1w/1m
- Impedance: 8 Ohms
- Dimensions:
10 3/4" W x 14 1/2" H x 3 5/8" D
- Mounting Dimensions:
8 3/4" W x 12 3/4" H
- 3.7 lbs. Each

Specifications subject to change



For more information contact us at:

Speco Technologies 200 New Highway, Amityville, NY 11701 Web: www.specotech.com
Toll Free: 1-800-645-5516 In Metro NY: 631-957-8700 Fax: 631-957-9142 or 631-957-3880