

**THE FLEXIBILITY
TO FIT YOUR NEEDS
& YOUR BUDGET!**



Great For:



Bands

Live PA



Clubs



DJs



INTRODUCING
XSP SERIES
HIGH-POWERED PROFESSIONAL POWERED SPEAKERS



AMERICAN AUDIO

www.americanaudio.us
©American Audio® Los Angeles, CA 90040 USA. Specifications subject to change without notice.

MORE ON NEXT PAGE

XSP SERIES

HIGH-POWERED PROFESSIONAL POWERED SPEAKERS



XSP-8A

- 8-inch, 2-way Powered Speaker
- 100W built-in Bi-amplifier system
- Time Aligned Crossover
- ABS nylon fiber cabinet with handle
- Flyable or Stand Mountable
- Full grille
- XLR Mic/Line input with Volume Control
- Dimensions (LxWxH): 11.5" x 9" x 16.5" / 290x230x420mm
- Weight: 18 lbs. / 9 kg.

Speaker Specifications:

- Frequency Response: 20Hz - 20KHz
- Crossover: 3.3k
- Nominal Dispersion: 90° x 50° (HXV)

Amplifier Specifications:

- Power consumption: 12 Watts
- Line: -20dB(100mV)
- Microphone: -40dB(10mV)
- Output Sensitivity: 97.4 ± 2dB/m/w

XSP-10A

- 10-inch 2-way Powered Speaker
- 200W built-in Bi-amplifier system
- 1-inch Compression Driver
- Time Aligned Electronic Crossover
- Flyable or Stand Mountable
- Full grille
- Built-in mixer with 1 Line input; 1 Mic input; Treble & Bass Control; Channel and Master Volume
- XLR through output
- Dimensions (LxWxH): 14" x 11" x 19" / 355x280x480mm
- Weight: 31 lbs. / 14 kg.

Speaker Specifications:

- Frequency Response: 20Hz-20KHz
- Crossover: 3.5k
- Nominal Dispersion: 90°x50° (HXV)

Amplifier Specifications:

- Power consumption: 12 Watts
- Line: -20dB(100mV)
- Microphone: -40dB(10mV)
- Output Sensitivity: 97.4 ± 2dB/m/w



XSP-12A

- High-powered 12-inch, 2-way Powered Speaker
- 300W built-in Bi-amplifier system
- Neodymium components
- 1.75" compression driver
- Time Aligned Electronic Crossover
- Flyable or Stand Mountable
- Full grille
- Built-in mixer with 1 Line input; 1 Mic input; Treble & Bass Control; Channel and Master Volume
- XLR through output
- Dimensions (LxWxH): 16" x 12" x 23" / 405x305x585mm
- Weight: 44 lbs. / 20 kg.

Speaker Specifications:

- Frequency Response: 20Hz - 20KHz
- Crossover: 3.8k
- Nominal Dispersion: 90° x 50° (HXV)

Amplifier Specifications:

- Power consumption: 12 Watts
- Line: -20dB(100mV)
- Microphone: -40dB(10mV)
- Output Sensitivity: 97.4 ± 2dB/m/w

XSP-15A

- High-powered 15-inch, 2-way Powered Speaker
- 400W built-in Bi-amplifier system
- Neodymium components
- 1.75" compression driver
- Time Aligned Electronic Crossover
- Flyable or Stand Mountable
- Full grille
- Built-in mixer with 1 Line input; 2 Mic inputs; Treble & Bass Control; Channel and Master Volume
- XLR through output
- Dimensions (LxWxH): 17" x 15" x 27" / 430x380x685mm
- Weight: 57 lbs. / 26 kg.

Speaker Specifications:

- Frequency Response: 20Hz - 20KHz
- Crossover: 4.8k
- Nominal Dispersion: 90° x 50° (HXV)

Amplifier Specifications:

- Power consumption: 12 Watts
- Line: -20dB(100mV)
- Microphones: -40dB(10mV)
- Output Sensitivity: 97.4 ± 2dB/m/w

