

DVR4TH250* 4 Channel Hybrid Pentaplex H.264 DVR
DVR8TH250* 8 Channel Hybrid Pentaplex H.264 DVR
DVR16TH250* 16 Channel Hybrid Pentaplex H.264 DVR

*Standard DVR comes with a 250GB HDD - other configurations available up to 6TB internal**

Available with per camera

Digital Deterrent™

Audio For Security or Retail Applications



Features

- Free Speco DDNS server for use with dynamic IP addresses
- Mac® & PC compatible software included
- Hybrid Operation: Up to 4 channels with popular protocols supported including Speco Internet Protocol (SIP), ACTi, Axis, Sony, Vivotek, Hunt, Sanyo & others
- Selectable H.264, MPEG4, or MJPEG compression
- POS/ATM support with text overlay and searchable database
- Pentaplex operation enabling simultaneous live view or playback while continuing to record, network transfer
- Remote monitoring, recording, playback, change system settings and dome camera control via network and/or internet
- Jog shuttle for easy operation
- Real Time live display
- Remote control included - individually control up to 16 DVRs
- Rack ears included
- Recording rate up to 480 fps
- 4/8/16 channels of audio input
- 3/7/15 channels of 2-way audio
- Supports 3 SATA HDDs
- Digital output via HDMI cable
- DVD/RW Standard for video clip exporting
- USB 2.0 port for video clip exporting, supports USB Flash drives
- Easy software upgrade via Network, USB Flash Drives, or CD/DVD
- Configurable per channel normal and event recording frame rate & picture quality or globally via EZ record
- Free Central Management System (CMS) software allows viewing of 256 simultaneous channels on a PC
- Email notification of alarm events
- Per channel built-in dome camera protocol (through RS485) including Pelco D, Pelco P, AD422, Fastrax, JVC
- Automatic camera detection (Plug & Play)
- Digital Zoom 2 x 2 in live mode and playback
- Covert camera operation provides enhanced security, administrator control
- Dynamically programmable recording priority, motion detection, alarms and scheduling
- Programmable call-monitor switching sequence

**6TB maximum if DVD/RW is removed



Remote & Rack Ears Included

- Auto reboot feature: on/off
- Up to 30 second pre-alarm recording
- USB mouse and keyboard supported
- Multiple language on-screen menus
- Password to secure installation with 8 configurable user authentication levels
- Network software supports static IP, DHCP, PPPoE & DDNS
- Network hardware supports 10/100/1000 NIC
- Dimensions: 4 7/8" H X 17 1/4" W X 16 3/4" D
- Weight: 18.45 lbs. with 1 HDD (HDD weighs 1 lb.)
- Power Consumption: Start up @ 90W, Running @ 60W
- HDD size: 250GB, 1TB, 2TB, 3TB and 4TB configurations**
- Operating temperature: 14° F to 120° F
- UL Listed
- 3 year warranty

Speco Technologies is constantly developing product improvements.

We reserve the right to modify product design and specifications without notice and without incurring any obligation.

Rev. 2/18/10

For more information contact Speco Technologies

200 New Highway, Amityville, NY 11701 • Toll Free: 1-800-645-5516 • Fax: 631-957-9142 or 631-957-3880

www.specotech.com

Technical Specifications:
4, 8 or 16 Channel H.264 Hybrid
Pentaplex Digital Video Recorders



MODEL NAME		DVR4TH250	DVR8TH250	DVR16TH250	
Video	Operation System	Embedded (Linux)			
	Video Standard	NTSC / PAL switch selectable			
	Video Operation	Pentaplex+ (Live, Record, Playback, Remote, and Internet access)			
	Resolution – Live Video	NTSC: 720 x 480 pixels PAL: 720 x 576 pixels			
	Input	BNC x 4, BNC x 1 1.0Vp-p / 75 Ohm	BNC x 8, BNC x 1 1.0Vp-p / 75 Ohm	BNC x 16, BNC x 1 1.0Vp-p / 75 Ohm	
	Outputs	Main Monitor	VGA x 1, BNC x 1, S-Video x 1, 1.0Vp-p / 75 Ohm		
		Call Monitor	BNC x 1 1.0Vp-p / 75 Ohm		
		Looping	BNC x 4, BNC x 1 1.0Vp-p / 75 Ohm	BNC x 8, BNC x 1 1.0Vp-p / 75 Ohm	BNC x 16, BNC x 1 1.0Vp-p / 75 Ohm
	VGA Output	800 x 600, 1024 x 768, 1280 x 1024 pixels @ 60Hz, 75Hz			
	Digital Output	Via HDMI cable			
	Picture Refresh Rate (Live View)	NTSC: 480 PPS (16 CH) / PAL: 400 PPS (16 CH)			
Digital Zoom (Live & Playback)	2 x 2				
Camera Installation	Plug & Play				
Audio	Input	4, Line-In	8, Line-In	16, Line-In	
	Main Output	RCA x 1, Line-Out			
	Output	4, Line-Out	8, Line-Out	16, Line-Out	
	2-Way Audio	3/7/15 Channels Supported			
	Recording Mode	Always Real Time Record, Synchronized w/ Video			
	Compression Method	ADPCM, G.726			
	File Size	8KB / Sec.			
	Operation	Local and Remote			
Playback	Only for Video Original Speed				
Recording	Compression Method	H.264 / MPEG4 / MJPEG			
	Recording Mode	Schedule, Alarm, Motion Detection			
	Pre-Alarm	0~30 Sec.			
	Resolution & Rate	NTSC	720x480:	120 fps in MPEG-4 & MJPEG, 60 fps in H.264	
			720x240:	240 fps in MPEG-4 & MJPEG, 120 fps in H.264	
			352x240:	480 fps in MPEG-4 & MJPEG, 240 fps in H.264	
	Recording Quality	8 levels presets, adjustable			
Image Size	2K to 24K Byte / picture				
Storage Mode	Linear / Circular				
Playback	Playback	Play, Stop, Pause, Rewind, Forward, Search			
	Playback Speed Adjustment	Yes 1X, 2X...32X			
	Retrieve	Date / Time, Event Playback			
	Data Life Time	Yes (Programmable)			
Storage	Built-in Storage	X4 SATA, HDD / DVD+RW			
	Built-in HDD	Up to 3 built-in HDDs (3TB max.)			
	External Storage	USB HDD			
	Export	USB 2.0 ports, X4, supports ThumbDrive®, DVD+RW			
Alarm	Alarm Input	X4, Terminal Block	X8, Terminal Block	X16, Terminal Block	
	Alarm Detection	N.C. / N.O., Programmable			
	Auditory Alert	Built-in Buzzer			
	Motion Detection	15 X 11 Grid Array, Sensitivity, Trig Level Adjustable			
	Video Loss Detection	Programmable			
	Alarm Relay Output	X2, Terminal Block, 1.0A / 24V (Programmable)			
Communication	Network Connectivity	Ethernet RJ-45 connector, 10/100/1000Mbps, supports DHCP/PPPoE/DDNS			
	Remote Control Software	SpecoRemote™ / CMS			
	Access Remote	8 Levels			
	Remote Operation	Monitoring, Playback, Recording, System Setup, Dome Camera Control, Remote Burn			
	RS232C	D-sub 9 pin female			
	RS485	Terminal Block			
	Dome Control Protocol	Pelco D, Pelco P, AD422, Fastrax, JVC			
	IP Cameras	Up To 4 Channels			
IP Camera Protocols	Speco Internet Protocol (SIP), Xvision, ONVIF, AMTK, Luxon, Sanyo, Hunt, Acti, Sony, Axis 200, Vivotek 7000				

For more information contact Speco Technologies 200 New Highway, Amityville, NY 11701
Toll Free: 1-800-645-5516 Fax: 631-957-9142 or 631-957-3880 Website: www.specotech.com