


Intensifier™ 2 Series Weatherproof Tamper Resistant Dome Camera with Chameleon™ Cover

HT7246iHR	2.8-12mm Auto Iris Varifocal Lens
HT7247iHR	9-22mm Auto Iris Varifocal Lens
HT7250iHR	5-50mm Auto Iris Varifocal Lens

Features

- Intensifier™ 2 Series - see in extreme low light conditions without IR LEDs (requires only 0.002 lux)
- HLC for enhanced backlight operation
- Digital Image Stabilization and Advanced Noise Reduction Circuitry eliminate blur
- Relay Outputs are triggered by built-in video motion detection
- 580 line high resolution for extreme detail
- Chameleon™ Cover - snaps on and can be painted to match any décor
- Dual Voltage Operation: 12V DC or 24V AC (auto-sensing) with line-lock
- Wall & ceiling mountable with 3-way internal mount
- Weatherproof / Tamper Resistant
- Indoor or outdoor - meets all your surveillance needs
- [5 year warranty](#)



Specifications

Horizontal Resolution: 580 TV lines
 Intensifier™: Built-in (selectable from 2x to 256x)
 Image Device: 1/3" Sony Super-HAD™ CCD
 Min. Object Illumination: 0.002 lux (Intensifier™) 0.03 lux (shutter)
 Effective Picture Element: 410K
 HLC/SLC (Speco Light Compensation): Advanced backlighting controls
 White Balance: W-ATW / S-ATW / AWC / MANUAL
 Electronic Shutter: 1/60-1/100,000 seconds
 AGC: AGC-L, AGC-M, AGC-H, OFF selectable
 Video S/N Ratio: Greater than 52db
 Weatherproof Standard: IP-66
 Tamper Resistant construction: Aluminum composite/polycarbonate

Operating Environment: -20°F to 122°F
 Video Signal Output: 1.0V(p-p) NTSC composite, 75 Ohm / BNC Connector + Video Test Connector
 Power Consumption: 230mA (DC) / 3.8W (AC)
 Power Requirement: 12V DC or 24V AC (Dual Voltage)
 Weight: 24 ounces
 Scanning System: 2:1 interlaced 525 lines / 60 fields / 30 frames
 Synchronization: Internal / line lock selectable through OSD
 S-DNR Video Noise Reduction: OFF / LOW / MIDDLE / HIGH
 Motion Detection: 8 zones - relay outputs
 On-Screen Display (OSD): Built-in
 Privacy function: ON / OFF (8 Programmable Zones)
 Dimensions: 6.29" W x 3.89" H

Optional Accessories (Sold Separately):

7246WMT BCP	Weatherproof wall mount Corner/pole mount for use with 7246WMT wall mount	DFM2 CVCTPEXT	Dome wall/ceiling flush mount kit Junction Box used for connections and/or conduit applications
------------------------	--	--------------------------	--

Speco Technologies is constantly developing product improvements.
 We reserve the right to modify product design and specifications without notice and without incurring any obligation.

Rev. 2/16/10

For more information contact Speco Technologies

200 New Highway, Amityville, NY 11701 • Toll Free: 1-800-645-5516 • Fax: 631-957-9142 or 631-957-3880
www.specotech.com