

# CI2+ – Technical Specifications

## Electrical characteristics

AD/DA		24 bit
Sample rate		48 kHz (max)
Gain		+60 dB (- 60 dB ~ -16 dB)
HI-Z switch	Input impedance	500 ohms
Frequency response		20 Hz – 20 kHz (-3 dB @ 1 kHz)
THD+N		0.05% (@ 1 kHz, output level: +4 dBu)
Dynamic range		96 dB (A-weighted)
Power consumption	USB (bus-powered)	5 V 500 mA 2.5 W

## General specifications

Power requirements	<b>USB-powered</b>
Physical dimensions (H x W x D)	<b>45.4 mm x 190 mm x 134.5 mm</b>
Box dimensions (H x W x D)	<b>86 mm x 270 mm x 180 mm</b>
Net weight	<b>720 g</b>
Included accessories	CI2+ unit, Tools for CI2+ CD-ROM (Mac/PC hybrid), Cubase Essential 5 DVD-ROM (Mac/PC hybrid, also contains demo project), eLicensor USB dongle, activation code sheet, printed CI2+ operation manual (EN/DE/FR+JA), USB cable
Optional accessories	Yamaha FC5 (footswitch), Yamaha BMS10A (mic stand adapter)

## Minimum system requirements

Macintosh	Windows
Mac OS X version 10.5.5, 10.6 Power PC G5 CPU (Intel Core Duo CPU recommended) 1024 MB RAM 1 GB of free HDD space Display resolution 1280 x 800 pixels DVD-ROM drive USB component port for CI2+ connection Internet access required for license activation	Windows XP Home Edition (SP3) and XP Professional (SP3), Windows Vista, Windows 7 2 GHz CPU (dual core CPU recommended) 1024 MB RAM 1 GB of free HDD space Display resolution 1280 x 800 pixels DVD-ROM drive USB component port for CI2+ connection Internet access required for license activation

For recommended systems, please refer to our website [www.steinberg.net](http://www.steinberg.net) in the Support section under DAW Components.