Technical Data Sheet RG6/U Type CCTV Coaxial Cable



2833 West Chestnut Street Washington, PA 15301 Toll Free: (800) 245-4964 Fax: (724) 222-6420 www.westpenn-wpw.com

	www.westpenn-wpw.com	
PART NUMBER:	806	
DESCRIPTION:	RG6/U – 1 Conductor 18 AWG Solid, 95% Bare copper braid and an overall PVC Jacket.	
NEC RATING:	СМ	
APPROVALS:	(UL) C(UL) Listed or c(ETL)us Listed	
APPLICATION:	Indoor for: Security Cable - CCTV	

Construction Parameters:

Conductor	18 AWG Bare Copper		
Stranding	Solid		
Insulation Material	Gas Injected Polyethylene		
Insulation Thickness	.180" Nom.		
Number of Conductors	1 Center Conductor		
Shield	95% Bare Copper Braid		
Jacket Material	PVC		
Overall Cable Diameter	0.270" Nom.		
Approximate Cable Weight	26 Lbs/1M' Nom.		
Flame Rating	UL 1685		

Electrical & Environmental Properties:			db/100ft
Temperature Rating Max.Capacitance Between Conductors @ 1 KHz Velocity of Propagation Impedance DC Resistance per Conductor @ 20deg C Jacket Color RoHS Compliant	-20deg C to 60deg C 16.2 pf/ft Nom. 82% Nom. 75 ohms Nom. 6.5 Ohms/1M' Nom. Black Yes	1 10 50 100 400 700 1000	.24 .52 1.18 1.83 3.95 5.38 6.45
Mechanical Properties: Max. Recommended Pull Tension	41 lbs.	-	

Max. Recommended Pull Tension Min. Bend Radius (Install)

Connectors and Accessories

75 ohm BNC Crimp	CN-BM73-5	Crimp Tool: TL-107	Strip Tool: TL-121
Compression BNC 75 ohm	CN-BNCP-6 or CN-CSBNC-6Comp.	Tool: TL-SNSA Stri	p Tool: TL-CSST
Compression RCA	CN-RCAP-6 or CN-CSRCA-6	Comp. Tool: TL-SNSA	Strip Tool: TL-CSST

Specification Issue Date: 7/06

This document is the property of West Penn Wire. The information contained herein is considered Proprietary and not to be reproduced by any means Without written consent of West Penn Wire Standard Lengths are 1000ft. The Jacket is sequentially footmarked. The information presented here is, to the best of our knowledge, is true and accurate. However, since conditions of use are beyond our control, all recommendations or suggestions are presented without guarantee or responsibility on our part. We disclaim all liability in connection with the use of information contained herein or otherwise.

2.5"