

VM-2HxI (previously VM-2HDMIxI)

1:2 HDMI Distribution Amplifier









The VM-2Hxl is a distribution amplifier for HDMI signals. The unit reclocks and equalizes the signal and distributes it to two identical outputs.



VM-2HxI (previously VM-2HDMIxI)

FEATURES

- Max. Data Rate 2.25Gbps.
- HDTV Compatible.
- HDCP Compliant.
- HDMI Support HDMI (V.1.4 with Deep Color, x.v.Color™, Lip Sync, CEC).
- 3D Pass-Through.
- I-EDIDProTM Kramer Intelligent EDID ProcessingTM - Intelligent EDID handling & processing algorithm ensures Plug and Play operation for HDMI systems.
- Kramer Equalization & re-Klocking™ Technology - Rebuilds the digital signal integrity to travel longer distances.
- Active Output LED.
- Compact DigiTOOLS® 3 units can be rack mounted side-by-side in a 1U rack space with the optional RK-3T rack adapter.

TECHNICAL SPECIFICATIONS

INPUT: 1 HDMI connector.

OUTPUTS: 2 HDMI connectors.

BANDWIDTH: Supports up to 2.25Gbps

bandwidth per graphic channel.

COMPLIANCE WITH Supports HDMI 1.3 and

HDMI STANDARD: HDCP.

CONTROLS: EDID SETUP button, input

select button.

INDICATOR LEDs: IN 1, IN 2, OUT 1, OUT 2,

and ON LEDs.

POWER SOURCE: 5V DC, 910mA.

DIMENSIONS: 12cm x 7.2cm x 2.4cm

(4.7" x 2.8" 1.0") W, D, H.

WEIGHT: 0.3kg (0.67lbs) approx.

ACCESSORIES: Power supply, bracket

installation kit.

OPTIONS: HDMI/HDMI male-to-male

cables, RK-3T 19" rack

adapter.