

TX330 – Multimedia Projector

Bold, Bright and Brilliant

The TX330, an ultra-portable, XGA digital projector, is designed for the road warrior. Ideal for “grab and go” presentations, the Optoma TX330 is unparalleled in size, weight and connections. It also features BrilliantColor™ technology and a DLP® chipset from Texas Instruments for crisp and amazing picture quality.

Features

- Ultra-portable 2.4-lb DLP projector
- Native XGA resolution and HD-compatible
- 2200 ANSI lumens and 2000:1 contrast ratio
- Connections include HDMI, VGA, S-Video, Composite Video and USB
- Ideal presentation remote with laser pointer and page-advance features
- Up to 5000 hours lamp life

Specifications

Display Technology

Single 0.55" DMD DLP Technology by Texas Instruments

Resolution

Native XGA (1024 x 768)

Maximum Resolution

SXGA+ (1400 x 1050)

Brightness (Typical)

2200 ANSI Lumens

Contrast Ratio

2000:1 (Full On/Full Off)

Lamp Life and Type*

5000/3000 Hours (STD/Bright)
165W P-VIP

Throw Ratio

1.95 to 2.15:1 (Distance/Width)

Image Size (Diagonal)

22.9" to 302" (0.58 to 7.67m)

Projection Distance

3.3' to 39.37' (1.0 to 12m)

Remote Control

Fully Featured Remote Control with Mouse and Laser Pointer

Displayable Colors

16.7 Million

Aspect Ratio

4:3 Native, 16:9 Compatible

Uniformity

85%

Offset

115%

Computer Compatibility

VGA, SVGA, XGA, SXGA, SXGA+, WXGA Resized, VESA, PC and Macintosh Compatible

Video Compatibility

NTSC, PAL, SECAM, SDTV (480i), EDTV (480p), HDTV (576i/p, 720p, 1080i)

User Controls

Complete On-Screen Menu Adjustments in 22 Languages

Keystone Correction

± 18° Vertical

Horizontal Scan Rate

15 to 100 kHz

Vertical Refresh Rate

43 to 85 Hz

Projection Lens

F=2.41~2.55, f=21.79~23.99mm, 1.10x Manual Zoom and Focus

I/O Connectors

HDMI, VGA-In, Composite Video, S-Video, USB

Security

Kensington® Lock Port

Projection Method

Front, Rear, Ceiling Mount, Table Top

Weight

2.4 lbs (1.1 kg)

Dimensions (W x H x D)

8" x 2.5" x 6.1"
(205.5 x 64 x 156 mm)



Noise Level (STD/Bright)

31dB/33dB

Power Supply

AC Input 100-240V, Auto-Switching

Power Consumption

225 Watts (Maximum), <1 Watt (Standby)

Operating Temperature

41 - 104°F (5 - 40°C) (80% Humidity), Adjustable Fan Speed for High Altitude Application

Standard Accessories

AC Power Cord, VGA to VGA Cable, USB Cable, Carrying Case, Remote Control, Batteries for Remote, Quick Start Guide, Warranty Card and User's Manual

Optional Accessories

Ceiling Mount, S-Video Cable, VGA to Component Cable, Composite Video Cable, DVI to HDMI Adapter, HDMI Cable, Gold Service Warranty and Panoview™ Series Screens

Warranty

3 Years Limited Parts and Labor, 1 Year on Lamp

UPC

796435 41 690 4

Accessory Part Numbers

Lamp: BL-FP165A
Remote: BR-5021L
Case: BK-4022

* Lamp life is dependent upon many factors, including lamp mode, display mode, usage, environmental conditions and more. Lamp brightness may decrease over time.