

**D8LS** 8 Channel DVR with Digital Deterrent™

**D16LS** 16 Channel DVR with Digital Deterrent™

D8LS500 / 1TB / 2TB / 4TB / 6TB

D16LS500 / 1TB / 2TB / 4TB / 6TB


## Features

View on iPhone®, Blackberry® or Android®

- 8 or 16 composite video input connectors
- Multiple monitor connectors: 1 BNC Video Out, 1 Spot, 1 VGA
- Multiple search engines (Date/Time, Calendar, Record Table, Event, Motion, Museum)
- EZ Setup Wizard
- Auto Port Forwarding (uPnP) and SSL encryption
- User-friendly Graphical User Interface (GUI) menu and mouse user interface system
- Multiple recording modes (Time-lapse, Pre-event, Alarm, Motion, Text-in and Panic)
- Two-way Audio Communication
- 4-Channel audio recording and 1-Channel audio playback
- Time synchronization using industry standard protocol
- Built-in DVD RW Drive
- Self-diagnostics with automatic notification including hard disk drive S.M.A.R.T. protocol
- Automatic O/S recovery
- H.264 recording
- Recording rate up to 480 fps
- Free Speco DDNS service for use with dynamic IP addresses
- MAC® & PC compatible software included
- POS/ATM support with text overlay and searchable database
- Simultaneous live view or playback while continuing to record, network transfer
- Text message alerts of system activity and status
- Remote monitoring, recording, playback, change system settings and dome camera control via network and/or Internet
- Real time live display
- IR Remote control included - individually control up to 16 DVRs
- Multiple analytics such as museum search and advanced motion detection
- USB 2.0 port for video clip exporting
- Easy software upgrade via Network or USB Flash drive
- Configurable per channel normal and event recording frame rate & picture quality or globally via EZ record
- Full system monitoring
- Free Central Management System (Speco Central) software allows viewing of multiple DVRs on a PC
- Email notification of alarm events
- Free iPhone® app available from iTunes



Storage from 500GB up to 6TB



BlackBerry®




- Per channel built-in PTZ camera protocol including Pelco D
- Automatic camera detection (Plug & Play)
- Digital Zoom in live mode and playback
- Covert camera operation provides enhanced security and administrator control
- Playback while watching live on same monitor
- Up to 30 minutes pre-alarm recording
- Up to 15 minutes post-alarm recording
- Hard drive status monitoring
- Remote upgrade
- USB mouse and keyboard supported (not included)
- Multiple language on-screen menus
- Password to secure installation with configurable user authentication levels
- DVR supports static IP, DHCP, PPPoE and DDNS
- Power consumption: AC100-240 V - 50/60Hz, 1.2 - 0.6A
- Operating temperature: 41° F to 104° F
- Dimensions: 16.9" W x 3.46" H x 15.7" D
- Weight: 16.76 lbs.
- 3 year warranty

### EZ Set-Up Wizards!

One click wizard guides you to set up essentials of the system in a logical and easy to understand sequence.

- Date/Time • Recording method • Recording video quality • Network



Speco Technologies is constantly developing and improving products.

We reserve the right to modify product design and specifications without notice and without incurring any obligation.

Rev. 9/6/11

For more information contact Speco Technologies

200 New Highway, Amityville, NY 11701 • Toll Free: 1-800-645-5516 • Fax: 631-957-9142 or 631-957-3880  
www.specotech.com

### EZSetup Wizard

One click Wizard guides you to setup essentials of the system in a logical and easy-to-understand sequence.

- Date/Time Setup
- Recording Method Setup
- Recording Video Quality Setup
- Network Setup

### Applications

**Speco Central**

Remote software providing 64 cameras live/ playback, event monitoring, local recording, E-map and device management.

**Speco Mobile**

Remote monitoring software running on mobile devices like Android and Blackberry.

**Speco Remote**

Web based remote monitoring software which can be downloaded from web browsers in ActiveX format.

**Speco Player**

Self executable video player containing non-alterable recorded data from the DVR.

**Speco Mobile-I**

Remote monitoring software for iPhone and iTouch.

Model Name	D8LS	D16LS
Video Inputs	8	16
Video Outputs	1 BNC, 1 VGA, 1 SPOT	1 BNC, 1 VGA, 1 SPOT
Display Resolution	720 x 480	
Loop Out	8	16
<b>RECORD &amp; PLAYBACK</b>		
Compression	H.264	
Recording Rate	240 fps@CIF / 240 fps@2CIF / 120 fps@D1	480 fps@CIF / 240 fps@2CIF / 120 fps@D1
Playback Rate	240 fps @ CIF	480 fps @ CIF
Recording Mode	Time-Lapse, Event, Pre-Event (up to 30 min), Text-In, Panic	
Search Mode	Date/Time, Record Table, Calendar, Event, Motion, Museum, Text-In	
<b>SYSTEM</b>		
Operating System	Embedded Linux	
Firmware Base	XDR Type	
Storage	Max. 4 HDD	
Data Export	USB (HDD, FlashDrive), SATA DVD±RW	
<b>NETWORK</b>		
Connection	Ethernet	
Protocols	Manual, ADSL, DHCP, DDNS	
Remote Software	Speco Central, Speco Remote	
Max Transmission Rate	120 CIF	
<b>INTERFACE</b>		
Audio In / Out	RCA 4/1	
Alarm In / Out	8 / 1 (relay, NO)	16 / 1 (relay, NO)
Serial Interface	RS232, RS485	
External Interface	2 x USB 2.0	
User Interface	Front Buttons, Mouse, IR Remote Control, Remote Keyboard	
<b>OTHER</b>		
Dimensions (W x H x D)	16.9" x 3.46" x 15.7", 2U, Rack Mount	
Unit Weight	16.76 lbs.	16.76 lbs.
Operating Temperature	41° F ~ 104° F	
Operating Humidity	0% ~ 90%	
Power	AC 100-240 V~, 50/60Hz, 1.2 ~ 0.6A	
Approvals	FCC, UL, CE, CB	

Please note that specifications and unit exterior design are subject to change without notification.