

CVC320WP
CVC320WPW

Black Housing
White Housing



Features

- Completely waterproof with underwater operation capabilities to a maximum depth of 90 ft.
- Nitrogen filled housing protects internal components
- Available in black or white housings (60 ft. cable included with black model and 3 ft. cable included with white model)
- Clip-on sunshield included
- RoHS compliant

Specifications

Image Device	1/3" CCD B/W image sensor
Picture Elements	512 (H) x 492 (V)
Resolution	420 TV lines
Minimum Illumination	0.02 lux without IR LEDs, 0 lux when IR LEDs are on
Electronic Shutter Control	Auto 1/60-1/100,000 sec.
Lens/Angle Of View	3.6mm - wide angle
Synchronizing System	Internal
Interlace	2:1
Video S/N Ratio	Greater than 48dB
Operating Temperature	-14°F to 120°F
Video Output Level	1.0 Vp-p, 75 ohm composite video
IR LEDs	8 @ 850 NM, controlled by CDs Sensor
Outputs/Connections	BNC-video, Power - DC jack
Power Requirements	12V DC power supply included - UL & CSA listed
Power Consumption	200mA
Housing Material	Brass
Mounting Bracket	Included
Scanning Frequency	Hor. 15.75 KHz Vert. 60 Hz
Scanning system	EIA standard 525 TV lines 60 fields/sec.
Dimensions	1-1/2" (H) x 2" (D)
Weight	7.4 oz.
Cable	60 ft. of power/video cable (CVC320WP) 3 ft. of power/video cable (CVC320WPW)