



TruLink® HDMI® over Cat5E Extender

- Video bandwidth: 2.25Gbps
- Adjustable equalization
- Supports the following resolutions using Cat5E* cabling:
 - 40m at 1920 x 1080 pixels (1080p 12 bit)
 - 60m at 1920 x 1080 pixels (1080i)
 - 60m at 1280 x 720 (720p)
- One Year Warranty

*Cat6 cables may also be used.

TruLink® HDMI® over Cat5E Extender

Electrical Specifications:

Video Bandwidth:	2.25Gbps	
Input TMDS Signal:	1.2V (Peak-to-Peak)	
Input DDC Signal:	5V (Peak-to-Peak)	
Resolution/Distance Supported:	40M	1920x1080 (1080p 12bit)
	60M	1920x1080 (1080i)
	60M	1280x720 (720p)

Power Adapter Specifications*:

Power Input:	100-240VAC ~47/63Hz
	0.48A Max.
Power Output:	5VDC
	2.5A
	12.5W Max.
Pin Diameter:	5.5mm
Center Pin Polarity:	Positive

*The Power Adapter must be connected to the DC input on the remote unit.

Physical Characteristics:

Video Input Connector (Base):	Type A HDMI Female - 19pin
Video Output Connector:	Type A HDMI Female - 19pin
Connector Plating:	Gold
Connector Plating Thickness:	15Ωm
Housing Material:	Metal
Operating Temperature Range:	0° - 70°C
Storage Temperature Range:	0° - 70°C
Weight:	0.95lb
Dimensions:	Base Unit - 69.9 x 25.4 x 69.9mm
	Remote Unit - 69.9 x 25.4 x 69.9mm

