



## VP-438

### 10-Input Analog & HDMI ProScale™ Presentation Digital Scaler/Switcher



The VP-438 is a high-performance presentation scaler/switcher for HDMI, computer graphics, composite video and component video signals. It scales the video, embeds the audio, and outputs the signal to the HDMI, computer graphics and RGBHV video outputs together with digital and analog stereo audio outputs.



## VP-438

---

### FEATURES

---

- **Video Inputs** - 4 HDMI, 2 computer graphics video on 15-pin HD connectors, 2 composite video & 2 component video on RCA connectors.
- **Scaled Outputs** - A single output signal simultaneously available in 3 formats: 1 HDMI, 1 RGBHV on BNC connectors & 1 computer graphics video on a 15-pin HD connector.
- **22 Output Resolutions** - Up to UXGA and 1080p.
- **HDTV Compatible.**
- **HDCP Compliant** - The HDCP (High Definition Content Protection) license agreement allows copy-protected data on the HDMI input to pass only to the HDMI output.
- **K-Storm™ Scaling Technology** - Kramer's extremely high-performance scaling technology. High-quality 3:2 and 2:2 pull down de-interlacing and full up and down scaling of computer graphics video input signals.
- **Multi-Standard** - PAL & NTSC.
- **Companion AFV (Audio-Follow-Video)** - Stereo audio for every input (on terminal blocks) and individual level controls.
- **Multiple Aspect Ratio Selections** - Full, overscan, underscan, letter box & panscan.
- **Built-in ProcAmp** - Color, hue, sharpness, noise, contrast, and brightness.
- **Audio Outputs** - 1 S/PDIF & 1 unbalanced stereo audio on RCA connectors.
- **Front Panel Control** - Audio mute, video blanking & freeze frame.
- **Front Panel Lockout.**
- **Non-Volatile Memory** - Saves final settings.
- **Flexible Control Options** - Front panel, IR remote (included) with OSD (on-screen display) & RS-232.
- **Worldwide Power Supply** - 100-240V AC.
- **Standard 19" Rack Mount Size** - 1U. Rack "ears" included.



## VP-438

---

### TECHNICAL SPECIFICATIONS

---

INPUTS:	4 HDMI connectors (HDMI, HDCP version 1.1); 2 VGA on a 15-pin HD connector; 2 composite video on an RCA connector; 2 component video each on 3 RCA connectors; 4 HDMI, 2 PC, 2 COMP, 1 CV unbalanced stereo audio on 10 3-pin terminal block connectors.
OUTPUT:	1 RGBHV on 5 BNC connectors; 1 HDMI connector (HDMI, HDCP version 1.1); 1 VGA on a 15-pin HD connector; 1 S/PDIF on an RCA connector; 1 analog stereo audio on 2 RCA connectors.
H FREQUENCY:	15.63–90kHz.
V FREQUENCY:	50–100Hz.
RGB SYNCs:	H and V TTL separated syncs.
RGB LEVEL:	1.2Vpp max, 75Ω load.
XGA OUT LEVEL:	1.2Vpp max, 75Ω load.
S/PDIF OUT LEVEL:	0.55Vpp constant.
OUTPUT RESOLUTIONS:	720p60, 1080i60, 1080p60, 576i, 576p, 720p50, 1080i50, 1080p50, WXGA, WXGA+, WSXGA, WUXGA, NATIVE, VGA, SVGA, XGA, SXGA, SXGA+, UXGA, 480i, 480p, 1280x80.
CONTROLS:	Input selector buttons; blank, mute, freeze buttons; menu, enter, menu arrows, reset to XGA/720p, lock buttons, RS-232, Ethernet.
POWER SOURCE:	100–240V AC, 33VA max.
DIMENSIONS:	19" x 7" x 1U (W, D, H), rack mountable.
WEIGHT:	2.7kg (6lbs) approx.
ACCESSORIES:	Power cord, rack "ears".



VP-438

