

Lowell Wall-mount Tilt-out Rack

Description:

The LWTR is ideal for (surface or recessed) wall installation of rack-mount and non-rackmount electronics in schools, training facilities, retail stores or similar areas. Suitable for installation in brick, concrete block or stud wall construction. Two styles:

• Surface-mount: Model No. LWTR-3S.

- Backbox: 29.125"W x 29.125"H x 4"D
- Rack Frame: 29.06"W x 29.06"H x 1.81"D
- Projection from Wall: 5.81"
- Overall: 29.125"W x 29.125"H x 5.81"D

• Recessed: Model No. LWTR-3R mounts 4" into wall with the adjustable rack frame projecting 1.81" out from wall surface.

- Backbox: 26.00"W x 26.01"H x 4"D
- Rack Frame: 29.06"W x 29.06"H x 1.81"D
- Projection from Wall: 1.81"
- Overall: 29.06"W x 29.06"H x 5.81"D



Features:

- Backbox and rack frame boxed separately.
- One pair of adjustable (7-position) rails, tapped 10-32
- Two adjustable-height hold-down brackets secure non-rackmount consumer gear.
- Vent slots at bottom and top (beneath integral handle)
- Knockouts for conduit access (.875" on surface model and .5-.75" on recessed model)
- Key-lock
- Device cutouts with factory installed cover plates: (3) frame-mounted and (2) internal for installation of optional Decora®-style devices (low-voltage only).
- Two steel hinges provide solid support when opened to the 90-degree service position.
- Panel mounting hardware: PilotPoint screws & captive washers.
- Includes E.O. box in bottom
- Steel construction with beveled edges and neutral Network Grey wrinkle powder epoxy finish
- Panel Space: 3U (5.25")
- Accepts equipment up to 19"W x 5.25"H x 17.5"D

Note: some electronic devices may require rack to be in full-open (90-degree) service position to operate correctly.

A&E Specifications:


Wall-mount rack for tilt-out operation shall be Lowell Model _____. Rack shall provide 3U (5.25") panel mounting space for 19"W rackmount electronics. Unit shall include two hold-down brackets to secure non-rackmount components. Assembly shall measure _____ overall. [Recessed model shall mount 4" into wall with 1.81" rack-frame projection. Surface-mount model shall project from




Model No.	Description	Mounting Style	Overall W	Overall H	Overall D	Projection from Wall
LWTR-3R	Wall-mount Tilt-out Rack	recessed	29.06"	29.06"	5.81"	1.81"
LWTR-3S	Wall-mount Tilt-out Rack	surface	29.125"	29.125"	5.81"	5.81"

One Rack Unit (RU or U) = 1.75"

Model No. LWTR-3S (surface-mount)



Model No. LWTR-3R (recessed)



All measurements are inches.

Spec. No. **1154**
(rev. 01.19.12)
pg. 2 of 2

©2011 Lowell Manufacturing Company, 100 Ingram Dr., Pacific MO 63069. Phone-800.325.9660 Fax-636.257.6606. Lowell makes every effort to provide accurate information while reserving the right to change specifications and/or improve manufacturing methods without notification. (lowellmfg.com)

Lowell[™]