

Product Specification Sheet

Catalog Number: CT-P-(length)

Air Handling Cable Ties

- Ideal Applications: Air Handling Spaces, above drop ceilings and below raised flooring
- Meets UL 1565 low smoke generation, low heat release, and mechanical strength test
- UL Listed suitable for use in Air Handling Spaces in accordance with the Section 300.22 (C) and (D) of the National Electrical Code and Rules 12-010 (3), (4), and (5) and 12-020 of the Canadian Electrical Code, Part 1
- Strong and Pure manufactured from filtered nylon 6/6 reducing particle contamination (8-14" versions)
- Halar ties feature low smoke density and high flame resistance and are ideal for plenum areas where smoke generation is a concern (4" version)
- UL File E168851 Certified Positioning Devices ANSI/UL1565



Part Number	Color	Length Inch/mm	Width Inch/mm	Thickness Inch/mm	Tie Tensile	Bundle Diameter	Per Bag	Per Case	UL-CSA	Mil-Spec Reference
CT-P-4	Red	4.0/101.6	.094/2.387	.042/1.066	12 lb.	.875	100	5,000	UL-CSA	
CT-P-8	Burgundy	7.56/192.07	.180/4.572	.052/1.320	50 lb.	1.875	100	5,000	UL-CSA	MS3367-1-35
CT-P-12	Burgundy	11.25/285.75	.180/4.572	.052/1.320	50 lb.	3.062	100	5,000	UL-CSA	MS3367-7-35
CT-P-14	Burgundy	14.56/369.87	.180/4.572	.052/1.320	50 lb.	4.125	100	5,000	UL-CSA	MS3367-2-35

Tolerance:

.xxx = .005

.xx = .015

Fraction = 1/32"

Bulk Packaging Available with Minimum Buy and 2 Week Lead Time

ROHS Compliant

Sold in Case Quantities

Form Revision Date: 04/15/2004



FOR IMMEDIATE SERVICE
FAX YOUR ORDER
719-260-0075

CALL TO PLACE YOUR ORDER TODAY
800-530-8998
MOST ORDERS SHIPPED WITHIN 48 HOURS