

D-Cerno-D

Digital Discussion Delegate Unit w/ Fixed Mic 12 in. (30 cm)



Configurations

Digital Discussion Delegate Unit w/ Fixed Mic 12 in. (30 cm)

The D-Cerno-D is a delegate discussion unit that comes in a stylish low-profile design but maintains a superior sound quality. The system uses shielded Cat5 cable, and installing the units is extremely simple and worry-free because there is no initialization process and the unit automatically makes adjustments to the detected flow of the signal.

The cable connections are concealed under the unit, maintaining the stylish intent of the system. Using touch sensor technology, the microphone can be simply activated by touching the speak icon.

Additionally, the touch buttons allow for effortless cleaning and disinfecting because there are no gaps where dirt and germs could collect. The shielded microphone is advanced in its interference rejection of GSM devices, ensuring perfect sound at all time.

Highlights

- Delegate unit with a 12 in. (30 cm) fixed mic
- Digital signal processing
- Stylish, unobtrusive, low-profile design
- Touch sensor button technology
- Loop-through, daisy chain cabling
- Advanced interference rejection
- High quality integrated loudspeaker
- Concealed cable connections
- Microphone LED ring
- Built-in headphone connection

Includes

One (1) D-Cerno-D Digital Discussion Delegate Unit w/ Fixed Mic 12 in. (30 cm)
(1) Shielded Cat5 STP Cable

Used With

D-Cerno-D Digital Discussion Delegate Unit w/ Fixed Mic 12 in. (30 cm)
D-Cerno-C Digital Discussion Chairman Unit w/ Fixed Mic 12 in. (30 cm)
D-Cerno-D Digital Discussion Delegate Unit w/ Fixed Mic 12 in. (30 cm)
D-Cerno-C Digital Discussion Chairman Unit w/ Fixed Mic 12 in. (30 cm)
D-Cerno-DL Digital Discussion Delegate Unit w/ Fixed Mic 20 in. (50 cm)
D-Cerno-CL Digital Discussion Chairman Unit w/ Fixed Mic 20 in. (50 cm)
D-Cerno-CU Digital Discussion Central Unit
D-Cerno-CUR Digital Discussion Central Unit w/Digital Recording
D-Cerno-TC Digital Discussion 12-Unit and 1-CU Storage/Carrying Case



D-Cerno-D Specifications*

Audio	Frequency Response	25Hz to 15KHz (± 3 dB)
	Loudspeaker Diameter	1.75 in. (44 mm)
	Loudspeaker Maximum Power	3 W RMS
	Headphone Load Impedance	>32 ohm <1k ohm
	Quality	16 Bit Digital

Controls & Indicators	Microphone Button	Button with Red/Green backlit illuminating LED; red indicates microphone is active, green indicates request-to-speak.
	Microphone LED	Lit RED when the microphone is active. Flashing when in the request-to-speak queue.
	LED Bar	Lit GREEN when in the request-to-speak queue.
	Headphone Volume Control	Two (2) touch buttons "-" and "+" for control of the headphone volume.

Interconnections	D-Cerno Network	Two (2) RJ45 connections for connecting to the daisy chain.
	Headphone Connector	One (1) 3.5 mm (0.14 in.) mono headphone connector.

Power	Power Consumption	2 Watts
-------	-------------------	---------

Physical	Dimensions (H x W x D)	1.97 x 8.27 x 5.31 in. (50 x 210 x 135 mm)
	Microphone Length	12 in. (30 cm)
	Color	Black
	Unit Weight	1.4 lbs. (0.6 kg)
	Shipping Weight	4.0 lbs. (3.2 kg)
	Mounting	Tabletop

*Specifications are subject to change without notification.