



Day/Night Weather Resistant Color Bullet Cameras/63 IR LEDs







VL7038IRVF	2.8-12mm auto iris varifocal lens
VL7039IRVF	6-50mm auto iris varifocal lens

Features

- 1/3" Sony™ Super-Had II™ CCD
- High Performance W-V DSP chip
- 600 TV lines resolution
- Multi-mount is a unique mount allowing installers to manipulate the camera to almost every angle with simplicity
- Zero noise and no ghosting effect with digital noise reduction (DNR)
- True day & night (ICR IR cut filter removable)
- External control rings for easy focus & distance adjustment
- Highest resolution: vivid, sharp picture in complete darkness
- Front glass heater: with thermic rays & built-in temperature sensor for immediate removal of condensation
- 5 year warranty



Specifications

Image Sensor.....	1/3" Sony Super-HAD II™ CCD	Sense-Up.....	Off / Auto (selectable limit x2 - x256)
Resolution.....	600 TV lines	Mirror.....	Off / Mirror / V-Rev / Rotate
Minimum Illumination.....	CDS off 0.15 lux, CDS on 0.00003 lux	Digital Zoom.....	On (1x - 16x) / Off
Total Pixels.....	811 (H) x 508 (V)	Power Consumption.....	12VDC, 220mA (CDS off) 700mA (CDS on) Heater on adj: 220-700mA 24VAC 150mA (CDS off) 450mA (CDS off) Heater on adj: 170-450mA
Effective Pixels.....	768 (H) x 494 (V)	Power Supply.....	12VDC / 24VAC (dual voltage) (power supply not supplied) Operating Temperature/ Humidity.....
Number Of IR Leds.....	63		14° F - 122° F / RH 95% max.
IR Range.....	Up To 131'	Storage Temperature/ Humidity.....	-4° F - 140° F / RH 95% max.
White Balance.....	ATW / Outdoor / Indoor / Manual AWC (1,700°K - 11,000°K)	Dimensions.....	5.4" (W) x 3.25" (H) x 11.5" (L)
Gain Control.....	High / Low / Off,	Weight.....	4 lbs.
S/N Ratio.....	More than 52dB (AGC off, Weight on)		
Backlight Compensation.....	HLC / BLC / Off		
Electronic Shutter Speed.....	1/50, 1/60 sec. - 1/100,000 sec.		
OSD.....	Built-in	Optional Accessories	
DNR.....	Off / On (level adjustable)		INTJS Square Junction Box
D-WDR.....	Indoor / Outdoor / Off		INTCM Corner/Pole Adaptor
Sharpness.....	0-31' (level adjustable)		PSW4 Power Supply
Privacy.....	On / Off (12 zones)		PSW5 Power Supply
Scanning System.....	2:1 interlace		
Synchronization.....	Internal		
Day & Night.....	Color / BW / Auto / EXT		
Motion Detection.....	On / Off (8 zones)		

Speco Technologies is constantly developing and improving products.
We reserve the right to modify product design and specifications without notice and without incurring any obligation.

Rev. 1/24/12

For more information contact Speco Technologies
200 New Highway, Amityville, NY 11701 • Toll Free: 1-800-645-5516 • Fax: 631-957-9142 or 631-957-3880
www.specotech.com