

Complete Group Collaboration Appliance for Small and Medium Sized Rooms



Part Numbers:

998-8900-000 North America
998-8900-001 International

The Vaddio™ GroupSTATION is a complete media collaboration appliance for small and medium meeting spaces. GroupSTATION incorporates all the audio & video functions required for group collaboration in a compact sleek and robust form-factor. This multipurpose appliance is used for local presentations, PC-based Unified Communications, and VoIP conferencing.

Image: GroupSTATION Wall Unit



Image: MicPOD™ Dock

The GroupSTATION system consists of a table-based MicPOD Dock and a wall-mounted GroupSTATION Wall Unit. The MicPOD Dock functions as the microphones, user interface, and PC dock. Four (4) cardioid microphone elements, each with its own AEC (acoustic echo canceller), provide a 360° pickup pattern for all participants. Vaddio's SmartMic technology ensures that pristine, crystal clear audio is maintained for both local and far-end participants with hands-free, automatic operation. A capacitive touch user interface on the MicPOD Dock provides for dialing, volume and mute along with video controls for zoom, PIP, and a 2-input source selection for complete operator control during a conference. The MicPOD Dock features interfaces for a PC, laptop or tablet, HDMI or VGA inputs to locally extend the PC to the room monitor and a USB 2.0 UVC and UAC compliant connection. Once the laptop is docked, media functions are extended from the PC for room operations.

The GroupSTATION wall unit includes a pair of 2-way loudspeakers with a HD camera in the center. Like the ZoomSHOT™ camera, the GroupSTATION camera has an auto-focus, 19X motorized zoom lens and is directly wired into the main processor in the wall unit. ZoomSHOT can be manually positioned for pan and tilt. The GroupSTATION also includes an HDMI output for the room LCD monitor extending the PC or laptop's screen when docked. A supplied single Cat-6e shielded cable (25-feet) connects the GroupSTATION with the MicPOD Dock carrying power, video, audio, and network making installation a pure breeze.

SYSTEM INCLUDES

The Vaddio GroupSTATION System includes:

- One (1) Group-STATION MicPOD Dock Controller
- One (1) GroupSTATION Wall Unit
- One (1) Premium GroupSTATION Wall Mount and Cable Tray
- One (1) Set Mounting Hardware
- One (1) 25' (7.62m) Cat-6e Shielded Cable
- One (1) 24 VDC Power Supply



GroupSTATION

MicPOD
Dock

Cat-6e
LINK
Cable

GENERAL SPECIFICATIONS

Part Numbers: 999-8900-000 North America, 999-8900-001 Int'l

GroupSTATION Sound Bar	Camera: 19X Optical Zoom, Manual Pan/Tilt, 1/2.8-Type Exmor High-speed, PS CMOS Sensor	GroupSTATION MicPOD Dock	Dialing Pad, Volume Control, Mute Audio Control, Camera Zoom In/Out Control, Power On/Off (Stand-by) and ON Screen Display of user controls (for dialing support)
Minimum Illumination	0.7 LUX (F1.6, 50IRE)	USB Interface	Connector: USB Micro-B, USB 2.0 UVC and UAC Compliant
Horiz. Viewing Angle	58° Wide End to 3.1° Tele End, 16:9 Format	Video Inputs	HDMI Video Input and DE-15 Input for RGBHV (switchable)
Speakers	1-Pair 2-way Speakers and 2x25W Class D Amps	Network Interface	Connector: RJ-45, 10/100 Base-T, RTSP & HLS Supported
VoIP	SIP User Agent (OSD for Dialing)	Supported UC Video Clients	Skype, Cisco Jabber, Adobe Connect 8, Microsoft Lync, WebEx, Citrix GoToMeeting, LifeSize ClearSea, Polycom M100, Vidyio, Google Plus (see FAQ for more options)
Inputs/Outputs	Power Jack (coaxial 5.5mm x 2.5mm), RJ-45 for Cat-6e Shielded LINK Cable, HDMI Out to Monitor, Network RJ-45 Connection (LAN/WAN)		