Specifications

Туре

Compact digital still camera with built-in flash, 16x Optical Zoom, 4x Digital Zoom and 64x Combined Optical Zoom with Optical Image Stabilizer

Image Capture Device

Type 16.0 Megapixel, 1/2.3-inch CCD

Total Pixels Approx. 16.6 Megapixels

Effective Pixels Approx. 16.0 Megapixels

Lens

Focal Length 5.0 (W) - 80.0 (T) mm (35mm film equivalent: 28 - 448 mm)

Digital Zoom 4.0x

Focusing Range Normal: 2.0 in. (5cm) - infinity (W), 2.0ft. (60cm) - infinity (T) Auto/Manual: 0.4 in. (1cm) - infinity (W), 2.0ft. (60cm) - infinity (T) Macro AF: 0.4 in. - 1.6ft. (1 - 50cm) (W)

Autofocus System TTL Autofocus, Manual Focus

Viewfinders

Optical Viewfinder Not available

LCD Monitor 3.0-inch TFT color LCD with wide viewing angle

LCD Pixels Approx. 230,000 dots

LCD Coverage Approx. 100%

Aperture and Shutter

Maximum Aperture f/3.5 (W) , f/5.9 (T)

Shutter Speed 1-1/3200 sec.

15-1/3200 sec. (Total shutter speed range)

Exposure Control

Sensitivity Auto, ISO 100 - 1600

Light Metering Method Evaluative*, Center-weighted Average, Spot** * Facial brightness is evaluated in Face Detection AF ** Metering frame is fixed to the center

Exposure Control Method Manual Exposure, Program Shift, Safety Shift, AE Lock

Exposure Compensation Still Images: ± stops in 1/3-stop increments Videos: ± 2 stops in 1/3-stop increments (Not available when shooting movies)

White Balance

White Balance Control Auto*, Daylight, Cloudy, Tungsten, Fluorescent, Fluorescent H, Custom

* Camera automatically sets the optimal ISO speed according to shooting mode.

Flash

Built-in Flash Auto, Flash On, Slow Synchro, Flash Off

• Facial brightness is also evaluated in Face Detect.

Flash Range 1.6 ft. - 9.8 ft. (W), 2.0 - 6.6 ft. (T) (50cm - 3.0m (W), (60cm - 2.0m (T))

Image brightness may diminish depending on the shooting distance

Recycling Time 15 sec. or less (battery voltage: 3.0 V)

Flash Exposure Compensation ±2 stops in 1/3-stop increments

Shooting Specifications

Shooting Modes M, Av, Tv, P, Live View Control, Auto, SCN*¹, Creative Filters^{*2}, Discreet, Movie^{*3}

• Shooting movies is possible with the movie button

- *1 Portrait, Face Self-timer, Low Light, Snow, Fireworks
- ^{*2} Fisheye Effect, Miniature Effect, Toy Camera Effect, Monochrome, Super Vivid, Poster Effect

*3 Standard

Photo Effects My Colors Off, Vivid, Neutral, Sepia, Black & White, Positive Film, Lighter Skin Tone, Darker Skin Tone, Vivid Blue, Vivid Green, Vivid Red, Custom Color*

*Adjustment of contrast, sharpness, saturation, red, green, blue and skin tone are available

Self Timer

Approx. 10-sec. delay/approx. 2-sec. delay, custom*

*Delay time (0-15 sec. (in one-second increments), 20/25/30 sec.) and number of shots (1-10 shots (in one-shot increments)) can be specified.

Wireless Control Not Available

Continuous Shooting

- Normal: Approx. 0.8 shots/sec. (in P mode) Normal: Approx. 2.8 shots/sec. (in Low Light mode)
- 2. AF: Approx. 0.5 shots/sec. (in P mode)
- 3. LV: Approx. 0.6 shots/sec. (in P mode)
- Under conditions where the flash does not fire automatically
- Differs depending on the zoom position

Image Storage

Storage Media SD Memory Card, SDHC Memory Card, SDXC Memory Card

File Format Design rule for Camera File System, DPOF (Version 1.1) compliant

Image Recording Format Superfine / Fine

JPEG Compression Mode Still Image: 2.3 (JPEG) Video: MOV (image data: H.264, Audio: Linear PCM (Stereo))

Number of Recording Pixels Still Images:

- 1. 16:9 Large: 4608 x 2592; Medium 1:3264 x 1832; Medium 2: 1920 x 1080; Small: 640 x 360
- 2. 3:2 Large: 4608 x 3072; Medium 1:3264 x 2176; Medium 2: 1600 x 1064; Small: 640 x 424

- 3. 4:3 Large: 4608 x 3456; Medium 1:3264 x 2448; Medium 2: 1600 x 1200; Small: 480 x 480
- 4. 1:1 Large: 3456 x 3456; Medium 1: 2448 x 2448; Medium 2: 1200 x 1200; Small: 480 x 480

Videos: HD 1280 x 720: 25 fps Miniature Effect HD 1280 x 720: 5 fps / 2.5 fps / 1.25 fps Miniature Effect 640 x 480: 6 fps / 3 fps / 1.5 fps 640 x 480: 30 fps (29.97)

Number of Recordable Images

Image data

| | | 16:9 | | | 3:2 | | | 4:3 | | |
|------------------|----|----------------------|-------|--------|----------------------|-------|--------|----------------------|-------|--------|
| | | File Size (KB) | 8GB | 32GB | File Size (KB) | 8GB | 32GB | File Size (KB) | 8GB | 32GB |
| I | SF | 5184 | 1506 | 6081 | 6144 | 1272 | 5136 | 6912 | 1131 | 4567 |
| Large (L1) | F | 3069 | 2531 | 10219 | 3638 | 2135 | 8620 | 4093 | 1903 | 7684 |
| Medium 1 (M1) | SF | 2595 | 2958 | 11943 | 3083 | 2505 | 10115 | 3436 | 2252 | 9094 |
| | F | 1537 | 4912 | 19826 | 1825 | 4162 | 16802 | 2060 | 3721 | 15020 |
| Medium 2 (M2) | SF | 1095 | 6822 | 27537 | 899 | 8187 | 33044 | 1002 | 7442 | 30040 |
| | F | 604 | 12280 | 49567 | 496 | 14448 | 58314 | 558 | 12927 | 52176 |
| Small (S) | SF | 188 | 35089 | 141622 | 221 | 30703 | 123919 | 249 | 27291 | 110150 |
| | F | 113 | 49125 | 198271 | 133 | 40937 | 165225 | 150 | 40937 | 165225 |
| Medium* (M) | F | NA | NA | NA | NA | NA | NA | 1144 | 6638 | 26792 |

| | | 1:1 | | | |
|----------------|----|----------------------|-------|--------|--|
| | | File Size (KB) | 8GB | 32GB | |
| Large (L1) | SF | 5184 | 1506 | 6081 | |
| Large (L1) | F | 3069 | 2531 | 10219 | |
| Medium 1 (M1) | SF | 2601 | 2958 | 11943 | |
| Medium I (MII) | F | 1540 | 4912 | 19826 | |
| Medium 2 (M2) | SF | 760 | 9824 | 39653 | |
| | F | 420 | 16374 | 66090 | |
| Small (S) | SF | 188 | 35089 | 141622 | |
| Small (S) | F | 113 | 49125 | 198271 | |
| Medium* (M) | F | NA | NA | NA | |

Note: SF=Superfine F=Fine

* When in Low Light.

• The approximate number of images recordable on memory cards other than the above can be calculated by using the above figures as a reference and extrapolating accordingly.

Time of Recordable Movies

Movie data

| | Miniature Effect | | | | | | | |
|-------------------------|-------------------------------|-------------------------------|-------------------------------|-------------------------------|-------------------------------|-------------------------------|--|--|
| | H | D: 1280 x 7 | 720 | 640 x 480 | | | | |
| | 5x | 10x | 20x | 5x | 10x | 20x | | |
| | 5 fps*1 | 2.5 fps*1 | 1.25 fps*1 | 6 fps* ² | 3 fps* ² | 1.5 fps*2 | | |
| Movie Size (KB/sec.) | 487 | 243 | 122 | 246 | 123 | 61 | | |
| 8GB | 4 hrs. 00 min. 33 sec. | 7 hrs. 34 min. 23 sec. | 13 hrs. 37 min. 54 sec. | 7 hrs. 34 min. 23 sec. | 13 hrs. 37 min. 54 sec. | 22 hrs. 43 min. 11 sec. | | |
| 32GB | 16 hrs. 11 min. 39 sec. | 30 hrs. 35 min. 22 sec. | 55 hrs. 03 min. 40 sec. | 30 hrs. 35 min. 22 sec. | 55 hrs. 03 min. 40 sec. | 91 hrs. 46 min. 07 sec. | | |

| | Other | | | |
|----------------------|------------------------|------------------------|--|--|
| | HD: 1280 x 720 | 640 x 480 | | |
| | 25 fps | 30 fps* ³ | | |
| Movie Size (KB/sec.) | 2621 | 1416 | | |
| 8GB | 49 min. 15 sec. | 1 hr. 28 min. 53 sec. | | |
| 32GB | 3 hrs. 19 min. 00 sec. | 5 hrs. 59 min. 05 sec. | | |

*¹ Playback frame rate is 25 fps.
*² Playback frame rate is 30 fps*³.
*³ Actual frame rate is 29.97 fps.

Playback Specifications

Playback Modes File

Stills & Videos:

Auto Rotate (Automatic vertical/horizontal detection), Image Advance (Transition Effects, Scroll Display), Rotate, Favorites, My Category, Smart Shuffle, Group Playback, Slideshow (Repeat, Interval, Effect)

Still Images:

Single, Index (4-130 thumbnails), Magnification (2-10x), Information Display, Red-eye Correction, i-Contrast, Resize, My Colors, Histogram, Overexposure Warning

Videos: Normal Playback^{*1}, Skip Backward^{*2}, Previous Frame^{*3}, Next Frame^{*3}, Skip Forward^{*2}

*1 Audio settings available in 5 levels

*2 Approximately 4 seconds

*3 Slow motion available

Erasing Specifications

Erase Modes

Select Image, Select Range, Select All Images

- The image data in the memory card stored with the Design rule for Camera File systems format can be erased (however, ٠ protected images cannot be erased).
- Using the Movie editing function, sections of the movie (1 sec. increments) can be deleted. •

Interfaces

Video Out NTSC/PAL (dedicated connector (female) with unified type of digital, audio and video)

Audio Out Stereo (dedicated connector (female) with unified type of digital, audio and video)

Other

SD memory card slot; direct connection to Canon SELPHY, PIXMA Photo Printers & PictBridge compatible printers

Power Source Battery Pack NB-6LH, AC Adapter Kit ACK-40

Shooting Capacity Approx. 300 shots Approx. 440 shots in ECO Mode

Playback Time Approx. 7 hours

Physical Specifications

Operating Temperature 32-104°F/0-40°C

Operating Humidity 10-90%

Dimensions (W x H x D) 4.25 x 2.80 x 1.73 in. / 108.0 x 71.0 x 43.9mm

Weight 8.85 oz. / 251g (CIPA standard) 8.04 oz. / 228g (camera only)

Note: 27 display languages provided (English, German, French, Dutch, Danish, Finnish, Italian, Norwegian, Swedish, Spanish, Simplified/Traditional Chinese, Japanese, Russian, Portuguese, Korean, Greek, Polish, Czech, Hungarian, Turkish, Thai, Arabic, Romanian, Ukrainian, Farsi, and Hindi).

All data are based on Canon's Standard Test Method. Subject to change without notice.

Canon, DIGIC, ELPH, PIXMA, and PowerShot and SELPHY are registered trademarks of Canon Inc. in the United States and may also be registered trademarks or trademarks in other countries. Microsoft, Windows and Windows Vista are trademarks or registered trademarks of Microsoft Corporation in the United States and/or other countries. Mac is a trademark of Apple, Inc., registered in the United States and other countries. All other products and brand names are registered trademarks, trademarks or service marks of their respective owners in the United States and/or other countries.

[†] Prices and specifications subject to change without notice. Actual prices are determined by individual dealers and may vary.