

PFWX-51B

4,750 lumens, WXGA, single-chip DLP Present projector



WXGA
1280x800

5K
LUMENS

1-CHIP
DLP™

Offering a brightness level of 4,750 lumens and WXGA resolution, this compact Present projector will perfectly complement the meeting room it's installed in. What's more, it can be set up as tabletop or ceiling device with equal ease.

Why you'll love the Present range

- **Stylish design** that seamlessly blends in with your office interior
- **High-quality images** with an unmatched level of detail and contrast
- **Button-free and cable-free** for simple operation and less clutter
- **Reliable DLP technology** for true ease of mind
- **Easily upgradable** with future connectivity add-ons
- **Low cost of ownership** thanks to DLP technology and sealed optics
- Preset image modes that allow for **flexible color management**
- **Intuitive control menu** with the most common features at your fingertips
- **User-friendly remote control** that features just one button

ClickShare Inside

Supporting the integration of optional connectivity modules, the Present projectors are fully future-proof and can easily be upgraded with extra functionalities. Based on Barco's wireless presentation system ClickShare, the '**ClickShare Inside**' option can be nicely integrated under the hood of the projector and allows users to wirelessly share their content on-screen, for true collaboration.

BARCO

Visibly yours

Product specifications**PFWX-51B**

| | |
|---|---|
| Projector type | WXGA single-chip DLP projector |
| Technology | 0.65" DMD |
| Color wheel | 5-segment (RGBWY) |
| Resolution | 1,280 x 800 WXGA |
| Brightness | 4,750 ANSI lumens* 3,300 ANSI lumens (eco-mode)* *Measurement, measuring conditions, and method of notation all comply with ISO 21118 international standards. |
| Contrast ratio | 1,800:1 |
| Brightness uniformity | 85% |
| Aspect Ratio | 16:10 |
| Lens type | F lens |
| Lenses | 1.62-2.03:1; 2.02-3.03:1; 0.81:1 |
| Optical lens shift | Vertical: -30% to +110% / horizontal: -10% to +10% |
| Lamps | 1 x 370W P-VIP |
| Lamp lifetime | Up to 1,500 hours (full power) / Up to 3,500 hours (eco mode) |
| Transport with lamp | Yes |
| Orientation | table - ceiling |
| Integrated web server | Yes |
| 3D | Yes |
| Keystone correction | app. 40° vertical |
| Inputs | DVI, HDMI, BNC (RGBHV), Component, Display Port, 2 VGA inputs for PC or Laptop, RCA R/L Audio input, Audio-In, RJ45, S-Video, Composite Video, Rs232c, VGA-Out, and Audio-Out |
| Input Resolutions | up to WUXGA (1,920 x 1,200) 60Hz |
| Software tools | Projector Toolset |
| Control | IR, RS232, RJ45 |
| Network connection | 10/100 base-T, RJ-45 connection |
| Power requirements | AC input 100 ~ 240 app. 10% voltage (auto ranging) |
| Max. power consumption | 480W @ 100V/460W @ 240V 365W @ 100VAC/355W @ 240VAC (eco mode)/ less than 0.5W (standby) |
| Noise level (typical at 25°C/77°F) | 42 dBA (bright mode)/ 37 dBA (eco mode) |
| Operational ambient temperature | 5-35°C / 41°-95°F |
| Operational humidity | 10-85% |
| Dimensions (WxLxH) | 460 x 446 x 209 mm |
| Weight | 12 kg (26.5 lb) |
| Shipping dimensions (WxLxH) | 594 x 568 x 355mm |
| Shipping Weight from Factory | 16.8 kg |
| Certifications | CB test certificate, US emc, US safety, CE emc and safety, CCC emc and safety |
| Warranty | 3 years standard warranty** **Warranty and service conditions can differ from region to region. Contact your local sales or service rep for more details |