

140304

Fixture	10'			20'			30'			
	Beam Diameter (WxH)	foot-candle	lux	Beam Diameter (WxH)	foot-candle	lux	Beam Diameter (WxH)	foot-candle	lux	
5in1	FXLD1018FRP5I	6	158	1590	10.5	38	415	15.5	19	208
4in1	FXLD1036C4O	8 x 8	580	5840	13 x 13	150	1680	18 x 18	70	760
	FXLD836C4I	3	370	3950	5	100	1100	7	52	560
	FXLD818B4I									
	FXKD818FRP4I2	3	115	1240	5	35	394	7	19	184
	FXKD818FRP4I4	6	105	1150	10	32	353	15	16	184
	FXLD89FRP4I	3	62	672	5	22	234	-	-	-
3in1	FXLD348C3O	5 x 5	218	2280	8 x 8	56	612	10 x 10	26	275
	FXLD348R3I	(@6.5") 2' 9"	-	7800	9' 6"	-	620	14' 9"	-	290
	FXLD336ZM3I	3 x 3	170	1806	6 x 6	45	481	10 x 10	22	220
		8 x 8	50	531	14 x 14	15	145	20 x 20	8	75
2in1	FXLD618C2I									
	FXLD68FP2I									
Discrete	FXLD548C4O	5 x 5	550	5870	8 x 8	145	1570	12 x 12	70	747
	FXLD360C5O	4 x 4	385	4140	10 x 10	101	1097	16 x 16	47	504
	FXLD354WAO	4 x 4	134	1460	8 x 8	36	376	10 x 10	18	172
	FXLD136RGB	4 x 4	143	1558	5 x 5	40	425	7 x 7	20	188
LED ELLIPSOIDAL	FXLE1260W19	-	-	-	7x7	230	2500	11x11	111	1214
	FXLE1260W26	-	-	-	10x10	160	1723	16x16	58.5	628
	FXLE1260W36	-	-	-	14x14	111.5	1200	20x20	48	516
	FXLE1260W50	10x10	200	2160	16x16	50	635	-	-	-
	FXLE1232W19	3	972	10450	7	224	2410	10	102	1130
	FXLE1232W26	4.5	658	7120	9.5	149	1620	14.5	70	770
	FXLE1232W36	6	437	4520	12.5	105	1130	19	49	540
	FXLE1232W50	10	219	2360	19	51	565	-	-	-