

Technical Data Sheet

Professional Audio Snake

WEST PENN WIRE



2833 West Chestnut Street
Washington, PA 15301
Toll Free: (800) 245-4964
Fax: (724) 222-6420
www.westpenn-wpw.com

PART NUMBER:	D25432
DESCRIPTION:	22 AWG.- 6 PAIR Stranded tinned copper conductors, individually shielded with an overall jacket.
NEC RATING:	CMP
APPROVALS:	(UL) Listed
APPLICATION:	Indoor Plenum Area for: Intercom, Security, Sound, Audio, Background Music, and Power Limited Control Circuits.

Construction Parameters:

Conductor	22 AWG Tinned Copper
Stranding	7x30
Insulation Material	Teflon
Insulation Thickness	0.010" Nom.
Number of Conductors	12 (6 Pair)
Shield	Each Pair 100% Aluminum Foil
Drain	Stranded Tinned Copper
Jacket Material	Flexible Plenum
Jacket Thickness	0.017" Nom.
Overall Cable Diameter	0.304" Nom.
Approximate Cable Weight	69 Lbs/1M' Nom.
Flame Rating	UL NFPA 262

Electrical & Environmental Properties:

Temperature Rating	-20°C To +60°C
Operating Voltage	300 V RMS
Max.Capacitance Between Conductors @ 1 KHz	25 pf/ft Nom.
Capacitance Between Conductors to Shield @ 1 KHz	45 pf/ft Nom.
DC Resistance per Conductor @ 20deg C	17 Ohms/1M' Nom.
Insulation Colors	Black/Red-Red, Black/White-White, Black/Green-Green, Black/Blue-Blue, Black/Yellow-Yellow,Black/Brown-Brown
Jacket Color	Gray
RoHS Compliant	Yes

Mechanical Properties:

Max. Recommended Pull Tension	126 Lbs.
Min. Bend Radius (Install)	3.0"

Specification Issue Date: 7/06

This document is the property of West Penn Wire.
The information contained herein is considered
Proprietary and not to be reproduced by any means
Without written consent of West Penn Wire

Standard Lengths are 1000ft.
The Jacket is sequentially footmarked.
The information presented here is, to the best of our
knowledge, is true and accurate. However, since
conditions of use are beyond our control, all
recommendations or suggestions are presented
without guarantee or responsibility on our part. We
disclaim all liability in connection with the use of
information contained herein or otherwise.